

NAME:- Sourav Paul

GROUP:- D2

REG. NO:- 20214056


BRANCH:- CSE DEPT.

## ASSIGNMENT - 04

2. Consider the string on  $\{a, b\}$  defined by the requirements below. For each, construct an accepting NDFA.

i) Design an NDFA for all strings over  $\{a, b\}$  start with 'ab'.

Ans:- State diagram



CODE:-

```
#include<bits/stdc++.h>
```

```
using namespace std;


bool solve(string str)
{
    int n = str.size();
    if(n<2)
        return false;
    if(str[0]=='a' && str[1]=='b')
    {
        return true;
    }
    return false;
}

int main()
{
    string str;
    cin>>s;
    cout<<(solve(s)?"ACCEPT":"REJECT")<<endl;

    return 0;
}
```

**ii) Design an N DFA for all strings over {a, b} end with 'ab'.**

**ANS:- State diagram**



**CODE : -**

```
#include<bits/stdc++.h>

using namespace std;

bool solve(string str)
{
    int n=str.size();

    if(n<2)
        return false;

    if(str[n-2]=='a' && str[n-1]=='b')
    {
        return true;
    }
}
```

```

    return false;
}


int main()
{
    string str;
    cin>>str;
    cout<<(solve(str)?"ACCEPT":"REJECT")<<endl;

    return 0;
}

```

**iii) Design an N DFA for all strings over {a, b} having substring 'ab'.**

**Ans:- State diagram**



**CODE :-**

```
#include<bits/stdc++.h>
using namespace std;
bool solve(string str)
{
    int n=str.size();
    if(n<2)
        return false;

    for(int i=0;i<n-1;i++)
    {
        if(str[i]=='a' && str[i+1]=='b')
            return true;
    }


    return false;
}

int main()
{
    string str;
    cin>>str;
    cout<<(solve(s)?"ACCEPT":"REJECT")<<endl;

    return 0;
}
```

**3.Construct an NDFA over {a, b, c} that accepts the language {ab, abc}.**

**Ans:- State diagram**



**CODE :**

```
#include<bits/stdc++.h>

using namespace std;

bool solve(string str)
{
    int n=str.size();
    if(n>3 || n<=1)
        return false;

    if(str=="abc" || str=="ab")
    {
        return true;
    }

    return false;
}
```

```


int main()
{
    string str;
    cin>>str;
    cout<<(solve(s)?"ACCEPT":"REJECT")<<endl;

    return 0;
}

```

**4.Design an N DFA that accepts a language  $\{b^n a \mid n \geq 1\}$**

**Ans:- State diagram**



**CODE :**

```

#include<bits/stdc++.h>

using namespace std;

```

```
bool solve(string str)
{
    int n=str.size();
    if(n<2)
        return false;
    for(int i=0;i<n-1;i++)
    {
        if(str[i]!='b')
            return false;
        if(str[n-1]!='a')
            return false;
    }


    return true;
}

int main()
{
    string str;
    cin>>str;
    cout<<(solve(str)?"ACCEPT":"REJECT")<<endl;
}
```



**5.Design an N DFA with no more than five states for set  $\{abab^n|n \geq 0\} \cup \{aba^n|n \geq 0\}$**

**Ans:- State diagram**



**CODE :-**

```
#include<bits/stdc++.h>

using namespace std;

bool solve(string str)
{
    int n=str.size();
    if(n<2 || str[0]!='b' || str[1]!='a')
        return false;
    if(n==2 || (n==3 && s[2]=='a'))
        return true;
    if (n==3 && s[2]!='b')
        return false;

    for(int i=3;i<n;i++)
```

```

{
    if(str[i]!=s[3])
        return false;
}
return true;
}


int main()
{
    string str;cin>>str;
    cout<<(solve(s)?"ACCEPT":"REJECT")<<endl;

    return 0;
}

```

**6. Design an NDFFA for all strings containing at least two a's or exactly two b's.**

**Ans:- State diagram**



**CODE :-**

```

#include<bits/stdc++.h>

using namespace std;

bool solve(string str,int n)
{
    int counta=0;
    int countb=0;
    for(int i=0;i<n;i++)
    {
        if(counta && str[i]=='a')
            return true;

        if(str[i]=='a')
            counta++;

        if(str[i]=='b' && countb<4)
            countb++;
    }
}

```

```
    }  
    return cntb==2;  
}  
  
int main()  
{  
    string str;  
    cin>>str;  
    int n=str.size();  
    cout<<(solve(str,n)? "ACCEPT": "REJECT")<<endl;  
  
    return 0;  
}
```