

Summary Timeline

Tasks summary

Task	Time spent	Score
CyclicRotation C#	1 min	100%

Total score

100%

Tasks Details

Easy	1. CyclicRotation	Task Score	Correctness	Performance
	Rotate an array to the right by a given number of steps.	100%	100%	Not assessed

Task description

An array A consisting of N integers is given. Rotation of the array means that each element is shifted right by one index, and the last element of the array is moved to the first place. For example, the rotation of array A = [3, 8, 9, 7, 6] is [6, 3, 8, 9, 7] (elements are shifted right by one index and 6 is moved to the first place).

The goal is to rotate array A K times; that is, each element of A will be shifted to the right K times.

Write a function:

```
class Solution { public int[] solution(int[] A, int K); }
```

that, given an array A consisting of N integers and an integer K, returns the array A rotated K times.


For example, given

```
A = [3, 8, 9, 7, 6]
K = 3
```

Solution

Programming language used:	C#	
Total time used:	1 minutes	?
Effective time used:	1 minutes	?
Notes:	not defined yet	

Task timeline



Code: 18:49:55 UTC, cs, final, [show code in pop-up](#)
score: 100

the function should return [9, 7, 6, 3, 8]. Three rotations were made:

[3, 8, 9, 7, 6] -> [6, 3, 8, 9, 7]
[6, 3, 8, 9, 7] -> [7, 6, 3, 8, 9]
[7, 6, 3, 8, 9] -> [9, 7, 6, 3, 8]

For another example, given

A = [0, 0, 0]
K = 1

the function should return [0, 0, 0]

Given

A = [1, 2, 3, 4]
K = 4

the function should return [1, 2, 3, 4]

Assume that:

- N and K are integers within the range [0..100];
- each element of array A is an integer within the range [-1,000..1,000].

In your solution, focus on **correctness**. The performance of your solution will not be the focus of the assessment.

Copyright 2009–2022 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

```
1 using System;
2
3 /* Lesson 2.1 - Cyclic Rotation
4  * Paulo Santos
5  * 24.Nov.2022
6  */
7 class Solution {
8     public int[] solution(int[] A, int K) {
9
10         /*
11          * Check the input
12          */
13         if (A == null)
14             throw new ArgumentNullException();
15
16         var len = A.Length; // the size
17         var ans = new int[len]; // the answer
18
19         /*
20          * Iterates through the array
21          * shifting the elements to the right
22          */
23         for(var i = 0; i < len; i++){
24             ans[(i + K) % len] = A[i];
25         }
26         return ans;
27     }
28 }
```

Analysis summary

The solution obtained perfect score.

Analysis

Example tests	
▶ example	✓ OK
first example test	
▶ example2	✓ OK
second example test	
▶ example3	✓ OK
third example test	
Correctness tests	
▶ extreme_empty	✓ OK
empty array	
▶ single	✓ OK
one element, 0 <= K <= 5	
▶ double	✓ OK
two elements, K <= N	
▶ small1	✓ OK
small functional tests, K < N	
▶ small2	✓ OK
small functional tests, K >= N	
▶ small_random_all_rotations	✓ OK
small random sequence, all rotations, N = 15	
▶	

medium_random

✓ OK

medium random sequence, N = 100



maximal

✓ OK

maximal N and K