

# Sensitivity of a flux balance analysis solution with respect to input data

**Author(s): Ronan M.T. Fleming, Leiden University**

**Reviewer(s):**

## INTRODUCTION

Consider an FBA problem

$$\begin{aligned} \max \quad & c^T v \\ \text{s.t.} \quad & Sv = b \\ & l \leq v \leq u \end{aligned}$$

The local sensitivity of the optimal objective value  $\mathcal{L}^* = c^T v^*$  with respect to a changes in the input data  $\{b, l, u\}$  is given by

$$\frac{\partial \mathcal{L}^*}{\partial b} = y^*$$

$$\frac{\partial \mathcal{L}^*}{\partial l} = -w_l^*$$

$$\frac{\partial \mathcal{L}^*}{\partial u} = w_u^*$$

where  $y^*$  is a vector of shadow prices and  $w = w_l - w_u$  is a vector of reduced costs. That is, a shadow price is the partial derivative of the optimal value of the objective function with respect to  $b_i$ . It indicates how much net production, or net consumption, of each metabolite increases (positive), or decreases (negative), the optimal value of the objective. The reduced costs,  $-w_l$  and  $w_u$  are the partial derivative of the optimal value of the objective function with respect to the lower and upper bounds on a reaction, respectively. They indicate how much relaxation, or tightening, of each bound increases, or decreases, the optimal objective, respectively. In the COBRA Toolbox, shadow prices and reduced costs are calculated by `optimizeCbModel`. When using the function

```
FBAsolution = optimizeCbModel(model, 'max');
```

the shadow prices and reduced costs are given by `FBAsolution.y` and `FBAsolution.w`, respectively.

For a more complete theoretical description, see: [cobratoolbox/tutorials/intro\\_sensitivityAnalysis.pdf](https://cobratoolbox.github.io/tutorials/intro_sensitivityAnalysis.pdf)

## MATERIALS - EQUIPMENT SETUP

Please ensure that all the required dependencies (e.g., `git` and `curl`) of The COBRA Toolbox have been properly installed by following the installation guide [here](#). Please ensure that the COBRA Toolbox has been initialised (`tutorial_initialize.mlx`) and verify that the pre-packaged LP and QP solvers are functional (`tutorial_verify.mlx`).

# PROCEDURE



























## Load E. coli core model

The most direct way to load a model into The COBRA Toolbox is to use the `readCbModel` function. For example, to load a model from a MAT-file, you can simply use the filename (with or without file extension).

```
fileName = 'ecoli_core_model.mat';
if ~exist('modelOri','var')
modelOri = readCbModel(fileName);
end
%backward compatibility with primer requires relaxation of upper bound on
%ATPM
modelOri = changeRxnBounds(modelOri,'ATPM',1000,'u');
model = modelOri;
%setp the matlab e.coli metabolic map parameters
outputFormatOK = changeCbMapOutput('matlab');
map=readCbMap('ecoli_core_map');
options.zeroFluxWidth = 0.1;
options.rxnDirMultiplier = 10;
```

model

1x1 struct with 28 fields

Field ▲	Value	Size
 S	72x95 sparse do...	72x95
 mets	72x1 cell	72x1
 b	72x1 double	72x1
 csense	72x1 char	72x1
 rxns	95x1 cell	95x1
 lb	95x1 double	95x1
 ub	95x1 double	95x1
 c	95x1 double	95x1
 osenseStr	'max'	1x3
 genes	137x1 cell	137x1
 rules	95x1 cell	95x1
 metCharges	72x1 int32	72x1
 metFormulas	72x1 cell	72x1
 metNames	72x1 cell	72x1
 metInChIString	72x1 cell	72x1
 metKEGGID	72x1 cell	72x1
 metChEBIID	72x1 cell	72x1
 metPubChemID	72x1 cell	72x1
 grRules	95x1 cell	95x1
 rxnGeneMat	95x137 sparse d...	95x137
 rxnConfidence...	95x1 double	95x1
 rxnNames	95x1 cell	95x1
 rxnNotes	95x1 cell	95x1
 rxnECNumbers	95x1 cell	95x1
 rxnReferences	95x1 cell	95x1
 subSystems	95x1 cell	95x1

The meaning of each field in a standard model is defined in the [standard COBRA model field definition](#).

In general, the following fields should always be present:

- **S**, the stoichiometric matrix
- **mets**, the identifiers of the metabolites
- **b**, Accumulation (positive) or depletion (negative) of the corresponding metabolites. 0 Indicates no concentration change.
- **csense**, indicator whether the b vector is a lower bound ('G'), upper bound ('L'), or hard constraint 'E' for the metabolites.
- **rxns**, the identifiers of the reactions
- **lb**, the lower bounds of the reactions
- **ub**, the upper bounds of the reactions
- **c**, the linear objective
- **genes**, the list of genes in your model
- **rules**, the Gene-protein-reaction rules in a computer readable format present in your model.
- **osenseStr**, the objective sense either 'max' for maximisation or 'min' for minimisation

## Sensitivity Analysis

In the E. coli core model, when maximising ATP production, what is the shadow price of cytosolic protons?

Hint: `FBAsolution.y`

What is your biochemical interpretation of this change in objective in the current context?

Hint: `printFluxVector`, `drawFlux`

Perturb the model in such a way as to increase the optimal rate of ATP hydrolysis ('ATPM') by exactly one unit. How does this compare with the theoretical prediction?

Hint: `change model.b`

In the E. coli core model, when maximising ATP production, what is the reduced cost of glucose exchange?

Hint: `FBAsolution.rcost`

What is your biochemical interpretation of this?

Hint: use `drawFlux` with a perturbed optimal reaction rate vector

**Perturb the model in such a way as to increase the optimal rate of ATP hydrolysis ('ATPM') by exactly 17.5 units. How does this compare with the theoretical prediction?**

**Hint:** change model.lb

## TROUBLESHOOTING

Note that, if an optimization problem is reformulated from a maximisation to a minimisation problem, then the signs of each of the dual variables is reversed.

## TIMING

*1 hr.*

## ANTICIPATED RESULTS

Understanding of how an optimal objective will change in response to changing the input data.

## *Acknowledgments*

Part of this tutorial was originally written by Jeff Orth and Ines Thiele for the publication "What is flux balance analysis?"

## REFERENCES

1. Orth. J., Thiele, I., Palsson, B.O., What is flux balance analysis? Nat Biotechnol. Mar; 28(3): 245–248 (2010).
2. Laurent Heirendt & Sylvain Arreckx, Thomas Pfau, Sebastian N. Mendoza, Anne Richelle, Almut Heinken, Hulda S. Haraldsdottir, Jacek Wachowiak, Sarah M. Keating, Vanja Vlasov, Stefania Magnusdottir, Chiam Yu Ng, German Preciat, Alise Zagare, Siu H.J. Chan, Maike K. Aurich, Catherine M. Clancy, Jennifer Modamio, John T. Sauls, Alberto Noronha, Aarash Bordbar, Benjamin Cousins, Diana C. El Assal, Luis V. Valcarcel, Inigo Apaolaza, Susan Ghaderi, Masoud Ahookhosh, Marouen Ben Guebila, Andrejs Kostromins, Nicolas Sompairac, Hoai M. Le, Ding Ma, Yuekai Sun, Lin Wang, James T. Yurkovich, Miguel A.P. Oliveira, Phan T. Vuong, Lemmer P. El Assal, Inna Kuperstein, Andrei Zinovyev, H. Scott Hinton, William A. Bryant, Francisco J. Aragon Artacho, Francisco J. Planes, Egils Stalidzans, Alejandro Maass, Santosh Vempala, Michael Hucka, Michael A. Saunders, Costas D. Maranas, Nathan E. Lewis, Thomas Sauter, Bernhard Ø. Palsson, Ines Thiele, Ronan M.T. Fleming, **Creation and analysis of biochemical constraint-based models: the COBRA Toolbox v3.0**, Nature Protocols, volume 14, pages 639–702, 2019 [doi.org/10.1038/s41596-018-0098-2](https://doi.org/10.1038/s41596-018-0098-2).