

Лабораторная работа №4 по курсу «Проектирование интеллектуальных систем»

Выполнил:
Хотин П.Ю.
ИУ5-24М

In [1]:

```
import keras
from keras.datasets import cifar10
from keras.preprocessing.image import ImageDataGenerator
from keras.models import Sequential
from keras.layers import Dense, Dropout, Activation, Flatten
from keras.layers import Conv2D, MaxPooling2D
import os
from keras.constraints import maxnorm
from keras.optimizers import SGD
```

Using TensorFlow backend.

In [13]:

```
from keras.callbacks import ModelCheckpoint, TensorBoard
import datetime
```

In [3]:

```
batch_size = 32
num_classes = 10
epochs = 5
num_predictions = 20
```

In [4]:

```
(x_train, y_train), (x_test, y_test) = cifar10.load_data()
print('x_train shape:', x_train.shape)
print(x_train.shape[0], 'train samples')
print(x_test.shape[0], 'test samples')
x_train = x_train.astype('float32')
x_test = x_test.astype('float32')
x_train = x_train / 255.0
x_test = x_test / 255.0
y_train = keras.utils.to_categorical(y_train, num_classes)
y_test = keras.utils.to_categorical(y_test, num_classes)
```

```
x_train shape: (50000, 32, 32, 3)
50000 train samples
10000 test samples
```

Создание базовой модели

In [5]:

```
def create_model():
    model = Sequential()
    model.add(Conv2D(32, (3, 3), input_shape=(32, 32, 3), padding='same', activation='relu',
kernel_constraint=maxnorm(3)))
    model.add(Dropout(0.2))
    model.add(Conv2D(64, (3, 3), activation='relu', padding='same', kernel_constraint=maxnorm(3)))
    model.add(MaxPooling2D(pool_size=(2, 2)))
    model.add(Conv2D(128, (3, 3), input_shape=(32, 32, 3), padding='same', activation='relu',
kernel_constraint=maxnorm(3)))
    model.add(MaxPooling2D(pool_size=(2, 2)))
    model.add(Dropout(0.2))
    model.add(Flatten())
    model.add(Dense(512, activation='relu', kernel_constraint=maxnorm(3)))
    model.add(Dropout(0.5))
    model.add(Dense(num_classes, activation='softmax'))
    lr = 0.01
    decay = lr/epochs
    sgd = SGD(lr=lr, momentum=0.9, decay=decay, nesterov=False)
    model.compile(loss='categorical_crossentropy', optimizer=sgd, metrics=['accuracy'])
    return model
```

In [6]:

```
model = create_model()
model.summary()
```

WARNING:tensorflow:From /Users/paulik/Универ/giis/env/lib/python3.7/site-packages/tensorflow_core/python/ops/resource_variable_ops.py:1630: calling BaseResourceVariable.__init__ (from tensorflow.python.ops.resource_variable_ops) with constraint is deprecated and will be removed in a future version.

Instructions for updating:

If using Keras pass *_constraint arguments to layers.

WARNING:tensorflow:From /Users/paulik/Универ/giis/env/lib/python3.7/site-packages/keras/backend/tensorflow_backend.py:4070: The name tf.nn.max_pool is deprecated. Please use tf.nn.max_pool2d instead.

Model: "sequential_1"

Layer (type)	Output Shape	Param #
conv2d_1 (Conv2D)	(None, 32, 32, 32)	896
dropout_1 (Dropout)	(None, 32, 32, 32)	0
conv2d_2 (Conv2D)	(None, 32, 32, 64)	18496
max_pooling2d_1 (MaxPooling2)	(None, 16, 16, 64)	0
conv2d_3 (Conv2D)	(None, 16, 16, 128)	73856
max_pooling2d_2 (MaxPooling2)	(None, 8, 8, 128)	0
dropout_2 (Dropout)	(None, 8, 8, 128)	0
flatten_1 (Flatten)	(None, 8192)	0
dense_1 (Dense)	(None, 512)	4194816
dropout_3 (Dropout)	(None, 512)	0
dense_2 (Dense)	(None, 10)	5130
Total params: 4,293,194		
Trainable params: 4,293,194		
Non-trainable params: 0		

Создание колбеков для чекпоинтов и тензорборда

In [19]:

```
checkpoint_path = "training_checkpoints/cp.ckpt"
checkpoint_dir = os.path.dirname(checkpoint_path)

# Создаем коллбек сохраняющий веса модели
cp_callback = ModelCheckpoint(filepath=checkpoint_path,
                              save_weights_only=True,
                              verbose=1, period=1)

log_dir = "logs/fit/" + datetime.datetime.now().strftime("%Y%m%d-%H%M%S")
tensorboard_callback = TensorBoard(log_dir=log_dir, histogram_freq=1)
```

In [20]:

```
model.fit(x_train,
          y_train,
          validation_data=(x_test, y_test),
          epochs=epochs,
          batch_size=batch_size,
          callbacks=[cp_callback, tensorboard_callback])
```

Train on 50000 samples, validate on 10000 samples

Epoch 1/5

50000/50000 [=====] - 144s 3ms/step - loss: 1.3515 - accuracy: 0.5139 - val_loss: 1.2078 - val_accuracy: 0.5714

Epoch 00001: saving model to training_checkpoints/cp.ckpt

WARNING:tensorflow:From /Users/paulik/Универ/giis/env/lib/python3.7/site-packages/keras/callbacks/tensorboard_v1.py:343: The name tf.Summary is deprecated. Please use tf.compat.v1.Summary instead.

Epoch 2/5

50000/50000 [=====] - 148s 3ms/step - loss: 1.2331 - accuracy: 0.5586 - val_loss: 1.1382 - val_accuracy: 0.5968

Epoch 00002: saving model to training_checkpoints/cp.ckpt

Epoch 3/5

50000/50000 [=====] - 150s 3ms/step - loss: 1.1496 - accuracy: 0.5888 - val_loss: 1.0749 - val_accuracy: 0.6157

Epoch 00003: saving model to training_checkpoints/cp.ckpt

Epoch 4/5

50000/50000 [=====] - 148s 3ms/step - loss: 1.0878 - accuracy: 0.6127 - val_loss: 1.0749 - val_accuracy: 0.6157

```


50000/50000 [=====] - 148s 3ms/step - loss: 1.0385 - accuracy: 0.6314 - v
al_loss: 1.0217 - val_accuracy: 0.6399

Epoch 00004: saving model to training_checkpoints/cp.ckpt
Epoch 5/5
50000/50000 [=====] - 148s 3ms/step - loss: 1.0385 - accuracy: 0.6314 - v
al_loss: 0.9857 - val_accuracy: 0.6484

Epoch 00005: saving model to training_checkpoints/cp.ckpt

Out[20]:
<keras.callbacks.callbacks.History at 0x136d04b10>

```



Сохранение полной модели

```

In [29]:
# os.getcwd()
save_dir = os.path.join(os.getcwd(), 'models')
print(save_dir)
model_name = 'modelpkh.h5'
model_path = os.path.join(save_dir, model_name)
model.save(model_path)
print('Saved trained model at %s ' % model_path)

```

```
/Users/paulik/Универ/giis/models
Saved trained model at /Users/paulik/Универ/giis/models/modelpkh.h5
```

In [30]:

```
# Score trained model.
def model_evaluate(model1):
    scores = model1.evaluate(x_test, y_test, verbose=1)
    print('Test loss:', scores[0])
    print('Test accuracy:', scores[1])
```

Проверка точности базовой модели без тренировки

In [17]:

```
#Ненатренированная модель
model2 = create_model()
model_evaluate(model2)
```

WARNING:tensorflow:From /Users/paulik/Универ/giis/env/lib/python3.7/site-packages/keras/backend/tensorflow_backend.py:422: The name tf.global_variables is deprecated. Please use tf.compat.v1.global_variables instead.

```
10000/10000 [=====] - 5s 520us/step
Test loss: 2.306235139465332
Test accuracy: 0.09300000220537186
```

Точность показала 9%

Теперь создадим базовую модель и загрузим веса из чекпоинтов, полученных в результате обучения

In [31]:

```
model_trained = create_model()
model_trained.load_weights(checkpoint_path)
model_evaluate(model_trained)
```

```
10000/10000 [=====] - 6s 579us/step
Test loss: 0.9856774023056031
Test accuracy: 0.6484000086784363
```

Точность на тестовой выборке составила 64%

Ответы на вопросы:

- 1) tensorboard --logdir logs/fit и далее перейти по ссылке
- 2) tf.keras.backend.clear_session() для tfv.2.1
- 3) Коллекция - это объект похожий на словарь, в котором мы храним элементы узлов графа. Например, в коллекцию сохраняется переменная измерения точности и входные элементы модели.
- 4) Для записи дефолтных метрик:

```
log_dir = "logs/fit/" + datetime.datetime.now().strftime("%Y%m%d-%H%M%S")
```

```
tensorboard_callback = TensorBoard(log_dir=log_dir, histogram_freq=1)
```

Для записи дополнительных статистик в цикле итерации эпох используются команды:

```
with train_summary_writer.as_default():
```

```
tf.summary.scalar('loss', train_loss.result(), step=epoch)
```

```
tf.summary.scalar('accuracy', train_accuracy.result(), step=epoch)
```

(для выборки обучения, в случае тестовой: test_summary_writer.as_default())

In []: