

Package ‘sejmRP’

September 7, 2015

Title An information about deputies and votings in Polish diet

Version 0.1

Date 2015-08-06

Author Piotr Smuda [aut, cre],Przemyslaw Biecek [aut],Tomasz Mikolajczyk [ctb]

Maintainer Piotr Smuda <piotrsmuda@gmail.com>

Description Set of functions that access information about deputies and votings in Polish diet from webpage <http://www.sejm.gov.pl/>.
The package was developed as a result of an internship in MI2 Group - <http://mi2.mini.pw.edu.pl/>, Faculty of Mathematics and Information Science, Warsaw University of Technology.

Depends R (>= 3.1.0)

License GPL-2

LazyLoad true

LazyData true

Imports DBI, dplyr, RPostgreSQL, rvest, stringi, XML

R topics documented:

create_database	1
deputies_add_new	3
deputies_create_table	4
deputies_get_data	5
deputies_get_ids	6
deputies_update_table	7
get_deputies_table	7
get_filtered_votes	8
get_statements_table	10
get_votes_table	11
get_votings_table	12
remove_database	13
statements_create_table	14
statements_get_statement	15
statements_get_statements_data	16

statements_update_table	17
votes_create_table	18
votes_get_clubs_links	19
votes_get_results	20
votes_match_deputies_ids	21
votes_update_table	22
votings_create_table	23
votings_get_date	24
votings_get_meetings_links	24
votings_get_meetings_table	25
votings_get_votings_links	26
votings_get_votings_table	27
votings_update_table	28

create_database	<i>Creating database</i>
-----------------	--------------------------

Description

Function `create_database` creates a database with four empty tables: `deputies`, `votings`, `votes`, `statements`.

Usage

```
create_database(dbname, user, password, host)
```

Arguments

<code>dbname</code>	name of database
<code>user</code>	name of user
<code>password</code>	password of database
<code>host</code>	name of host

Details

Created tables:

1. `deputies` with columns:
 - 1) `id_deputy` - deputy's id,
 - 2) `surname_name` - deputy's names and surnames,
2. `votings` with columns:
 - 1) `id_voting` - voting's id,
 - 2) `nr_meeting` - meeting's number,
 - 3) `date_meeting` - meeting's date,
 - 4) `nr_voting` - voting's number,
 - 5) `topic_voting` - voting's topic,
 - 6) `link_results` - link with voting's results,
3. `votes` with columns:
 - 1) `id_vote` - vote's id,
 - 2) `id_deputy` - deputy's id,
 - 3) `id_voting` - voting's id,
 - 4) `vote` - deputy's vote, one of: `'Za'`, `'Przeciw'`,

```

        'Wstrzymal sie', 'Nieobecny',
5) club - deputy's club,
4. statements with columns:
1) id_statement - statement's id, like:
   (meeting's number).(voting's number).(statement's number),
2) surname_name - author of statement,
3) date_statement - statement's date,
4) statement - content of statement.

```

Value

invisible NULL

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```

## Not run:
create_database(dbname, user, password, host)
## End(Not run)

```

deputies_add_new	<i>Adding new deputies to table</i>
------------------	-------------------------------------

Description

Function `deputies_add_new` adds new deputies to a table with deputies.

Usage

```
deputies_add_new(dbname, user, password, host, type, id)
```

Arguments

<code>dbname</code>	name of database
<code>user</code>	name of user
<code>password</code>	password of database
<code>host</code>	name of host
<code>type</code>	type of deputies which be add to table with deputies: active, inactive
<code>id</code>	id of deputies from which we start add new deputies

Details

Function `deputies_add_new` adds new deputies to a table with deputies. Also there is a choice between types of deputies, because on the page of Polish diet deputies are splitted into *active* and *inactive*. In addition id of the last added deputy in *deputies* table is needed.

Value

invisible NULL

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
deputies_add_new(dbname, user, password, host, 'active', id)
deputies_add_new(dbname, user, password, host, 'inactive', id)
## End(Not run)
```

```
deputies_create_table
```

Creating table with deputies

Description

Function `deputies_create_table` creates a table with deputies.

Usage

```
deputies_create_table(dbname, user, password, host)
```

Arguments

<code>dbname</code>	name of database
<code>user</code>	name of user
<code>password</code>	password of database
<code>host</code>	name of host

Value

invisible NULL

Note

Use only this function for first time, when the *deputies* table is empty. Then use `deputies_update_table`.
All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
deputies_create_table(dbname, user, password, host)
## End(Not run)
```

deputies_get_data *Getting data about deputies*

Description

Function `deputies_get_data` gets data about deputies.

Usage

```
deputies_get_data(type)
```

Arguments

`type` type of deputies which be add to table with deputies: active, inactive

Details

Function `deputies_get_data` gets deputies' ids and personal data like name and surname. Also there is a choice between types of deputies, because on the page of Polish diet deputies are splitted into *active* and *inactive*.

Value

data frame with two columns: `id_deputy`, `surname_name`

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
deputies_get_data('active')
deputies_get_data('inactive')
## End(Not run)
```

deputies_get_ids	<i>Getting deputies' ids</i>
------------------	------------------------------

Description

Function `deputies_get_ids` gets deputies' ids from *deputies* table.

Usage

```
deputies_get_ids(dbname, user, password, host,  
  windows = .Platform$OS.type == 'windows')
```

Arguments

<code>dbname</code>	name of database
<code>user</code>	name of user
<code>password</code>	password of database
<code>host</code>	name of host
<code>windows</code>	information of used operation system; default: <code>.Platform\$OS.type == 'windows'</code>

Details

Function `deputies_get_ids` gets deputies' ids from *deputies* table. As result of this function you get named character vector with ids, where their names are names and surnames of deputies. Because of encoding issue on Windows operation system, you need to select if you use Windows.

Value

named character vector

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:  
deputies_get_ids(dbname, user, password, host, TRUE)  
deputies_get_ids(dbname, user, password, host, FALSE)  
## End(Not run)
```

deputies_update_table
Updating table with deputies

Description

Function `deputies_update_table` updates a table with deputies.

Usage

```
deputies_update_table(dbname, user, password, host)
```

Arguments

dbname	name of database
user	name of user
password	password of database
host	name of host

Value

invisible NULL

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:  
deputies_update_table(dbname, user, password, host)  
## End(Not run)
```

`get_deputies_table` *Importing deputies table from a database*

Description

Function `get_deputies_table` imports deputies table from a database.

Usage

```
get_deputies_table(dbname = 'sejmrp', user = 'reader',  
  password = 'qux94874', host = 'services.mini.pw.edu.pl',  
  sorted_by_id = TRUE, windows = .Platform$OS.type == 'windows')
```

Arguments

dbname	name of database; default: 'sejmrp'
user	name of user; default: 'reader'
password	password of database; default: 'qux94874'
host	name of host; default: 'services.mini.pw.edu.pl'
sorted_by_id	information if table should be sorted by id; default: TRUE
windows	information of used operation system; default: .Platform\$OS.type == 'windows'

Details

Function `get_deputies_table` imports deputies table from a database. The result of this function is a data frame with deputies' data. Because of encoding issue on Windows operation system, you need to select if you use Windows.

Value

data frame

Note

Default parameters use privileges of 'reader'. It can only SELECT data from database. All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
deputies <- get_deputies_table()
dim(deputies)
# [1] 512  2
names(deputies)
# [1] 'id_deputy'      'surname_name'
## End(Not run)
```

`get_filtered_votes` *Retrieve filtered votes from a database*

Description

Function `get_filtered_votes` reads filtered votes from a database.

Usage

```
get_filtered_votes(dbname = 'sejmrp', user = 'reader',
  password = 'qux94874', host = 'services.mini.pw.edu.pl',
  windows = .Platform$OS.type == 'windows', clubs = character(0),
  dates = character(0), meetings = integer(0), votings = integer(0),
  deputies = character(0), topics = character(0))
```


Arguments

dbname	name of database; default: 'sejmrp'
user	name of user; default: 'reader'
password	password of database; default: 'qux94874'
host	name of host; default: 'services.mini.pw.edu.pl'
windows	information of used operation system; default: <code>.Platform\$OS.type == 'windows'</code>
clubs	names of clubs that will be taken to filter data from database; default: <code>character(0)</code>
dates	period of time that will be taken to filter data from database; default: <code>character(0)</code>
meetings	range of meetings' numbers that will be taken to filter data from database; default: <code>integer(0)</code>
votings	range of votings' numbers that will be taken to filter data from database; default: <code>integer(0)</code>
deputies	full names of deputies that will be taken to filter data from database; default: <code>character(0)</code>
topics	text patterns that will be taken to filter data from database; default: <code>character(0)</code>

Details

Function `get_filtered_votes` reads filtered votes from a database. The result of this function is an invisible data frame with statements' data.

Possible filters:

1. clubs - names of clubs. This filter is a character vector with elements like for example: 'PO', 'PiS', 'SLD'. It is possible to choose more than one club.
2. dates - period of time. This filter is a character vector with two elements in date format 'YYYY-MM-DD', where the first describes left boundary of period and the second right boundary. It is possible to choose only one day, just try the same date as first and second element of vector.
3. meetings - range of meetings' numbers. This filter is a integer vector with two elements, where the first describes a left boundary of range and the second a right boundary. It is possible to choose only one meeting, just try the same number as first and second element of vector.
4. votings - range of votings' numbers. This filter is a integer vector with two elements, where the first describes a left boundary of range and the second a right boundary. It is possible to choose only one voting, just try the same number as first and second element of vector.
5. deputies - full names of deputies. This filter is a character vector with full names of deputies in format: 'surname first_name second_name'. If you are not sure if the deputy you were thinking about has second name, try 'surname first_name' or just 'surname'. There is high probability that proper deputy will be chosen. It is possible to choose more than one deputy.
6. topics - text patterns. This filter is a character vector with text patterns of topics that you are interested about. Note that the votings' topics are written like sentences, so remember about case inflection of nouns and adjectives and use stems of words as patterns. For example if you want to find votings about education (in Polish: szkolnictwo) try 'szkolnictw'. It is possible to choose more than one pattern.

If you did not choose any filter, the whole database will be downloaded. Note that, due to data size ($\leq \sim 150$ MB) it may take few seconds / minutes to download all votes.

Because of encoding issue on Windows operation system, you also need to select if you use Windows.

Value

data frame with NULL

Note

Default parameters use privileges of 'reader'. It can only SELECT data from database.
All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
filtered_votes <- get_filtered_votes()
dim(filtered_votes)
# [1] 2741899      8
names(filtered_votes)
[1] 'surname_name' 'club' 'vote' 'id_voting' 'nr_meeting'
[6] 'nr_voting' 'date_meeting' 'topic_voting'
object.size(filtered_votes)
# 144250888 bytes
## End(Not run)
```

```
get_statements_table
```

Importing statements table from a database

Description

Function `get_statements_table` imports statements table from a database.

Usage

```
get_statements_table(dbname = 'sejmrp', user = 'reader',
  password = 'qux94874', host = 'services.mini.pw.edu.pl',
  sorted_by_id = TRUE, windows = .Platform$OS.type == 'windows')
```

Arguments

<code>dbname</code>	name of database; default: 'sejmrp'
<code>user</code>	name of user; default: 'reader'
<code>password</code>	password of database; default: 'qux94874'
<code>host</code>	name of host; default: 'services.mini.pw.edu.pl'
<code>sorted_by_id</code>	information if table should be sorted by id; default: TRUE
<code>windows</code>	information of used operation system; default: <code>.Platform\$OS.type == 'windows'</code>

Details

Function `get_statements_table` imports statements table from a database. The result of this function is a data frame with statements' data. Because of encoding issue on Windows operation system, you need to select if you use Windows.

Value

data frame

Note

Default parameters use privileges of 'reader'. It can only SELECT data from database. All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
statements <- get_statements_table()
dim(statements)
# [1] 42169      4
names(statements)
# [1] 'id_statement' 'surname_name' 'date_statement' 'statement'
## End(Not run)
```

get_votes_table	<i>Importing votes table from a database</i>
-----------------	--

Description

Function `get_votes_table` imports votes table from a database.

Usage

```
get_votes_table(dbname = 'sejmrp', user = 'reader',
  password = 'qux94874', host = 'services.mini.pw.edu.pl',
  sorted_by_id = TRUE, windows = .Platform$OS.type == 'windows')
```

Arguments

dbname	name of database; default: 'sejmrp'
user	name of user; default: 'reader'
password	password of database; default: 'qux94874'
host	name of host; default: 'services.mini.pw.edu.pl'
sorted_by_id	information if table should be sorted by id; default: TRUE
windows	information of used operation system; default: <code>.Platform\$OS.type == 'windows'</code>

Details

Function `get_votes_table` imports votes table from a database. The result of this function is a data frame with votes' data. Because of encoding issue on Windows operation system, you need to select if you use Windows.

Value

data frame

Note

Default parameters use privileges of 'reader'. It can only SELECT data from database.

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
votes <- get_votes_table()
dim(votes)
# [1] 2741899      5
names(votes)
# [1] 'id_vote'      'id_deputy'    'id_voting'    'vote'         'club'
# ' object.size(votes)
# 87767112 bytes
## End(Not run)
```

`get_votings_table` *Importing votings table from a database*

Description

Function `get_votings_table` imports votings table from a database.

Usage

```
get_votings_table(dbname = 'sejmrp', user = 'reader',
  password = 'qux94874', host = 'services.mini.pw.edu.pl',
  sorted_by_id = TRUE, windows = .Platform$OS.type == 'windows')
```

Arguments

<code>dbname</code>	name of database; default: 'sejmrp'
<code>user</code>	name of user; default: 'reader'
<code>password</code>	password of database; default: 'qux94874'
<code>host</code>	name of host; default: 'services.mini.pw.edu.pl'
<code>sorted_by_id</code>	information if table should be sorted by id; default: TRUE
<code>windows</code>	information of used operation system; default: <code>.Platform\$OS.type == 'windows'</code>

Details

Function `get_votings_table` imports votings table from a database. The result of this function is a data frame with votings' data. Because of encoding issue on Windows operation system, you need to select if you use Windows.

Value

data frame

Note

Default parameters use privileges of 'reader'. It can only SELECT data from database.

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
votings <- get_votings_table()
dim(votings)
# [1] 5969    6
names(votings)
# [1] 'id_voting'    'nr_meeting'    'date_meeting'
# [4] 'nr_voting'    'topic_voting'  'link_results'
## End(Not run)
```

remove_database	<i>Removing database</i>
-----------------	--------------------------

Description

Function `remove_database` remove whole database.

Usage

```
remove_database(dbname, user, password, host)
```

Arguments

dbname	name of database
user	name of user
password	password of database
host	name of host

Value

invisible NULL

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
remove_database(dbname, user, password, host)
## End(Not run)
```

```
statements_create_table
```

Creating table with deputies' statements

Description

Function `statements_create_table` creates a table with deputies' statements.

Usage

```
statements_create_table(dbname, user, password, host,
  home_page = 'http://www.sejm.gov.pl/Sejm7.nsf/')
```

Arguments

<code>dbname</code>	name of database
<code>user</code>	name of user
<code>password</code>	password of database
<code>host</code>	name of host
<code>home_page</code>	main page of polish diet: http://www.sejm.gov.pl/Sejm7.nsf/

Value

invisible NULL

Note

Use only this function for first time, when the *statements* table is empty. Then use `statements_update_table`. All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda, Tomasz Mikolajczyk

Examples

```
## Not run:
statements_create_table(dbname, user, password, host)
## End(Not run)
```

`statements_get_statement`*Getting statements*

Description

Function `statements_get_statement` gets statement's content.

Usage

```
statements_get_statement (page)
```

Arguments

<code>page</code>	deputy's statement's page
-------------------	---------------------------

Details

Function `statements_get_statement` gets statement's content. Example of page with deputy's statement: <http://www.sejm.gov.pl/Sejm7.nsf/wypowiedz.xsp?posiedzenie=15&dzien=1&wyp=008>

Value

character vector

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda, Tomasz Mikolajczyk

Examples

```
## Not run:
page <- paste0('http://www.sejm.gov.pl/Sejm7.nsf/',
               'wypowiedz.xsp?posiedzenie=15&dzien=1&wyp=008')
statements_get_statement (page)
## End(Not run)
```

```
statements_get_statements_data
```

Getting data about statements

Description

Function `statements_get_statements_data` gets data about statements.

Usage

```
statements_get_statements_data(statements_links,
  home_page = 'http://www.sejm.gov.pl/Sejm7.nsf/')
```

Arguments

<code>statements_links</code>	list of elements of XMLNodeSet class with statements' ids, links and their's authors
<code>home_page</code>	main page of polish diet: http://www.sejm.gov.pl/Sejm7.nsf/

Details

Function `statements_get_statements_data` gets data about statements like author, page with content of statement and it's id.

Value

data frame with three columns: names, `statements_links`, ids

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda, Tomasz Mikolajczyk

Examples

```
## Not run:
page <- html(paste0('http://www.sejm.gov.pl/Sejm7.nsf/',
  'wypowiedz.xsp?posiedzenie=15&dzien=1&wyp=0'))
page <- html_nodes(page, '.stenogram')
statements_links <- html_nodes(page, 'h2 a')
statements_get_statements_data(statements_links,
  home_page = 'http://www.sejm.gov.pl/Sejm7.nsf/')
## End(Not run)
```

`statements_update_table`*Updating table with deputies' statements*

Description

Function `statements_update_table` updates a table with deputies' statements.

Usage

```
statements_update_table(dbname, user, password, host,  
    home_page = 'http://www.sejm.gov.pl/Sejm7.nsf/')
```

Arguments

<code>dbname</code>	name of database
<code>user</code>	name of user
<code>password</code>	password of database
<code>host</code>	name of host
<code>home_page</code>	main page of polish diet: http://www.sejm.gov.pl/Sejm7.nsf/

Value

invisible NULL

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda, Tomasz Mikolajczyk

Examples

```
## Not run:  
statements_update_table(dbname, user, password, host)  
## End(Not run)
```

votes_create_table *Creating table with votes*

Description

Function `votes_create_table` creates a table with votes.

Usage

```
votes_create_table(dbname, user, password, host,  
  home_page = 'http://www.sejm.gov.pl/Sejm7.nsf/',  
  windows = .Platform$OS.type == 'windows')
```

Arguments

<code>dbname</code>	name of database
<code>user</code>	name of user
<code>password</code>	password of database
<code>host</code>	name of host
<code>home_page</code>	main page of polish diet: http://www.sejm.gov.pl/Sejm7.nsf/
<code>windows</code>	information of used operation system; default: <code>.Platform\$OS.type == 'windows'</code>

Value

invisible NULL

Note

Use only this function for first time, when the *votes* table is empty. Then use `votes_update_table`.

There is a possibility that someone's voice reader broke during voting and this situation is treated like this deputy was absent. Even if deputy made a decision, he's/she's vote is 'Nieobecny'.

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:  
home_page <- http://www.sejm.gov.pl/Sejm7.nsf/  
votes_create_table(dbname, user, password, host, home_page, TRUE)  
votes_create_table(dbname, user, password, host, home_page, FALSE)  
## End(Not run)
```

`votes_get_clubs_links`*Getting links with voting's results for each club*

Description

Function `votes_get_clubs_links` gets links with voting's results for each club from voting's page.

Usage

```
votes_get_clubs_links(home_page = 'http://www.sejm.gov.pl/Sejm7.nsf/',  
  page)
```

Arguments

<code>home_page</code>	main page of polish diet: http://www.sejm.gov.pl/Sejm7.nsf/
<code>page</code>	voting's page

Details

Function `votes_get_clubs_links` gets links with voting's results for each club from voting's page. Example of a voting's page: <http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=glosowania&NrKadencji=7&NrPosiedzenia=1&NrGlosowania=1>

Value

data frame with two columns: club, links

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:  
home_page <- 'http://www.sejm.gov.pl/Sejm7.nsf/'  
page <- paste0('http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?',  
  'symbol=glosowania&NrKadencji=7&NrPosiedzenia=1&NrGlosowania=1')  
votes_get_clubs_links(home_page, page)  
## End(Not run)
```

votes_get_results *Getting voting's results for each club*

Description

Function `votes_get_results` gets voting's results for each club.

Usage

```
votes_get_results(page)
```

Arguments

page	club's voting's results page
------	------------------------------

Details

Function `votes_get_results` gets voting's results for each club. Example of page with voting's results of PO club: <http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=klubglos&IdGlosowania=37494&KodKlubu=PO>

Value

data frame with two columns: deputy, vote

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
page <- paste0('http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?',
               'symbol=klubglos&IdGlosowania=37494&KodKlubu=PO')
votes_get_results(page)
votes_get_results(page)
## End(Not run)
```

votes_match_deputies_ids

Matching deputies to theirs' ids

Description

Function `votes_match_deputies_ids` matches deputies from voting's results page to theirs' ids from *deputies* table.

Usage

```
votes_match_deputies_ids(dbname, user, password, host, page,
  windows = .Platform$OS.type == 'windows')
```

Arguments

<code>dbname</code>	name of database
<code>user</code>	name of user
<code>password</code>	password of database
<code>host</code>	name of host
<code>page</code>	club's voting's results page
<code>windows</code>	information of used operation system; default: <code>.Platform\$OS.type == 'windows'</code>

Details

Function `votes_match_deputies_ids` matches deputies from voting's results page to theirs' ids from *deputies* table. The result of this function is a data frame with deputies' data, ids and votes. Because of encoding issue on Windows operation system, you need to select if you use Windows. Example of page with voting's results of PO club: <http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=klubglos&IdGlosowania=37494&KodKlubu=PO>

Value

data frame with three columns: deputy, vote, id

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
page <- paste0('http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?',
  'symbol=klubglos&IdGlosowania=37494&KodKlubu=PO')
votes_match_deputies_ids(dbname, user, password, host, page, TRUE)
votes_match_deputies_ids(dbname, user, password, host, page, FALSE)
## End(Not run)
```

votes_update_table *Updating table with votes*

Description

Function votes_update_table updates a table with votes.

Usage

```
votes_update_table(dbname, user, password, host,
  home_page = 'http://www.sejm.gov.pl/Sejm7.nsf/',
  windows = .Platform$OS.type == 'windows')
```

Arguments

dbname	name of database
user	name of user
password	password of database
host	name of host
home_page	main page of polish diet: http://www.sejm.gov.pl/Sejm7.nsf/
windows	information of used operation system; default: <code>.Platform\$OS.type == 'windows'</code>

Value

invisible NULL

Note

There is a possibility that someone's voice reader broke during voting and this situation is treated like this deputy was absent. Even if deputy made a decision, he's/she's vote is 'Nieobecny'.

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
home_page <- http://www.sejm.gov.pl/Sejm7.nsf/
votes_update_table(dbname, user, password, host, home_page, TRUE)
votes_update_table(dbname, user, password, host, home_page, FALSE)
## End(Not run)
```

votings_create_table

Creating table with votings

Description

Function `votings_create_table` creates a table with votings.

Usage

```
votings_create_table(dbname, user, password, host,
  home_page = 'http://www.sejm.gov.pl/Sejm7.nsf/', page =
  'http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=posglos&NrKadencji=7')
```

Arguments

<code>dbname</code>	name of database
<code>user</code>	name of user
<code>password</code>	password of database
<code>host</code>	name of host
<code>home_page</code>	main page of polish diet: http://www.sejm.gov.pl/Sejm7.nsf/
<code>page</code>	page with votings in polish diet: http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=posglos&NrKadencji=7

Value

invisible NULL

Note

Use only this function for first time, when the *votings* table is empty. Then use `votings_update_table`.

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
votings_create_table(dbname, user, password, host)
## End(Not run)
```

votings_get_date	<i>Getting date of meeting</i>
------------------	--------------------------------

Description

Function `votings_get_date` gets a date of meeting.

Usage

```
votings_get_date (page)
```

Arguments

page	meeting's page
------	----------------

Details

Example of a meeting's page: <http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=listaglos&IdDnia=1179>

Value

date in format YYYY-MM-DD as character

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
page <- 'http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=listaglos&IdDnia=1179'
votings_get_date (page)
## End (Not run)
```

votings_get_meetings_links	<i>Getting meetings' links</i>
----------------------------	--------------------------------

Description

Function `votings_get_meetings_links` gets meetings' links.

Usage

```
votings_get_meetings_links (
  home_page = 'http://www.sejm.gov.pl/Sejm7.nsf/', page =
  'http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=posglos&NrKadencji=7')
```


Arguments

home_page	main page of polish diet: http://www.sejm.gov.pl/Sejm7.nsf/
page	page with votings in polish diet: http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=posglos&NrKadencji=7

Value

character vector

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:  
votings_get_meetings_links()  
## End(Not run)
```

votings_get_meetings_table
Getting meetings' table

Description

Function `votings_get_meetings_table` gets meetings' table.

Usage

```
votings_get_meetings_table(page =  
  'http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=posglos&NrKadencji=7')
```

Arguments

page	page with votings in polish diet: http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=posglos&NrKadencji=7
------	---

Details

Function `votings_get_meetings_table` gets meetings' table. The result of this function is a data frame with three columns, where the first includes numbers of meetings, the second theirs' dates in Polish and the third is with numbers of votings on each meeting.

Value

data frame with three unnamed columns

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
votings_get_meetings_table()
## End(Not run)
```

```
votings_get_votings_links
      Getting votings' links
```

Description

Function `votings_get_votings_links` gets votings' links from meeting's page.

Usage

```
votings_get_votings_links(home_page = 'http://www.sejm.gov.pl/Sejm7.nsf/',
  page)
```

Arguments

<code>home_page</code>	main page of polish diet: http://www.sejm.gov.pl/Sejm7.nsf/
<code>page</code>	meeting's page

Details

Example of a meeting's page: <http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=listaglos&IdDnia=1179>

Value

character vector

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
home_page <- 'http://www.sejm.gov.pl/Sejm7.nsf/'
page <- 'http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=listaglos&IdDnia=1179'
votings_get_votings_links(home_page, page)
## End(Not run)
```

votings_get_votings_table
Getting votings' table

Description

Function `votings_get_votings_table` gets votings' table from meeting's page.

Usage

```
votings_get_votings_table (page)
```

Arguments

page	meeting's page
------	----------------

Details

Function `votings_get_votings_table` gets votings' table from meeting's page. Example of a meeting's page: <http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=listaglos&IdDnia=1179>. The result of this function is a data frame with three columns, where the first includes numbers of votings, the second voting's time and the third is with voting's topics.

Value

data frame with three columns: Nr, Godzina (Time), Temat (Topic)

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:  
page <- 'http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=listaglos&IdDnia=1179'  
votings_get_votings_table (page)  
## End (Not run)
```

`votings_update_table`*Updating table with votings*

Description

Function `votings_update_table` updates table with votings.

Usage

```
votings_update_table(dbname, user, password, host,  
  home_page='http://www.sejm.gov.pl/Sejm7.nsf/', page=  
  'http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=posglos&NrKadencji=7')
```

Arguments

<code>dbname</code>	name of database
<code>user</code>	name of user
<code>password</code>	password of database
<code>host</code>	name of host
<code>home_page</code>	main page of polish diet: http://www.sejm.gov.pl/Sejm7.nsf/
<code>page</code>	page with votings in polish diet: http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=posglos&NrKadencji=7

Value

invisible NULL

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:  
votings_update_table(dbname, user, password, host)  
## End(Not run)
```