

Package ‘sejmRP’

January 3, 2016

Title An Information About Deputies and Votings in Polish Diet from seventh to eighth term of office

Version 1.3

Date 2016-01-03

Maintainer Piotr Smuda <piotrsmuda@gmail.com>

Description Set of functions that access information about deputies and votings in Polish diet from webpage <http://www.sejm.gov.pl/>. The package was developed as a result of an internship in MI2 Group - <http://mi2.mini.pw.edu.pl/>, Faculty of Mathematics and Information Science, Warsaw University of Technology.

BugReports <http://github.com/mi2-warsaw/sejmRP/issues>

Depends R (>= 3.1.0)

License GPL-2

LazyLoad true

LazyData true

Imports DBI, dplyr, RPostgreSQL, rvest, stringi, XML, xml2

RoxygenNote 5.0.1

NeedsCompilation no

Author Piotr Smuda [aut, cre],
Przemysław Biecek [aut],
Tomasz Mikołajczyk [ctb]

R topics documented:

create_database	2
deputies_add_new	3
deputies_create_table	4
deputies_get_data	5
deputies_get_ids	6
deputies_update_table	7
get_deputies_table	8
get_filtered_votes	9
get_statements_table	11
get_votes_table	12
get_votings_table	13
remove_database	14

safe_html	15
safe_readHTMLTable	15
statements_create_table	16
statements_get_statement	17
statements_get_statements_data	18
statements_get_statements_table	19
statements_update_table	20
votes_create_table	21
votes_get_clubs_links	22
votes_get_results	23
votes_match_deputies_ids	24
votes_update_table	25
votings_create_table	26
votings_get_date	27
votings_get_meetings_links	27
votings_get_meetings_table	28
votings_get_votings_links	29
votings_get_votings_table	30
votings_update_table	31

Index **32**

create_database	<i>Creating database</i>
-----------------	--------------------------

Description

Function create_database creates a database with four empty tables: deputies, votings, votes, statements.

Usage

```
create_database(dbname, user, password, host)
```

Arguments

dbname	name of database
user	name of user
password	password of database
host	name of host

Details

Created tables:

1. deputies with columns:

- 1) id_deputy - deputy's id,
- 2) nr_term_of_office - Polish Diet's number of term of office,
- 3) surname_name - deputy's names and surnames,

2. votings with columns:

- 1) id_voting - voting's id,
- 2) nr_term_of_office - Polish Diet's number of term of office,

- 3) nr_meeting - meeting's number,
- 4) date_meeting - meeting's date,
- 5) nr_voting - voting's number,
- 6) topic_voting - voting's topic,
- 7) link_results - link with voting's results,
- 3. votes with columns:
 - 1) id_vote - vote's id,
 - 2) nr_term_of_office - Polish Diet's number of term of office,
 - 3) id_deputy - deputy's id,
 - 4) id_voting - voting's id,
 - 5) vote - deputy's vote, one of: 'Za', 'Przeciw',
'Wstrzymal sie', 'Nieobecny',
 - 6) club - deputy's club,
- 4. statements with columns:
 - 1) id_statement - statement's id, like:
(meeting's number).(voting's number).(statement's number),
 - 2) nr_term_of_office - Polish Diet's number of term of office,
 - 3) surname_name - author of statement,
 - 4) date_statement - statement's date,
 - 5) titles_order_points - title of order points,
 - 6) statement - content of statement.

Value

invisible NULL

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
create_database(dbname, user, password, host)
## End(Not run)
```

deputies_add_new	<i>Adding new deputies to table</i>
------------------	-------------------------------------

Description

Function `deputies_add_new` adds new deputies to a table with deputies.

Usage

```
deputies_add_new(dbname, user, password, host, type, id,
  nr_term_of_office = 8)
```

Arguments

dbname	name of database
user	name of user
password	password of database
host	name of host
type	type of deputies which be add to table with deputies: active, inactive
id	id of deputies from which we start add new deputies
nr_term_of_office	number of term of office of Polish Diet; default: 8

Details

Function `deputies_add_new` adds new deputies to a table with deputies. Also there is a choice between types of deputies, because on the page of Polish diet deputies are splitted into *active* and *inactive*. In addition id of the last added deputy in *deputies* table is needed.

Value

invisible NULL

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
deputies_add_new(dbname, user, password, host, 'active', id)
deputies_add_new(dbname, user, password, host, 'inactive', id)
## End(Not run)
```

`deputies_create_table` *Creating table with deputies*

Description

Function `deputies_create_table` creates a table with deputies.

Usage

```
deputies_create_table(dbname, user, password, host,
  nr_term_of_office = 8)
```

Arguments

dbname	name of database
user	name of user
password	password of database
host	name of host
nr_term_of_office	number of term of office of Polish Diet; default: 8

Value

invisible NULL

Note

Use only this function for first time, when the *deputies* table is empty. Then use `deputies_update_table`. All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
deputies_create_table(dbname, user, password, host)
## End(Not run)
```

deputies_get_data	<i>Getting data about deputies</i>
-------------------	------------------------------------

Description

Function `deputies_get_data` gets data about deputies.

Usage

```
deputies_get_data(type, nr_term_of_office = 8)
```

Arguments

type	type of deputies which be add to table with deputies: active, inactive
nr_term_of_office	number of term of office of Polish Diet; default: 8

Details

Function `deputies_get_data` gets deputies' ids and personal data like name and surname. Also there is a choice between types of deputies, because on the page of Polish diet deputies are splitted into *active* and *inactive*.

Value

data frame with two columns: id_deputy, surname_name

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
deputies_get_data('active')
deputies_get_data('inactive')
## End(Not run)
```

deputies_get_ids	<i>Getting deputies' ids</i>
------------------	------------------------------

Description

Function deputies_get_ids gets deputies' ids from *deputies* table.

Usage

```
deputies_get_ids(dbname, user, password, host,
  nr_term_of_office = 8, windows = .Platform$OS.type == 'windows')
```

Arguments

dbname	name of database
user	name of user
password	password of database
host	name of host
nr_term_of_office	number of term of office of Polish Diet; default: 8
windows	information of used operation system; default: .Platform\$OS.type == 'windows'

Details

Function deputies_get_ids gets deputies' ids from *deputies* table. As result of this function you get named character vector with ids, where their names are names and surnames of deputies. Because of encoding issue on Windows operation system, you need to select if you use Windows.

Value

named character vector

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
deputies_get_ids(dbname, user, password, host, TRUE)
deputies_get_ids(dbname, user, password, host, FALSE)
## End(Not run)
```

deputies_update_table *Updating table with deputies*

Description

Function `deputies_update_table` updates a table with deputies.

Usage

```
deputies_update_table(dbname, user, password, host,
  nr_term_of_office = 8)
```

Arguments

<code>dbname</code>	name of database
<code>user</code>	name of user
<code>password</code>	password of database
<code>host</code>	name of host
<code>nr_term_of_office</code>	number of term of office of Polish Diet; default: 8

Value

invisible NULL

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
deputies_update_table(dbname, user, password, host)
## End(Not run)
```

get_deputies_table	<i>Importing deputies table from a database</i>
--------------------	---

Description

Function get_deputies_table imports deputies table from a database.

Usage

```
get_deputies_table(dbname = 'sejmrp', user = 'reader',
  password = 'qux94874', host = 'services.mini.pw.edu.pl',
  sorted_by_id = TRUE, windows = .Platform$OS.type == 'windows')
```

Arguments

dbname	name of database; default: 'sejmrp'
user	name of user; default: 'reader'
password	password of database; default: 'qux94874'
host	name of host; default: 'services.mini.pw.edu.pl'
sorted_by_id	information if table should be sorted by id; default: TRUE
windows	information of used operation system; default: .Platform\$OS.type == 'windows'

Details

Function get_deputies_table imports deputies table from a database. The result of this function is a data frame with deputies' data. Because of encoding issue on Windows operation system, you need to select if you use Windows.

Value

data frame

Note

Default parameters use privileges of 'reader'. It can only SELECT data from database.
All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
deputies <- get_deputies_table()
dim(deputies)
# [1] 983 3
names(deputies)
# [1] 'id_deputy' 'nr_term_of_office' 'surname_name'
## End(Not run)
```

get_filtered_votes	<i>Retrieve filtered votes from a database</i>
--------------------	--

Description

Function `get_filtered_votes` reads filtered votes from a database.

Usage

```
get_filtered_votes(dbname = 'sejmrp', user = 'reader',
  password = 'qux94874', host = 'services.mini.pw.edu.pl',
  windows = .Platform$OS.type == 'windows', clubs = character(0),
  dates = character(0), terms_of_office = integer(0),
  meetings = integer(0), votings = integer(0),
  deputies = character(0), topics = character(0))
```

Arguments

<code>dbname</code>	name of database; default: 'sejmrp'
<code>user</code>	name of user; default: 'reader'
<code>password</code>	password of database; default: 'qux94874'
<code>host</code>	name of host; default: 'services.mini.pw.edu.pl'
<code>windows</code>	information of used operation system; default: <code>.Platform\$OS.type == 'windows'</code>
<code>clubs</code>	names of clubs that will be taken to filter data from database; default: <code>character(0)</code>
<code>dates</code>	period of time that will be taken to filter data from database; default: <code>character(0)</code>
<code>terms_of_office</code>	range of terms of office's numbers that will be taken to filter data from database; default: <code>integer(0)</code>
<code>meetings</code>	range of meetings' numbers that will be taken to filter data from database; default: <code>integer(0)</code>
<code>votings</code>	range of votings' numbers that will be taken to filter data from database; default: <code>integer(0)</code>
<code>deputies</code>	full names of deputies that will be taken to filter data from database; default: <code>character(0)</code>
<code>topics</code>	text patterns that will be taken to filter data from database; default: <code>character(0)</code>

Details

Function `get_filtered_votes` reads filtered votes from a database. The result of this function is an invisible data frame with statements' data.

Possible filters:

1. `clubs` - names of clubs. This filter is a character vector with elements like for example: 'PO', 'PiS', 'SLD'. It is possible to choose more than one club.
2. `dates` - period of time. This filter is a character vector with two elements in date format 'YYYY-MM-DD', where the first describes left boundary of period and the second right boundary. It is possible to choose only one day, just try the same date as first and second element of vector.

3. terms_of_office - range of terms of office's numbers. This filter is a integer vector with two elements, where the first describes a left boundary of range and the second a right boundary. It is possible to choose only one term of office, just try the same number as first and second element of vector.
4. meetings - range of meetings' numbers. This filter is a integer vector with two elements, where the first describes a left boundary of range and the second a right boundary. It is possible to choose only one meeting, just try the same number as first and second element of vector.
5. votings - range of votings' numbers. This filter is a integer vector with two elements, where the first describes a left boundary of range and the second a right boundary. It is possible to choose only one voting, just try the same number as first and second element of vector.
6. deputies - full names of deputies. This filter is a character vector with full names of deputies in format: 'surname first_name second_name'. If you are not sure if the deputy you were thinking about has second name, try 'surname first_name' or just 'surname'. There is high probability that proper deputy will be chosen. It is possible to choose more than one deputy.
7. topics - text patterns. This filter is a character vector with text patterns of topics that you are interested about. Note that the votings' topics are written like sentences, so remember about case inflection of nouns and adjectives and use stems of words as patterns. For example if you want to find votings about education (in Polish: szkolnictwo) try 'szkolnictw'. It is possible to choose more than one pattern.

If you did not choose any filter, the whole database will be downloaded. Note that, due to data size ($\leq \sim 150$ MB) it may take few seconds / minutes to download all votes.

Because of encoding issue on Windows operation system, you also need to select if you use Windows.

Value

data frame with NULL

Note

Default parameters use privileges of 'reader'. It can only SELECT data from database.

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
filtered_votes <- get_filtered_votes()
dim(filtered_votes)
# [1] 2826483      9
names(filtered_votes)
[1] 'surname_name' 'nr_term_of_office' 'club' 'vote' 'id_voting'
[6] 'nr_meeting' 'nr_voting' 'date_meeting' 'topic_voting'
object.size(filtered_votes)
# 148694336 bytes
## End(Not run)
```

get_statements_table *Importing statements table from a database*

Description

Function get_statements_table imports statements table from a database.

Usage

```
get_statements_table(dbname = 'sejmrp', user = 'reader',  
  password = 'qux94874', host = 'services.mini.pw.edu.pl',  
  sorted_by_id = TRUE, windows = .Platform$OS.type == 'windows')
```

Arguments

dbname	name of database; default: 'sejmrp'
user	name of user; default: 'reader'
password	password of database; default: 'qux94874'
host	name of host; default: 'services.mini.pw.edu.pl'
sorted_by_id	information if table should be sorted by id; default: TRUE
windows	information of used operation system; default: .Platform\$OS.type == 'windows'

Details

Function get_statements_table imports statements table from a database. The result of this function is a data frame with statements' data. Because of encoding issue on Windows operation system, you need to select if you use Windows.

Value

data frame

Note

Default parameters use privileges of 'reader'. It can only SELECT data from database. All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:  
statements <- get_statements_table()  
dim(statements)  
# [1] 43432 6  
names(statements)  
# [1] 'id_statement' 'nr_term_of_office' 'surname_name'  
# [4] 'date_statement' 'titles_order_points' 'statement'  
## End(Not run)
```

get_votes_table	<i>Importing votes table from a database</i>
-----------------	--

Description

Function `get_votes_table` imports votes table from a database.

Usage

```
get_votes_table(dbname = 'sejmrp', user = 'reader',
  password = 'qux94874', host = 'services.mini.pw.edu.pl',
  sorted_by_id = TRUE, windows = .Platform$OS.type == 'windows')
```

Arguments

<code>dbname</code>	name of database; default: 'sejmrp'
<code>user</code>	name of user; default: 'reader'
<code>password</code>	password of database; default: 'qux94874'
<code>host</code>	name of host; default: 'services.mini.pw.edu.pl'
<code>sorted_by_id</code>	information if table should be sorted by id; default: TRUE
<code>windows</code>	information of used operation system; default: <code>.Platform\$OS.type == 'windows'</code>

Details

Function `get_votes_table` imports votes table from a database. The result of this function is a data frame with votes' data. Because of encoding issue on Windows operation system, you need to select if you use Windows.

Value

data frame

Note

Default parameters use privileges of 'reader'. It can only SELECT data from database.
All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
votes <- get_votes_table()
dim(votes)
# [1] 2826483 6
names(votes)
# [1] 'id_vote' 'nr_term_of_office' 'id_deputy' 'id_voting' 'vote' 'club'
object.size(votes)
# 90474040 bytes
```

```
## End(Not run)
```

get_votings_table	<i>Importing votings table from a database</i>
-------------------	--

Description

Function get_votings_table imports votings table from a database.

Usage

```
get_votings_table(dbname = 'sejmrp', user = 'reader',  
  password = 'qux94874', host = 'services.mini.pw.edu.pl',  
  sorted_by_id = TRUE, windows = .Platform$OS.type == 'windows')
```

Arguments

dbname	name of database; default: 'sejmrp'
user	name of user; default: 'reader'
password	password of database; default: 'qux94874'
host	name of host; default: 'services.mini.pw.edu.pl'
sorted_by_id	information if table should be sorted by id; default: TRUE
windows	information of used operation system; default: .Platform\$OS.type == 'windows'

Details

Function get_votings_table imports votings table from a database. The result of this function is a data frame with votings' data. Because of encoding issue on Windows operation system, you need to select if you use Windows.

Value

data frame

Note

Default parameters use privileges of 'reader'. It can only SELECT data from database.

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
votings <- get_votings_table()
dim(votings)
# [1] 6212 7
names(votings)
# [1] 'id_voting' 'nr_term_of_office' 'nr_meeting'
# [4] 'date_meeting' 'nr_voting' 'topic_voting'
# [7] 'link_results'
## End(Not run)
```

remove_database	<i>Removing database</i>
-----------------	--------------------------

Description

Function remove_database remove whole database.

Usage

```
remove_database(dbname, user, password, host)
```

Arguments

dbname	name of database
user	name of user
password	password of database
host	name of host

Value

invisible NULL

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
remove_database(dbname, user, password, host)
## End(Not run)
```

safe_html	<i>Safe html scrapping</i>
-----------	----------------------------

Description

Function safe_html tries to download the URL several times.

Usage

```
safe_html(page, time = 60, attempts = 10)
```

Arguments

page	requested URL
time	sleep interval after each failure
attempts	max number of tries (if there is a problem with connection)

Details

Function safe_html performs 10 (by default) attempts to download the URL and waits 60sec (by default) after each failure

Value

character vector

Author(s)

Przemyslaw Biecek

Examples

```
## Not run:
page <- paste0('http://www.sejm.gov.pl/Sejm7.nsf/',
               'wypowiedz.xsp?posiedzenie=15&dzien=1&wyp=008')
safe_html(page)
## End(Not run)
```

safe_readHTMLTable	<i>Safe html table scrapping</i>
--------------------	----------------------------------

Description

Function safe_readHTMLTable tries to download the table from given URL several times.

Usage

```
safe_readHTMLTable(..., time = 60, attempts = 10)
```

Arguments

...	arguments that will be passed to readHTMLTable
time	sleep interval after each failure
attempts	max number of tries (if there is a problem with connection)

Details

Function safe_readHTMLTable performs 10 (by default) attempts to download the URL and waits 60sec (by default) after each failure

Value

character vector

Author(s)

Przemyslaw Biecek

Examples

```
## Not run:
page <- paste0('http://www.sejm.gov.pl/Sejm7.nsf/',
               'posiedzenie.xsp?posiedzenie=99&dzien=2')
safe_readHTMLTable(page)
## End(Not run)
```

```
statements_create_table
```

Creating table with deputies' statements

Description

Function statements_create_table creates a table with deputies' statements.

Usage

```
statements_create_table(dbname, user, password, host,
                        nr_term_of_office = 8)
```

Arguments

dbname	name of database
user	name of user
password	password of database
host	name of host
nr_term_of_office	number of term of office of Polish Diet; default: 8

Value

invisible NULL

Note

Use only this function for first time, when the *statements* table is empty. Then use *statements_update_table*. All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda, Tomasz Mikolajczyk

Examples

```
## Not run:
statements_create_table(dbname, user, password, host)
## End(Not run)
```

statements_get_statement

Getting statements

Description

Function *statements_get_statement* gets statement's content.

Usage

```
statements_get_statement(page, ...)
```

Arguments

page	deputy's statement's page
...	other arguments, that will be passed to <i>safe_html()</i>

Details

Function *statements_get_statement* gets statement's content. Example of page with deputy's statement: <http://www.sejm.gov.pl/Sejm7.nsf/wypowiedz.xsp?posiedzenie=15&dzien=1&wyp=008>

Value

character vector

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda, Tomasz Mikolajczyk

Examples

```
## Not run:
page <- paste0('http://www.sejm.gov.pl/Sejm7.nsf/',
               'wypowiedz.xsp?posiedzenie=15&dzien=1&wyp=008')
statements_get_statement(page)
## End(Not run)
```

statements_get_statements_data

Getting data about statements

Description

Function statements_get_statements_data gets data about statements.

Usage

```
statements_get_statements_data(statements_links,
                               home_page = 'http://www.sejm.gov.pl/')
```

Arguments

statements_links	list of elements of XMLNodeSet class with statements' ids, links and their's authors
home_page	main page of polish diet: http://www.sejm.gov.pl/

Details

Function statements_get_statements_data gets data about statements like author, page with content of statement and it's id.

Value

data frame with three columns: names, statements_links, ids

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda, Tomasz Mikołajczyk

Examples

```
## Not run:
page <- safe_html(paste0('http://www.sejm.gov.pl/Sejm7.nsf/',
                          'wypowiedz.xsp?posiedzenie=15&dzien=1&wyp=0'))
page <- html_nodes(page, '.stenogram')
statements_links <- html_nodes(page, 'h2 a')
statements_get_statements_data(statements_links,
                               home_page = 'http://www.sejm.gov.pl/Sejm7.nsf/')
## End(Not run)
```

statements_get_statements_table

Getting statements' table

Description

Function statements_get_statements_table gets statements' table from meeting's page.

Usage

```
statements_get_statements_table(page)
```

Arguments

page meeting's page

Details

Function statements_get_statements_table gets statements' table. from meeting's page. Example of a meeting's page: <http://www.sejm.gov.pl/Sejm7.nsf/posiedzenie.xsp?posiedzenie=99&dzien=2> The result of this function is a data frame with three columns, where the first includes author of statement, the second the number of order point and the third is a title of order point.

Value

data frame with three unnamed columns

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
page <- 'http://www.sejm.gov.pl/Sejm7.nsf/posiedzenie.xsp?posiedzenie=99&dzien=2'
statements_get_statements_table(page)
## End(Not run)
```

`statements_update_table`*Updating table with deputies' statements*

Description

Function `statements_update_table` updates a table with deputies' statements.

Usage

```
statements_update_table(dbname, user, password, host,  
                        nr_term_of_office = 8, verbose = FALSE)
```

Arguments

<code>dbname</code>	name of database
<code>user</code>	name of user
<code>password</code>	password of database
<code>host</code>	name of host
<code>nr_term_of_office</code>	number of term of office of Polish Diet; default: 8
<code>verbose</code>	if TRUE then additional info will be printed

Value

invisible NULL

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda, Tomasz Mikolajczyk

Examples

```
## Not run:  
statements_update_table(dbname, user, password, host)  
## End(Not run)
```

votes_create_table	<i>Creating table with votes</i>
--------------------	----------------------------------

Description

Function votes_create_table creates a table with votes.

Usage

```
votes_create_table(dbname, user, password, host,  
  nr_term_of_office = 8, windows = .Platform$OS.type == 'windows')
```

Arguments

dbname	name of database
user	name of user
password	password of database
host	name of host
nr_term_of_office	number of term of office of Polish Diet; default: 8
windows	information of used operation system; default: .Platform\$OS.type == 'windows'

Value

invisible NULL

Note

Use only this function for first time, when the *votes* table is empty. Then use votes_update_table.

There is a possibility that someone's voice reader broke during voting and this situation is treated like this deputy was absent. Even if deputy made a decision, he's/she's vote is 'Nieobecny'.

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:  
votes_create_table(dbname, user, password, host, 7, TRUE)  
votes_create_table(dbname, user, password, host, 7, FALSE)  
## End(Not run)
```

votes_get_clubs_links *Getting links with voting's results for each club*

Description

Function votes_get_clubs_links gets links with voting's results for each club from voting's page.

Usage

```
votes_get_clubs_links(home_page = 'http://www.sejm.gov.pl/Sejm8.nsf/',  
  page)
```

Arguments

home_page	main page of polish diet: http://www.sejm.gov.pl/Sejm8.nsf/
page	voting's page

Details

Function votes_get_clubs_links gets links with voting's results for each club from voting's page.
Example of a voting's page: <http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=glosowania&NrKadencji=7&NrPosiedzenia=1&NrGlosowania=1>

Value

data frame with two columns: club, links

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:  
home_page <- 'http://www.sejm.gov.pl/Sejm7.nsf/'  
page <- paste0('http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?',  
  'symbol=glosowania&NrKadencji=7&NrPosiedzenia=1&NrGlosowania=1')  
votes_get_clubs_links(home_page, page)  
## End(Not run)
```

votes_get_results	<i>Getting voting's results for each club</i>
-------------------	---

Description

Function votes_get_results gets voting's results for each club.

Usage

```
votes_get_results(page)
```

Arguments

page	club's voting's results page
------	------------------------------

Details

Function votes_get_results gets voting's results for each club. Example of page with voting's results of PO club: <http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=klubglos&IdGlosowania=37494&KodKlubu=PO>

Value

data frame with two columns: deputy, vote

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
page <- paste0('http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?',
               'symbol=klubglos&IdGlosowania=37494&KodKlubu=PO')
votes_get_results(page)
## End(Not run)
```

`votes_match_deputies_ids`*Matching deputies to theirs' ids*

Description

Function `votes_match_deputies_ids` matches deputies from voting's results page to theirs' ids from *deputies* table.

Usage

```
votes_match_deputies_ids(dbname, user, password, host, page,  
  nr_term_of_office = 8, windows = .Platform$OS.type == 'windows')
```

Arguments

<code>dbname</code>	name of database
<code>user</code>	name of user
<code>password</code>	password of database
<code>host</code>	name of host
<code>page</code>	club's voting's results page
<code>nr_term_of_office</code>	number of term of office of Polish Diet; default: 8
<code>windows</code>	information of used operation system; default: <code>.Platform\$OS.type == 'windows'</code>

Details

Function `votes_match_deputies_ids` matches deputies from voting's results page to theirs' ids from *deputies* table. The result of this function is a data frame with deputies' data, ids and votes. Because of encoding issue on Windows operation system, you need to select if you use Windows. Example of page with voting's results of PO club: <http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=klubglos&IdGlosowania=37494&KodKlubu=PO>

Value

data frame with three columns: deputy, vote, id

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
page <- paste0('http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?',
               'symbol=klubglos&IdGlosowania=37494&KodKlubu=P0')
votes_match_deputies_ids(dbname, user, password, host, page, 7, TRUE)
votes_match_deputies_ids(dbname, user, password, host, page, 7, FALSE)
## End(Not run)
```

votes_update_table	<i>Updating table with votes</i>
--------------------	----------------------------------

Description

Function votes_update_table updates a table with votes.

Usage

```
votes_update_table(dbname, user, password, host,
  nr_term_of_office = 8, windows = .Platform$OS.type == 'windows',
  verbose = FALSE)
```

Arguments

dbname	name of database
user	name of user
password	password of database
host	name of host
nr_term_of_office	number of term of office of Polish Diet; default: 8
windows	information of used operation system; default: .Platform\$OS.type == 'windows'
verbose	if TRUE then additional info will be printed

Value

invisible NULL

Note

There is a possibility that someone's voice reader broke during voting and this situation is treated like this deputy was absent. Even if deputy made a decision, he's/she's vote is 'Nieobecny'.

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
votes_update_table(dbname, user, password, host, 7, TRUE)
votes_update_table(dbname, user, password, host, 7, FALSE)
## End(Not run)
```

votings_create_table *Creating table with votings*

Description

Function `votings_create_table` creates a table with votings.

Usage

```
votings_create_table(dbname, user, password, host,
  nr_term_of_office = 8)
```

Arguments

<code>dbname</code>	name of database
<code>user</code>	name of user
<code>password</code>	password of database
<code>host</code>	name of host
<code>nr_term_of_office</code>	number of term of office of Polish Diet; default: 8

Value

invisible NULL

Note

Use only this function for first time, when the *votings* table is empty. Then use `votings_update_table`.
All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
votings_create_table(dbname, user, password, host)
## End(Not run)
```

votings_get_date	<i>Getting date of meeting</i>
------------------	--------------------------------

Description

Function votings_get_date gets a date of meeting.

Usage

```
votings_get_date(page)
```

Arguments

page	meeting's page
------	----------------

Details

Example of a meeting's page: <http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=listaglos&IdDnia=1179>

Value

date in format YYYY-MM-DD as character

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:  
page <- 'http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=listaglos&IdDnia=1179'  
votings_get_date(page)  
## End(Not run)
```

votings_get_meetings_links	<i>Getting meetings' links</i>
----------------------------	--------------------------------

Description

Function votings_get_meetings_links gets meetings' links.

Usage

```
votings_get_meetings_links(  
  home_page = 'http://www.sejm.gov.pl/Sejm8.nsf/', page =  
  'http://www.sejm.gov.pl/Sejm8.nsf/agent.xsp?symbol=posglos&NrKadencji=8')
```

Arguments

home_page	main page of polish diet: http://www.sejm.gov.pl/Sejm8.nsf/
page	page with votings in polish diet: http://www.sejm.gov.pl/Sejm8.nsf/agent.xsp?symbol=posglos&NrKadencji=8

Value

character vector

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:  
votings_get_meetings_links()  
## End(Not run)
```

votings_get_meetings_table
Getting meetings' table

Description

Function `votings_get_meetings_table` gets meetings' table.

Usage

```
votings_get_meetings_table(page =  
  'http://www.sejm.gov.pl/Sejm8.nsf/agent.xsp?symbol=posglos&NrKadencji=8')
```

Arguments

page	page with votings in polish diet: http://www.sejm.gov.pl/Sejm8.nsf/agent.xsp?symbol=posglos&NrKadencji=8
------	---

Details

Function `votings_get_meetings_table` gets meetings' table. The result of this function is a data frame with three columns, where the first includes numbers of meetings, the second theirs' dates in Polish and the third is with numbers of votings on each meeting.

Value

data frame with three unnamed columns

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
votings_get_meetings_table()
## End(Not run)
```

votings_get_votings_links
Getting votings' links

Description

Function `votings_get_votings_links` gets votings' links from meeting's page.

Usage

```
votings_get_votings_links(home_page = 'http://www.sejm.gov.pl/Sejm8.nsf/',
  page)
```

Arguments

<code>home_page</code>	main page of polish diet: http://www.sejm.gov.pl/Sejm8.nsf/
<code>page</code>	meeting's page

Details

Example of a meeting's page: <http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=listaglos&IdDnia=1179>

Value

character vector

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:  
home_page <- 'http://www.sejm.gov.pl/Sejm7.nsf/'  
page <- 'http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=listaglos&IdDnia=1179'  
votings_get_votings_links(home_page, page)  
## End(Not run)
```

votings_get_votings_table
Getting votings' table

Description

Function `votings_get_votings_table` gets votings' table from meeting's page.

Usage

```
votings_get_votings_table(page)
```

Arguments

<code>page</code>	meeting's page
-------------------	----------------

Details

Function `votings_get_votings_table` gets votings' table from meeting's page. Example of a meeting's page: <http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=listaglos&IdDnia=1179> The result of this function is a data frame with three columns, where the first includes numbers of votings, the second voting's time and the third is with voting's topics.

Value

data frame with three columns: Nr, Godzina (Time), Temat (Topic)

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:  
page <- 'http://www.sejm.gov.pl/Sejm7.nsf/agent.xsp?symbol=listaglos&IdDnia=1179'  
votings_get_votings_table(page)  
## End(Not run)
```

votings_update_table *Updating table with votings*

Description

Function votings_update_table updates table with votings.

Usage

```
votings_update_table(dbname, user, password, host,
  nr_term_of_office = 8, verbose = FALSE)
```

Arguments

dbname	name of database
user	name of user
password	password of database
host	name of host
nr_term_of_office	number of term of office of Polish Diet; default: 8
verbose	if TRUE then additional info will be printed

Value

invisible NULL

Note

All information is stored in PostgreSQL database.

Author(s)

Piotr Smuda

Examples

```
## Not run:
votings_update_table(dbname, user, password, host)
## End(Not run)
```

Index

`create_database`, [2](#)

`deputies_add_new`, [3](#)
`deputies_create_table`, [4](#)
`deputies_get_data`, [5](#)
`deputies_get_ids`, [6](#)
`deputies_update_table`, [7](#)

`get_deputies_table`, [8](#)
`get_filtered_votes`, [9](#)
`get_statements_table`, [11](#)
`get_votes_table`, [12](#)
`get_votings_table`, [13](#)

`remove_database`, [14](#)

`safe_html`, [15](#)
`safe_readHTMLTable`, [15](#)
`statements_create_table`, [16](#)
`statements_get_statement`, [17](#)
`statements_get_statements_data`, [18](#)
`statements_get_statements_table`, [19](#)
`statements_update_table`, [20](#)

`votes_create_table`, [21](#)
`votes_get_clubs_links`, [22](#)
`votes_get_results`, [23](#)
`votes_match_deputies_ids`, [24](#)
`votes_update_table`, [25](#)
`votings_create_table`, [26](#)
`votings_get_date`, [27](#)
`votings_get_meetings_links`, [27](#)
`votings_get_meetings_table`, [28](#)
`votings_get_votings_links`, [29](#)
`votings_get_votings_table`, [30](#)
`votings_update_table`, [31](#)