

Database changed

MariaDB [nuevaEmpresa]> DELIMITER //

MariaDB [nuevaEmpresa]> CREATE PROCEDURE ac09semanaIf(IN dia INT)

```
-> BEGIN
->     DECLARE nombre_dia VARCHAR(10);
->     IF dia = 1 THEN SET nombre_dia = 'Lunes';
->     ELSEIF dia = 2 THEN SET nombre_dia = 'Martes';
->     ELSEIF dia = 3 THEN SET nombre_dia = 'Miércoles';
->     ELSEIF dia = 4 THEN SET nombre_dia = 'Jueves';
->     ELSEIF dia = 5 THEN SET nombre_dia = 'Viernes';
->     ELSEIF dia = 6 THEN SET nombre_dia = 'Sábado';
->     ELSEIF dia = 7 THEN SET nombre_dia = 'Domingo';
->     ELSE SET nombre_dia = 'Día no válido';
->     END IF;
->     SELECT nombre_dia AS resultado;
-> END//
```

Query OK, 0 rows affected (0.041 sec)

MariaDB [nuevaEmpresa]> DELIMITER ;

MariaDB [nuevaEmpresa]> call ac09semanaIf(3);

```
+-----+
| resultado |
+-----+
| Miércoles |
+-----+
```

1 row in set (0.003 sec)

Query OK, 0 rows affected (0.003 sec)

```
MariaDB [nuevaEmpresa]> CALL ac09semanaCasIng(1, 'CAS');
```

```
+-----+  
| resultado |
```

```
+-----+  
| Lunes     |
```

```
+-----+
```

```
1 row in set (0.004 sec)
```

```
Query OK, 0 rows affected (0.004 sec)
```

```
MariaDB [nuevaEmpresa]> CALL ac09semanaCasIng(1, 'ING');
```

```
+-----+  
| resultado |
```

```
+-----+  
| Monday    |
```

```
+-----+
```

```
1 row in set (0.001 sec)
```

```
Query OK, 0 rows affected (0.002 sec)
```

```
MariaDB [nuevaEmpresa]> CALL ac09semanaCasIng(7, 'CAS');
```

```
+-----+  
| resultado |
```

```
+-----+  
| Domingo   |
```

```
+-----+
```

```
1 row in set (0.001 sec)
```

```
Query OK, 0 rows affected (0.002 sec)
```

```
MariaDB [nuevaEmpresa]> CALL ac09semanaCasIng(7, 'ING');
```

```
+-----+  
| resultado |
```

```
+-----+  
| Sunday    |
```

```
+-----+
```

```
1 row in set (0.001 sec)
```

```
Query OK, 0 rows affected (0.003 sec)
```

```

MariaDB [nuevaEmpresa]> DELIMITER //
MariaDB [nuevaEmpresa]> CREATE PROCEDURE ac09insertaHabilidad(IN cod VARCHAR(10), IN des VARCHAR(30))
-> BEGIN
->     IF CHAR_LENGTH(TRIM(cod)) = 5 THEN
->         INSERT INTO habilidad (CodHab, DesHab) VALUES (cod, des);
->     END IF;
-> END//
Query OK, 0 rows affected (0.018 sec)

MariaDB [nuevaEmpresa]> DELIMITER ;
MariaDB [nuevaEmpresa]> CALL ac09insertaHabilidad('CONTA', 'Contabilidad');
Query OK, 1 row affected (0.012 sec)

MariaDB [nuevaEmpresa]> CALL ac09insertaHabilidad('SQL', 'Base de datos');
Query OK, 0 rows affected (0.001 sec)

MariaDB [nuevaEmpresa]> CALL ac09insertaHabilidad('JAVA1', 'Programacion Java');
Query OK, 1 row affected (0.009 sec)

MariaDB [nuevaEmpresa]> SELECT * FROM habilidad;
+-----+-----+
| CodHab | DesHab |
+-----+-----+
| CONTA  | Contabilidad |
| FONTA  | Fontanería |
| GEREN  | Gerencia |
| GESCO  | Gestión Contable |
| INFOR  | INFORMATICA |
| MARKE  | Marketing |
| MECAN  | Mecanografía |
| JAVA1  | Programacion Java |
| RELPU  | Relaciones Públicas |
| TELEF  | Telefonista |
+-----+-----+
10 rows in set (0.002 sec)

```

```

MariaDB [nuevaEmpresa]> DROP PROCEDURE IF EXISTS ac@9upsertHabilidad;
Query OK, 0 rows affected (0.035 sec)

MariaDB [nuevaEmpresa]>
MariaDB [nuevaEmpresa]> DELIMITER //
MariaDB [nuevaEmpresa]> CREATE PROCEDURE ac@9upsertHabilidad(IN cod VARCHAR(10), IN des VARCHAR(30))
-> BEGIN
->     IF CHAR_LENGTH(cod) = 5 THEN
->         IF EXISTS (SELECT 1 FROM habilidad WHERE CodHab = cod) THEN
->             UPDATE habilidad SET DesHab = des WHERE CodHab = cod;
->         ELSE
->             INSERT INTO habilidad (CodHab, DesHab) VALUES (cod, des);
->         END IF;
->     END IF;
-> END//
Query OK, 0 rows affected (0.017 sec)

```

```

MariaDB [nuevaEmpresa]> DELIMITER //
MariaDB [nuevaEmpresa]> CREATE PROCEDURE ac@9upsertHabilidadPlus(IN cod VARCHAR(10), IN des VARCHAR(30))
-> BEGIN
->     IF cod IS NULL OR des IS NULL THEN
->         SELECT 'Error: los parametros no pueden ser nulos' AS resultado;
->     ELSEIF CHAR_LENGTH(cod) != 5 THEN
->         SELECT 'Error: el codigo debe tener exactamente 5 caracteres' AS resultado;
->     ELSE
->         IF EXISTS (SELECT 1 FROM habilidad WHERE CodHab = cod) THEN
->             UPDATE habilidad SET DesHab = des WHERE CodHab = cod;
->             SELECT 'Habilidad actualizada correctamente' AS resultado;
->         ELSE
->             INSERT INTO habilidad (CodHab, DesHab) VALUES (cod, des);
->             SELECT 'Habilidad insertada correctamente' AS resultado;
->         END IF;
->     END IF;
-> END//
Query OK, 0 rows affected (0.019 sec)

MariaDB [nuevaEmpresa]> DELIMITER ;

```

```

MariaDB [nuevaEmpresa]> CALL ac@9upsertHabilidadPlus('REACT', 'ReactJS');
+-----+
| resultado |
+-----+
| Habilidad insertada correctamente |
+-----+
1 row in set (0.021 sec)

Query OK, 1 row affected (0.022 sec)

MariaDB [nuevaEmpresa]> CALL ac@9upsertHabilidadPlus('REACT', 'React avanzado');
+-----+
| resultado |
+-----+
| Habilidad actualizada correctamente |
+-----+
1 row in set (0.007 sec)

Query OK, 1 row affected (0.008 sec)

MariaDB [nuevaEmpresa]> CALL ac@9upsertHabilidadPlus(NULL, 'algo');
+-----+
| resultado |
+-----+
| Error: los parametros no pueden ser nulos |
+-----+
1 row in set (0.001 sec)

Query OK, 0 rows affected (0.002 sec)

```