

```

Database changed
MariaDB [ac11]> delimiter //
MariaDB [ac11]> create or replace trigger trg_alumnado_before_insert
-> before insert on alumnado
-> for each row
-> begin
->     if new.email is null or new.email = '' then
->         set new.email = crearEmail(new.nombre, new.apellidos, new.curso);
->     end if;
-> end //
Query OK, 0 rows affected (0.099 sec)

MariaDB [ac11]> delimiter ;
MariaDB [ac11]>
MariaDB [ac11]> -- create table for log of email changes
MariaDB [ac11]> create table logCambiosEmail (
->     id int auto_increment primary key,
->     idAlumno int,
->     fechaHora datetime,
->     oldEmail varchar(255),
->     newEmail varchar(255)
-> );
ERROR 1050 (42S01): Table 'logCambiosEmail' already exists
MariaDB [ac11]>
MariaDB [ac11]> delimiter //
MariaDB [ac11]> create or replace trigger trg_alumnado_after_update
-> after update on alumnado
-> for each row
-> begin
->     if old.email != new.email then
->         insert into logCambiosEmail (idAlumno, fechaHora, oldEmail, newEmail)
->         values (new.id, now(), old.email, new.email);
->     end if;
-> end //
Query OK, 0 rows affected (0.071 sec)

MariaDB [ac11]> delimiter ;
MariaDB [ac11]>

```

```

MariaDB [ac11]> CREATE TRIGGER ac1104triggerGuardarAlumnosAfterDelete
-> AFTER DELETE ON alumnado
-> FOR EACH ROW
-> BEGIN
->     INSERT INTO logAlumnosEliminados (idAlumno, fechaHora, nombre, apellido, email)
->     VALUES (OLD.id, NOW(), OLD.nombre, OLD.apellidos, OLD.email);
-> END$$
Query OK, 0 rows affected (0.050 sec)

MariaDB [ac11]>
MariaDB [ac11]> DELIMITER ;
MariaDB [ac11]>

```

```

MariaDB [ac11]> CREATE TRIGGER trg_alumnado_after_insert
-> AFTER INSERT ON alumnado
-> FOR EACH ROW
-> BEGIN
->     INSERT INTO logCambiosEmail (idAlumno, fechaHora, oldEmail, newEmail)
->     VALUES (NEW.id, NOW(), NULL, NEW.email);
-> END$$
Query OK, 0 rows affected (0.048 sec)

MariaDB [ac11]>
MariaDB [ac11]> DELIMITER ;
MariaDB [ac11]>
MariaDB [ac11]> -- insert alumno para probar el trigger
MariaDB [ac11]> DELETE FROM alumnado WHERE id = 6;
Query OK, 1 row affected (0.011 sec)

MariaDB [ac11]> INSERT INTO alumnado (id, nombre, apellidos, curso)
-> VALUES (6, 'Juan', 'Perez', '1 ESO');
Query OK, 1 row affected (0.023 sec)

MariaDB [ac11]>
MariaDB [ac11]> -- mostrar el log de cambios de email
MariaDB [ac11]> SELECT * FROM logCambiosEmail;
+-----+-----+-----+-----+-----+
| id | idAlumno | fechaHora          | oldEmail | newEmail |
+-----+-----+-----+-----+-----+
| 1 | 6 | 2026-04-23 16:00:44 | NULL    | jperez5@1 eso.kursal.es |
+-----+-----+-----+-----+-----+
1 row in set (0.002 sec)

```