

How to find out the length of the array :

```

//Returns the length of the array
public class ArrayLength {

    public static void main(String[] args) {

        //Create an array of 10 elements
        int arr[] = new int[10];

        //Print out the length of the array
        System.out.println("The length of the array is "+arr.length);

    }

}

//Finding the length of the array using command line argument.

public class ArrayLengthCommand {

    public static void main(String[] args) {

        //Print out the length of the array
        System.out.println("The length of the array is "+args.length);

    }

}

//Array Length using Command Line
public class ArrayLengthCommand2 {

    public static void main(String[] args) {

        //Print out the length of the array
        System.out.println("The length of the array is "+args.length);

    }

}

//Array Length using Command Line
public class ArrayLengthCommand3 {

    public static void main(String[] args) {

        //Print out the length of the array
        System.out.println("The length of the array is "+args.length);

    }

}

```

What is Eclipse IDE ?

Eclipse IDE for "Integrated Development Environment". By using eclipse IDE, we can develop, compile and execute java programs in a single instance.


The main purpose of Eclipse IDE is to reduce the development time, once the development time will be reduced then automatically the cost of the project will be reduced.

How to create a Project in Eclipse IDE :

```
File -> New -> Project OR Java Project -> Provide the Name for the project (Name : J1) -> Finish
```

It creates a package in java :

A package is nothing but folder in windows. It is mainly used to arrange our java programs.



Approach 2:

CD / Repet	
Software	Games
Music	Just Programs

If we arrange our Java classes into a particular group by using packages (folders) then we will get the following two advantages :

- 1) Fast searching is possible.
- 2) Names can be protected.

Example :

We have a Date class available in java.util package where as We have another Date class available in java.sql package.

Program that describes a package is folder in windows :

~~~~~

A package is a namespace in java and it must be the first statement of any java program.

```

Package-related Program :
// Addition.java
package basic arithmetic;

public class Addition
{
    public static void main(String[] args)
    {
        int a = 10;
        int b = 20;
        System.out.println("Sum is "+(a+b));
    }
}

// Comment for compilation of the classes which contains Package statement.
[java -d . Addition.java]

[java -d . Addition.java]

// Explanation : Addition.java contains class Arithmetic package. Here first of all class folder will be created, under this folder another folder i.e arithmetic will be created, this folder will
// contain Addition.java file.

Command to run the above program :
java -cp . Arithmetic

```

Types of Packages :

1) **Predefined OR Built-in package** : The packages which are created by java software people for arranging the programs are called predefined package.

Example : java.lang, java.util, java.io, java.sql, java.net and so on



2) **userdefined package OR Custom package :** The packages which are created by user for arranging the user-defined programs are called user-defined package.

```

const newOrder = {
  items: [
    {
      item: 'apple',
      quantity: 1,
    },
    {
      item: 'banana',
      quantity: 2,
    },
    {
      item: 'orange',
      quantity: 3,
    },
  ],
  shipping: 10,
};

```

How to enable command line arguments by using Eclipse IDE :

WAP in java to pass some value from command line argument based on the following criteria :

- If the array length is 0 : It should print "length is 0"
- If the array length is 1 : It should find the square of the number
- If the array length is 2 : It should print sum of the number

```
public static void main(String[] args) {
    String length = "0";
    for (int i = 0; i < args.length; i++) {
        if (args[i].length() > length) {
            length = args[i].length() + "0";
        }
    }
    for (int i = 0; i < args.length; i++) {
        String temp = String.format("%0" + length + "s", args[i]);
        System.out.print(temp + " ");
    }
}
```

Steps to execute the command Line Argument Program using Eclipse IDE

Right click on the program -> Run As -> Run (configuration) -> Verify your main class name -> select argument tab -> pass the appropriate value -> Run