

KR C5 micro



Accessories

- External battery box
- Plug pack
- Mounting bracket
- Power supply lead
- SSD card 60 GB (optional)
- Mounting frame, 19-inch (optional)
- KUKA smartPAD cable reel (optional)
- KUKA.EtherNetSwitch Dual-Port (optional)
- KUKA.EtherNetSwitch Quad-Port (optional)

Basic data

Maximum number of servo axes	6
Width	300 mm
Height	134 mm
Depth	392 mm
Weight	approx. 9.8 kg

Operating conditions

Ambient temperature during operation	0 °C to 45 °C (273 K to 318 K)
Protection rating (IEC 60529)	IP 20
Air humidity	-
Classification of environmental conditions (EN 60721-3-3)	3K4

Electrical data

Rated supply voltage	AC 1x 200 V - 240 V
Mains-side fusing	1x 16 A slow-blowing, type C
Mains frequency	50...60 Hz

Interfaces

IT interfaces	Display Port; GbE; USB 3.0
Field bus and communication standards	PROFINET®; PROFIsafe; PROFInergy; EtherCAT®; MQTT; OPC; OPC UA

Input/output signals

- XG12 16 input / output signals 24 V
- Various I/O and communication options

Teach pendant

Teach pendant	KUKA smartPAD-2
---------------	-----------------