

In [1]:

```
import pandas as pd
import numpy as np
import seaborn as sns
import matplotlib.pyplot as plt
```

In [2]:

```
s=pd.read_csv(r"C:\Users\krish\Downloads\Mobile_Price_Classification_test.csv")
s
```

Out[2]:

	id	battery_power	blue	clock_speed	dual_sim	fc	four_g	int_memory	m_dep	mobile_wt	...	pc	px_height
0	1	1043	1	1.8	1	14	0	5	0.1	193	...	16	226
1	2	841	1	0.5	1	4	1	61	0.8	191	...	12	746
2	3	1807	1	2.8	0	1	0	27	0.9	186	...	4	1270
3	4	1546	0	0.5	1	18	1	25	0.5	96	...	20	295
4	5	1434	0	1.4	0	11	1	49	0.5	108	...	18	749
...
995	996	1700	1	1.9	0	0	1	54	0.5	170	...	17	644
996	997	609	0	1.8	1	0	0	13	0.9	186	...	2	1152
997	998	1185	0	1.4	0	1	1	8	0.5	80	...	12	477
998	999	1533	1	0.5	1	0	0	50	0.4	171	...	12	38
999	1000	1270	1	0.5	0	4	1	35	0.1	140	...	19	457

1000 rows × 21 columns

In [3]:

```
s.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 1000 entries, 0 to 999
Data columns (total 21 columns):
#   Column          Non-Null Count  Dtype
---  -
0   id               1000 non-null   int64
1   battery_power    1000 non-null   int64
2   blue             1000 non-null   int64
3   clock_speed      1000 non-null   float64
4   dual_sim         1000 non-null   int64
5   fc               1000 non-null   int64
6   four_g           1000 non-null   int64
7   int_memory       1000 non-null   int64
8   m_dep            1000 non-null   float64
9   mobile_wt        1000 non-null   int64
10  n_cores          1000 non-null   int64
11  pc               1000 non-null   int64
12  px_height        1000 non-null   int64
13  px_width         1000 non-null   int64
14  ram              1000 non-null   int64
15  sc_h             1000 non-null   int64
16  sc_w             1000 non-null   int64
17  talk_time        1000 non-null   int64
18  three_g          1000 non-null   int64
19  touch_screen     1000 non-null   int64
20  wifi             1000 non-null   int64
dtypes: float64(2), int64(19)
memory usage: 164.2 KB
```

In [4]:

```
x=s.drop('wifi',axis=1)
y=s['wifi']
```

In [5]:

```
s['dual_sim'].value_counts()
```

Out[5]:

```
dual_sim
1      517
0      483
Name: count, dtype: int64
```

In [6]:

```
m={"three_g":{"Yes":1,"No":0}}
s=s.replace(m)
print(s)
```

	id	battery_power	blue	clock_speed	dual_sim	fc	four_g	int_memory	
0	1	1043	1	1.8	1	14	0	5	\
1	2	841	1	0.5	1	4	1	61	
2	3	1807	1	2.8	0	1	0	27	
3	4	1546	0	0.5	1	18	1	25	
4	5	1434	0	1.4	0	11	1	49	
..	
995	996	1700	1	1.9	0	0	1	54	
996	997	609	0	1.8	1	0	0	13	
997	998	1185	0	1.4	0	1	1	8	
998	999	1533	1	0.5	1	0	0	50	
999	1000	1270	1	0.5	0	4	1	35	

	m_dep	mobile_wt	...	pc	px_height	px_width	ram	sc_h	sc_w	
0	0.1	193	...	16	226	1412	3476	12	7	\
1	0.8	191	...	12	746	857	3895	6	0	
2	0.9	186	...	4	1270	1366	2396	17	10	
3	0.5	96	...	20	295	1752	3893	10	0	
4	0.5	108	...	18	749	810	1773	15	8	
..	
995	0.5	170	...	17	644	913	2121	14	8	
996	0.9	186	...	2	1152	1632	1933	8	1	
997	0.5	80	...	12	477	825	1223	5	0	
998	0.4	171	...	12	38	832	2509	15	11	
999	0.1	140	...	19	457	608	2828	9	2	

	talk_time	three_g	touch_screen	wifi
0	2	0	1	0
1	7	1	0	0
2	10	0	1	1
3	7	1	1	0
4	7	1	0	1
..
995	15	1	1	0
996	19	0	1	1
997	14	1	0	0
998	6	0	1	0
999	3	1	0	1

[1000 rows x 21 columns]

In [7]:

```
x=s.drop('wifi',axis=1)
y=s['wifi']
```

In [8]:

```
from sklearn.model_selection import train_test_split
x_train,x_test,y_train,y_test=train_test_split(x,y,train_size=0.7,random_state=42)
x_train.shape,x_test.shape
```

Out[8]:

```
((700, 20), (300, 20))
```

In [9]:

```
from sklearn.ensemble import RandomForestClassifier
rfc=RandomForestClassifier()
rfc.fit(x_train,y_train)
```

Out[9]:

```
RandomForestClassifier()
RandomForestClassifier()
```

In [10]:

```
rf=RandomForestClassifier()
```

In [11]:

```
params={'max_depth':[2,3,5,10,20], 'min_samples_leaf':[5,10,20,50,100,200], 'n_estimators':[10,25,30,50,100,200]}
```

In [3]:

```
from sklearn.model_selection import GridSearchCV
grid_search=GridSearchCV(estimator=rf,param_grid=params,cv=2,scoring="accuracy")
grid_search.fit(x_train,y_train)
```

NameError

Traceback (most recent call last)

Cell In[3], line 2

```
1 from sklearn.model_selection import GridSearchCV
----> 2 grid_search=GridSearchCV(estimator=rf,param_grid=params,cv=2,scoring="accuracy")
      3 grid_search.fit(x_train,y_train)
```

NameError: name 'rf' is not defined

In [2]:

```
grid_search.best_score_
```

NameError

Traceback (most recent call last)

Cell In[2], line 1

```
----> 1 grid_search.best_score_
```

NameError: name 'grid_search' is not defined

In []:

```
rf_best=grid_search.best_estimator_
```

In [4]:

```
#trainData
import pandas as pd
import numpy as np
import seaborn as sns
import matplotlib.pyplot as plt
```

In [5]:

```
s=pd.read_csv(r"C:\Users\krish\Downloads\Mobile_Price_Classification_train.csv")
s
```

Out[5]:

	battery_power	blue	clock_speed	dual_sim	fc	four_g	int_memory	m_dep	mobile_wt	n_cores	...	px_height
0	842	0	2.2	0	1	0	7	0.6	188	2	...	20
1	1021	1	0.5	1	0	1	53	0.7	136	3	...	905
2	563	1	0.5	1	2	1	41	0.9	145	5	...	1263
3	615	1	2.5	0	0	0	10	0.8	131	6	...	1216
4	1821	1	1.2	0	13	1	44	0.6	141	2	...	1208
...
1995	794	1	0.5	1	0	1	2	0.8	106	6	...	1222
1996	1965	1	2.6	1	0	0	39	0.2	187	4	...	915
1997	1911	0	0.9	1	1	1	36	0.7	108	8	...	868
1998	1512	0	0.9	0	4	1	46	0.1	145	5	...	336
1999	510	1	2.0	1	5	1	45	0.9	168	6	...	483

2000 rows × 21 columns

In [6]:

```
s.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 2000 entries, 0 to 1999
Data columns (total 21 columns):
#   Column          Non-Null Count  Dtype
---  -
0   battery_power    2000 non-null   int64
1   blue             2000 non-null   int64
2   clock_speed      2000 non-null   float64
3   dual_sim         2000 non-null   int64
4   fc               2000 non-null   int64
5   four_g           2000 non-null   int64
6   int_memory       2000 non-null   int64
7   m_dep            2000 non-null   float64
8   mobile_wt        2000 non-null   int64
9   n_cores          2000 non-null   int64
10  pc               2000 non-null   int64
11  px_height        2000 non-null   int64
12  px_width         2000 non-null   int64
13  ram              2000 non-null   int64
14  sc_h             2000 non-null   int64
15  sc_w             2000 non-null   int64
16  talk_time        2000 non-null   int64
17  three_g          2000 non-null   int64
18  touch_screen     2000 non-null   int64
19  wifi             2000 non-null   int64
20  price_range      2000 non-null   int64
dtypes: float64(2), int64(19)
memory usage: 328.2 KB
```

In [7]:

```
s['dual_sim'].value_counts()
```

Out[7]:

```
dual_sim
1    1019
0     981
Name: count, dtype: int64
```

In [8]:

```
x=s.drop('wifi',axis=1)
y=s['wifi']
```

In [9]:

```
from sklearn.model_selection import train_test_split
x_train,x_test,y_train,y_test=train_test_split(x,y,train_size=0.7,random_state=42)
x_train.shape,x_test.shape
```

Out[9]:

```
((1400, 20), (600, 20))
```

In [10]:

```
rf=RandomForestClassifier()
```

```
-----
NameError                                Traceback (most recent call last)
Cell In[10], line 1
----> 1 rf=RandomForestClassifier()
```

NameError: name 'RandomForestClassifier' is not defined

In []:

```
params={'max_depth':[2,3,5,10,20], 'min_samples_leaf':[5,10,20,50,100,200], 'n_estimators':[10,25,30,50,100,200]}
```

In []:

```
from sklearn.model_selection import GridSearchCV
grid_search=GridSearchCV(estimator=rf,param_grid=params,cv=2,scoring="accuracy")
grid_search.fit(x_train,y_train)
```

In []:

```
grid_search.best_score_
```

In []:

```
rf_best=grid_search.best_estimator_
```

In []: