

**Spring Boot Reactive Programming** is based on **Project Reactor** and enables building **non-blocking, event-driven** applications using the **Reactive Streams** specification. It is designed to handle large volumes of data and I/O-bound tasks with better scalability and lower resource consumption.

---



## Key Concepts of Reactive Programming

1. **Reactive Streams** – A specification for asynchronous stream processing with non-blocking backpressure.
  2. **Publishers and Subscribers** – The core of reactive programming:
    - **Publisher** – Emits data.
    - **Subscriber** – Consumes data.
    - **Subscription** – Represents the connection between Publisher and Subscriber.
    - **Processor** – A hybrid of Publisher and Subscriber (used to transform data).
  3. **Backpressure** – A mechanism to handle the situation where a subscriber cannot keep up with the publisher's data rate.
- 



## Reactive Libraries in Spring Boot

- **Project Reactor** – Core library for reactive programming in Spring.
  - **Mono** – Represents 0 or 1 element.
  - **Flux** – Represents 0 to N elements (like a stream).

```
reactiveDemoApplication.java ProductController.java ReactiveController.java MonoFlux.java
1 package com.wipro;
2 import reactor.core.publisher.Mono;
3 import reactor.core.publisher.Flux;
4
5 public class MonoFlux{
6     public static void main(String[] args) {
7
8         Mono<String> m = Mono.just("pavan").log(); //mono returns the single data
9         m.subscribe(x -> System.out.println(x));
10
11         Flux<String> f = Flux.just("pavan","prem","sreenu","bharathi").log(); //flux returns the multiple data
12         f.subscribe(x -> System.out.println(x));
13     }
14 }
15
16 /* comment the flux and run the mono
17
18 14:19:40.437 [main] INFO reactor.Mono.Just.1 -- | onSubscribe([Synchronous Fuseable] Operators.ScalarSubscription)
19 14:19:40.442 [main] INFO reactor.Mono.Just.1 -- | request(unbounded)
20 14:19:40.442 [main] INFO reactor.Mono.Just.1 -- | onNext(pavan)
21 pavan
22 14:19:40.443 [main] INFO reactor.Mono.Just.1 -- | onComplete()
23
24 */
25 //remove all comments and run
26 /*
27 14:22:18.499 [main] INFO reactor.Mono.Just.1 -- | onSubscribe([Synchronous Fuseable] Operators.ScalarSubscription)
28 14:22:18.507 [main] INFO reactor.Mono.Just.1 -- | request(unbounded)
29 14:22:18.508 [main] INFO reactor.Mono.Just.1 -- | onNext(pavan)
30 pavan
31 14:22:18.510 [main] INFO reactor.Mono.Just.1 -- | onComplete()
32 14:22:18.702 [main] INFO reactor.Flux.Array.2 -- | onSubscribe([Synchronous Fuseable] FluxArray.ArraySubscription)
33 14:22:18.702 [main] INFO reactor.Flux.Array.2 -- | request(unbounded)
34 14:22:18.702 [main] INFO reactor.Flux.Array.2 -- | onNext(pavan)
35 pavan
36 14:22:18.702 [main] INFO reactor.Flux.Array.2 -- | onNext(prem)
37 prem
38 14:22:18.703 [main] INFO reactor.Flux.Array.2 -- | onNext(sreenu)
39 sreenu
40 14:22:18.703 [main] INFO reactor.Flux.Array.2 -- | onNext(bharathi)
41 bharathi
42 14:22:18.703 [main] INFO reactor.Flux.Array.2 -- | onComplete()
43
44
```

- **WebFlux** – Reactive alternative to Spring MVC, built on top of Project Reactor.
- **R2DBC** – Reactive SQL database client.
- **Spring Data MongoDB** – Reactive MongoDB client.
- **Spring Security** – Supports reactive programming for authentication and authorization

## Spring Boot Reactive Programming - Explained Simply

### What is Spring Boot Reactive Programming?

Imagine you run a restaurant. Traditional programming (blocking) is like having only one waiter who serves one customer at a time. If a customer takes time to decide their order, the waiter just stands there waiting, unable to serve others.

Now, **Reactive Programming** is like having a smart waiter who can handle multiple customers at once. If one customer is thinking, the waiter moves on to take another order and comes back later. This makes the restaurant run more efficiently.

In technical terms, **Spring Boot Reactive Programming** allows applications to handle multiple tasks efficiently by **not blocking** resources while waiting for slow operations (like database queries, API calls, etc.). It is built on **Project Reactor** and uses concepts like **Mono** and **Flux** to process data streams asynchronously.

---

## Advantages of Spring Boot Reactive Programming

### 1. Better Performance 🚀

- It can handle more users with fewer system resources, making apps faster and more scalable.

### 2. Efficient Resource Utilization ↻

- No threads are wasted waiting for slow responses. The system continues working on other tasks.

### 3. Handles High Traffic Easily 🚦

- Ideal for applications that deal with real-time data or heavy loads (e.g., chat applications, stock market updates, streaming services).

### 4. Non-blocking Nature ⌚

- Unlike traditional approaches where a request waits for a response, in reactive programming, tasks run in the background while the system continues handling other requests.

---





















## Why Use It?

- If your application deals with **large-scale, real-time data processing** (e.g., Netflix, Facebook feeds, IoT applications).
  - If you want to improve **scalability and efficiency** without increasing hardware costs.
  - If your app makes **a lot of database/API calls** and you want to avoid waiting time.
- 

## Conclusion

Spring Boot Reactive Programming helps build fast, scalable, and efficient applications by allowing tasks to execute **asynchronously and non-blockingly**. If your application needs to handle many concurrent users and real-time updates, it's a great choice!

<https://github.com/PavanKalyan96Dev/ReactiveProgramming-Demo>

- ▼  reactive-demo [boot]
  - ▼  src/main/java
    - ▼  com.wipro
      - >  ReactiveDemoApplication.java
    - ▼  com.wipro.controller
      - >  ProductController.java
      - >  ReactiveController.java
    - ▼  com.wipro.entity
      - >  Product.java
    - ▼  com.wipro.repository
      - >  ProductRepository.java
    - ▼  com.wipro.services
      - >  ProductService.java
      - >  ReactiveService.java
  - ▼  src/main/resources
    -  application.properties
  - ▼  src/test/java
    - ▼  com.wipro
      - >  ReactiveDemoApplicationTests.java
  - >  JRE System Library [JavaSE-17]

```
C:\Users\miniMiracle>docker run -d -p 27017:27017 --name my-mongo mongo:6.0
Unable to find image 'mongo:6.0' locally
6.0: Pulling from library/mongo
fccc1bcb87a2: Download complete
dab55db4115b: Download complete
ee4de8767950: Download complete
8fc5e73c1095: Download complete
3e17abcf9d3: Download complete
c85b9d4f6d4c: Download complete
53b33edd63f2: Download complete
9cb31e2e37ea: Download complete
Digest: sha256:453e114d98c392b929706b84f56d5f7996704826fcc84ce0c6d4a34c247f46b4
Status: Downloaded newer image for mongo:6.0
c526066b725da1f41203dbe12882ca4abda7062f0373cd6617bc045e87d119fe
```

```
C:\Users\miniMiracle>docker ps
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS	NAMES
c526066b725d	mongo:6.0	"docker-entrypoint.s..."	13 seconds ago	Up 11 seconds	0.0.0.0:27017->27017/tcp	my-mongo
63c91b3956a1	mysql:latest	"docker-entrypoint.s..."	45 hours ago	Up 45 hours	3306/tcp, 33060/tcp	mysql-db

```
C:\Users\miniMiracle>docker exec -it my-mongo mongosh
Current Mongosh Log ID: 67cfd9bc3a2a180aeb544ca6
Connecting to:      mongodb://127.0.0.1:27017/?directConnection=true&serverSelectionTimeoutMS=2000&appName=mongosh+2.3.8
Using MongoDB:      6.0.20
Using Mongosh:      2.3.8

For mongosh info see: https://www.mongodb.com/docs/mongodb-shell/

To help improve our products, anonymous usage data is collected and sent to MongoDB periodically (https://www.mongodb.com/legal/privacy-policy).
You can opt-out by running the disableTelemetry() command.

-----
The server generated these startup warnings when booting
2025-03-11T06:20:44.076+00:00: Using the XFS filesystem is strongly recommended with the WiredTiger storage engine. See http://dochub.mongodb.org/core/prodnotes-filesystem
2025-03-11T06:20:44.780+00:00: Access control is not enabled for the database. Read and write access to data and configuration is unrestricted
2025-03-11T06:20:44.782+00:00: /sys/kernel/mm/transparent_hugepage/enabled is 'always'. We suggest setting it to 'never'.
```

```

test> show dbs
admin    40.00 KiB
config   12.00 KiB
local    40.00 KiB
test> show dbs
admin    40.00 KiB
config   12.00 KiB
local    40.00 KiB
test> use reactive_db
switched to db reactive_db
reactive_db> db.products.insertOne({ name: "Sample Product", price: 99.99 })
{
  acknowledged: true,
  insertedId: ObjectId('67cfe3353a2a180aeb544ca7')
}
reactive_db> show dbs
admin      40.00 KiB
config     60.00 KiB
local      40.00 KiB
reactive_db 8.00 KiB
reactive_db> show collections
products
reactive_db> db.products.find().pretty()
[
  {
    _id: ObjectId('67cfe3353a2a180aeb544ca7'),
    name: 'Sample Product',

```


← → ↻ ⓘ localhost:9094/products




```

▼ [
  ▼ {
    "id": "67cfe3353a2a180aeb544ca7",
    "name": "Sample Product",
    "price": 99.99
  }
]

```



Hello, Reactive World!



Adding the data in postman

Now we'll get them

GET localhost:9094/products Send

Params Authorization Headers (9) Body Scripts Settings Cookies Beautify

☐ none ☐ form-data ☐ x-www-form-urlencoded ☒ raw ☐ binary ☐ GraphQL JSON

```
1 {
2   "name": "Laptop",
3   "price": 1500.00
4 }
5
```

Body Cookies Headers (2) Test Results 200 OK 8 ms 217 B

{ } JSON Preview Visualize

```
1 [
2   {
3     "id": "67cfe3353a2a180aeb544ca7",
4     "name": "Sample Product",
5     "price": 99.99
6   },
7   {
8     "id": "67cfe5e7e2dbdc70ecaef314",
9     "name": "Laptop",
10    "price": 1500.0
11  }
12 ]
```

Find and replace Console Postbot Runner Start Proxy Cookies Vault Trash

## Get product by id

GET localhost:9094/products/65f8c123abcd98765432 Send

Params Authorization Headers (9) Body Scripts Settings Cookies Beautify

☐ none ☐ form-data ☐ x-www-form-urlencoded ☒ raw ☐ binary ☐ GraphQL JSON

```
1 {
2   "name": "Laptop",
3   "price": 1500.00
4 }
5
```

GET localhost:9094/reactive/hello Send

Params Authorization Headers (9) Body Scripts Settings Cookies Beautify

☐ none ☐ form-data ☐ x-www-form-urlencoded ☒ raw ☐ binary ☐ GraphQL JSON

1 {


Body Cookies Headers (2) Test Results 200 OK 4 ms 101 B

Raw Preview Visualize

```
1 Hello, Reactive World!
```

## Get the stream of numbers





```
reactive_db> db.products.find().pretty()
[
  {
    _id: ObjectId('67cfe3353a2a180aeb544ca7'),
    name: 'Sample Product',
    price: 99.99
  },
  {
    _id: ObjectId('67cfe5e7e2dbdc70ecaef314'),
    name: 'Laptop',
    price: 1500,
    _class: 'com.wipro.entity.Product'
  }
]
```

<https://chatgpt.com/share/67d02277-e76c-8011-a33d-6af5a0f0c2aa>

In **Project Reactor**, which is the reactive programming library used in **Spring WebFlux**, **Mono** and **Flux** are two core reactive types.

## 1. **Mono<T>**

- Represents **zero or one** element.
- Used for cases where you expect at most one result.
- Example use case: Fetching a single user from the database.

**Example:**

```
java                                                                    Copy Edit

Mono<String> monoExample = Mono.just("Hello, Mono!");
monoExample.subscribe(System.out::println);
```

**Output:**

```
                                                                    Copy Edit

Hello, Mono!
```





## 2. Flux<T>

- Represents **zero or more** elements (a stream of data).
- Used for cases where multiple results are expected.
- Example use case: Fetching all employees from a database.

### Example:



java

 Copy  Edit

```
Flux<String> fluxExample = Flux.just("Java", "Spring", "WebFlux");  
fluxExample.subscribe(System.out::println);
```

### Output:

nginx

 Copy  Edit

```
Java  
Spring  
WebFlux
```

## Key Differences

Feature	Mono	Flux
Number of elements	0 or 1	0 to N
Used for	Single item or empty result	Multiple items (stream)
Example	<code>Mono.just("Hello")</code>	<code>Flux.just("A", "B", "C")</code>

what is the benefit of using reactive programming when you compare with traditional programming?

Reactive programming offers several benefits over traditional (imperative) programming, especially in high-throughput and event-driven applications. Below are the key advantages:

---

## 1. Non-Blocking & Asynchronous Execution

**Traditional:** Uses blocking I/O operations, meaning each request waits until the previous one completes.

**Reactive:** Uses **non-blocking I/O**, allowing the system to handle multiple operations simultaneously.

- ♦ **Example:** In a traditional Spring MVC app, a request to fetch user data would block the thread until the database responds. In WebFlux, the request is non-blocking, allowing the thread to handle other requests in the meantime.

## 2. Better Resource Utilization (Fewer Threads)

**Traditional:** Creates new threads for each request, leading to high memory usage and thread exhaustion.

**Reactive:** Uses **event loops** and a small thread pool (Netty event loop), making it efficient in handling thousands of concurrent users.

- ♦ **Example:** A traditional Tomcat server uses one thread per request, whereas a reactive Netty-based server can handle multiple requests using fewer threads.

---

## 3. High Performance & Scalability

**Traditional:** Struggles with scaling under heavy load due to thread blocking.

**Reactive:** Handles high loads efficiently because non-blocking operations free up threads.

- ♦ **Example:** Suitable for applications that deal with **real-time data streaming**, such as stock price updates, chat applications, or IoT.