

Collection Framework

In this assignment, you are required to write a menu-driven Java program that allows the user to add patients to a priority queue, display the next patient (and remove him/her from the queue), show a list of all patients currently waiting for treatment, and exit the program. The program should simulate the scheduling of patients in a clinic. Use the attached `Patient` class provided along with this assignment.

Your program should schedule patients in the queue according to the emergency of their cases from 1 to 5 (the higher the value, the higher the priority). If two patients have the same emergency value, use their order of arrival to set their priority (the lower the order, the higher the priority). It is up to you to have the `Patient` class implement either `Comparable` or `Comparator`.

Create a class `PatientManager` that has an attribute named `waitingList` of the type `PriorityQueue<Patient>` and a public method, `start()`. When `start` is called, it should display the following menu of choices to the user, and then ask the user to enter a choice from 1 to 4:

```
-----  
(1) New Patient.  
(2) Next Patient.  
(3) Waiting List.  
(4) Exit.  
-----
```

Here is a description of each choice:

- (1) Ask the user for the patient's name and the emergency from 1 to 5 (1 = low, and 5 = life-and-death). Your program should create an instance of `Patient` using the entered data and add it to the priority queue. Note that your program should not ask the user for the value of the patient's order of arrival. Instead, it should use a counter that is automatically incremented whenever a patient is added to the queue.
- (2) Display the name of the next patient in the priority queue and remove him/her from the queue.
- (3) Display the full list of all patients that are still in the queue.
- (4) End the program.

Make sure your `PatientManager` class is robust. It should not crash when a user enters invalid value. Instead, it should display an error message followed by an action depending on the type of error (see the sample run below).

Test your program by instantiating your `PatientManager` class in a `main` method and calling the `start` method.

Note: Add more helper methods and attributes as needed to the `PatientManager` class.

Collection Framework

Sample run (Read carefully to determine the required response in different situations)

```
-----
(1) New Patient.
(2) Next Patient.
(3) Waiting List.
(4) Exit.
-----
* Choose an item from the menu: 8
(x) Wrong choice.
* Choose an item from the menu: two
(x) Wrong choice.
* Choose an item from the menu: 2
- No more patients.
* Choose an item from the menu: 3
- No patients in the list.
* Choose an item from the menu: 1
  Enter patient's name: Abdallah
  Enter emergency [1 (low) to 5 (life-and-death)]: 8
  (x) Wrong value. Try again: critical
  (x) Wrong value. Try again: 3
  Patient added to the waiting list.
* Choose an item from the menu: 1
  Enter patient's name: John
  Enter emergency [1 (low) to 5 (life-and-death)]: 4
  Patient added to the waiting list.
* Choose an item from the menu: 3
  Waiting list includes:
  - John
  - Abdallah
* Choose an item from the menu: 1
  Enter patient's name: Lili
  Enter emergency [1 (low) to 5 (life-and-death)]: 4
  Patient added to the waiting list.
* Choose an item from the menu: 3
  Waiting list includes:
  - John
  - Lili
  - Abdallah
* Choose an item from the menu: 2
  - John is treated.
* Choose an item from the menu: 2
  - Lili is treated.
* Choose an item from the menu: 2
  - Abdallah is treated.
* Choose an item from the menu: 2
  - No more patients.
* Choose an item from the menu: 4

Program terminated. Good bye!!
```