

Write Test

190 sec.

[Home](#) [Write Test](#) [Write Program](#) [Result](#) [Change](#)

[Password](#) [Logout](#)

1.

Can we create more than one context in react application ?

- ☒ Yes
☐ No

Ans: A

2.

We can pass the data from child to all direct or indirect parents using context API ?

- ☐ Yes
☒ No

Ans: B

3.

Can I use all JavaScript events in React ?

- ☒ Yes
☐ No

Ans: A

4.

useState returns an array, that array contains how many elements ?

- ☐ 0

190 sec.

- ☐ 1
- ☒ 2
- ☐ 3

Ans: C

5.

Below which hook we used to handle lifecycle phases in React ?

- ☐ useState
- ☒ useEffect
- ☐ useRef
- ☐ useMemo

Ans: B

6.

```
const [data,setData]=React.useState(0);
```

```
for(let i=0;i<5;i++){  
  setData((val)=>{  
    return val+1  
  })  
}
```

what is the value of data

- ☐ 0
- ☒ 5
- ☐ 1
- ☐ Error

Ans: B

7.

```
const [data,setData]=React.useState(0);
```

190 sec.

```
for(let i=0;i<5;i++){  
  setData(data+1)  
}
```

what is the value of data

- ☐ 0
- ☐ 5
- ☒ 1
- ☐ Error

Ans: C

8.

useEffect hook take max how many arguments ?

- ☐ 1
- ☒ 2
- ☐ 3
- ☐ 4

Ans: B

9.

```
const myRef=React.useRef();
```

which attribute key we used to bind above myRef to an element ?

- ☒ ref
- ☐ id
- ☐ name
- ☐ class

Ans: A

10.

```
const [data,setData]=React.useState(0);
```

Can we pass function as an argument to setData function ?

190 sec.

- ☐ No
- ☒ Yes

Ans: B

11.

Using which hook , we can consume the data from context ?

- ☐ useRef
- ☐ useState
- ☒ useContext
- ☐ useMemo

Ans: C

12.

In React event handler method called by passing one argument , what is the argument?

- ☐ array
- ☐ number
- ☒ SyntheticBaseEvent
- ☐ None of the above

Ans: C

13.

```
const myRef=React.useRef(100)
```

myRef.current ?

- ☐ undefined
- ☒ 100
- ☐ null
- ☐ Error

Ans: B

190 sec.

14.

useState hook takes maximum how many arguments ?

- ☐ 0
- ☒ 1
- ☐ 2
- ☐ 3

Ans: B

15.

In React, event handler method called by passing how many arguments ?

- ☒ one
- ☐ two
- ☐ three
- ☐ zero

Ans: A

16.

```
React.useEffect(()=>
```

```
  ,[cnt,name])
```

In the above code snippet, when the callback method called ?

- ☒ in mounting phase
- ☒ cnt state variable updation
- ☒ name prop value updation
- ☐ every state or prop variables updation

Ans: ABC

190 sec.

17.

Below which lib, used to compile JSX code ?

- ☐ react lib
- ☐ reactDOM lib
- ☒ babel lib
- ☐ bootstrap lib

Ans: C

18.

In React event handler should a function or function call ?

- ☒ function
- ☐ function call

Ans: A

19.

In redux , reducer take how many arguments ?

- ☐ 1
- ☒ 2
- ☐ 3
- ☐ 4

Ans: B

20.

When we can get the invalid hook call error?

- ☒ call hooks outside the functional component
- ☒ call hook inside the class component
- ☐ call hook inside the functional component

Ans: AB

WRITE AGAIN

190 sec.