

Write Test

117 sec.

[Home](#) [Write Test](#) [Write Program](#) [Result](#) [Change](#)

[Password](#) [Logout](#)

1.

```
React.useEffect(()=>
  return ()=>{
    console.log("called");
  }
},[])
```

In the above code snippet, when the “called” text printed in the console?

- ☐ in Mounting Phase
- ☐ in Updating Phase
- ☒ in Unmounting Phase
- ☐ All the above

Ans: C

2.

The type of data which is stored in redux store?

- ☒ object
- ☐ array
- ☐ number

Ans: A

3.

How we can prepare the templates in React ?

- ☒ using components

- ☐ using classes
- ☐ using functions

117 sec.

Ans: A

4.

How we can prevent component unwanted rerenderings ?

- ☒ React.memo
- ☐ React.useMemo
- ☐ React.useCallback
- ☐ React.useTransition

Ans: A

5.

In React event handler method called by passing one argument , what is the argument?

- ☐ array
- ☐ number
- ☒ SyntheticBaseEvent
- ☐ None of the above

Ans: C

6.

Can we create more than one context in react application ?

- ☒ Yes
- ☐ No

Ans: A

7.

In redux , reducer take how many arguments ?

117 sec.

- ☐ 1
- ☒ 2
- ☐ 3
- ☐ 4

Ans: B

8.

```
const myRef=React.useRef()
```

what is the values of myRef.current ?

- ☐ null
- ☒ undefined

Ans: B

9.

```
React.useEffect(()=>
```

```
  },[cnt,name])
```

In the above code snippet, when the callback method called ?

- ☒ in mounting phase
- ☒ cnt state variable updation
- ☒ name prop value updation
- ☐ every state or prop variables updation

Ans: ABC

10.

How we can come to know the performance of react component

- ☒ using Profiler
- ☐ using Portal

Ans: A

117 sec.

11.

```
React.useEffect(()=>
  

  })
```

In the above code snippet, when the callback method called ?

- ☒ in Mounting phase
- ☒ In Updating phase
- ☐ in unmouting phase
- ☐ Above All

Ans: AB

12.

```
const App=(props)=>{
  

  }
```

In the above App props parameter is which type ?

- ☐ number
- ☐ array
- ☒ object
- ☐ string

Ans: C

13.

Can we change the prop value inside the child component?

- ☒ No
- ☐ Yes

Ans: A

14.

117 sec.

```
const [cnt,setCnt]=React.useState(0)
```

if we update the cnt like below

```
for(let i=0;i<5;i++){  
  setCnt((currVal)=>{  
    return currVal+1  
  })  
}
```

now what is the cnt value ?

- ☐ 1
☒ 5

Ans: B

15.

Which lib used to render content inside the container in React ?

- ☐ react lib
☒ ReactDOM lib
☐ Babel lib
☐ reactStrap lib

Ans: B

16.

In React component JSX can we apply inline style using below syntax

JSX:

```
<div style="color:red">Sachin</div>
```

- ☐ Yes
☒ No

Ans: B

117 sec.

17.

useRef hook return type ?

- ☒ object
- ☐ array
- ☐ number
- ☐ string

Ans: A

18.

useEffect hook take max how many arguments ?

- ☐ 1
- ☒ 2
- ☐ 3
- ☐ 4

Ans: B

19.

```
const [cnt,setCnt]=React.useState(0)
```

if we update the cnt like below

```
for(let i=0;i<5;i++){  
  setCnt(cnt+1)  
}
```

now what is the cnt value ?

- ☒ 1
- ☐ 5

Ans: A

117 sec.

20.

```
const App=({name})=>{  
  return <div>{name.length}</div>  
}  
App.defaultProps={  
  name:"UV"  
}  
<App name="Sachin" />
```

- ☐ 0
- ☐ 2
- ☒ 6

Ans: C

WRITE AGAIN