

# Write Test

156 sec.

[Home](#) [Write Test](#) [Write Program](#) [Result](#) [Change](#)

[Password](#) [Logout](#)

1.

```
React.useEffect(()=>
```

```
  },[cnt])
```

In the above code snippet, when the callback method called ?

- ☒ in mounting phase
- ☒ for every cnt state variable value updationn
- ☐ for any state variable updation
- ☐ Above All

**Ans: AB**

2.

```
const App=(props)=>{
```

```
}
```

```
<App n1="100" >10</App>
```

How we can retrieve 10 value inside the App component

- ☐ props.n1
- ☐ props
- ☒ props.children

**Ans: C**

3.

We can pass the data from parent to all direct or indirect childrens using context API? **156 sec.**

- ☒ Yes  
☐ No

**Ans: A**

4.

```
const [cnt,setCnt]=React.useState(0)
```

if we update the cnt like below

```
for(let i=0;i<5;i++){  
  setCnt((currVal)=>{  
    return currVal+1  
  })  
}
```

now what is the cnt value ?

- ☐ 1  
☒ 5

**Ans: B**

5.

Using which method we can get the forwarded reference ?

- ☐ React.getRef  
☒ React.forwardRef

**Ans: B**

6.

156 sec.

```
const App=({name})=>{  
  return <div>{name.length}</div>  
}  
App.defaultProps={  
  name:"UV"  
}  
<App />
```

- ☐ 0  
☒ 2

**Ans: B**

7.

Using which methods, we can create context ?

- ☐ React.useEffect  
☒ React.createContext  
☐ React.myContext  
☐ React.useRef

**Ans: B**

8.

How many ways we can get the data from promise object

- ☒ then  
☒ await  
☐ async  
☐ onload

**Ans: AB**

9.

```
const myRef=React.useRef();
```

which attribute key we used to bind above myRef to an element ?

156 sec.

- ☒ ref
- ☐ id
- ☐ name
- ☐ class

**Ans: A**

10.

Below using which hook, we can manage the state at application level ?

- ☐ useState
- ☐ useRef
- ☒ useReducer
- ☐ useMemo

**Ans: C**

11.

`const myRef=React.useRef()`

what is the values of `myRef.current` ?

- ☐ null
- ☒ undefined

**Ans: B**

12.

All hooks in react are which type ?

- ☐ number
- ☒ function
- ☐ array
- ☐ object

**Ans: B**

13.

156 sec.

```
const [cnt,setCnt]=React.useState(0)
```

if we update the cnt like below

```
for(let i=0;i<5;i++){  
  setCnt(cnt+1)  
}
```

now what is the cnt value ?

- ☒ 1
- ☐ 5

**Ans: A**

14.

React.useRef() returns one object, which contains which default property.

- ☐ name
- ☐ ref
- ☒ current
- ☐ value

**Ans: C**

15.

Why we go for redux ?

- ☒ statemanagement at application level
- ☐ statemanagement at component level

**Ans: A**

16.

```
const App=(props)=>{
```

```
}
```

156 sec.

In the above App props parameter is which type ?

- ☐ number
- ☐ array
- ☒ object
- ☐ string

**Ans: C**

17.

```
const myRef=React.useRef(100)
```

myRef.current ?

- ☐ undefined
- ☒ 100
- ☐ null
- ☐ Error

**Ans: B**

18.

```
React.useEffect(()=>
```

```
},{cnt,name})
```

In the above code snippet, when the callback method called ?

- ☒ in mounting phase
- ☒ cnt state variable updation
- ☒ name prop value updation
- ☐ every state or prop variables updation

**Ans: ABC**

19.

How we can hold the data which is coming from outside to the component?  
156 sec.

- ☐ refs
- ☒ props
- ☐ context
- ☐ updater

**Ans: B**

20.

```
const [data,setData]=React.useState(0);
```

Can we pass function as an argument to setData function ?

- ☐ No
- ☒ Yes

**Ans: B**

WRITE AGAIN