

# Write Test

131 sec.

[Home](#) [Write Test](#) [Write Program](#) [Result](#) [Change](#)

[Password](#) [Logout](#)

1.

We can pass the data from child to all direct or indirect parents using context API ?

- ☐ Yes  
☒ No

**Ans: B**

2.

useState hook return type ?

- ☐ number  
☒ array  
☐ object  
☐ string

**Ans: B**

3.

```
const App=(props)=>{
```

```
}
```

```
<App n1="100" >10</App>
```

How we can retrieve 10 value inside the App component

- ☐ props.n1  
☐ props

Ans: C

4.

```
const [data,setData]=React.useState(0);
```

```
for(let i=0;i<5;i++){  
  setData((val)=>{  
    return val+1  
  })  
}
```

what is the value of data

- ☐ 0  
☒ 5  
☐ 1  
☐ Error

Ans: B

5.

useState hook takes maximum how many arguments ?

- ☐ 0  
☒ 1  
☐ 2  
☐ 3

Ans: B

6.

Below using which hook, we can manage the state at application level ?

- ☐ useState

131 sec.

- ☐ useRef
- ☒ useReducer
- ☐ useMemo

**Ans: C**

7.

In React event handler method called by passing one argument , what is the argument?

- ☐ array
- ☐ number
- ☒ SyntheticBaseEvent
- ☐ None of the above

**Ans: C**

8.

In React, event name should be in the camelCase ?

- ☒ Yes
- ☐ No

**Ans: A**

9.

How we can pass the data from child component to parent component ?

- ☒ callbacks
- ☐ props
- ☐ refs
- ☐ updater

**Ans: A**

10.

Which lib used to recognize

131 sec.

```
const App={()=>{
```

```
}
```

App as a component ?

- ☒ react lib
- ☐ reactDOM lib
- ☐ Babel lib
- ☐ reactStrap lib

**Ans: A**

11.

```
const App=(props)=>{
```

```
}
```

```
<App n1="10"></App>
```

How we can retrieve n1 value inside the App component

- ☒ props.n1
- ☐ props

**Ans: A**

12.

```
const App=({name})=>{
```

```
  return <div>{name.length}</div>
```

```
}
```

```
App.defaultProps={
```

```
  name:"UV"
```

```
}
```

```
<App name="Sachin" />
```

- ☐ 0
- ☐ 2
- ☒ 6

131 sec.

**Ans: C**

13.

Below which hook we used to handle lifecycle phases in React ?

- ☐ useState
- ☒ useEffect
- ☐ useRef
- ☐ useMemo

**Ans: B**

14.

We can pass the data from child component to parent component using callbacks, So we need to define callback function ?

- ☐ child component
- ☒ parent component
- ☐ As a global function

**Ans: B**

15.

In React component JSX can we apply inline style using below syntax

JSX:

```
<div style={{color:"red"}}>Sachin</div>
```

- ☒ Yes
- ☐ No

**Ans: A**

131 sec.

16.

Using which attribute key we can provide the data to the context ?

- ☐ name
- ☒ value
- ☐ data
- ☐ object

**Ans: B**

17.

```
const App=({name}){  
  return <div>{name.length}</div>  
}
```

<App />

- ☐ 0
- ☒ error

**Ans: B**

18.

```
const myRef=React.useRef();
```

which attribute key we used to bind above myRef to an element ?

- ☒ ref
- ☐ id
- ☐ name
- ☐ class

**Ans: A**

19.

How many ways we can get the data from promise object

- ☒ then
- ☒ await
- ☐ async
- ☐ onload

131 sec.

**Ans: AB**

20.

In React component JSX can we apply inline style using below syntax

JSX:

```
<div style="color:red">Sachin</div>
```

- ☐ Yes
- ☒ No

**Ans: B**

WRITE AGAIN