

Write Test

187 sec.

[Home](#) [Write Test](#) [Write Program](#) [Result](#) [Change](#)

[Password](#) [Logout](#)

1.

useState hook takes maximum how many arguments ?

- ☐ 0
- ☒ 1
- ☐ 2
- ☐ 3

Ans: B

2.

```
const [data,setData]=React.useState(0);
```

```
for(let i=0;i<5;i++){  
  setData(data+1)  
}
```

what is the value of data

- ☐ 0
- ☐ 5
- ☒ 1
- ☐ Error

Ans: C

3.

```
const App=(props)=>{
```

Hi...Buddy

How can I help you ?

187 sec.

```
}
```

```
<App n1="100" >10</App>
```

How we can retrieve 10 value inside the App component

- ☐ props.n1
- ☐ props
- ☒ props.children

Ans: C

4.

In React component JSX can we apply inline style using below syntax

JSX:

```
<div style="color:red">Sachin</div>
```

- ☐ Yes
- ☒ No

Ans: B

5.

Below which statement is valid ?

- ☒ useCallback works at function level
- ☒ useMemo works at variable level
- ☒ React.memo works at component level
- ☒ useState used to manage the state of the variable at application level

Ans: ABC

6.

How we can come to know the performance of react c

- ☒ using Profiler

Hi...Buddy

How can I help you ?

☐ using Portal

187 sec.

Ans: A

7.

In React component JSX can we apply inline style using below syntax

JSX:

```
<div style={{color:"red"}}>Sachin</div>
```

☒ Yes

☐ No

Ans: A

8.

How we can pass the data from child component to parent component ?

☒ callbacks

☐ props

☐ refs

☐ updater

Ans: A

9.

How we can prepare the templates in React ?

☒ using components

☐ using classes

☐ using functions

Ans: A

10.

Hi...Buddy

How can I help you ?

- ☒ Yes
☐ No

187 sec.

Ans: A

11.

React.useRef() returns one object, which contains which default property.

- ☐ name
☐ ref
☒ current
☐ value

Ans: C

12.

Can we create more than one context in react application ?

- ☒ Yes
☐ No

Ans: A

13.

axios.get(-) method return type

- ☒ Promise Object
☐ object
☐ Array
☐ Number

Ans: A

14.

In React, event handler method called by passing how many arguments ?

- ☒ one

Hi...Buddy
How can I help you ?

- ☐ three
- ☐ zero

187 sec.

Ans: A

15.

useRef hook return type ?

- ☒ object
- ☐ array
- ☐ number
- ☐ string

Ans: A

16.

Using which attribute key we can provide the data to the context ?

- ☐ name
- ☒ value
- ☐ data
- ☐ object

Ans: B

17.

```
const [cnt,setCnt]=React.useState(0)
```

if we update the cnt like below

```
for(let i=0;i<5;i++){  
  setCnt(cnt+1)  
}
```

now what is the cnt value ?

- ☐ 1

Hi...Buddy

How can I help you ?

Ans: A

187 sec.

18.

```
const App=(props)=>{
```

```
}
```

```
<App n1="10"></App>
```

How we can retrieve n1 value inside the App component

☒ props.n1

☐ props

Ans: A

19.

useEffect hook take max how many arguments ?

☐ 1

☒ 2

☐ 3

☐ 4

Ans: B

20.

Which lib used to recognize

```
const App=()=>{
```

```
}
```

App as a component ?

Hi...Buddy

How can I help you ?

- ☒ react lib
- ☐ ReactDOM lib
- ☐ Babel lib
- ☐ reactStrap lib

187 sec.

Ans: A

WRITE AGAIN

Hi...Buddy

How can I help you ?