

# Write Test

168 sec.

[Home](#) [Write Test](#) [Write Program](#) [Result](#) [Change](#)

[Password](#) [Logout](#)

1.

In React component JSX can we apply inline style using below syntax

JSX:

```
<div style={{color:"red"}}>Sachin</div>
```

☒ Yes

☐ No

**Ans: A**

2.

```
const [data,setData]=React.useState(0);
```

```
for(let i=0;i<5;i++){
```

```
  setData((val)=>{
```

```
    return val+1
```

```
  })
```

```
}
```

what is the value of data

☐ 0

☒ 5

☐ 1

☐ Error

**Ans: B**

168 sec.

3.

```
React.useEffect(()=>
  return ()=>{
    console.log("called");
  }
},[])
```

In the above code snippet, when the “called” text printed in the console?

- ☐ in Mounting Phase
- ☐ in Updating Phase
- ☒ in Unmounting Phase
- ☐ All the above

**Ans: C**

4.

React is a library or framework?

- ☒ library
- ☐ framework

**Ans: A**

5.

React.useRef() returns one object, which contains which default property.

- ☐ name
- ☐ ref
- ☒ current
- ☐ value

**Ans: C**

6.

Using which methods, we can create context ?

168 sec.

- ☐ React.useEffect
- ☒ React.createContext
- ☐ React.myContext
- ☐ React.useRef

**Ans: B**

7.

Can I use all JavaScript events in React ?

- ☒ Yes
- ☐ No

**Ans: A**

8.

How many ways we can get the data from promise object

- ☒ then
- ☒ await
- ☐ async
- ☐ onload

**Ans: AB**

9.

```
const App=({name})=>{
  return <div>{name.length}</div>
}
App.defaultProps={
  name:"UV"
}
<App />
```

- ☐ 0  
☒ 2

168 sec.

**Ans: B**

10.

```
const [data,setData]=React.useState(0);
```

Can we pass function as an argument to setData function ?

- ☐ No  
☒ Yes

**Ans: B**

11.

We can pass the data from parent to all direct or indirect childrens using context API?

- ☒ Yes  
☐ No

**Ans: A**

12.

useEffect hook take max how many arguments ?

- ☐ 1  
☒ 2  
☐ 3  
☐ 4

**Ans: B**

13.

Props are read only in react ?

- ☒ Yes
- ☐ No

168 sec.

**Ans: A**

14.

How we can hold the data which is coming from outside to the component ?

- ☐ refs
- ☒ props
- ☐ context
- ☐ updater

**Ans: B**

15.

```
React.useEffect(()=>
```

```
},[])
```

In the above code snippet, when the callback method called ?

- ☒ Only after mounting
- ☐ Every updation
- ☐ Just before unmounting
- ☐ Above All

**Ans: A**

16.

is JSX code will compile ?

- ☒ Yes
- ☐ No

**Ans: A**

168 sec.

17.

Below which hook we used to handle lifecycle phases in React ?

- ☐ useState
- ☒ useEffect
- ☐ useRef
- ☐ useMemo

**Ans: B**

18.

Below which statement is valid ?

- ☒ useCallback works at function level
- ☒ useMemo works at variable level
- ☒ React.memo works at component level
- ☐ useState used to manage the state of the variable at application level

**Ans: ABC**

19.

Which lib used to render content inside the container in React ?

- ☐ react lib
- ☒ ReactDOM lib
- ☐ Babel lib
- ☐ reactStrap lib

**Ans: B**

20.

useState hook takes maximum how many arguments ?

- ☐ 0
- ☒ 1
- ☐ 2
- ☐ 3

Ans: B

168 sec.

WRITE AGAIN