

# Write Test

**144 sec.**[Home](#) [Write Test](#) [Write Program](#) [Result](#) [Change](#)[Password](#) [Logout](#)

1.

```
const App=({name})=>{  
  return <div>{name.length}</div>  
}  
App.defaultProps={  
  name:"UV"  
}  
<App />
```

- ☐ 0  
☒ 2

**Ans: B**

2.

In React, event handler method called by passing how many arguments ?

- ☒ one  
☐ two  
☐ three  
☐ zero

**Ans: A**

3.

useState returns an array, that array contains how many

- ☐ 0  
☐ 1

Hi...Buddy  
How can I help you ?

144 sec.

- ☒ 2  
☐ 3

**Ans: C**

4.

useRef hook return type ?

- ☒ object  
☐ array  
☐ number  
☐ string

**Ans: A**

5.

Below using which hook, we can manage the state at application level ?

- ☒ useState  
☐ useRef  
☐ useReducer  
☐ useMemo

**Ans: C**

6.

In React component JSX can we apply inline style using below syntax

JSX:

`<div style={{color:"red"}}>Sachin</div>`

- ☒ Yes  
☐ No

**Ans: A**

Hi...Buddy  
How can I help you ?

144 sec.

7.

Props are read only in react ?

- ☒ Yes  
☐ No

Ans: A

8.

How many ways we can get the data from promise object

- ☒ then  
☒ await  
☐ async  
☐ onload

Ans: AB

9.

useEffect hook take max how many arguments ?

- ☐ 1  
☒ 2  
☐ 3  
☐ 4

Ans: B

10.

```
const App=({name})=>{  
  return <div>{name.length}</div>  
}  
App.defaultProps={  
  name:"UV"
```

Hi...Buddy  
How can I help you ?

144 sec.

```
}
```

```
<App name="Sachin" />
```

- ☐ 0
- ☐ 2
- ☒ 6

Ans: C

11.

In redux , reducer take how many arugments ?

- ☐ 1
- ☒ 2
- ☐ 3
- ☐ 4

Ans: B

12.

Using which method we can get the forwarded reference ?

- ☐ React.getRef
- ☒ React.forwardRef

Ans: B

13.

React.useRef() returns one object, which contains which default property.

- ☐ name
- ☐ ref
- ☒ current
- ☐ value

Ans: C

Hi...Buddy  
How can I help you ?

144 sec.

14.

Using which methods, we can create context ?

- ☐ React.useEffect
- ☒ React.createContext
- ☐ React.myContext
- ☐ React.useRef

Ans: B

15.

How we can pass the data from child component to parent component ?

- ☒ callbacks
- ☐ props
- ☐ refs
- ☐ updater

Ans: A

16.

Below which statement is valid

- ☒ using useReducer hook, we can manage the state at application level
- ☒ using useReducer hook, we can manage the state at component level
- ☒ using useState hook, we can manage the state at application level
- ☒ using useContext we can consume the data from context

Ans: ABCD

17.

Can we change the prop value inside the child component?

- ☒ No
- ☐ Yes

Ans: A

Hi...Buddy  
How can I help you ?

144 sec.

18.

Below which lib, used to compile JSX code ?

- ☐ react lib
- ☐ reactDOM lib
- ☒ babel lib
- ☐ bootstrap lib

Ans: C

19.

```
const App=(props)=>{
```

```
}
```

```
<App n1="100" >10</App>
```

How we can retrieve 10 value inside the App component

- ☐ props.n1
- ☐ props
- ☒ props.children

Ans: C

20.

```
const [data,setData]=React.useState(0);
```

Can we pass function as an argument to setData function ?

- ☐ No
- ☒ Yes

Ans: B

Hi...Buddy

How can I help you ?

WRITE AGAIN

144 sec.

Hi...Buddy  
How can I help you ?