Write Test

159 sec.

Home   Write Test   Write Program   Result   Change

Password   Logout

1.

Which lib used to recognize

const App=()=>{

}

App as a component ?

- ○ react lib
- ○ reactDOM lib
- ○ Babel lib
- ○ reactStrap lib

Ans: A

2.

const App=(props)=>{

}

<App n1="10"></App>

How we can retrieve n1 value inside the App component

- ○ props.n1
- ○ props

Ans: A

Hi...Buddy

How can I help you ?

159 sec.

3.

In React, event name should be in the camelCase ?

◉ Yes
◯ No

Ans: A

4.

How we can pass the data from child component to parent component ?

◉ callbacks
◯ props
◯ refs
◯ updater

Ans: A

5.

Props are read only in react ?

◉ Yes
◯ No

Ans: A

6.

Can we forward reference(useRef()) one component to another component?

◉ Yes
◯ No

Ans: A

Hi...Buddy
How can I help you ?

3.

Using which hook , we can consume the data from context ?

159 sec.

○ useRef
○ useState
◉ useContext
○ useMemo

Ans: C

8.

Using which attribute key we can provide the data to the context ?

○ name
◉ value
○ data
○ object

Ans: B

9.

const [data,setData]=React.useState(0);

Can we pass function as an argument to setData function ?

○ No
◉ Yes

Ans: B

10.

const App=(props)=>{

}

<App n1="100" >10</App>

How we can retrieve 10 value inside the App compone

Hi...Buddy

How can I help you ?

○ props.n1
○ props
◉ props.children

Ans: C

11.

How many ways we can get the data from promise object

☑ then
☑ await
☐ async
☐ onload

Ans: AB

12.

axios.get(-) method return type

◉ Promise Object
○ object
○ Array
○ Number

Ans: A

13.

Below which hook we used to handle lifecycle phases in React ?

○ useState
◉ useEffect
○ useRef
○ useMemo

Ans: B

Hi...Buddy

How can I help you ?

14.

In React, event handler method called by passing how many arguments ?

159 sec.

- ◉ one
- ○ two
- ○ three
- ○ zero

Ans: A

15.

React.useEffect(()=>

},[cnt,name])

In the above code snippet, when the callback method called ?

- ☐ in mounting phase
- ☑ cnt state variable updation
- ☑ name prop value updation
- ☐ every state or prop variables updation

Ans: ABC

16.

Which lib used to render content inside the container in React ?

- ○ react lib
- ◉ reactDOM lib
- ○ Babel lib
- ○ reactStrap lib

Ans: B

17.

useState hook return type ?

- ○ number
- ◉ array
- ○ object

Hi...Buddy

How can I help you ?

○ string

Ans: B

18.

Why we go for redux ?

◉ statemanagement at application level
○ statemanagement at component level

Ans: A

19.

const myRef=React.useRef()

what is the values of myRef.current ?

○ null
◉ undefined

Ans: B

20.

const App=(props)=>{

}

In the above App props parameter is which type ?

○ number
○ array
◉ object
○ string

Ans: C

Hi...Buddy

How can I help you ?

WRITE AGAIN

159 sec.

Hi...Buddy

How can I help you ?