

# Write Test

77 sec.

[Home](#) [Write Test](#) [Write Program](#) [Result](#) [Change](#)

[Password](#) [Logout](#)

1.

React.useRef() returns one object, which contains which default property.

- ☐ name
- ☐ ref
- ☒ current
- ☐ value

**Ans: C**

2.

Below which lib, used to compile JSX code ?

- ☐ react lib
- ☐ reactDOM lib
- ☒ babel lib
- ☐ bootstrap lib

**Ans: C**

3.

useRef hook return type ?

- ☒ object
- ☐ array
- ☐ number
- ☐ string

**Ans: A**

77 sec.

4.

Using which hook , we can consume the data from context ?

- ☐ useRef
- ☐ useState
- ☒ useContext
- ☐ useMemo

**Ans: C**

5.

React is a library or framework?

- ☒ library
- ☐ framework

**Ans: A**

6.

In React event handler method called by passing one argument , what is the argument?

- ☐ array
- ☐ number
- ☒ SyntheticBaseEvent
- ☐ None of the above

**Ans: C**

7.

Below using which hook, we can manage the state at application level ?

- ☐ useState
- ☐ useRef
- ☒ useReducer
- ☐ useMemo

Ans: C

77 sec.

8.

Below which statement is valid

- ☒ using useReducer hook, we can manage the state at application level
- ☒ using useReducer hook, we can manage the state at component level
- ☒ using useState hook, we can manage the state at application level
- ☒ using useContext we can consume the data from context

Ans: ABCD

9.

Below which hook we used to handle lifecycle phases in React ?

- ☐ useState
- ☒ useEffect
- ☐ useRef
- ☐ useMemo

Ans: B

10.

```
const myRef=React.useRef(100)
```

myRef.current ?

- ☐ undefined
- ☒ 100
- ☐ null
- ☐ Error

Ans: B

11.

In React component JSX can we apply inline style using below syntax

JSX:

77 sec.

```
<div style={{color:"red"}}>Sachin</div>
```

- ☒ Yes
- ☐ No

**Ans: A**

12.

Which lib used to render content inside the container in React ?

- ☐ react lib
- ☒ ReactDOM lib
- ☐ Babel lib
- ☐ reactStrap lib

**Ans: B**

13.

```
const myRef=React.useRef();
```

which attribute key we used to bind above myRef to an element ?

- ☒ ref
- ☐ id
- ☐ name
- ☐ class

**Ans: A**

14.

useState hook return type ?

- ☐ number
- ☒ array
- ☐ object
- ☐ string

Ans: B

77 sec.

15.

Using which attribute key we can provide the data to the context ?

- ☐ name
- ☒ value
- ☐ data
- ☐ object

Ans: B

16.

```
const App=({name})=>{  
  return <div>{name.length}</div>  
}  
App.defaultProps={  
  name:"UV"  
}  
<App />
```

- ☐ 0
- ☒ 2

Ans: B

17.

Using which methods, we can create context ?

- ☐ React.useEffect
- ☒ React.createContext
- ☐ React.myContext
- ☐ React.useRef

Ans: B

77 sec.

18.

useState returns an array, that array contains how many elements ?

- ☐ 0
- ☐ 1
- ☒ 2
- ☐ 3

Ans: C

19.

```
const App=(props)=>{
```

```
}
```

In the above App props parameter is which type ?

- ☐ number
- ☐ array
- ☒ object
- ☐ string

Ans: C

20.

```
const App=(props)=>{
```

```
}
```

```
<App n1="100" >10</App>
```

How we can retrieve 10 value inside the App component

- ☐ props.n1
- ☐ props
- ☒ props.children

Ans: C

77 sec.

WRITE AGAIN