

Write Test

120 sec.[Home](#) [Write Test](#) [Write Program](#) [Result](#) [Change](#)[Password](#) [Logout](#)

1.

```
React.useEffect(()=>
```

```
  ,[cnt,name])
```

In the above code snippet, when the callback method called ?

- ☐ in mounting phase
- ☒ cnt state variable updation
- ☒ name prop value updation
- ☐ every state or prop variables updation

Ans: ABC

2.

In React component JSX can we apply inline style using below syntax

JSX:

```
<div style={{color:"red"}}>Sachin</div>
```

- ☒ Yes
- ☐ No

Ans: A

3.

is JSX code will compile ?

- ☒ Yes
- ☐ No

Hi...Buddy
How can I help you ?

Ans: A**120 sec.**

4.

```
const [data,setData]=React.useState(0);
```

Can we pass function as an argument to setData function ?

- ☐ No
☒ Yes

Ans: B

5.

Which lib used to recognize

```
const App=()=>{
```

```
}
```

App as a component ?

- ☒ react lib
☐ reactDOM lib
☐ Babel lib
☐ reactStrap lib

Ans: A

6.

Can we create more than one context in react application ?

- ☒ Yes
☐ No

Ans: A

Hi...Buddy
How can I help you ?

120 sec.

7.

```
React.useEffect(()=>
  return ()=>{
    console.log("called");
  }
},[])
```

In the above code snippet, when the “called” text printed in the console?

- ☒ in Mounting Phase
- ☐ in Updating Phase
- ☐ in Unmounting Phase
- ☐ All the above

Ans: C

8.

```
const myRef=React.useRef();
```

which attribute key we used to bind above myRef to an element ?

- ☒ ref
- ☐ id
- ☐ name
- ☐ class

Ans: A

9.

Using which methods, we can create context ?

- ☐ React.useEffect
- ☒ React.createContext
- ☐ React.myContext
- ☐ React.useRef

Ans: B

Hi...Buddy
How can I help you ?

120 sec.

10.

useState hook returns an array, that array contains two elements , the second element type is ?

- ☐ number
- ☐ array
- ☐ string
- ☒ function

Ans: D

11.

While loading the component, how many ways we can pass the data ?

<App></App >

- ☒ as a children
- ☒ as an attribute
- ☐ as a props
- ☐ as a callback

Ans: AB

12.

```
const App=({name})=>{  
  return <div>{name.length}</div>  
}  
App.defaultProps={  
  name:"UV"  
}  
<App />
```

- ☐ 0
- ☒ 2

Ans: B

Hi...Buddy
How can I help you ?

120 sec.

13.

How we can pass the data from child component to parent component ?

- ☒ callbacks
- ☐ props
- ☐ refs
- ☐ updater

Ans: A

14.

How many ways we can get the data from promise object

- ☒ then
- ☒ await
- ☐ async
- ☐ onload

Ans: AB

15.

```
const myRef=React.useRef()
```

what is the values of myRef.current ?

- ☐ null
- ☒ undefined

Ans: B

16.

```
const [data,setData]=React.useState(0);
```

```
for(let i=0;i<5;i++){  
  setData(data+1)  
}
```

Hi...Buddy
How can I help you ?

120 sec.

what is the value of data

- ☐ 0
- ☐ 5
- ☒ 1
- ☐ Error

Ans: C

17.

useEffect hook take max how many arguments ?

- ☐ 1
- ☒ 2
- ☐ 3
- ☐ 4

Ans: B

18.

How we can come to know the performance of react component

- ☒ using Profiler
- ☐ using Portal

Ans: A

19.

useRef hook return type ?

- ☒ object
- ☐ array
- ☐ number
- ☐ string

Ans: A

Hi...Buddy
How can I help you ?

120 sec.

20.

useState hook return type ?

- ☐ number
- ☒ array
- ☐ object
- ☐ string

Ans: B

WRITE AGAIN

Hi...Buddy
How can I help you ?