

Write Test

96 sec.[Home](#) [Write Test](#) [Write Program](#) [Result](#) [Change](#)[Password](#) [Logout](#)

1.

```
const [cnt,setCnt]=React.useState(0)
```

if we update the cnt like below

```
for(let i=0;i<5;i++){  
  setCnt((currVal)=>{  
    return currVal+1  
  })  
}
```

now what is the cnt value ?

- ☐ 1
☒ 5

Ans: B

2.

Below which lib, used to compile JSX code ?

- ☐ react lib
☐ reactDOM lib
☒ babel lib
☐ bootstrap lib

Ans: C

3.

Hi...Buddy
How can I help you ?

96 sec.

```
const App=({name})=>{  
  return <div>{name.length}</div>  
}  
App.defaultProps={  
  name:"UV"  
}  
<App />
```

- ☐ 0
☒ 2

Ans: B

4.

Using which attribute key we can provide the data to the context ?

- ☐ name
☒ value
☐ data
☐ object

Ans: B

5.

In redux , reducer take how many arugments ?

- ☐ 1
☒ 2
☐ 3
☐ 4

Ans: B

6.

```
const [cnt,setCnt]=React.useState(0)
```

Hi...Buddy

How can I help you ?

96 sec.

if we update the cnt like below

```
for(let i=0;i<5;i++){  
  setCnt(cnt+1)  
}
```

now what is the cnt value ?

- ☒ 1
☐ 5

Ans: A

7.

```
const myRef=React.useRef();
```

which attribute key we used to bind above myRef to an element ?

- ☒ ref
☐ id
☐ name
☐ class

Ans: A

8.

In React, event handler method called by passing how many arguments ?

- ☒ one
☐ two
☐ three
☐ zero

Ans: A

9.

Using which methods, we can create context ?

Hi...Buddy

How can I help you ?

96 sec.

- ☐ React.useEffect
- ☒ React.createContext
- ☐ React.myContext
- ☐ React.useRef

Ans: B

10.

How we can pass the data from child component to parent component ?

- ☒ callbacks
- ☐ props
- ☐ refs
- ☐ updater

Ans: A

11.

How we can come to know the performance of react component

- ☒ using Profiler
- ☐ using Portal

Ans: A

12.

In React event handler method called by passing one argument , what is the argument?

- ☐ array
- ☐ number
- ☒ SyntheticBaseEvent
- ☐ None of the above

Ans: C

Hi...Buddy
How can I help you ?

13.

Can we change the prop value inside the child component?

96 sec.

- ☒ No
☐ Yes

Ans: A

14.

```
React.useEffect(()=>
  return ()=>{
    console.log("called");
  }
},[])
```

In the above code snippet, when the “called” text printed in the console?

- ☐ in Mounting Phase
☐ in Updating Phase
☐ in Unmounting Phase
☒ All the above

Ans: C

15.

const myRef=React.useRef()

what is the values of myRef.current ?

- ☐ null
☒ undefined

Ans: B

16.

Using which method we can get the forwarded referen

Hi...Buddy
How can I help you ?

96 sec.

- ☐ React.getRef
☒ React.forwardRef

Ans: B

17.

useState hook returns an array, that array contains two elements , the second element type is ?

- ☐ number
☐ array
☐ string
☒ function

Ans: D

18.

```
React.useEffect(()=>  
  
})
```

In the above code snippet, when the callback method called ?

- ☒ in Mounting phase
☒ In Updating phase
☐ in unmounting phase
☐ Above All

Ans: AB

19.

```
React.useEffect(()=>  
  
),[cnt,name])
```

In the above code snippet, when the callback method

- ☒ in mounting phase

Hi...Buddy
How can I help you ?

- ☒ cnt state variable updation
- ☒ name prop value updation
- ☐ every state or prop variables updation

96 sec.**Ans: ABC**

20.

Below using which hook, we can manage the state at application level ?

- ☐ useState
- ☐ useRef
- ☒ useReducer
- ☐ useMemo

Ans: C[WRITE AGAIN](#)

Hi...Buddy
How can I help you ?