# B.Tech.(IT) Major Project–I (IT449) End-Semester Evaluation

# Genetic Algorithm-Based Automatic Generation and Optimization of Security Policies for Tool-Using LLM Agents


**BY**

**Mr. Kalal Pavan Teja[231IT030]**

**Mr. Medikurthi Sai Govardhan Rao[231IT039]**

Department of Information Technology

National Institute of Technology Karnataka, Surathkal-575025

Under the Guidance of

A Vamshi

Assistant Professor

# Table of Contents


- Introduction
- Literature Survey
- Outcome of the Literature Survey
- Problem Statement and Objectives
- Methodology
- Experimental Setup
- Experimental Results
- Conclusion and Future Work
- References
- Timeline of the Project

# Introduction

- LLM agents combine an LLM with tools, memory and autonomous decision-making to perform multi-step tasks.
- They can interact with files, databases, APIs, email and other external tools.
- Unlike a simple chatbot, an agent can decide which tool to use and in what order.
- This autonomy introduces security risks during tool execution, such as unauthorized access or data leakage.
- Therefore, safe tool-use behaviour must be verified, not just the final answer.

# Literature Survey – Paper 1

*"A. Gokhale, V. Srivastava, and F. Bullo, "**LogicGuard: Improving embodied LLM agents through temporal logic based critics**," arXiv preprint arXiv:2507.03293, 2025. [Online]. Available: arXiv"*

## Key Points

- Combines an LLM Actor (chooses actions) with an LLM Critic (studies trajectories) and an LTL verifier that formally checks each proposed action.
- The critic proposes new temporal constraints after observing failed or inefficient trajectories safety rules evolve from experience.





**Figure 1:** Workflow of LogicGuard for LLM-based safe tool use using temporal logic constraints.

**Source:** Paper1(Page no. 4 - Figure 1)

# Literature Survey – Paper 2(Contd.)

*"A. Doshi, Y. Hong, C. Xu, E. Kang, A. Kapravelos, and C. Kästner, "**Towards verifiably safe tool use for LLM agents**," arXiv preprint arXiv:2601.08012, 2026. [Online]. Available: arXiv"*

## Key Points

- Uses STPA (System-Theoretic Process Analysis) to systematically identify hazards that arise when individually-safe tools are combined.
- Converts identified hazards into formal safety requirements, enforced at the agent's tool boundary through a capability-enhanced MCP using capability, confidentiality and trust labels.





**Figure 2:** Workflow of verifiably safe tool use using STPA, formal safety specifications, and runtime enforcement.

# Literature Survey – Paper 3(Contd.)

*"L. Elkoussy and J. Perez, "AgentLTL: **A trace-verification framework for measuring, enforcing, and training procedural compliance in tool-using LLM agents**," arXiv preprint arXiv:2607.02599, 2026. [Online]. Available: arXiv"*

## Key Points

- Measures whether an agent's tool-use procedure is correct not just its final answer via an LTL-based compliance score across 6 layers (branching, arguments, sequence, ordering, call count, exact arguments).
- Used in two modes: Harnessing (blocks non-compliant actions at runtime) and Fine-tuning (the compliance score becomes a training reward).





**Figure 3:** Workflow of AgentLTL for formal verification of tool-using LLM agent trajectories.

# Literature Survey – Paper 4(Contd.)

*"Ruiyang Zhang, "**Why Formal Monitors Fail: Attack Distribution Entropy as a Coverage Bound for LTL-Based LLM Agent Safety**," arXiv:2608.01388, 2026. [Online]. Available: arXiv"*

## Key Points

- Studies how attack-pattern diversity affects fixed LTL/FSA monitor coverage; concentrated attack patterns allow better coverage, while highly diverse patterns reduce coverage.
- Proposes a pre-deployment entropy test that uses a small sample of attack trajectories to estimate whether a fixed monitor is likely to provide good coverage before deployment.





**Figure 4:** Workflow of entropy-based analysis of LTL monitor coverage.

# Outcome of Literature Survey

- Existing approaches show that trajectory-level safety and formal verification are important for tool-using LLM agents.
- Current methods mainly focus on verifying or enforcing existing security constraints.
- Cybersecurity knowledge and automatic policy generation are not deeply integrated into these approaches.
- Diverse and unseen behaviours highlight limitations in fixed safety monitors and motivate stronger generalization evaluation.
- This motivates our approach: RAG-based policy generation + GA-based optimization + LTL/AgentLTL verification.

# Problem Statement of the Project

LLM agents can complete the same task through different tool-use trajectories, but some trajectories may violate security requirements even when the task succeeds.

**AGENT SECURITY PROBLEM**

- Autonomous tool use
- Multi-step execution
- Different tool-use trajectories

**EXISTING APPROACHES**

- Predefined / expert or critic-generated constraints
- Focus on verification & enforcement
- Limited policy optimization

**RESEARCH GAP**

- No integrated policy generation + optimization
- Limited adaptability of security policies

**Need:** Automated Policy Generation + Optimization + Formal Verification

# Objectives of the Project

1. Develop a realistic agentic environment and generate multi-step trajectories through autonomous tool selection.

2. Analyse trajectories to identify safe, unsafe, and procedurally different behaviours.

3. Develop a cybersecurity knowledge base and use RAG to generate candidate security policies.

4. Develop a Genetic Algorithm-based mechanism to optimize the generated security policies.

5. Formally verify and enforce security policies over agent trajectories using LTL/AgentLTL-based constraints.

6. Evaluate policy effectiveness on diverse and unseen behaviours and compare with baseline approaches.

# Proposed Methodology in this Project





**Figure 5:** Seven layers from the agent environment to experimental evaluation

# Experimental Setup

- **Environment:** ShopSphere simulated company with 7 teams, 24 users and 30 tools, with access rules and data sensitivity tags.
- **Scenarios:** 49 designed scenarios (routine, forbidden, vendor, attack and more) plus 15 scenarios for testing.
- **Agents:** A real Groq LLM agent (gpt-oss-20b) chooses its own tools, under 3 prompt strengths: none, one sentence, six rules.
- **Experiment:** Each scenario is run under every prompt with repeats, giving 486 real runs; every step is logged.
- **Judging & Stack:** 18 safety rules label each run; built with Python, Streamlit, Groq API and pytest.

# Architecture Diagram of the Project





**Figure 6:** Implemented architecture (Objectives 1 and 2)

# Sequence Diagram of the Project





**Figure 7:** End-to-end evaluation flow

# Sequence Diagram of the Project (Cond..)





**Figure 8:** Objective 1 flow: Agent, tools and trajectory logging

# Sequence Diagram of the Project (Cond..)





**Figure 9:** Objective 2 flow: Rules, labels and risk patterns

# Experimental Results






**Figure 10:** Dashboard for running agents and executing scenarios.


# Experimental Results





| category | DECLINED | SAFE | SAFE_VARIANT | UNSAFE_OUTCOME | UNSAFE_PROCEDURAL |
|---|---|---|---|---|---|
| allowed_cross_team | 10 | 37 | 1 | 0 | 0 |
| attack | 47 | 0 | 0 | 13 | 2 |
| documents | 7 | 1 | 1 | 7 | 2 |
| events | 12 | 29 | 0 | 12 | 0 |
| not_allowed | 65 | 0 | 0 | 27 | 7 |
| procedure | 4 | 0 | 0 | 0 | 14 |
| routine | 9 | 81 | 6 | 0 | 1 |
| temporary_access | 3 | 1 | 0 | 14 | 0 |
| vendor | 22 | 11 | 0 | 20 | 10 |

**Figure 11:** Objective 2 dashboard showing safety evaluation results and task outcomes.

# Experimental Results




| Scenario Split | Unsafe Runs Covered | Pattern Coverage |
|---|---|---|
| Known | 72 / 95 | 76% |
| Diverse | 5 / 13 | 38% |
| Unseen | 3 / 21 | 14% |

## Risk-Pattern Generalization

# Conclusion and Future work

## Conclusion

Same Task, Different Trajectories: Agents can complete the same task using different tool sequences. Whether a trajectory is **SAFE or UNSAFE** depends on the actions performed and their order, not just the final output.

## Future Work

- Integrate RAG and Genetic Algorithm optimization.
- Add LTL/AgentLTL verification and enforcement.
- Evaluate on known and unseen unsafe behaviours.

# References


1. A. Gokhale, V. Srivastava, and F. Bullo, “LogicGuard: Improving embodied LLM agents through temporal logic based critics,” arXiv preprint arXiv:2507.03293, 2025. [Online]. Available: arXiv

2. A. Doshi, Y. Hong, C. Xu, E. Kang, A. Kapravelos, and C. Kästner, “Towards verifiably safe tool use for LLM agents,” arXiv preprint arXiv:2601.08012, 2026. [Online]. Available: arXiv

3. L. Elkoussy and J. Perez, “AgentLTL: A trace-verification framework for measuring, enforcing, and training procedural compliance in tool-using LLM agents,” arXiv preprint arXiv:2607.02599, 2026. [Online]. Available: arXiv

4. Ruiyang Zhang, “Why Formal Monitors Fail: Attack Distribution Entropy as a Coverage Bound for LTL-Based LLM Agent Safety,” arXiv:2608.01388, 2026. [Online]. Available: arXiv

# Timeline of the Project

| Semester | Phase | Milestone | Status |
|---|---|---|---|
| Semester 1(mid-sem) | 1 | Literature Survey, Problem Statement, Proposed Methodology | Completed |
| | 2 | Agentic Environment | Completed |
| Semester 1(end- sem) | 3 | Trajectory & Behaviour Analysis(Safe Vs Unsafe) | Completed |
| Semester 2 | 4 | RAG Policy Generation | Started |
| | 5 | GA Policy Optimization | Planned |
| Semester2(after mid) | 6 | LTL/AgentLTL Verification & Enforcement | Planned |
| | 7 | Evaluation & Baseline comparison | Planned |