

BASH-Project-1

1. Bash CASE Statements.

1. To demonstrate the use of the case statement.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ nano caseStatement1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ chmod 755 caseStatement1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ cat caseStatement1.sh
#!/bin/bash
echo "Do you know Java Programming?"
read -p "Yes/No? : " Answer

case $Answer in
    Yes|yes|y|Y)
        echo "That's amazing."
        echo
        ;;
    No|no|N|n)
        echo "It's easy. Let's start learning from javatpoint."
        ;;
esac
pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ ./caseStatement1.sh
Do you know Java Programming?
Yes/No? : y
That's amazing.

pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ ./caseStatement1.sh
Do you know Java Programming?
Yes/No? : n
It's easy. Let's start learning from javatpoint.
pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ ./caseStatement1.sh
Do you know Java Programming?
Yes/No? : m
pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$
```

2. To demonstrate combined scenario where there is also a default case when no previous matched case is found.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ nano caseStatement2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ chmod 755 caseStatement2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ cat caseStatement2.sh
#!/bin/bash

echo "Which Operating System are you using?"
echo "Windows, Android, Chrome, Linux, Others?"
read -p "Type your OS Name: " OS

case $OS in
    Windows|windows)
        echo "That's common. You should try something new."
        echo
        ;;
    Android|android)
        echo "This is my favorite. It has lots of applications."
        echo
        ;;
    Chrome|chrome)
        echo "Cool!!! It's for pro users. Amazing Choice."
        echo
        ;;
    Linux|linux)
        echo "You might be serious about security!!"
        echo
        ;;
    *)
        echo "Sounds interesting. I will try that."
        echo
        ;;
esac

pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ _
```

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ ./caseStatement2.sh
Which Operating System are you using?
Windows, Android, Chrome, Linux, Others?
Type your OS Name: linux
You might be serious about security!!

pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ ./caseStatement2.sh
Which Operating System are you using?
Windows, Android, Chrome, Linux, Others?
Type your OS Name: ANDROID
Sounds interesting. I will try that.

pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ ./caseStatement2.sh
Which Operating System are you using?
Windows, Android, Chrome, Linux, Others?
Type your OS Name: Windows
That's common. You should try something new.

pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ ./caseStatement2.sh
Which Operating System are you using?
Windows, Android, Chrome, Linux, Others?
Type your OS Name: CHroMe
Sounds interesting. I will try that.

pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ ./caseStatement2.sh
Which Operating System are you using?
Windows, Android, Chrome, Linux, Others?
Type your OS Name: mac
Sounds interesting. I will try that.

pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ ./caseStatement2.sh
Which Operating System are you using?
Windows, Android, Chrome, Linux, Others?
Type your OS Name: Android
This is my favorite. It has lots of applications.

pavan@5b3d002ed32e50d:~/Bash_Script_files/CaseStatements$ _
```

2. Bash FOR loop.

1. Basic example of 'for loop'.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ vi for1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ chmod 755 for1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ cat for1.sh
#!/bin/bash
#
learn="Start learning from Javatpoint."
for learn in $learn
do
    echo $learn
done
echo "Thank You."

pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ ./for1.sh
Start
learning
from
Javatpoint.
Thank You.
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$
```

2. Basic example to print a series of numbers from 1 to 10.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ vi for2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ chmod 755 for2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ cat for2.sh
#!/bin/bash

for num in {1..10}
do
    echo $num
done
echo "Series of numbers from 1 to 10."

pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ ./for2.sh
1
2
3
4
5
6
7
8
9
10
Series of numbers from 1 to 10.
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$
```

3. For Loop to Read a Range with Increment.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ vi for3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ chmod 755 for3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ cat for3.sh
#!/bin/bash
#
#For Loop to Read a Range with Increment

for num in {1..10};
do
    echo $num
done

pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ ./for3.sh
1
2
3
4
5
6
7
8
9
10
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ _
```

4. For Loop to Read a Range with Decrement.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ vi for4.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ chmod 755 for4.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ cat for4.sh
#!/bin/bash
#
#For Loop to Read a Range with Decrement

for num in {10..1};
do
    echo $num
done

pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ ./for4.sh
10
9
8
7
6
5
4
3
2
1
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$
```

5. Array Declaration.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ vi for5.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ chmod 755 for5.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ cat for5.sh
#!/bin/bash

arr=("Welcome" "to" "Javatpoint")

for i in "${arr[@]}"
do
    echo "$i"
done

pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ ./for5.sh
Welcome
to
Javatpoint
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/For$ _
```

3.BASH WHILE Loop.

1. To get specified numbers using BASH WHILE Loop.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops$ mkdir while
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops$ cd while/
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ ls
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ nano whileLoop1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ chmod 755 whileLoop1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ cat whileLoop1.sh
#!/bin/bash

read -p "Enter starting number: " snum
read -p "Enter ending number: " enum

while [[ $snum -le $enum ]]; do
    echo $snum
    ((snum++))
done

echo "This is the sequence that you wanted."
```

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/While$ ./whileLoop1.sh
Enter starting number: 3
Enter ending number: 8
3
4
5
6
7
8
This is the sequence that you wanted.
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/While$ ./whileLoop1.sh
Enter starting number: 3
Enter ending number: -8
This is the sequence that you wanted.
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/While$ ./whileLoop1.sh
Enter starting number: -4
Enter ending number: 5
-4
-3
-2
-1
0
1
2
3
4
5
This is the sequence that you wanted.
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/While$ ./whileLoop1.sh
Enter starting number: -15
Enter ending number: -12
-15
-14
-13
-12
This is the sequence that you wanted.
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/While$
```

2. To get specified numbers using BASH WHILE Loop with Multiple Conditions.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ nano whileLoop2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ chmod u=rwx whileLoop2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ cat whileLoop2.sh
#!/bin/bash

read -p "Enter starting number: " snum
read -p "Enter ending number: " enum

while [[ $snum -lt $enum || $snum == $enum ]];
do
    echo $snum
    ((snum++))
done

echo "This is the sequence that you wanted."

pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ ./whileLoop2.sh
Enter starting number: -200
Enter ending number: -195
-200
-199
-198
-197
-196
-195
This is the sequence that you wanted.
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ ./whileLoop2.sh
Enter starting number: 12
Enter ending number: 9
This is the sequence that you wanted.
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$
```

- ```
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ nano whileLoop3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ chmod a+x whileLoop3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ cat whileLoop3.sh
#!/bin/bash
#An infinite while loop

while :; do echo "welcome to UST."; done
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$
```

[illegible]



4. To use Break Statement in BASH WHILE Loop.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ nano whileLoop4.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ chmod 755 whileLoop4.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ cat whileLoop4.sh
#!/bin/bash

echo "Countdown for Website Launching..."
i=10
while [$i -ge 1]
do
 if [$i == 2]
 then
 echo "Mission Aborted, Some Technical Error Found."
 break
 fi
 echo "$i"
 ((i--))
done

pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$./whileLoop4.sh
Countdown for Website Launching...
10
9
8
7
6
5
4
3
Mission Aborted, Some Technical Error Found.
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$
```

5. To use Continue Statement in BASH WHILE Loop.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ nano whileLoop5.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ chmod 755 whileLoop5.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ cat whileLoop5.sh
#!/bin/bash

i=0
while [$i -le 10]
do
 ((i++))
 if [["$i" == 5]]; then
 continue
 fi
 echo "Current Number : $i"
done

echo "Skipped number 5 using Continue Statement."

pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$./whileLoop5.sh
Current Number : 1
Current Number : 2
Current Number : 3
Current Number : 4
Current Number : 6
Current Number : 7
Current Number : 8
Current Number : 9
Current Number : 10
Current Number : 11
Skipped number 5 using Continue Statement.
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$
```

6. To use BASH WHILE Loop in C-Style (C programming language).

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ nano whileLoop6.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ chmod 755 whileLoop6.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$ cat whileLoop6.sh
#!/bin/bash

i=1
while ((i <= 10))
do
 echo $i
 let i++
done

pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$./whileLoop6.sh
1
2
3
4
5
6
7
8
9
10
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/while$
```

## 4.BASH UNTIL Loop

1. Bash Until Loop with a single condition.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops$ mkdir Until
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops$ cd Until/
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/Until$ ls
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/Until$ nano untilLoop1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/Until$ chmod u=rwx untilLoop1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/Until$ cat untilLoop1.sh
#!/bin/bash

i=1
until [$i -gt 10]
do
 echo $i
 ((i++))
done

pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/Until$./untilLoop1.sh
1
2
3
4
5
6
7
8
9
10
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/Until$ _
```

2. Bash Until Loop with multiple conditions.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/Until$ nano untilLoop2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/Until$ chmod 755 untilLoop2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/Until$ cat untilLoop2.sh
#!/bin/bash

max=5
a=1
b=0

until [[$a -gt $max || $b -gt $max]]; do
 echo "a = $a & b = $b."
 ((a++))
 ((b++))
done

pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/Until$./untilLoop2.sh
a = 1 & b = 0.
a = 2 & b = 1.
a = 3 & b = 2.
a = 4 & b = 3.
a = 5 & b = 4.
pavan@5b3d002ed32e50d:~/Bash_Script_files/loops/Until$
```

## 5.BASH Strings

1. To check whether two strings are equal using “=” operator.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ nano string1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ nano string1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ chmod u=rwx string1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ cat string1.sh
#!/bin/bash
#Script to check whether two strings are equal.

str1="WelcometoUST."
str2="UST"
if [$str1 = $str2];
then
echo "Both the strings are equal."
else
echo "Strings are not equal."
fi
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$./string1.sh
Strings are not equal.
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$
```

2. To check whether two strings are equal using “!=” operator

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ nano string2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ chmod u=rwx string2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ cat string2.sh
#!/bin/bash
#Script to check whether two strings are equal.

str1="WelcometoUST."
str2="UST"

if [[$str1 != $str2]];
then
echo "Strings are not equal."
else
echo "Strings are equal."
fi
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$./string2.sh
Strings are not equal.
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ _
```

3. To check if string1 is less than string2 equal using "<" operator.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ nano string3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ chmod 755 string3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ cat string3.sh
#!/bin/sh

str1="WelcometoUST"
str2="UST"
if [$str1 \< $str2];
then
 echo "$str1 is less then $str2"
else
 echo "$str1 is not less then $str2"
fi
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$./string3.sh
WelcometoUST is not less then UST
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$
```

4. To check if string1 is greater than string2.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ nano string4.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ chmod 755 string4.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ cat string4.sh
#!/bin/sh

str1="WelcometoUST"
str2="UST"
if [$str1 \> $str2];
then
 echo "$str1 is greater then $str2"
else
 echo "$str1 is less then $str2"
fi
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$./string4.sh
WelcometoUST is greater then UST
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$
```

5. To check if the string is zero or greater than zero.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ nano string5.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ chmod 755 string5.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ cat string5.sh
#!/bin/sh

str="WelcometoUST"

if [-n $str];
then
 echo "String is not empty"
else
 echo "String is empty"
fi
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$./string5.sh
String is not empty
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ _
```

6. To check if the string is empty or equal to zero.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ nano string6.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ chmod 755 string6.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ cat string6.sh
#!/bin/sh
str=""

if [-z $str];
then
 echo "String is empty."
else
 echo "String is non-empty."
fi
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$./string6.sh
String is empty.
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ _
```

## 6.BASH FIND String Length

1. To find the length of a string using `${#string_variable_name}`.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ nano findString1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ chmod u=rwx findString1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ cat findString1.sh
#!/bin/bash
#Bash program to find the length of a string

str="Welcome to UST"
length=${#str}

echo "Length of '$str' is $length"
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$./findString1.sh
Length of 'Welcome to UST' is 14
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$
```

2. To find the length of a string using ``expr length "$str"``.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ nano findString2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ chmod 755 findString2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ cat findString2.sh
#!/bin/bash
#Bash script to find the length of a string

str="Welcome to UST"
length=`expr length "$str"`

echo "Length of '$str' is $length"
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$./findString2.sh
Length of 'Welcome to UST' is 14
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$
```

3. To find the length of a string using ``expr "$str" : '.*'``.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ nano findString3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ chmod 755 findString3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ cat findString3.sh
#!/bin/bash
#Bash script to find the length of a string

str="Welcome to UST"
length=`expr "$str" : '.*'`

echo "Length of '$str' is $length"
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$./findString3.sh
Length of 'Welcome to UST' is 14
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ _
```

4. To find the length of a string using `wc` command.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ nano findString4.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ chmod 744 findString4.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ cat findString4.sh
#!/bin/bash
#Bash script to find the length of a string

str="Welcome to UST"
length=`echo $str | wc -c`

echo "Length of '$str' is $length"
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$./findString4.sh
Length of 'Welcome to UST' is 15
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ _
```

5. To find the length of a string using `awk` command.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ nano findString5.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ chmod u=rwx findString5.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$ cat findString5.sh
#!/bin/bash
#Bash script to find the length of a string

str="Welcome to UST"
length=`echo $str | awk '{print length}'`

echo "Length of '$str' is $length"
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$./findString5.sh
Length of 'Welcome to UST' is 14
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/Find$
```



## 7. Bash Split String

### 1. Bash Split String by Space.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$ nano splitString1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$ chmod 755 splitString1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$ cat splitString1.sh
#!/bin/bash
read -p "Enter any string separated by space: " str

IFS=' '
read -ra ADDR <<<"$str" #reading str as an array as tokens separated by IFS

for i in "${ADDR[@]}"; #accessing each element of array
do
echo "$i"
done
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$./splitString1.sh
Enter any string separated by space: Welcome to UST
Welcome
to
UST
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$ _
```

### 2. Bash Split String by Symbol.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$ nano splitString2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$ chmod a+x splitString2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$ cat splitString2.sh
#!/bin/bash

read -p "Enter Name, State and Age separated by a comma: " entry

IFS=','
read -a strarr <<<"$entry"

echo "Name : ${strarr[0]}"
echo "State : ${strarr[1]}"
echo "Age : ${strarr[2]}"

pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$./splitString2.sh
Enter Name, State and Age separated by a comma: Dan,US,05-12-1992
Name : Dan
State : US
Age : 05-12-1992
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$
```

3. Bash Split String by Symbol without \$IFS variable.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$ nano splitString3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$ chmod u=rwx splitString3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$ cat splitString3.sh
#!/bin/bash

read -p "Enter any string separated by colon(:) " str
readarray -d : -t strarr <<<"$str"

printf "\n"

for ((n=0; n < ${#strarr[*]}; n++))
do
 echo "${strarr[n]}"
done

pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$./splitString3.sh
Enter any string separated by colon(:) Hi:Hello:UST:says Hello to all:END..

Hi
Hello
UST
says Hello to all
END..

pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$
```

4. Bash Split String by another string without \$IFS variable.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$ nano splitString4.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$ chmod 744 splitString4.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$ cat splitString4.sh
#!/bin/bash

str="WeLearnWelcomeLearnYouLearnOnLearnJavatpoint"
delimiter=Learn
s=strdelimiter
array=()

while [[$s]]; do
 array+=("${s%%"$delimiter"*}")
 s=${s#"${delimiter}"}
done

declare -p array

pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$./splitString4.sh
declare -a array=([0]="We" [1]="Welcome" [2]="You" [3]="On" [4]="Javatpoint")
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$
```

5. Bash Split String using Trim Command.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$ nano splitString5.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$ chmod 755 splitString5.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$ cat splitString5.sh
#!/bin/bash

my_str="We;welcome;you;on;javatpoint."
my_arr=($(echo $my_str | tr ";" "\n"))

for i in "${my_arr[@]}"
do
 echo $i
done

pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$./splitString5.sh
We
welcome
you
on
javatpoint.
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SplitString$
```

## 8. Bash Substring

1. To Extract till Specific Characters from Starting.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$ nano subString1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$ chmod 755 subString1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$ cat subString1.sh
#!/bin/bash
#Script to extract first 10 characters of a string
echo "String: We welcome you on Javatpoint."
str="We welcome you on Javatpoint."
echo "Total characters in a String: ${#str} "
substr="${str:0:10}"
echo "Substring: $substr"
echo "Total characters in Substring: ${#substr} "
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$./subString1.sh
String: We welcome you on Javatpoint.
Total characters in a String: 29
Substring: We welcome
Total characters in Substring: 10
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$ _
```

2. To Extract from Specific Character onwards.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$ nano subString2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$ chmod u=rwx subString2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$ cat subString2.sh
#!/bin/bash
#Script to print from 11th character onwards
str="We welcome you on Javatpoint."
substr="${str:11}"
echo "$substr"
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$./subString2.sh
you on Javatpoint.
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$
```

3. To Extract a Single Character.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$ nano subString3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$ chmod 755 subString3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$ cat subString3.sh
#!/bin/bash
#Script to print 11th character of a String
str="We welcome you on Javatpoint."
substr="${str:11:1}"
echo "$substr"
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$./subString3.sh
y
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$ _
```

4. To Extract the specific characters from last.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$ nano subString4.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$ chmod a+x subString4.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$ cat subString4.sh
#!/bin/bash
#Script to extract 11 characters from last
str="We welcome you on UST."
substr="${str:(-4)}"
echo "$substr"
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$./subString4.sh
UST.
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/SubString$
```

## 9. Bash Concatenate String

1. Write Variables Side by Side.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ mkdir ConcatenateString
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings$ cd ConcatenateString/
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ nano concatenateString1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ nano concatenateString1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ chmod u=rwx concatenateString1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ cat concatenateString1.sh
#!/bin/bash
#Script to Concatenate Strings
#Declaring the first String
str1="We welcome you"
#Declaring the Second String
str2=" on Javatpoint."
#Combining first and second string
str3="$str1$str2"
#Printing a new string by combining both
echo $str3
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$./concatenateString1.sh
We welcome you on Javatpoint.
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$
```

2. Using Double Quotes.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ nano concatenateString2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ chmod 755 concatenateString2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ cat concatenateString2.sh
#!/bin/bash
#Script to Concatenate Strings
#Declaring String Variable
str="We welcome you"
#Add the variable within the string
echo "$str on Javatpoint."
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$./concatenateString2.sh
We welcome you on Javatpoint.
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ _
```

3. Using Append Operator with Loop.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ nano concatenateString3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ chmod a+x concatenateString3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ cat concatenateString3.sh
#!/bin/bash
echo "Printing the name of the programming languages"
#Initializing the variable before combining
lang=""
#for loop for reading the list
for value in 'java' 'python' 'C' 'C++';
do
lang+="$value " #Combining the list values using append operator
done
#Printing the combined values
echo "$lang"
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$./concatenateString3.sh
Printing the name of the programming languages
javapythonCC++
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ _
```

4. Using the Printf Function.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ nano concatenateString4.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ chmod u=rwx concatenateString4.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ cat concatenateString4.sh
#!/bin/bash
str="Welcome"
printf -v new_str "$str to Javatpoint."
echo $new_str
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$./concatenateString4.sh
Welcome to Javatpoint.
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$
```

5. Using Literal Strings.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ nano concatenateString5.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ chmod 755 concatenateString5.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ cat concatenateString5.sh
#!/bin/bash
str="Welcome to"
newstr="${str} Javatpoint."
echo "$newstr"
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$./concatenateString5.sh
Welcome to Javatpoint.
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$
```

6. Using Underscore.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ nano concatenateString6.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ chmod u=rwx concatenateString6.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$ cat concatenateString6.sh
#!/bin/bash
str1="Hello"
str2="World!"
echo "${str1}_${str2}"
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$./concatenateString6.sh
Hello_World!
pavan@5b3d002ed32e50d:~/Bash_Script_files/Strings/ConcatenateString$
```

## 10. Bash Functions

1. To declare functions.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ nano function1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ chmod 755 function1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ cat function1.sh
#!/bin/bash

JTP () {
 echo 'Welcome to Javatpoint.'
}

JTP

echo
function JTP1 {
 echo 'Welcome to Javatpoint.'
}

JTP1
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$./function1.sh
Welcome to Javatpoint.

Welcome to Javatpoint.
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ _
```

2. To pass arguments to functions.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ nano function2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ nano function2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ chmod a+x function2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ cat function2.sh
#!/bin/bash
#Script to pass and access arguments

function_arguments()
{
 echo $1
 echo $2
 echo $3
 echo $4
 echo $5
}

#Calling function_arguments
function_arguments "We" "welcome" "you" "on" "Javatpoint."
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$./function2.sh
We
welcome
you
on
Javatpoint.
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ _
```

3. To understand how variables scope works.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ nano function3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ chmod a+x function3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ cat function3.sh
#!/bin/bash

v1='A'
v2='B'
my_var () {
 local v1='C'
 v2='D'
 echo "Inside Function"
 echo "v1 is $v1."
 echo "v2 is $v2."
}
echo "Before Executing the Function"
echo "v1 is $v1."
echo "v2 is $v2."
my_var
echo "After Executing the Function"
echo "v1 is $v1."
echo "v2 is $v2."
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$./function3.sh
Before Executing the Function
v1 is A.
v2 is B.
Inside Function
v1 is C.
v2 is D.
After Executing the Function
v1 is A.
v2 is D.
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$
```

4. To setup a return status for a function.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ nano function4.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ chmod u+rxw function4.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ cat function4.sh
#!/bin/bash
#Setting up a return status for a function

print_it () {
 echo Hello $1
 return 5
}

print_it User
print_it Reader
echo The previous function returned a value of $?
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$./function4.sh
Hello User
Hello Reader
The previous function returned a value of 5
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ _
```

5. To send the value to stdout using echo or printf commands.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ nano function5.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ chmod 755 function5.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ cat function5.sh
#!/bin/bash

print_it () {
 local my_greet="Welcome to Javatpoint."
 echo "$my_greet"
}

my_greet="$(print_it)"
echo $my_greet
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$./function5.sh
Welcome to Javatpoint.
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$
```

6. To override command using function.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ nano function6.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ chmod u=rwx function6.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$ cat function6.sh
#!/bin/bash
#Script to override command using function

echo () {
 builtin echo -n `date +"[%m-%d %H:%M:%S]"` " : "
 builtin echo $1
}

echo "Welcome to Javatpoint."
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$./function6.sh
[01-30 05:12:46] : Welcome to Javatpoint.
pavan@5b3d002ed32e50d:~/Bash_Script_files/Functions$
```



## 11. Bash Array

1. To print an element of an array with an index of 2.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ nano array1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ chmod 755 array1.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ cat array1.sh
#!/bin/bash
#Script to print an element of an array with an index of 2

#declaring the array
declare -a example_array=("Welcome" "To" "Javatpoint")

#printing the element with index of 2
echo ${example_array[2]}
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$./array1.sh
Javatpoint
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$
```

2. To print all the elements of the array.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ nano array2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ nano array2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ chmod u=wxr array2.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ cat array2.sh
#!/bin/bash
#Script to print all the elements of the array

#declaring the array
declare -a example_array=("Welcome" "To" "Javatpoint")

#Printing all the elements
echo "${example_array[@]}"
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$./array2.sh
Welcome To Javatpoint
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$
```

3. To print the keys of the array.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ nano array3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ chmod 755 array3.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ cat array3.sh
#!/bin/bash
#Script to print the keys of the array

#Declaring the Array
declare -a example_array=("Welcome" "To" "Javatpoint")

#Printing the Keys
echo "${!example_array[@]}"
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$./array3.sh
0 1 2
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$
```

4. To print all keys and values using loop through the array.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ nano array5.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ chmod 755 array5.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ cat array5.sh
#!/bin/bash
#Script to print all keys and values using loop through the array

declare -a example_array=("Welcome" "To" "Javatpoint")

#Array Loop
for i in "${!example_array[@]}"
do
echo The key value of element "${example_array[$i]}" is "$i"
done
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$./array5.sh
The key value of element Welcome is 0
The key value of element To is 1
The key value of element Javatpoint is 2
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ _
```

5. To loop through an array in C-style.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ nano array6.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ chmod a+x array6.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ cat array6.sh
#!/bin/bash
#Script to loop through an array in C-style

declare -a example_array=("Welcome" "To" "Javatpoint")

#Length of the Array
length=${#example_array[@]}

#Array Loop
for ((i=0; i < ${length}; i++))
do
echo $i ${example_array[$i]}
done
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$./array6.sh
0 Welcome
1 To
2 Javatpoint
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$
```

6. To add elements to an Array.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ nano array7.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ chmod 755 array7.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ cat array7.sh
#!/bin/bash

#Declaring an array
declare -a example_array=("Java" "Python" "PHP" "HTML")

#Adding new element
example_array[4]="JavaScript"

#Printing all the elements
echo "${example_array[@]}"
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$./array7.sh
Java Python PHP HTML JavaScript
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$
```

7. To update array element.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ nano array9.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ chmod 755 array9.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ cat array9.sh
#!/bin/bash

#Script to update array element

#Declaring the array
declare -a example_array=("We" "welcome" "you" "on" "SSSIT")

#Updating the Array Element
example_array[4]=Javatpoint

#Printig all the elements of the Array
echo ${example_array[@]}
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$./array9.sh
We welcome you on Javatpoint
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$
```

8. To delete the element from the array.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ nano array10.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ chmod u=rwx array10.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ cat array10.sh
#!/bin/bash

#Script to delete the element from the array

#Declaring the array
declare -a example_array=("Java" "Python" "HTML" "CSS" "JavaScript")

#Removing the element
unset example_array[1]

#Printing all the elements after deletion
echo "${example_array[@]}"
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$./array10.sh
Java HTML CSS JavaScript
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$
```

9. To delete the entire Array.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ nano array11.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ chmod 755 array11.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ cat array11.sh
#!/bin/bash
#Script to delete the entire Array

#Declaring the Array
declare -a example_array=("Java" "Python" "HTML" "CSS" "JavaScript")

#Deleting Entire Array
unset example_array

#Printing the Array Elements
echo ${!example_array[@]}

#Printing the keys
echo ${!example_array[@]}
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$./array11.sh

pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$
```

10. To slice Array Element from index 1 to index 3.

```
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ nano array12.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ chmod a+x array12.sh
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$ cat array12.sh
#!/bin/bash
#Script to slice Array Element from index 1 to index 3

#Declaring the Array
example_array=("Java" "Python" "HTML" "CSS" "JavaScript")

#Slicing the Array
sliced_array=("${example_array[@]:1:3}")

#Applying for loop to iterate over each element in Array
for i in "${sliced_array[@]}"
do
echo $i
done
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$./array12.sh
Python
HTML
CSS
pavan@5b3d002ed32e50d:~/Bash_Script_files/Arrays$
```