



Search...

Courses

Tutorials

Practice

Jobs



Problem

Editorial

Submissions

Comments



## Subarray Frequency Count Queries



Difficulty: **Medium**    Accuracy: **69.37%**    Submissions: **6K+**  
Points: **4**    Average Time: **25m**

Given an array **arr[]** of **n** integers and a 2D array **queries[][]** representing **q** queries, where each **queries[i]** consists of three integers: **l**, **r**, and **x**. For each query determine how many times the element **x** appears in the **arr[]** from index **l** to **r** (both inclusive).

Return a list of integers where the **i**-th value represents the answer to the **i**-th query.

### Examples:

**Input:** **arr[]** = [1, 2, 1, 3, 1, 2, 3], **queries[][]** = [[0, 4, 1], [2, 5, 2], [1, 6, 3], [0, 6, 5]]

**Output:** [3, 1, 2, 0]

### Explanation:

query [0, 4, 1] -> Subarray = [1, 2, 1, 3, 1], 1 appears 3 times

query [2, 5, 2] -> Subarray = [1, 3, 1, 2], 2 appears 1 time

query [1, 6, 3] -> Subarray = [2, 1, 3, 1, 2, 3] 3 appears 2 times

query [0, 6, 5] -> Subarray = [1, 2, 1, 3, 1, 2, 3], 5 appears 0 times

Python3

Start Timer

```
1 from bisect import bisect_left, bisect_right
2
3 class Solution:
4     def freqInRange(self, arr, queries):
5         pos = {}
6
7         # Store indices of each element
8         for i, x in enumerate(arr):
9             if x not in pos:
10                 pos[x] = []
11                 pos[x].append(i)
12
13         ans = []
14
15         for l, r, x in queries:
16             if x not in pos:
17                 ans.append(0)
18                 continue
19
20             idx = pos[x]
21
22             left = bisect_left(idx, l)
23             right = bisect_right(idx, r)
24
25             ans.append(right - left)
26
27         return ans
```