

Data Collection and Preprocessing Phase

Date	15 July 2024
Team ID	739646
Project Title	Number Oracle:Big Mart Sales Predictive Analysis
Maximum Marks	6 Marks

Data Exploration and Preprocessing Template

Identifies data sources, assesses quality issues like missing values and duplicates, and implements resolution plans to ensure accurate and reliable analysis.

Section	Description
Data Overview	Basic statistics, dimensions, and structure of the data.
Univariate Analysis	Exploration of individual variables (mean, median, mode, etc.).
Bivariate Analysis	Relationships between two variables (correlation, scatter plots).
Multivariate Analysis	Patterns and relationships involving multiple variables.

Outliers and Anomalies	Identification and treatment of outliers.
Data Preprocessing Code Screenshots	
Handling Missing Data	<pre> # Fill NaN values train_df['Item_Weight'].fillna(train_df['Item_Weight'].mean(), inplace=True) test_df['Item_Weight'].fillna(test_df['Item_Weight'].mean(), inplace=True) train_df['Outlet_Size'].fillna(train_df['Outlet_Size'].mode()[0], inplace=True) test_df['Outlet_Size'].fillna(test_df['Outlet_Size'].mode()[0], inplace=True) # Handle outliers using IQR </pre>
Data Transformation	<pre> # Handle outliers using IQR def handle_outliers(df, column): Q1 = df[column].quantile(0.25) Q3 = df[column].quantile(0.75) IQR = Q3 - Q1 lower_bound = Q1 - 1.5 * IQR upper_bound = Q3 + 1.5 * IQR df[column] = np.where(df[column] > upper_bound, upper_bound, np.where(df[column] < lower_bound, lower_bound, df[column])) numerical_columns = ['Item_Weight', 'Item_Visibility', 'Item_MRP', 'Item_Outlet_Sales'] for column in numerical_columns: handle_outliers(train_df, column) if column != 'Item_Outlet_Sales': handle_outliers(test_df, column) </pre>
Feature Engineering	<pre> # Encode categorical features le = LabelEncoder() cat_col = ['Item_Fat_Content', 'Item_Type', 'Outlet_Identifier', 'Outlet_Size', 'Outlet_Location_Type', 'Outlet_Type'] for col in cat_col: train_df[col] = le.fit_transform(train_df[col]) test_df[col] = le.transform(test_df[col]) </pre>
Save Processed Data	<pre> # Train-test split X = train_df.drop(columns=['Item_Outlet_Sales']) y = train_df['Item_Outlet_Sales'] X_train, X_val, y_train, y_val = train_test_split(X, y, test_size=0.3, random_state=42) </pre>

Loading Data

```
# Load datasets
train_df = pd.read_csv('/content/train.csv')
test_df = pd.read_csv('/content/test.csv')
sample_submission_df = pd.read_csv('/content/sample_submission.csv')
```