

## ASSIGNMENT – 4

1) mysql> SELECT Pname, color FROM P

-> WHERE city = 'London';

```
+-----+-----+
| Pname | color |
+-----+-----+
| Nut   | Red   |
| Screw | Blue  |
| Cog   | Red   |
+-----+-----+
3 rows in set (0.00 sec)
```

2) mysql> SELECT DISTINCT \* FROM suppliers

-> WHERE city = 'London';

```
+---+-----+-----+-----+
| s# | Sname | status | city |
+---+-----+-----+-----+
| S1 | Smith | 20     | London |
| S4 | Clark | 20     | London |
+---+-----+-----+-----+
2 rows in set (0.01 sec)
```

3) mysql> SELECT DISTINCT \*

-> FROM suppliers

-> WHERE city = 'Paris' OR city = 'Athens';

```
+---+-----+-----+-----+
| s# | Sname | status | city |
+---+-----+-----+-----+
| S2 | Jones | 10     | Paris |
| S3 | Blake | 30     | Paris |
| S5 | Adams | 30     | Athens |
+---+-----+-----+-----+
3 rows in set (0.00 sec)
```

4) mysql> SELECT \* FROM jobs

-> WHERE city = 'Athens';

```

+-----+
| J# | Jname | City |
+-----+
| J3 | Reader | Athens |
| J4 | Console | Athens |
+-----+
2 rows in set (0.00 sec)

```

5) mysql> SELECT Pname FROM parts

-> WHERE weight BETWEEN 12 AND 14;

```

+-----+
| Pname |
+-----+
| Nut |
| Screw |
| Cam |
+-----+
3 rows in set (0.00 sec)

```

6) mysql> SELECT \* FROM suppliers

-> WHERE status >= 20;

```

+-----+
| s# | Sname | status | city |
+-----+
| S1 | Smith | 20 | London |
| S3 | Blake | 30 | Paris |
| S4 | Clark | 20 | London |
| S5 | Adams | 30 | Athens |
+-----+
4 rows in set (0.00 sec)

```

7) mysql> SELECT \* FROM suppliers

-> WHERE CITY != 'London';

```

+-----+
| s# | Sname | status | city |
+-----+
| S2 | Jones | 10 | Paris |
| S3 | Blake | 30 | Paris |
| S5 | Adams | 30 | Athens |
+-----+
3 rows in set (0.00 sec)

```

8) mysql> SELECT DISTINCT city FROM suppliers;

```

+-----+
| city |
+-----+
| London |
| Paris |
| Athens |
+-----+

```

9) mysql> SELECT \*

-> FROM suppliers

-> ORDER BY city DESC;

```
+-----+-----+-----+-----+
| s# | Sname | status | city |
+-----+-----+-----+-----+
| S2 | Jones | 10 | Paris |
| S3 | Blake | 30 | Paris |
| S1 | Smith | 20 | London |
| S4 | Clark | 20 | London |
| S5 | Adams | 30 | Athens |
+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

10) mysql> SELECT \* FROM parts

-> ORDER BY city, Pname;

```
+-----+-----+-----+-----+-----+
| p# | Pname | color | weight | city |
+-----+-----+-----+-----+-----+
| p6 | Cog | Red | 19 | London |
| p1 | Nut | Red | 12 | London |
| p4 | Screw | Blue | 14 | London |
| p2 | Bolt | Green | 17 | Paris |
| p5 | Cam | Blue | 12 | Paris |
| p3 | Screw | Blue | 17 | Rome |
+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```

11) mysql> SELECT \* FROM suppliers

-> WHERE status BETWEEN 10 AND 20;

```
+-----+-----+-----+-----+
| s# | Sname | status | city |
+-----+-----+-----+-----+
| S1 | Smith | 20 | London |
| S2 | Jones | 10 | Paris |
| S4 | Clark | 20 | London |
+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

12) mysql> SELECT Pname, weight FROM parts

-> WHERE weight NOT BETWEEN 10 AND 15;

```
+-----+-----+
| Pname | weight |
+-----+-----+
| Bolt | 17 |
| Screw | 17 |
| Cog | 19 |
+-----+-----+
3 rows in set (0.00 sec)
```