

adjustments needed and even add an approver
 - When you are ready to submit your req, click Submit

If submitting a multi-line item Coupa req

- Click Add Another
- Use the drop down to find the additional line item you are linking
- Click Add Item
- Follow the instructions above for filling in the fields for that additional item
- Repeat until you have all of the line items added
- Click Submit
- The system will provide you with the link to your Coupa req (this will also be linked in your Allocadia line item's detail panel for each line item of your Coupa req)
- PLEASE NOTE - This does NOT mean your Coupa req has been submitted. This is taking you to the actual req in Coupa to review and you will still need to submit the req in Coupa.
- Click on your Coupa req link and review
- At this point you can make any adjustments needed and even add an approver
- When you are ready to submit your req, click Submit

SECTION: marketing/strategy-performance/dashboards/_index.md

Hierarchy of Marketing Dashboards

Marketing Analytics uses a hierarchical system when building dashboards to help guide the allowable complexity and frame the data for the intended user.

At the highest level, TD Marketing Key Dashboards are intended to provide insights into our top KPIs, while TD Marketing Functional Dashboards give the detailed insights functional marketing teams need. Ad hoc dashboards are meant to answer one-off questions, and are not meant to be used for ongoing KPI reporting. "TD" stands for Trusted Data, and it refers to models inside and from the common schema (see the Data Team handbook page here for more details)

Level	Intended User	Intended Use (examples)	
-----	-----	-----	
TD Marketing Key Dashboards	Execs / All GitLab Team Members	Top KPIs and Targets	
TD General Marketing Dashboards	GTM Teams / All of Marketing	Tracking Leading Indicators / Attributed Pipeline	
TD Marketing Functional Dashboards	Functional Marketing Teams	Campaign Performance / SDR Performance / Partner Sourced Opportunities	
Ad-Hoc	Specific Team Members	Insight into a one-off question	

Marketing Dashboards Supported by MS&A

TD Marketing Key Dashboards

Dashboard	Platform	Access Type	Description	
-----------	----------	-------------	-------------	--

Dashboard	Platform	Access Type	Description
Unified Marketing Funnel Dashboard	Tableau	General	Visualizes the user journey across marketing channels, website engagement, SaaS trials, to a paid conversion. This dashboard helps identify trends and assess the impact of strategic changes implemented by the Digital Marketing, Digital Experience, and Growth teams.

TD General Marketing Dashboards

Dashboard	Platform	Access Type	Description
Marketing Influenced Pipeline	Tableau	SAFE	Tracks marketing contribution to overall pipeline generation through a combination of Adobe Marketo Measure Touchpoints and Sales Qualified Source (SQS) to find opportunities that were influenced by Marketing. See the handbook page for more details.

TD Marketing Functional Dashboards

Function	Dashboard	Platform	Access Type	Description
Integrated Marketing	TD - Campaign Performance	Tableau	General	The source of truth dashboard for marketing campaign performance. It is a single pane of glass view for tracking campaign performance from an Inquiry to a closed won SAO. More detailed information is available on its handbook page.
SalesDev	Sales Dev Analytics Hub	Tableau	SAFE	A management-level view of overall SDR performance by a number of key metrics.
Partner Marketing	Partner Marketing	Tableau	SAFE	A view of partner sources opportunities, partner sourced persons and the partner trial program.
Digital Experience	GitLab - Digital Experience	Looker Studio	General	Visualized metrics in regards to traffic, engagements, and top-of-funnel web conversions for about.gitlab.com from Google Analytics.
Technical Writing	GitLab - Docs Website	Looker Studio	General	Visualized metrics in regards to traffic and engagements for docs.gitlab.com from Google Analytics.
Brand Strategy	GitLab - Brand Awareness - Web Performance	Looker Studio	General	Visualized metrics in regards to traffic, engagements, and top-of-funnel web conversions for Brand Awareness campaigns from Google Analytics and Search Console.
Product Marketing	GitLab - Product Marketing	Looker Studio	General	Visualized metrics in regards to traffic, engagements, and top-of-funnel web conversions for Blogs and Customer Stories from Google Analytics.

When to use TD - Campaign Performance vs Marketing Influenced Pipeline

While our Campaign Performance and Marketing Influenced Pipeline dashboards display similar data, they serve different purposes. The Campaign Performance dashboard is a live view of our campaign data as it exists in our marketing tools (SFDC, Marketo, Marketo Measure) today. It gives the best view into a campaign's near real-time performance.

The Marketing Influenced Pipeline dashboard uses snapshots of our Adobe Marketo Measure and Opportunity data taken on the last day of the fiscal quarter. Snapshotting ensures the total

amount of marketing influenced across our marketing campaigns credited to opportunities can not change as the live data is updated. Meaning GitLab has an unchanging record of marketing influence that we use to compare quarters without worrying that values have changed over time.

The Campaign Performance dashboard is better suited for reporting where close to live data is required, while the Marketing Influenced Pipeline dashboard is preferred when quarterly reviews are done, as the data remains unchanged for previous quarters.

Dashboard Development and Publishing Stages

MS&A uses the stages listed below to denote a dashboard's stage.

Ad-Hoc dashboards do not have a stage.

- Work in Progress (WIP) - Active development is still ongoing. Metrics, design, and location may change at any time. During this stage, we work with stakeholders to create an end product that meets their needs.
- User Acceptance Testing (UAT) - Primary development has been completed, and we are gathering feedback from the intended users and fixing bugs.
- Production - For a dashboard to be considered production, it must be published in the Production area of Tableau and have gone through the Tableau approval process.

Dashboard Building Guidelines

MS&A has agreed on high-level guidelines when presenting data in any visualization:

- Avoid showing fractional KPIs on key metrics that are not percentages (SAOs, MQLs, INQs). Instead, truncate the number. EG: 43 instead of 43.21

SECTION: marketing/strategy-performance/dashboards/td-campaign-performance.md

TD: Campaign Performance Dashboard

The TD: Campaign Performance dashboard is the source of truth dashboard for marketing campaign performance. It is based on Marketo Measure (Bizible) Touchpoints, where each Touchpoint represents a form submitted to a GitLab Marketing website from a person. TD: Campaign Performance (TDP) is based on MS&A's Lead to Revenue model that combines Touchpoints, persons, and Opportunities, allowing TDP to create a single pane of glass view from Inquiry to closed won SAO.

Cohorting

Unlike many of our other dashboards, the primary date is the Bizible Touchpoint created date. Cohorting to the Touchpoint date lets us show a single date filter and makes all the metrics relative to when the Touchpoint happened.

Using the Advanced Filters, the view can be filtered to add more date constraints.

Dashboard Tabs

Below is an outline of the dashboard's main tabs.

Drill Down Tabs

The Campaign, Regional, and Bizible Drill Down Tabs show point-in-time campaign information. These three tabs show the same information by different cuts.

Each tab has a different Tableau Hierarchy in the table view, which can be expanded to show more details. Below is a list of the hierarchies with their fields' names.

- Campaign - Bizible Integrated Campaign > Bizible Marketing Channel > Bizible Marketing Channel Path > UTM Contnet
- Regional - Account Demographics Geo > Sales Segmenet > Region > Area
- Bizible - Bizible Channel > Bizible Channel Path > Campaign

By Single Field

The Overview section shows an overview of leads and contacts for a selected time period. This section deduplicates leads and contacts, counting each person only once, regardless of the number of campaigns they belong to.

Key metrics are presented with the live status of associated inquiries and MQLs of selected campaigns.

Performance by Campaign

In the Performance by Campaign section, each unique person is counted as one per campaign, meaning they would be counted once if the same person were in more than one campaign.

In addition to the key metrics per campaign, we've added fields related to the budgeted and actual campaign spend. These are pulled from the Salesforce Campaign object to estimate the Pipeline to Campaign Spend Ratio (P2S). The SFDC campaign object gets its budget information by directly entering the budget in SFDC or from a linked Allocadia line item through the integration from Allocadia to SFDC.

Metrics

- Touchpoints - Number of unique persons that have engaged with the specific campaigns
- Inquiries - Number of people who have reached (or pasted) the inquiry stage and have a touchpoint associated with the campaign.
- MQLs - Number of people who have reached (or pasted) the marketing qualified lead stage and have a touchpoint associated with the campaign.
- Sales Accepted Leads - Number of leads who have reached (or pasted) the Sales Accepted Lead stage and have a touchpoint associated with the campaign.
- Influenced SAOs - Number of Sales Accepted Opportunities with influence from Marketing campaigns calculated using our custom multi-touch attribution model.
- Influenced SAOs [OC] - Number of Sales Accepted Opportunities with influence from Marketing campaigns calculated using our custom multi-touch attribution model limited to touchpoints that

were the last one before opportunity creation.

- Influenced Net ARR - The amount of NET ARR influenced by our Marketing campaigns using our custom multi-touch attribution model.
- Touched SAOs - The number of SAOs with at least one Marketing touchpoint.
- Cost - The campaign cost reported from the Campaign Object in SFDC. If the campaign cost is \$1, then the value is ignored. The field first looks like the actual cost for a value greater than \$5; if one is not present, it uses the estimated cost.
- The Advanced Filters can control the date range for these metrics, limiting them to only {MQLs, SAOs, etc} created in a given timeframe.

Dashboard Filters

Unless otherwise stated, all filters on the dashboard will filter data on all tabs.

The filters are divided into two groups. Primary Filters are shown at all times, and Advanced Filters are accessible by opening the Advanced Filters panel on the Campaign Drill Down` tab.

The bullets below describe the source of the values in the filters.

Primary Filters

- Touchpoint Date - Date range during which marketing touchpoint occurred
- Intergrated Budget Holder - Filters campaigns based on the Budget Holder field in SFDC/UTM parameters.
- Person Grouping - Filters to either First Order Persons and/or First Order Opps, plus all the combinations.
- SFDC Campaign Type - The Campaign Type field from SFDC. Selecting any non-null value will remove all touchpoints without an SFDC Campaign.
- Bizible Intergrated Campaign Name - Either the SFDC Campaign name or the value utmcampaign parameter.
- Medium - A combined field from utmmidium and Bizible Medium
- Source - A combined field from utmsource and Bizible Source
- UTM Content - The value of the utmcontent parameter.
- AlternativeSegment - Segment of the Person that interacted with the campaign defined using waterfall logic from multiple fields
- AlternativeGeo - Geo Region of the person that interacted with the campaign defined using waterfall logic from multiple fields
- BizibleChannel - Marketing channel that the campaign belongs to
- CampaignRegion - Salesforce field on the campaign
- CampaignSubRegion - Salesforce field on the campaign
- OrderType - Filters for Person/Opportunity of particular order type
- AccountTerritory - Account Territory of the Opportunity / Person where available. Currently, this field is only populated for a few leads, but it's reliable for the opportunity object for SAOs / Pipeline / Closed Won metrics.
- SalesAcceptedDate - Date range during which opportunity became SAO (filters only opportunity level information)

SECTION: marketing/strategy-performance/marketing-analytics-data/_index.md

<link rel="stylesheet" type="text/css" href="/stylesheets/biztech.css" />

Data Modeling Best Practices

As one of the core principles of the CDT's data modeling practices, Marketing Analytics follows the guidelines for creating Trusted Data wherever and whenever possible. Essentially, Trusted Data (TD) means that the models, at every step of the way, adhere to all coding and style guides and the information/results have been fully vetted as accurate and reliable. For you, the consumer, it means that you know the numbers and results you are viewing are correct.

Data modeling is both an artform and a science. There are numerous methodologies and guides to perform this task, and CDT has provided the Marketing Analytics team (and all other embedded data teams) with a number of very helpful tools - ranging from the SQL Style Guide, which outlines the ideal formats and functions for all SQL code in the data warehouse; to the Kimball Methodology, the framework for the ways that the various levels of models should be constructed and fit together to form the final tables ingested into Tableau for analysis.

The Kimball Methodology outlines key stages of table creation along the path from the raw source data to the fully ingestible mart/report tables most heavily used in Tableau and other BI tools.

1. Raw/Source

1. We start at the source layer, which is the system housing the data that needs to be analyzed (i.e. Salesforce, Marketo, Iterable, etc.)

1. The raw fields for each object (i.e. Opportunity, Account, Contact, etc.) are ingested, formatted, and named clearly and accurately in the raw/source table.

1. Prep

1. The raw/source fields are next pulled into a prep layer. It is here that base-level calculations, transformations, and other logical modeling steps are performed on the raw data to prepare it for the next stage in its data journey.

1. The prep layer is often the most complex of the layers, as it is the core repository for the primary logic performed on the raw data.

1. Dim/Fct

1. The prep models are split into two distinct tables

1. Fct: This table has a single unique ID as well as numerous other joinable IDs for a given object/data set. It is here that dates, IDs, and measurements (the numbers involved in business decisions) are stored and prepared.

1. Dim: This table houses a single unique ID for a given object/data set and then all of the descriptive information of a single ID-row of a fct table.

1. Each ID in a fct will have a single Dim table, and each Dim table will only have a single ID within it.

1. Dims are joined together by joining to the fct table that they share in common.

1. Mart

1. The mart layer combines the dims and fct models together to become a complete whole.

1. Marts have very little logic or calculations within them as they serve, primarily, to present a queryable final table for a given object or business process.

1. Report (rpt)

1. Report tables are built off of marts (usually). They are filtered offshoots of the whole mart data set and serve as a queryable table for a refined business question or process.

1. Example: You may have a mart of all opportunities in Salesforce, while having a report/rpt of all closed won opportunities - pre-filtering the mart's results provides a smaller and more agile data set when you know you only want a portion of the mart's whole.

Tech Stack Overview

CDT's and thus Marketing Analytics' data pipeline tech stack is straightforward, efficient, and effective.

It starts with extracting the raw/source data from each source system, as shown in the CDT Sources table. The extraction happens with a variety of tools based on which tool best supports the specific source system. In Marketing we primarily rely on Stitch (SFDC) and FiveTran (Marketo and Iterable and others). The extraction tool grabs all specified columns for each synced table/object and creates a raw-level table of those fields.

These raw tables are extracted into Snowflake, the repo/hub of all data at GitLab.

The next layer is the data build tool (dbt), which is a transformation layer of the modeling process. In dbt, SQL and other code is written to further transform, refine, calculate, and concatenate various fields and logic sets to create the prep layer as mentioned above.

The finished tables that dbt creates are once again pushed to Snowflake, where the dbt-created tables will live, accessible in the CDT data catalog, otherwise referred to as the Data Warehouse.

The last step in the process is to ingest the finished dbt-created, snowflake-housed tables into our BI tool of choice, which is usually Tableau - where dashboards and charts are created from the various tables, to allow easy analyses.

Data Flow

Source System	Source Object	Source Table
Prep Table	Dim Table	Fct Table
Mart Table		
----- ----- -----		
----- ----- -----		
--- -----		
SFDC	Account	sfdcaccountsource
prepcrmaccount	dimcrmaccount	fctcrmaccount
martcrmaccount		
SFDC	Bizible Attribution Touchpoint	sfdcbizibleattributiontouchpointsource
prepcrmattributiontouchpoint	dimcrmtouchpoint	fctcrmattributiontouchpoint
martcrmattributiontouchpoint		
SFDC	Bizible Person	sfdcbiziblepersonsource
prepcrmperson	dimcrmperson	fctcrmperson
martcrmperson		
SFDC	Bizible Touchpoint	sfdcbizibletouchpointsource

prepcrmtouchpoint	dimcrmtouchpoint	fctcrmtouchpoint	
martcrmtouchpoint			
SFDC	Campaign	sfdccampaignsource	
prepcampaign	dimcampaign	fctcampaign	N/A
SFDC	Campaign Member	sfdccampaignmembersource	
prepcampaign	dimcampaign	fctcampaign	N/A
SFDC	Contact	sfdccontactsource	
prepcrmperson	dimcrmperson	fctcrmperson	
martcrmperson			
SFDC	Event	sfdceventsource	
prepcrmevent	dimcrmevent	fctcrmevent	
martcrmevent			
SFDC	Lead	sfdcleadsources	
prepcrmperson	dimcrmperson	fctcrmperson	
martcrmperson			
SFDC	Opportunity	sfdcoppportunitysource	
prepcrmoppportunity	dimcrmpoppportunity	fctcrmpoppportunity	
martcrmpoppportunity			
SFDC	Task	sfdctasksource	
prepcrmtask	dimcrmtask	fctcrmtask	
martcrmtask			
SFDC	Users	sfdcuserssource	
prepcrmuser	dimcrmuser	N/A	N/A
Marketo	Activity-specific source tables	Marketo model source	
prepmarketoactivity	dimmarketoactivity	fctmarketoactivity	
martmarketoactivity			
Marketo	Lead/Person	marketoleadsources	
prepmarketoperson	N/A	N/A	
martmarketoperson			
Iterable	Campaign History	iterablecampaignhistorysource	
prepiterablecampaign	WIP	WIP	WIP
Iterable	Campaign List History	iterablecampaignlisthistorysource	
prepiterablecampaign	WIP	WIP	WIP
Iterable	Campaign Metrics	iterablecampaignmetricssources	
prepiterablecampaignmetrics	WIP	WIP	WIP
Iterable	Campaign Suppression List History	iterablecampaignsuppressionlisthistorysource	
prepiterablecampaign	WIP	WIP	WIP
Iterable	Channel	iterablechannelsources	
prepiterableuser	WIP	WIP	WIP
Iterable	Email Link Param History	iterableemaillinkparamhistorysource	
prepiterableemailtemplate	WIP	WIP	WIP

Iterable	Email Template History	iterableemailtemplatehistorysource
preIterableemailtemplate	WIP	WIP
Iterable	Event	iterableeventsource
preIterableevent	WIP	WIP
Iterable	List	iterablelistsource
preIterablelist	WIP	WIP
Iterable	List User History	iterablelistuserhistorysource
preIterablelist	WIP	WIP
Iterable	Message Type	iterablemessagetypesource
preIterablemessagetype	WIP	WIP
Iterable	Template History	iterabletemplatehistorysource
preIterableemailtemplate	WIP	WIP
Iterable	User History	iterableuserhistorysource
preIterableuser	WIP	WIP
Iterable	User Unsubscribed Channel	iterableuserunsubscribedchannelsource
preIterableuser	WIP	WIP
Iterable	User Unsubscribed Message	iterableuserunsubscribedmessagetypesource
preIterablemessagetype	WIP	WIP

Marketing Data Models

All GitLab data models are grouped and categorized in snowflake/dbt through a series of folders and hierarchy. Below are the primary Marketing data models, there folders, links, and descriptions. We've added another lvel of organization, the Grouping field, which is a custom grouping of the data models based on their usage and lineage. The list of groupings below, preceding the data model inventory table, will you give you a brief understanding of what each grouping represents.

Groupings

Grouping	Description
-----	-----
Event Performance	Models to calculate and analyze Event data streams.
L2R	Models built off the Lead to Revenue model. L2R is a consolidation of SFDC PErsons (leads/contacts), Accounts, Opportunities, and Bizible Touchpoints.
Marketo	Models built off of Marketo source data. These are often used in

conjunction with the L2R and Presentation Layer Model groupings for additional fields and information. |

| Presentation Layer Model | Models used in active and public Tableau Dashboards. These models are the most commonly used and presented for analysis.

|

| SFDC | Models built off of the SFDC Source tables. These are often used in conjunction with the L2R and Presentation Layer Model groupings for additional fields and information. |

| Web | Models built to model out web traffic data (top of funnel).

|

Models

Model Name	Model Folder	Grouping
Description		
Link		
----- ----- -----		
----- -----		

----- -----		

----- --- --- --- --- --- --- --- --- --- --- --- --- --- --- ---		
wkrpteventregistration	workspacemarketing/restrictedsafe	Event Performance
Table of Event registration data.		
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/restrictedsafe/wkrpteventregistration.sql		
rptl2rcampaigninteractions	commonmartmarketing/restrictedsafe	L2R
Tableau-specific table that unions martcrmtouchpoint with person, campaign data joined on and martcrmattributiontouchpoint with person, campaign and oppunitiy data.		
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/commonmartmarketing/restrictedsafe/rptl2rcampaigninteractions.sql		
rptl2rcampaigninteractionspaidaccount	commonmartmarketing/restrictedsafe	L2R
Filtered version of rptl2rcampaigninteractions on current paying accounts only		
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/commonmartmarketing/restrictedsafe/rptl2rcampaigninteractionspaidaccount.sql		
rptl2rcommunitydata	commonmartmarketing/restrictedsafe	L2R
Tableau-specific table that joins Zuora, Opportunity, and Lead To Revenue data to hone in on the community-owned opportunities and their related data points.		
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/commonmartmarketing/restrictedsafe/rptl2rcommunitydata.sql		
rptl2rprospects	commonmartmarketing/restrictedsafe	L2R
A refined subset of the rptleadtorevenue, focused exclusively on prospect data. It includes records where touchpoint dates and pipeline creation dates fall within the rolling past 365-day window		
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/commonmartmarketing/restrictedsafe/rptl2rprospects.sql		

		rptleadtoerevenue		commonmartmarketing/restrictedsafe		L2R
A consolidation and combination of the major SFDC Objects: Lead, Contact, Account, Opportunity, and Touchpoints. This model supports full funnel analysis and cohorting of data.						
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/commonmartmarketing/restrictedsafe/rptleadtoerevenue.sql						
		wkrptl2rcohortmodel		workspacemarketing/restrictedsafe		L2R
The basis of marketing/sales cohort analyses built from L2R, with pre-defined conversion dates at a per-record granularity.						
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/restrictedsafe/wkrptl2rcohortmodel.sql						
		marketoformfillsmissingtouchpoints		workspacemarketing		Marketo
Table of Marketo Form fills that don't have corresponding Bizible Touchpoints.						
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/marketoformfillsmissingtouchpoints.sql						
		martmarketoactivity		commonmartmarketing/restrictedsafe		Marketo
The Marketo Activity table.						
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/commonmartmarketing/restrictedsafe/martmarketoactivity.sql						
		martmarketoperson		commonmartmarketing		Marketo
The Marketo Person table.						
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/commonmartmarketing/martmarketoperson.sql						
		martmarketingcontactnopii		commonmartmarketing		Presentation Layer Model
A consolidation of major tech stack systems, focused on unifying person IDs across source systems.						
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/commonmartmarketing/martmarketingcontactnopii.sql						
		rpteventperformance		workspacemarketing/restrictedsafe		Presentation Layer Model
Table of Event-based performance metrics.						
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/restrictedsafe/rpteventperformance.sql						
		rptmarketinginfluencedpipeline		workspacemarketing/restrictedsafe		Presentation Layer Model
Table that calculates Marketing influence on pipeline metrics.						
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/restrictedsafe/rptmarketinginfluencedpipeline.sql						
		rptmarketinginfluencedpipelinelive		workspacemarketing/restrictedsafe		Presentation Layer Model
Table that calculates Marketing influence on pipeline metrics based on Live data.						
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/restrictedsafe/rptmarketinginfluencedpipelinelive.sql						
		rptsalesdevactivity		workspacemarketing/restrictedsafe		Presentation

Layer Model | Table of Sales Dev activities and engagements from SFDC data sources.

| <https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/restrictedsafe/rptsalesdevactivity.sql>

| |

| martcrmtributiontouchpoint | commonmartmarketing | SFDC

| The SFDC/Bizible Attribution Touchpoint mart table.

| <https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/commonmartmarketing/martcrmtributiontouchpoint.sql>

| |

| martcrmevent | commonmartsales | SFDC

| The SFDC Event object table.

| <https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/commonmartsales/martcrmevent.sql>

| |

| martcrmperson | commonmartmarketing | SFDC

| The SFDC Person (lead/contact) table.

| <https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/commonmartmarketing/martcrmperson.sql>

| |

| martcrmtask | commonmartsales | SFDC

| The SFDC Task object table.

| <https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/commonmartsales/martcrmtask.sql>

| |

| martcrmtouchpoint | commonmartmarketing | SFDC

| The SFDC /Bizible Person/Buyer Touchpoint table.

| <https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/commonmartmarketing/martcrmtouchpoint.sql>

| |

| digitalads | workspacemarketing | Paid Media

| A general consolidation of digital ad data.

| <https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/digitalads.sql>

| |

| gasessionhit | workspacemarketing | Web

| Joins Google Analytics 360 Session and Hit tables. Each row is a hit with the session data, which is repeated for each hit.

| <https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/gasessionhit.sql>

| |

| ga360sessionhitcustomdimension | workspacemarketing | Web

| Table of GA360 Session Custom data.

| <https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/ga360sessionhitcustomdimension.sql>

| |

| justglobalmediabuys | workspacemarketing | Paid Media

| Table of Media expenditure from Just Global.

| <https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/justglobalmediabuys.sql>

| |

handbookvaluespagecontributors	workspacemarketing	
Git log of contributors to the Values handbook page.		
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/handbookvaluespagecontributors.sql		
namespacecampaignattribution	workspacemarketing/restrictedsafe	
Table that combines Namespaces and Campaign data for attribution purposes.		
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/restrictedsafe/namespacecampaignattribution.sql		
rptcreatepartnertouchpoints	workspacemarketing/restrictedsafe	
A view used to find marketing ready partners and create touchpoints for them with hightouch		
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/restrictedsafe/rptcreatepartnertouchpoints.sql		
wkbdgusercompany	workspacemarketing	
A table to be used to connect GitLab[dot]com users to companies		
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/wkbdgusercompany.sql		
wkdimcompany	workspacemarketing	
Table of Company data points - outside of SFDC.		
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/wkdimcompany.sql		
wkmarketingunifiedfunnel	workspacemarketing	
An approach to create a unified funnel of Marketing metrics.		
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/wkmarketingunifiedfunnel.sql		
wkrptgiltab16expiringtokens	workspacemarketing	
Table of GitLab DotCom tokens set to expire.		
https://gitlab.com/gitlab-data/analytics/-/blob/master/transform/snowflake-dbt/models/workspaces/workspacemarketing/wkrptgiltab16expiringtokens.sql		

SECTION: marketing/strategy-performance/marketing-analytics-data/marketing-analytics-data-l2r.md

<link rel="stylesheet" type="text/css" href="/stylesheets/biztech.css" />

Rptleadtoerevenue

The Lead to Revenue report is the consolidation of the major lifecycle objects/marts: Person, Opportunity, Account, and both types of Bizible Touchpoints. It is a one-stop shop for nearly all Sales and Marketing metrics and data on the joined objects. It allows for quick analysis of funnel progression, cohorting of data points and metrics, and allows for a true funnel from lead creation to opportunity close to be created from one table.

Use Cases

- 1. Funnel stage progression of a given record
- 1. Count of records in a given funnel stage
- 1. Average velocity between funnel stages
- 1. Cohorting data around a given attribute

Key Fields

- 1. leadtorevenueid - The surrogate key that identifies a unique row in this model.
- 1. [kpi]daterange - KPI-specific date aggregations
- 1. biziblemql - Bizible TP data on the TP that occurs just prior to the MQL Date.
- 1. biziblemostrecent - Bizible TP data on the most recent TP on a person/opportunity

Key Metrics

- 1. Count of records by funnel stage
- 1. Count of Touchpoints between specific funnel stages
- 1. Overall velocity through the funnel
- 1. Funnel stage conversion rates

Data Lineage

- 1. Data is sourced from SFDC
- 1. The full lineage can be seen here

DBT Solution

The dbt solution generates a dimensional model from RAW source data. The exceptions are the following fields that are calculated based on business logic implemented within specific dbt models:

Field	Business Logic
-----	-----
leadtorevenueid	Defined in model
[kpi]daterange	Defined in model

Rptl2rcampaigninteractions

The L2R Campaign Interactions report table uses a primary union between person/buyer and attribution/opportunity touchpoint and related mart fields to derive its base table. From there, various calculations on date/time fields and related dimensions are performed.

Use Cases

L2R is the base table of Campaign reporting at GitLab. It combines touchpoints allowing us to create a single view that shows the top of the funnel to Influenced SAO. It is used to track the conformance of email, content, and paid media efforts.

Key Fields

- 1. Personordertype
 - 1. A derived Order Type for the person record, based on the isfirstorderperson SFDC field
- 1. Touchpointtype
 - 1. A denotation of whether the given touchpoint/record is a Person/Buyer or Opportunity/Attribution touchpoint.
- 1. Custom attribution fields (i.e. customsao)
 - 1. Calculations to sum up the custom model weights of an opportunity's touchpoints based on other criteria in the model
- 1. Personstatuschange
 - 1. A derived field to show the person record's progression from one status to another.
- 1. Ismdfcampaign
 - 1. A T/F flag that shows whether or not the campaign associated with the record will have MDF funding or not.
- 1. reportopportunity
 - 1. Derived fields to show the report-based attributes of the opportunity leveraging historical snapshot data where appropriate.
- 1. Issalesdevownedrecord
 - 1. A T/F flag to show whether or not the record is owned by a Sales Dev rep in SFDC.
- 1. daterange
 - 1. The pre-defined date aggregations of a given funnel-stage's date for the given record.

Key Metrics

- 1. Count of records/KPI totals by dimensions (campaign type, date, order type, etc.)
- 1. Count of touchpoints at given stages or from specific campaigns
- 1. Combined weighted Net ARR or Attributed touchpoints, by attribution model and dimension

Data Lineage

- 1. Data is sourced from SFDC and L2R
- 1. The full lineage can be seen here

Field	Business Logic
Custom attribution fields (i.e. customsao)	Defined in model
personstatuschange	Defined in model
ismdfcampaign	Defined in model
reportopportunity	Defined in model
issalesdevownedrecord	Defined in model

Rptl2rcampaigninteractionspaidaccount

Filtered version of rptl2rcampaigninteractions on current paying accounts only.

Use Cases

L2R is the base table of Customer-specific Campaign reporting at GitLab. It combines touchpoints allowing us to create a single view that shows the top of the funnel to Influenced SAO. It is used to track the conformance of email, content, and paid media efforts.

Key Fields

- 1. Personordertype
 - 1. A derived Order Type for the person record, based on the isfirstorderperson SFDC field
- 1. Touchpointtype
 - 1. A denotation of whether the given touchpoint/record is a Person/Buyer or Opportunity/Attribution touchpoint.
- 1. Custom attribution fields (i.e. customsao)
 - 1. Calculations to sum up the custom model weights of an opportunity's touchpoints based on other criteria in the model
- 1. Personstatuschange
 - 1. A derived field to show the person record's progression from one status to another.
- 1. Ismdfcampaign
 - 1. A T/F flag that shows whether or not the campaign associated with the record will have MDF funding or not.
- 1. reportopportunity
 - 1. Derived fields to show the report-based attributes of the opportunity leveraging historical snapshot data where appropriate.
- 1. Issalesdevownedrecord
 - 1. A T/F flag to show whether or not the record is owned by a Sales Dev rep in SFDC.
- 1. daterange
 - 1. The pre-defined date aggregations of a given funnel-stage's date for the given record.

Key Metrics

- 1. Count of records/KPI totals by dimensions (campaign type, date, order type, etc.)
- 1. Count of touchpoints at given stages or from specific campaigns
- 1. Combined weighted Net ARR or Attributed touchpoints, by attribution model and dimension

Data Lineage

- 1. Data is sourced from SFDC
- 1. The full lineage can be seen here

DBT Solution

The dbt solution generates a dimensional model from RAW source data. The exceptions are the following fields that are calculated based on business logic implemented within specific dbt models:

Field	Business Logic
Custom attribution fields (i.e. customsao)	Defined in model
personstatuschange	Defined in model
ismdfcampaign	Defined in model
reportopportunity	Defined in model
issalesdevownedrecord	Defined in model

Rptl2rcommunitydata

Tableau-specific table that joins Zuora, Opportunity, and Lead To Revenue data to hone in on the community-owned opportunities and their related data points.

Use Cases

1. Calculating community-driven KPIs
1. Split KPIs by Community project (SKU)

Key Fields

1. Communitydatatype - A grouping of SKUs (productrateplanid) to determine which of the 3 Community projects this record belongs to.
1. Numberofseats - The count of user seats on a given account/namespace.
1. daterange - KPI stage specific date aggregations
1. Islastsegmentversion - T/F flag to indicate if the record in question is the most recent version of an invoice charge.
1. Subscriptionorder - Incrementing number of subscriptions per Account
1. Isfirstsubscriptioninstitution - T/F flag to show whether or not the record in question is the first subscription for a given Account

Key Metrics

1. Numberofseats by dimension
1. Count of subscriptions per account
1. Conversion rate of subscriptions/opportunities over time by dimensions

Data Lineage

1. Data is sourced from SFDC
1. The full lineage can be seen here

DBT Solution

The dbt solution generates a dimensional model from RAW source data. The exceptions are the following fields that are calculated based on business logic implemented within specific dbt models:

Field	Business Logic
-----	-----
Communitydatatype	Defined in model
Numberofseats	Defined in model
Subscriptionorder	Defined in model
Isfirstsubscriptioninstitution	Defined in model

Rptl2rprospects

Tableau-specific table that is a filtered view of rptleadto revenue, focused entirely on First Order Prospects.

Use Cases

1. Funnel stage progression of a given record
1. Count of records in a given funnel stage
1. Average velocity between funnel stages
1. Cohorting data around a given attribute

Key Fields

1. leadtorevenueid - The surrogate key that identifies a unique row in this model.
1. [kpi]daterange - KPI-specific date aggregations
1. biziblemql - Bizible TP data on the TP that occurs just prior to the MQL Date.
1. biziblemostrecent - Bizible TP data on the most recent TP on a person/opportunity

Key Metrics

1. Count of records by funnel stage
1. Count of Touchpoints between specific funnel stages
1. Overall velocity through the funnel
1. Funnel stage conversion rates

Data Lineage

1. Data is sourced from SFDC
1. The full lineage can be seen here

DBT Solution

The dbt solution generates a dimensional model from RAW source data. The exceptions are the following fields that are calculated based on business logic implemented within specific dbt models:

Field	Business Logic
leadtovenueid	Defined in model
kpidaterange	Defined in model

Wkrptl2rcohortmodel

A Tableau-specific table, currently a WIP, that Cohorts the rptleadtovenue data, pre-calculating velocity and lag time between funnel stages. This is entirely focused around determining cohorted conversion rates and KPI counts.

Use Cases

1. Calculating cohorted velocity, conversion rate, and KPI counts

Key Fields

1. leadtovenueid - The surrogate key that identifies a unique row in this model.
1. [kpi]daterange - KPI-specific date aggregations
1. Kpitokpidays - Lag time (in days) between specific KPIs/Funnel stages. Also represents

conversion velocity.

Key Metrics

- 1. Count of records by funnel stage
- 1. Count of Touchpoints between specific funnel stages
- 1. Overall velocity through the funnel
- 1. Funnel stage conversion rates

Data Lineage

- 1. Data is sourced from SFDC
- 1. The full lineage can be seen here

DBT Solution

The dbt solution generates a dimensional model from RAW source data. The exceptions are the following fields that are calculated based on business logic implemented within specific dbt models:

Field	Business Logic
leadtovenueid	Defined in model
kpi]daterange	[Defined in model
kpitokpidays	Defined in model

SECTION: marketing/strategy-performance/marketing-analytics-data/marketing-analytics-data-sfdc.md

<link rel="stylesheet" type="text/css" href="/stylesheets/biztech.css" />

Martcrmattributiontouchpoint

The Attribution Touchpoint mart is the consolidated repository of Marketo Measure's (Bizible's) Attribution Touchpoint data. An Attribution Touchpoint is a touchpoint associated with an Opportunity in SFDC. This mart allows you to analyze engagement by Opportunity and/or Account during the entire lifecycle of either.

Use Cases

- 1. Attributed ARR
- 1. Touchpoints during a given stage

Key Fields

- 1. Attribution Touchpoint
 - 1. The record of engagement, captured through Bizible (Marketo Measure) that is associated with an Opportunity in SFDC.

- 1. Net ARR
 - 1. Definition
- 1. Attribution Models
 - 1. Bizible-defined
 - 1. Linear
 - 1. An even distribution of weight/attribution split amongst every touchpoint related to the record.
- 1. Is MGP Channel Based
 - 1. At least 2 unique marketing channel touchpoints for First Order and 3 unique marketing channel touchpoints for Growth opportunities, within a window of 365 days before Pipeline Created Date
- 1. Is MGP Opportunity
 - 1. Is MGP Channel Based = TRUE and Sales Qualified Source = SDR
- 1. Gitlab Model Weight
- 1. Time Decay Model Weight
- 1. Data Driven Model Weight
- 1. Touchpoint Sales Stage
 - 1. The Sales funnel stage the touchpoint occurred in.
- 1. Is FMM Influenced
 - 1. Whether a given touchpoint is influenced by FMM effort.
- 1. Is FMM Sourced
 - 1. Whether a given touchpoint is sourced by FMM effort.

Key Metrics

- 1. Attributed Weight
 - 1. The weight of a given touchpoint, based on which attribution model you are looking at.
- 1. Attributed Net ARR
 - 1. The attributed net arr, based on which attribution model you are looking at.

Data Lineage

- 1. Data is sourced from SFDC and Bizible/Marketo Measure
- 1. The full lineage can be seen here

DBT Solution

The dbt solution generates a dimensional model from RAW source data. The exceptions are the following fields that are calculated based on business logic implemented within specific dbt models:

Field	Business Logic
touchpointsalesstage	Defined in model
ismgpopportunity	Defined in model
isfmminfluenced	Defined in model
isfmmsourced	Defined in model

Martcrmevent

The SFDC Event mart is the organized and formatted consolidation of Event data from SFDC. Events are a form of Activity in SFDC, usually associated with meetings (digital or in-person).

Use Cases

1. Volume/timeline of Events in the Opportunity lifecycle
1. Efficacy of a given Event in progressing an Opportunity towards Closed Won.

Key Fields

1. salesdevrep
 1. The associated Sales Dev Rep and their Manager's information from SFDC

Key Metrics

1. Count of Events (dimcrmeventpk)

Data Lineage

1. Data is sourced from SFDC
1. The full lineage can be seen here

DBT Solution

The dbt solution generates a dimensional model from RAW source data.

Martcrmperson

The seamless combination of SFDC Leads and Contacts into a consolidated Person object. This mart allows for quick and easy access to both SFDC objects in a single table. It also integrates information from Bizible/Marketo Measure, Marketo, and IDs from other GitLab Tech Stack sources.

Use Cases

1. Number of people in a given funnel stage
1. Progression of a given person record through the funnel
1. Conversion from one funnel stage to the next

Key Fields

1. Dimcrmpersonid - the unique surrogate key for each person record

Key Metrics

1. MQL Count
1. Inquiry Count
1. Inquiry to MQL Conversion

Data Lineage

1. Data is sourced from SFDC
1. The full lineage can be seen here

DBT Solution

The dbt solution generates a dimensional model from RAW source data. The exceptions are the following fields that are calculated based on business logic implemented within specific dbt models:

Field	Business Logic
isleadsource	Defined in model
isabmtierinquiry	Defined in model
isabmtiermql	Defined in model
personfirstcountry	Defined in model
isexcludefromreporting	Defined in model

Martcrmtasks

The SFDC Tasks mart is the organized and formatted consolidation of Task data from SFDC. Tasks are usually notes from the Sales Dev or Sales team on actions taken or engagements that took place.

Use Cases

1. Volume/timeline of Tasks in the Opportunity lifecycle
1. Efficacy of a given Task in progressing an Opportunity towards Closed Won.

Key Fields

1. salesdevrep
 1. The associated Sales Dev Rep and their Manager's information from SFDC

Key Metrics

1. Count of Tasks (dimcrmtaskpk)

DBT Lineage

1. Data is sourced from SFDC
1. The full lineage can be seen here

DBT Solution

The dbt solution generates a dimensional model from RAW source data.

Martcrmtouchpoint

The Person/Buyer Touchpoint mart is the consolidated repository of Marketo Measure's (Bizible's) Person/Buyer Touchpoint data. A Person/Buyer Touchpoint is an engagement associated

with a Person (Lead/Contact) based on the rules set by the organization for important/capturable engagements.

Use Cases

1. Touchpoints during a given stage
1. Touchpoints per record

Key Fields

1. Buyer (Person) Touchpoint
 1. The record of engagement, captured through Bizible (Marketo Measure) that is associated with a Person (Lead/Contact) in SFDC.
1. Attribution Models
 1. Bizible-defined
 1. Linear
 1. An even distribution of weight/attribution split amongst every touchpoint related to the record.
1. Is FMM Influenced
 1. Whether a given touchpoint is influenced by FMM effort.
1. Is FMM Sourced
 1. Whether a given touchpoint is sourced by FMM effort.

Key Metrics

1. Attributed Weight
 1. The weight of a given touchpoint, based on which attribution model you are looking at.

Data Lineage

1. Data is sourced from SFDC and Bizible/Marketo Measure
1. The full lineage can be seen here

DBT Solution

The dbt solution generates a dimensional model from RAW source data. The exceptions are the following fields that are calculated based on business logic implemented within specific dbt models:

Field	Business Logic
isfmminfluenced	Defined in model
isfmmsourced	Defined in model

SECTION: marketing/the-source/index.md

The Source is managed by the Brand and Content Strategy & Ops teams, with support from Corporate Communications.

What is The Source?

AI-powered DevSecOps is transforming software development. To succeed in this new frontier and drive business success, leaders need actionable insights, best practices, and fresh perspectives.

The Source is a resource center where technical champions, economic buyers, and other influencers can find relevant content to help them make critical decisions and set their teams up for success with DevSecOps.

Content that belongs on The Source is:

- In-depth, relevant, and actionable
- About the interests, challenges, and pain points involved in software development
- Authored by GitLab's team of subject matter experts (executives, Field CTOs, Product Managers, and more)
- Aimed at helping C-suite executives and engineering and infrastructure leaders with their decision-making
- Written in alignment with the GitLab Style Guide

Content that belongs on the GitLab Blog:

- Product-focused articles
- Highly tactical and technical content (tutorials)
- Open source community content
- Company announcements

If you'd like to learn more about contributing to the GitLab Blog, visit the Blog Handbook or reach out on our internal Slack channel at the-source.

You can contribute to the success of The Source by spreading the word and sharing new posts with your network.

SECTION: marketing/virtual-events/_index.md

Overview {overview}

At GitLab, we believe everyone can contribute. Because nearly anyone with an internet connection and a device can participate in virtual events, as a speaker or an attendee, virtual events are an important part of fulfilling that mission. While our expertise in this area is still developing, this page documents the best practices we have studied and established for virtual events at GitLab.

Calendar {calendar}

To see all upcoming marketing activities, view the All-Marketing SSoT Calendar

<figure>


```
<iframe src="https://calendar.google.com/calendar/embed?height=600&wkst=1&bgcolor=%23B39DDB&ctz=America%2FLosAngeles&src=Z2l0bGFiLmNvbV9uMnNibXZmMjlqczBzM3BiM2ozaHFn91cC5jYWxlbmRhci5nb29nbGUuY29t&src=Z2l0bGFiLmNvbV8xcXZlNmc4MWRwOTFyOWhldnRrZn1cC5jYWxlbmRhci5nb29nbGUuY29t&src=Z2l0bGFiLmNvbV8xOGVqOHN0NmlxajZpYXB1NTNrajUzN1cC5jYWxlbmRhci5nb29nbGUuY29t&color=%23039BE5&color=%239E69AF&color=%230096FF&le=All%20GitLab%20Virtual%20Events&showCalendars=1" style="border:solid 1px 777" width="1000" height="600" frameborder="0" scrolling="no"></iframe>
</figure>
```

We have 3 separate Google calendars to manage different types and platforms of virtual events in GitLab:

- GitLab-Hosted On24 Webcasts/Workshops
- GitLab-Hosted Zoom Webcasts/Workshops
- External/Sponsored Virtual Events

All 3 calendars are consolidated into a single GitLab virtu