

ask another language and understand what the customer is trying to say. Please ensure that you only use the English language when responding tickets as the system may not detect the language correctly.

- Copy only the body of the content that needs translation.
 - When referring to a quoted texts from our customers, please only use the content that requires translation. Including snippets/code/elements may take more time to translate and could result in a mistranslation.
- Mind the punctuation.
 - Punctuation can be sometimes tricky for Unbabel so please be sure there are no unnecessary periods/punctuations in between.
- Single Word Use
 - It is likely that the response you are sending may be lost in translation, for example the word pass would differ to a boarding pass.

Zendesk Super App

^{Introduced via support-ops-project801}

A plugin controlled app that can do several things Zendesk related

The current plugins are:

- Create new ticket
 - > Allows an agent to create a new ticket using the same user as the ticket they are currently on.
- Due date picker
 - > This allows you to customize what the Due Date for a Task ticket is set for. By default, Zendesk only allows setting the date. This enables you to set the date, time, and timezone.
 - >
 - > You can also set the Due Date Note and disable (or enable) task notifications using this app.
- Escalated tickets
 - > This searches for tickets under the organization that have been escalated within the last 6 months.
- Related tickets
 - > This looks for tickets related to the current one based off the category (or subcategory) the ticket is currently using. It then displays up to 5 of them (sorted by the updateat value of the ticket, descending).
- Attachments
 - > Displays attachments present on the ticket.

App information:

- Located in the ticket sidebar
- Restricted by Group:
 - Support AMER
 - Support APAC
 - Support EMEA
- This application was developed in-house and can be found Zendesk Super App project.

ZenDuo

^{Introduced via [gitlab-com/support/support-team-meta6689](https://gitlab.com/support/support-team-meta6689)}

The ZenDuo application enables Duo Chat to work with Zendesk tickets.

You can choose from two pre-defined prompts:

- Summarize conversation
- Suggest KB article

or define up to two custom prompts.

For each custom prompt, you configure:

- Title: this is shown in the prompt dropdown list
- Button: the text shown on the action button
- Prompt: the actual prompt. Use the <<ticket-content>> placeholder, which will be replaced by the ticket content.

When you run a prompt, the application will send the ticket content (excluding file attachments) to Duo Chat and show its reply.

Note that large tickets have to be sent in multiple parts, so it can take a while before Duo Chat replies.

Once you've received a reply, you can choose:

- Copy to clipboard: copy the complete conversation (prompts and replies) to the clipboard.
- Chat: continue the conversation with Duo Chat.
- Done: hide the conversation, and be ready to start a new one.

When you send the initial prompt, a fresh conversation is always started, so there is no need to instruct Duo Chat to forget previous conversations.

The conversations you have with Duo Chat also show up in the GitLab Duo Chat history on e.g. GitLab.com as ZenDuo <ticket> <prompt>.

You can use this history to look up previous conversations, or continue on an old conversation.

App information:

- Located in the ticket sidebar
- This application was developed in-house and can be found ZenDuo project.

ZenGuard

^{Introduced via [gitlab-com/gl-security/corp/cust-support-ops/issue-tracker122](https://gitlab.com/gl-security/corp/cust-support-ops/issue-tracker122)}

Implements a warning system into Zendesk to warn (or block) potentially dangerous actions.

Current list of checks:

- Checks if due date is in the past, present, or too far in the future
- Checks if adding an end-user as a collaborator/CC
- Checks if setting to pending with an internal note
- Checks if trying to send a public reply on an on-hold ticket in a way that won't reset the timer
- Checks if trying to set it on-hold without a public reply (except for accepted situations)
- Checks if setting ticket to pending without a reply
- Checks if making unapproved form changes

App information:

- Located in the ticket sidebar
- This application was developed in-house and can be found in the ZenGuard project.

Zendesk US Government apps

Advanced SAST App

^{Introduced via support-team-meta6652}

The Advanced SAST App is a ticket app that enables a quick working of User requests for source code of LGPL-licensed components in GitLab Advanced SAST.

App information:

- Located in the ticket sidebar
- Restricted by Group:
 - Support
 - Support Managers
 - Support Operations
- This application was developed in-house and can be found Advanced SAST App project.

Advanced Search

Advanced Search is an app that provides a simple visual interface for constructing complex search queries against tickets, users, and organizations (orgs). It also enables you to export the search results in a CSV format.

App information:

- Located in the navbar
- This application was developed by Zendesk and is available in the Zendesk Marketplace.

Architecture Diagrams

^{Introduced via support-ops-project801}

This app uses the Organization field AM Project ID to check for an existing Account Management

project. If it finds it, it will then link to that project's Architecture Diagram.

App information:

- Located in the ticket sidebar
- This application was developed in-house and can be found GitLab Architecture project.

GitLab Reminders App

^{Introduced via support-team-meta3036}

The Reminders App appears in the navbar and allows the agent a more specialized view of tickets they are involved in. It currently shows:

- Tickets assigned to you with a pending/overdue task that are not in a Closed state
- Recent tickets you have viewed
- Tickets assigned to you that are not in a Closed state
- Tickets you are CC'd on that are not in a Closed state

It also allows you to quickly manage your tasks by seeing the notes you have left for said task, when it is due, and a button to quickly mark the task as done (remove the notes and due date).

App information:

- Located in the navbar
- This application was developed in-house and can be found GitLab Reminders App project.

GitLab Search

This app lets you use the gitlab.com API to search for issues/merge requests within Zendesk.

App information:

- Located in the topbar
- This application was developed in-house and can be found GitLab Search project.

Show Related Tickets

This uses the ticket subject to search for other tickets with a similar subject. This helps to locate potentially related tickets you can check to see how they were solved.

App information:

- Located in the ticket sidebar
- This application was developed by Zendesk and is available in the Zendesk Marketplace.

Zendesk Super App

^{Introduced via support-ops-project801}

A plugin controlled app that can do several things Zendesk related

The current plugins are:

- Create new ticket
 - > Allows an agent to create a new ticket using the same user as the ticket they are currently on.
- Due date picker
 - > This allows you to customize what the Due Date for a Task ticket is set for. By default, Zendesk only allows setting the date. This enables you to set the date, time, and timezone.
 - >
 - > You can also set the Due Date Note and disable (or enable) task notifications using this app.
- Escalated tickets
 - > This searches for tickets under the organization that have been escalated within the last 6 months.
- Related tickets
 - > This looks for tickets related to the current one based off the category (or subcategory) the ticket is currently using. It then displays up to 5 of them (sorted by the updateat value of the ticket, descending).
- Attachments
 - > Displays attachments present on the ticket.

App information:

- Located in the ticket sidebar
- Restricted by Group:
 - Support
 - Support Managers
 - Support Operations
- This application was developed in-house and can be found Zendesk Super App project.

ZenDuo

^{Introduced via gitlab-com/support/support-team-meta6689}

The ZenDuo application enables Duo Chat to work with Zendesk tickets.

You can choose from two pre-defined prompts:

- Summarize conversation
- Suggest KB article

or define up to two custom prompts.

For each custom prompt, you configure:

- Title: this is shown in the prompt dropdown list
- Button: the text shown on the action button
- Prompt: the actual prompt. Use the <<ticket-content>> placeholder, which will be replaced by

the ticket content.

When you run a prompt, the application will send the ticket content (excluding file attachments) to Duo Chat and show its reply.

Note that large tickets have to be sent in multiple parts, so it can take a while before Duo Chat replies.

Once you've received a reply, you can choose:

- Copy to clipboard: copy the complete conversation (prompts and replies) to the clipboard.
- Chat: continue the conversation with Duo Chat.
- Done: hide the conversation, and be ready to start a new one.

When you send the initial prompt, a fresh conversation is always started, so there is no need to instruct Duo Chat to forget previous conversations.

The conversations you have with Duo Chat also show up in the GitLab Duo Chat history on e.g. GitLab.com as ZenDuo <ticket> <prompt>.

You can use this history to look up previous conversations, or continue on an old conversation.

App information:

- Located in the ticket sidebar
- This application was developed in-house and can be found ZenDuo project.

ZenGuard

^{Introduced via gitlab-com/gitlab-security/corp/cust-support-ops/issue-tracker122}

Implements a warning system into Zendesk to warn (or block) potentially dangerous actions.

Current list of checks:

- Checks if due date is in the past, present, or too far in the future
- Checks if adding an end-user as a collaborator/CC
- Checks if setting to pending with an internal note
- Checks if trying to send a public reply on an on-hold ticket in a way that won't reset the timer
- Checks if trying to set it on-hold without a public reply (except for accepted situations)
- Checks if setting ticket to pending without a reply
- Checks if making unapproved form changes

App information:

- Located in the ticket sidebar
- This application was developed in-house and can be found in the ZenGuard project.

App development

```
{{% alert title="Note" color="primary" %}}
```

This is generalized information we have found helpful in the course of app development. It is not a single source of truth.

```
{{% /alert %}}
```

Understanding Zendesk Apps

Before you can start creating and editing apps in Zendesk, it is important to understand the ins and outs of both Zendesk Apps and Zendesk Apps framework.

There is a lot to this, so the Zendesk documentation is the best resource you have to learn the various ins and outs. This training documentation will cover what is viewed at "the most important" parts, but it is highly recommended you read and reference the Zendesk developer documentation as often as possible.

ZAT

ZAT, or Zendesk App Tools, is a ruby gem that makes working with Zendesk Apps locally considerably easier. It is highly recommended you install it on your computer:

```
bash
gem install rake
gem install zendeskappstools
```

To update it:

```
bash
gem update rake
gem update zendeskappstools
```

Sometimes on Mac terminal, you will get write permission error. You may use:

```
bash
sudo gem update rake
sudo gem update zendeskappstools
```

Note: ZAT is having issues with Ruby version 3.0.0 and plus. You'll likely need to use old stable versions like 2.6.3p62

manifest.json

This file is used to configure you application. As such, it is very important and vital it is accurate.

The common configuration settings are:

Setting	What it does	Required?
name	Specifies the name of the app	Y
author	Specifies the author of the app	Y
version	Specifies the app version	Y
frameworkVersion	Specifies the framework version to use	Y
location	Specifies where the app appears	Y
defaultLocale	Specifies the locale of the app	Y
parameters	The parameters to pass to the app during installation	N
domainWhitelist	The domains to allow use of secure parameters	N
private	Specifies whether the app can be only be installed in the app developer's account or not	N

Location

This setting determines where the app will appear and run. This is a very important setting. The first setting determines the product type location, and within that setting you can specify many other configurations, including the physical location the app will appear in. For the product type location, we always use support.

The physical locations are as follows:

String	Location/Purpose
ticketsidebar	The right side of all ticket view pages
newticketsidebar	The right side of all new ticket pages
ticketeditor	A button on the ticket editor box
navbar	An icon on the left-side navigation bar
topbar	An icon on the right side of the top menu
usersidebar	The right side of all user view pages
organizationsidebar	The right side of all organization view pages
background	The app runs in the background and does not display anywhere
modal	Used when the app creates modals

Within the physical location settings, you can include more configuration settings, with the most common being:

String	What it does	Variable type
autoHide	Tells the app to auto-collapse on first load	Boolean
autoLoad	Tells the app to automaticall local (defaults to true)	Boolean
signed	Specifies whether or not to use signed URLs	Boolean
url	The URL of the page to display in the iframe of the app	String
size	The initial app size (configure this in the app instead)	JSON

As an example, to have an app load "<https://google.com>" automatically in the ticket sidebar with a starting height of 200px, your configuration block would look like this:

```
json
"location": {
```



```

"support": {
  "ticketsidebar": {
    "autoLoad": true,
    "url": "https://google.com/",
    "size": {
      "height": "200px"
    }
  }
}
}
}

```

As another example, to have your app load in both the user and organization pages, rendering the locale assets/iframe.html file, you would do this:

```

json
"location": {
  "support": {
    "usersidebar": "assets/iframe.html",
    "organizationsidebar": "assets/iframe.html",
  }
}
}

```

Parameters

This is where you would define variables you want the app to use during installation.

Domain whitelists

If your app is using secure parameters and you plan to make requests outside of Zendesk, you must whitelist the domains in question. Each parameter is a hash that contains the following:

- name: the name of the parameter
- type: the type of parameter
- secure: ensures users cannot see the variable value when making HTTP requests (you should always use this)
- require: specifies if the parameter is required for installation

As an example, to use two required parameters (param1 and param2), both of which are text parameters in a secure way, you would do the following:

```

json
"parameters": [
  {
    "name": "param1",
    "type": "text",
    "secure": true,
    "required": true
  },

```

```
{
  "name": "param2",
  "type": "text",
  "secure": true,
  "required": true
}
```

During the installation of the app, Zendesk will ask you to give the values for these parameters. To utilize this in the code of your app, you will use this:

```
{{setting.NAMEOFPARAMETER}}
```

Where NAMEOFPARAMETER is the name you gave the parameter in the manifest.json file.

init

To create a client instance of the ZAF (Zendesk App Framework) client, you need to ensure the following is present in the javascript of your app:

```
javascript
var client = ZAFClient.init();
```

App resizing

To resize the app during runtime, you would use the invoke class, specifying you wish to invoke the resize function. This is done like so:

```
javascript
// First line shown to clarify you use the ZAF client object to do this
var zafclient = ZAFClient.init();
zafclient.invoke('resize', { width: '100%', height: '100px' });
```

Required javascript library

To utilize the ZAT, you must include the following javascript in your app's HTML file(s):

```
html
<script src="https://static.zdassets.com/zendeskappframeworksdk/2.0/zafsdk.min.js"></script>
```

Getting metadata

To get metadata and use it in your app, you need to use the ZAF client's get function. This takes an array of values to get from the ticket metadata, which you use in a function.

As an example, to get the ticket requester's name and the ticket's organization, and then log

them to the console, you would do the following:

```
javascript
// First line shown to clarify you use the ZAF client object to do this
var zafclient = ZAFClient.init();
zafclient.get(['ticket.requester.name', 'ticket.organization']).then(function(data) {
  console.log("Ticket requester name: " + data['ticket.requester.name']);
  console.log("Ticket organization: " + data['ticket.organization']);
});
```

As another example, to get the ticket's due date and the due date notes (a custom ticket field) and then log them to the console, you would do the following:

```
javascript
// First line shown to clarify you use the ZAF client object to do this
var zafclient = ZAFClient.init();
zafclient.get(['ticket.customField:duedate',
'ticket.customField:customfield360017383799']).then(function(data) {
  console.log("Due date": + data['ticket.customField:duedate']);
  console.log("Due date notes:" + data['ticket.customField:customfield360017383799']);
});
```

Making requests

Your app might need to make requests, whether they be "internal" (i.e. within Zendesk itself) or external. To do this, we use the request function of the client object.

The format of this is very close to that of making AJAX requests in jQuery. The format you will normally use is:

```
javascript
// First line shown to clarify you use the ZAF client object to do this
var zafclient = ZAFClient.init();
zafclient.request({
  method: 'REQUESTTYPE',
  url: 'URLTOUSE',
  contentType: 'CONTENTMEDIATOSEND',
  data: DATAOBJECT,
  secure: BOOLEAN,
  headers: HEADERSOBJECT
}).then(function(data) {
  // do stuff
});
```

The exact parameters in the request will vary from request to request.

As an example, if you wanted to update the due date of a ticket, you might do:

```

javascript
// First line shown to clarify you use the ZAF client object to do this
var zafclient = ZAFClient.init();
zafclient.request({
  method: 'PUT',
  url: '/api/v2/tickets/123456.json',
  contentType: 'application/json',
  data: JSON.stringify({
    dueat: new Date('2021-01-01').toISOString()
  }),
  secure: BOOLEAN,
  headers: HEADERSOBJECT
}).then(function(data) {
  console.log('Due date updated to 2021-01-01');
});

```

As another example, if you wanted to make a GET request to gitlab.com to find information about user ID 987654, using a secure parameter from app installation, you might do:

```

javascript
// First line shown to clarify you use the ZAF client object to do this
var zafclient = ZAFClient.init();
zafclient.request({
  method: "GET",
  url: 'https://gitlab.com/api/v4/users/987654?privatetoken={{setting.GitLabtoken}}',
  secure: true
}).then(function(data) {
  console.log('User email: ' + data.email);
});

```

Testing an app

There are two ways to test a Zendesk app before you put it into production:

Locally

```
{{% alert title="Note" color="primary" %}}
```

This cannot be done if your app is using secure parameters. Instead, you would need to install the app into the Sandbox and test from there.

```
{{% /alert %}}
```

To test your app locally, cd into the app directory on your local computer and then run the zat server command. This will start up a ZAT server on your computer. Once it has booted up, go to a Zendesk URL and put ?zat=true at the end. This will now load the apps from your local computer, allowing you to test out the app locally.

Via the Sandbox

If your app is using secure parameters, you will need to test via the Sandbox instead.

SECTION: security/customer-support-operations/docs/zendesk/articles.md

{{% alert title="Note" color="primary" %}}

This is an informational page for the Zendesk articles. It may not reflect the way we actually manage Zendesk articles.

If you are looking for information about maintaining articles (creating, editing, etc.), please see Articles workflow

{{% /alert %}}

Creating an article

For information on creating an article, please see Zendesk documentation.

Editing an article

For information on editing an article, please see Zendesk documentation.

Deleting an article

For information on deleting an article, please see Zendesk documentation.

SECTION: security/customer-support-operations/docs/zendesk/automations.md

{{% alert title="Note" color="primary" %}}

This is an informational page for the Zendesk automations. It may not reflect the way we actually manage Zendesk automations.

If you are looking for information about maintaining automations (creating, editing, etc.), please see Automations workflow

{{% /alert %}}

What are Zendesk automations?

As per Zendesk:

> Automations are similar to triggers because both define conditions and actions that modify ticket properties and optionally send email notifications to customers and agents. Where they

differ is that automations execute when a time event occurs after a ticket property was set or updated, rather than immediately after a ticket is created or updated.

The simpler way to think of it is automations are triggers that do not run instantly. They are time based than event based.

Creating an automation

For information on creating an automation, please see Zendesk documentation.

Cloning an automation

For information on cloning an automation, please see Zendesk documentation.

Editing an automation

For information on editing an automation, please see Zendesk documentation.

Reordering automations

For information on reordering automations, please see Zendesk documentation.

Deactivating an automation

For information on deactivating an automation, please see Zendesk documentation.

Deleting an automation

{{% alert title="Note" color="warning" %}}

You can only delete an automation if it is deactivated.

{{% /alert %}}

For information on deleting an automation, please see Zendesk documentation.

SECTION: security/customer-support-operations/docs/zendesk/ces.md

^{Introduced via support-team-meta6631}

{{% alert title="Note" color="primary" %}}

This is an informational page for the CES Surveys. It may not reflect the way we actually manage CES Surveys.

If you are looking for information about maintaining automations (creating, editing, etc.), please see CES Survey workflow

{{% /alert %}}

What are CES Surveys

CES (Customer Effort Score) surveys are forms we send out to customers to receive feedback from them on the level of effort required to work with support. A lower score indicates more effort was required while a higher score indicates less effort was required.

We use them as a replacement for SSAT/CSAT (support satisfaction/customer satisfaction).

Who receives them

We send out the CES survey to those who meet specific criteria. The exact criteria varies by Zendesk instance.

For Zendesk Global

- Must meet all of the following criteria:
 - The organization is not GitLab
 - Ticket form is not GitLab Incidents
 - Ticket form is not Billing
- Must meet at least one of the following criteria:
 - The ticket contains one of the following tags:
 - subdotcomultimate subdotcompremium subsmultimate subsmpremium subsmstarter subgitlabdedicated subconsumptionai subconsumptioncicdminutes subconsumptioneap subconsumptionduoenterprise subconsumptionduoamazonq subconsumptionduopremium subconsumptionstorage
 - The ticket form is L&R
 - The ticket form is Support Ops
 - The ticket form is Emergencies
 - The ticket form is Support Internal Request

For Zendesk US Government:

- Must meet all of the following criteria:
 - The organization is not GitLab
 - The ticket contains none of the following tags:
 - spamticket freecustomer comembargo csat-survey-sent needs-org-triggered

When are they sent out

We currently send out CES surveys on tickets that have been in the solved state for 24 (consecutive) hours.

Components

CES Processor

This takes information sent by Workato and processes it. It then checks the information against the ticket itself to determine if the request is valid. It currently checks:

- The ticket ID is present
- The ticket itself exists
- The ticket is not closed
- We have actually sent out a CES survey to them
- The submitter is the same person as the ticket requester

If any of the above fails, it will output a reason for failure and silently exit.

If no validation checks have failed, it will then do the following:

- Add a satisfaction rating (and comment if present) to the ticket
- Add the CES score to the ticket
- Add an entry to a google spreadsheet (as a backup)

The location of the project is here

CES Survey Form

This is the actual survey form sent to customers. The exact link received depends on the Zendesk instance the link was sent from:

- Zendesk Global
- Zendesk Global sandbox
- Zendesk US Government
- Zendesk US Government sandbox

Submissions from the form are sent to Workato.

The location of the source project is here. This is mirrored to here.

Zendesk Automations

These are used to send out the actual CES survey.

Zendesk Ticket Fields

These are used to store the CES survey numerical score.

Zendesk Triggers

These are used to create feedback issues for Support.

Workato

This is used to receive submissions from the CES Survey and send them to the CES Processor.

SECTION: security/customer-support-operations/docs/zendesk/dev-pulse.md

^{Introduced via support-ops-project970}

{{% alert title="Note" color="primary" %}}

This is an informational page for Dev Pulse. It may not reflect the way we actually manage Dev Pulse.

If you are looking for information about maintaining Dev Pulse, please see Dev Pulse workflow

{{% /alert %}}

What is Dev Pulse?

Dev Pulse is the name for a set of scripts and Zendesk setups we utilize to actively monitor various types of issues and merge requests in relation to bug resolution, feature request resolution, and requests for help (or RFH for short).

Through all the components, Dev Pulse allows a Zendesk ticket to stay in the On-hold while waiting on an issue or merge request to reach a specific state.

When the specific state is reached, the tickets within Zendesk using Dev Pulse are updated to indicate there has been a state change on the issue or merge request they were waiting on.

Where is the source code for Dev Pulse?

The source code for Dev Pulse is located in specific projects depending on the Zendeks instance(s) it runs on:

- Zendesk Global
- Zendesk US Government

How does Dev Pulse work in Zendesk?

On the Zendesk side of things, Dev Pulse works via the following components:

- 3 macros
- 3 views
- 1 ticket field
- 1 trigger
- 1 webhook

There are really two parts to what it does on the Zendesk side, initiating it and using tickets with a type of Problem.

Initiating it on a ticket

When a Zendesk agent applies one of the 3 macros, the following actions occur:

- A tag specific to that macro is added
 - waitingonbug for bug issues or merge requests

- waitingonfeaturerequest for feature request issues or merge requests
- waitingonrfh for RFH issues
- Tags related to other types and the processor are removed
 - waitingonfeaturerequest waitingonrfh processwaitingonissueormr for bug issues or merge requests
 - waitingonbug waitingonrfh processwaitingonissueormr for feature request issues or merge requests
 - waitingonbug waitingonfeaturerequest processwaitingonissueormr for RFH issues
- The Assignee for the ticket is set to the current user
- The Status for the ticket is set to On-hold
- The Ticket Stage value for the ticket is set to Other
- The Type value for the ticket is set to Incident

When the presence of one of the waitingforxx tags are added to a ticket (and the processwaitingonissueormr tag is not present), the trigger activates.

The trigger then adds the processwaitingonissueormr tag to the ticket and activates the webhook with the following form data:

Key	Value in Production	Value in Sandbox
variables[SANDBOX]	Not set in production	true
variables[TICKETID]	{{ticket.id}}	{{ticket.id}}
variables[TASK]	Analyze Ticket	Analyze Ticket

This will then trigger a webhook the corresponding gitlab.com project that will analyze and update the ticket.

Problem ticket types

While not anything directly stemming from Dev Pulse, it does utilize problem and incident tickets as a whole. For bugs and feature requests, a "parent" problem ticket is created. Using this problem ticket, you can update all the attached incident tickets to do one bulk update and solve.

How does Dev Pulse work on gitlab.com?

On the gitlab.com side, there are three real components to Dev Pulse:

- Analyzing a ticket
- Analyzing problem tickets
- Analyzing RFH tickets

Analyzing a ticket

This part is triggered via the Zendesk instance's webhook using a GitLab pipeline trigger. When triggered, specific parts of the code within the project will be run to perform an analysis of the request. The result of said analysis determine what actions are taken:

- For tickets waiting on bug or feature request resolution

- A check is done as to the validity of the issue or merge request link provided via the ticket.
- If the issue or merge request link provided via the ticket is not valid (is already closed, is already merged, does not exist, etc.), the ticket that triggered the analysis will have the following actions performed on it:
 - The Status of the ticket is set to Open
 - The Ticket Stage value of the ticket is set to NRT
 - An internal comment is added to the ticket indicating the link provided was not valid
- The ticket is then linked to an existing parent problem ticket. In cases where a parent problem ticket does not already exist, one is created first.
- For tickets waiting on RFH issues
 - As no action is needed for these at this stage, the code will exit with a status code of 0 for these

Analyzing problem tickets

This part is triggered via GitLab scheduled pipelines running at a schedule specified by the GitLab Support team. During this part, specific parts of the code will do the following:

- Locate all active parent problem tickets from the Zendesk instance
- Loops through all found active parent problem tickets to do the following:
 - Utilize the GitLab API to check on the state of the item that the parent problem ticket relates to
 - For issues, it checks if the issue has a state of closed
 - For merge requests, it checks if the merge request has a state of closed or merged
 - If the needed state has been hit, the script will then do the following:
 - Update all attached incident tickets with the following:
 - The Status of the ticket is set to Open
 - The Ticket Stage value of the ticket is set to NRT
 - An internal comment is letting those involved on the ticket know the parent problem ticket has been updated and a bulk update should be done shortly
 - Make a Slack post in a channel specific by CI/CD variables indicating the parent problem ticket is ready to be updated and solved

Analyzing RFH tickets

This part is triggered via GitLab scheduled pipelines running at a schedule that runs hourly. During this part, specific parts of the code will do the following:

- Locate all RFH tickets from the Zendesk instance
- Loops through all found RFH tickets to do the following:
 - Utilize the GitLab API to check on the state of the issue that the RFH ticket is waiting on. This state can be one of the following:
 - The state of the issue is closed
 - The last note on the issue was made by someone not on the support team AND said comment's timestamp is greater than (or equal to) the latest update timestamp on the ticket
 - If the needed state has been hit, the script will then update the ticket in the following way:
 - The Status of the ticket is set to Open
 - The Ticket Stage value of the ticket is set to NRT

- An internal comment is letting those involved on the ticket know the RFH issue has been updated

SECTION: security/customer-support-operations/docs/zendesk/dynamic-content.md

{{% alert title="Note" color="primary" %}}

This is an informational page for the Zendesk dynamic content. It may not reflect the way we actually manage Zendesk dynamic content.

If you are looking for information about maintaining dynamic content (creating, editing, etc.), please see Dynamic content workflow

{{% /alert %}}

What is Zendesk dynamic content?

As per Zendesk:

> Dynamic content is a combination of a default version of the text (typically in the same language as your default language) and variants for every other language that you support.

Using dynamic content

For information on using dynamic content in Zendesk, please see the Zendesk documentation.

Creating dynamic content

For information on creating dynamic content in Zendesk, please see the Zendesk documentation.

Editing dynamic content

For information on editing dynamic content in Zendesk, please see the Zendesk documentation.

Creating dynamic content variants

For information on creating dynamic content variants in Zendesk, please see the Zendesk documentation.

Editing dynamic content variants

This will be similar to the Zendesk documentation for creating a variant.

Instead, when you go to the dynamic content, you would click edit to the right of the variant you wish to edit.

Deleting dynamic content variants

For information on deleting dynamic content variants in Zendesk, please see the Zendesk documentation.

Deleting dynamic content

For information on deleting dynamic content in Zendesk, please see the Zendesk documentation.

SECTION: security/customer-support-operations/docs/zendesk/emails.md

{{% alert title="Note" color="primary" %}}

This is an informational page for the Zendesk emails. We are aiming to no longer use these, so all information within should never be used in a Zendesk instance unless explicitly part of a deployment process.

{{% /alert %}}

What are Zendesk emails

As per Zendesk:

> Email is one way that end-users can submit tickets to Zendesk Support and have conversations with agents to resolve their issues.

Basically, Zendesk emails enable an end-user to email an address and have a ticket created from it. Usage of this varies widely from instance to instance.

Creating a Zendesk email

For information on creating a Zendesk email in Zendesk, please see the Zendesk documentation.

Editing a Zendesk email

For information on editing a Zendesk email in Zendesk, please see the Zendesk documentation.

Deleting a Zendesk email

For information on deleting a Zendesk email in Zendesk, please see the Zendesk documentation.

SECTION: security/customer-support-operations/docs/zendesk/end-users.md

{{% alert title="Note" color="primary" %}}

This is an informational page for the Zendesk end-users. It may not reflect the way we actually manage Zendesk end-users.

If you are looking for information about maintaining end-users (creating, editing, etc.), please see End-users workflow

{{% /alert %}}

Creating an end-user

For information on creating an end-user in Zendesk, please see the Zendesk documentation.

Editing an end-user

For information on editing an end-user in Zendesk, please see the Zendesk documentation.

Assuming the identify of an end-user

For information on assuming the identity of an end-user in Zendesk, please see the Zendesk documentation.

Suspending an end-user

For information on suspending an end-user in Zendesk, please see the Zendesk documentation.

Deleting an end-user

{{% alert title="Note" color="warning" %}}

US Government has a Redis sync for its end-users. If you must delete a user from the US Government Zendesk instance, the entry for them must also be removed from the Redis cache.

{{% /alert %}}

For information on deleting an end-user in Zendesk, please see the Zendesk documentation.

End-user settings

{{% alert title="Note" color="danger" %}}

This should be the single source of truth for the settings used. Never make changes outside of approved workflows.

Always be cautious of changes. Many of these can have significant downstream impacts.

{{% /alert %}}

Zendesk Global

- Settings
 - Anyobdy can submit tickets
 - [x] Enabled
 - [x] Require authentication for request and uploads APIs.

- ☐ Ask users to register
- User registration message
 - > Please fill out this form, and we'll send you a welcome email to verify your email address and log you in.
- Allowlist
 - Will vary from instance to instance
- Blocklist
 - Will vary from instance to instance
- Account emails
 - User welcome email text
 - > Welcome to GitLab Support. Please click the link below to create a password and login.
 - ☐ Allow send a welcome email when a new user is created by an agent or administrator
 - Email verification user text
 - > We need to verify that you are the owner of this email address. Please follow the link below to verify.
- Allow users to view and edit their profile data
 - ☒ Enabled
- Allow users to change their password
 - ☒ Enabled
- Validate user phone numbers
 - ☐ Enabled
- Tags on users and organizations
 - ☒ Enabled
- Allow users to belong to multiple organizations
 - ☐ Enabled
- Satisfaction
 - Satisfaction ratings
 - ☒ Allow customers to rate tickets
 - Configuration Options
 - ☒ Ask a follow-up question after a bad rating
 - Reasons in use
 - The issue was not resolved
 - GitLab doesn't meet my needs
 - The answer wasn't delivered in a timely manner
 - The answer wasn't helpful
- Embedded satisfaction score widget
 - ☐ Allow me to display public satisfaction statistics

Zendesk US Government

- Settings
 - Anyobdy can submit tickets
 - ☒ Enabled
 - ☒ Require authentication for request and uploads APIs.
 - ☐ Ask users to register
 - User registration message
 - > Please fill out this form, and we'll send you a welcome email to verify your email address and log you in.
 - Allowlist
 - Will vary from instance to instance

- Blocklist
 - Will vary from instance to instance
- Account emails
 - User welcome email text
 - > Welcome to GitLab Federal Support. Please click the link below to create a password and sign-in.
 - ☐ Allow send a welcome email when a new user is created by an agent or administrator
 - Email verification user text
 - > We need to verify that you are the owner of this email address. Please follow the link below to verify.
 - Allow users to view and edit their profile data
 - ☒ Enabled
 - Allow users to change their password
 - ☒ Enabled
 - Validate user phone numbers
 - ☐ Enabled
 - Tags on users and organizations
 - ☒ Enabled
 - Allow users to belong to multiple organizations
 - ☐ Enabled
- Satisfaction
 - Satisfaction ratings
 - ☒ Allow customers to rate tickets
 - Configuration Options
 - ☒ Ask a follow-up question after a bad rating
 - Reasons in use
 - The issue was not resolved
 - GitLab doesn't meet my needs
 - The answer wasn't delivered in a timely manner
 - The answer wasn't helpful
 - Embedded satisfaction score widget
 - ☐ Allow me to display public satisfaction statistics

End-user authentication

{{% alert title="Note" color="danger" %}}

This should be the single source of truth for the settings used (for both instances). Never make changes outside of approved workflows.

Always be cautious of changes. Many of these can have significant downstream impacts.

{{% /alert %}}

- Tickets, help center, and community
 - ☒ Zendesk authentication
 - Password level: Medium
 - ☒ External authentication
 - ☒ Google
 - ☒ Microsoft

- [x] Facebook
- [] SAML
- [] JSON Web Token
- How end users sign in
 - Redirect to SSO
- Messaging
- Unused

SECTION: security/customer-support-operations/docs/zendesk/explore.md

{{% alert title="Note" color="primary" %}}

This is all informational on Zendesk Explore. We do not maintain the content within Zendesk Explore.

{{% /alert %}}

Overview

Zendesk Explore is a powerful analytics and reporting tool offered by Zendesk, designed to provide in-depth insights into customer support metrics and trends. With Explore, our team can analyze and visualize our support data to make informed decisions, improve customer experiences, and optimize support operations.

Explore offers a user-friendly interface that allows admins to create customized dashboards, reports, and queries without the need for coding knowledge. It integrates seamlessly with Zendesk Support, combining data from multiple sources to deliver comprehensive and actionable analytics.

Explore also offers API access, allowing you to programmatically retrieve data, create and manage queries, and integrate Explore with other systems or custom applications.

{{% alert title="Note" color="primary" %}}

Explore refreshes hourly which means Explore based data is not always real time depending on query.

{{% /alert %}}

{{% alert title="Tip" color="success" %}}

Whenever you start working on Explore yourself, please create a copy of dataset with your name or initials. This way it will preserve your own formulas in reports and dashboards you build.

{{% /alert %}}

Meanings of Common Terms

For detailed Glossary, please visit: <https://support.zendesk.com/hc/en-us/articles/4408824134810-Zendesk-Explore-glossary>

Dashboards

In Explore, Dashboards allow you to view, share, create and customize reports that give you an overview of your Zendesk data.

A dashboard consists of following components:

1. Static widgets: These widgets include reports, images, text, shapes, and tabs, do not impact the results of a report or how users interact with your dashboard. These widgets provide static content that remains unchanged.
1. Interactive widgets: They allow users to specify the specific results they want to view and how they want to view them. With interactive widgets, viewers can modify metrics or attributes, apply filters to refine results, and utilize what-if variables to perform analysis.
1. Live data widgets: As we use Zendesk Explore Enterprise version, we have real time live data widgets available too. These widgets provide real-time updates, ensuring that the data displayed is up-to-date and reflects the latest information available.

Types of Dashboards

Custom Dashboards

Custom dashboards in Zendesk Explore allow you to create personalized visualizations and reports tailored to your specific business needs. They enable you to track and analyze key metrics, monitor trends, and gain actionable insights to drive decision-making and improve your customer support operations.

{{% alert title="Tip" color="success" %}}

Always clone the Custom Dashboards whenever you want to change anything in them and work on new cloned Dashboard. You can do so by clicking the dashboard you want to clone. Click More > Clone.

{{% /alert %}}

Creating Custom Dashboards

Creating Custom Dashboard via Report Builder

To create a custom dashboard using the Report Builder in Zendesk Explore, follow these steps:

1. Open an existing report or create a new one in the Report Builder.
1. Click on the Save button, and then select Add to dashboard.
1. If you want to save the report to a new dashboard, choose the option to create a new dashboard. Enter a name for your dashboard.
1. If you prefer to save the report to an existing dashboard, select the option to use an

existing dashboard and choose the desired one.

1. Click Save.

Once the confirmation message appears in the right corner, you'll see the name of the new dashboard in the top toolbar of the Report Builder. You can also find the dashboard in the dashboards library. Simply click on the dashboard name to open it.

```
{{% alert title="Note" color="primary" %}}
```

The Report Builder always displays the name of the most recently saved dashboard.

```
{{% /alert %}}
```

Creating a Dashboard from the Dashboards Library

If you prefer to create dashboards rather than reports as part of your workflow, you can create new blank dashboards directly from the Dashboards Library. Follow these steps:

1. Click on the Dashboards Library icon (Dashboards Library Icon) on the left sidebar.
1. Click on the New dashboard option.

Tips to create effective Dashboards

1. Define your objectives: Clearly outline the goals and objectives of your custom dashboard. Determine the specific metrics and KPIs (Key Performance Indicators) you want to track. For example, you may want to monitor ticket volume, average resolution time, or customer satisfaction scores.
1. Identify relevant data and datasets: Determine the data sources and datasets you need to connect to your custom dashboard.
1. Select appropriate visualizations: Choose the most appropriate chart types and visualizations that effectively represent your data. Consider the nature of your metrics and the story you want to convey. Line charts, bar charts, and pie charts are commonly used, but explore other options based on your requirements.
1. Create queries: Use the Zendesk Explore Query Builder to create queries that fetch the data for your metrics. Apply filters, groupings, and calculations to generate the desired insights. Leverage the query functionality to analyze data from different angles and create multiple queries for different metrics.
1. Design an intuitive layout: Organize your charts and visualizations in a logical and intuitive manner on the dashboard. Group related metrics together and arrange them in a way that allows for easy comparison and understanding. Consider using sections, columns, and color schemes to enhance clarity.
1. Leverage dashboard interactivity: Take advantage of interactive features to enhance user experience and exploration. Add drill-through links that allow you to navigate to more detailed reports or data. Utilize filters that enable users to dynamically modify the data displayed on the dashboard.
1. Apply contextual filters: Contextual filters allow you to refine the data displayed on your dashboard based on specific criteria, such as time frames, regions, or agent performance. This helps you focus on the relevant data and gain deeper insights.
1. Regularly review and refine: Continuously review and refine your custom dashboard based on evolving business needs and feedback. Keep track of emerging trends, identify anomalies, and

adjust your metrics and visualizations accordingly. Regularly revisit your objectives to ensure alignment with your dashboard content.

1. Keep your custom dashboard focused and concise. Include only the most relevant metrics to avoid clutter and information overload.

1. Use color coding and visual cues to highlight important insights or trends. This helps users quickly identify critical information.

1. Leverage text and annotations to provide context and explanations for the metrics displayed on your dashboard. This ensures clarity and understanding for dashboard users.

1. Regularly share and collaborate on your custom dashboard with relevant stakeholders. Encourage feedback and use it to improve the dashboard's effectiveness.

1. Consider setting up scheduled reports to automatically distribute the dashboard to stakeholders. This ensures timely access to updated insights without the need for manual sharing.

Remember, the key to creating an effective custom dashboard lies in aligning it with your business objectives, selecting relevant metrics, and presenting the data in a visually appealing and easily understandable manner. Regularly review and update your custom dashboard to ensure its continued relevance and usefulness.

SECTION: security/customer-support-operations/docs/zendesk/forms.md

{{% alert title="Note" color="danger" %}}

This is an informational page for the Zendesk forms. It may not reflect the way we actually manage Zendesk forms.

If you are looking for information about maintaining forms (creating, editing, etc.), please see Forms workflow

{{% /alert %}}

What are ticket forms

Ticket forms are the forms utilized by the user to create tickets (when using the web UI). These then translate the responses on the form into ticket metadata.

These fall into one of two types:

- Public - meaning both agents and end-users can see these
- Internal - meaning only agents can see these

Creating a ticket form

For information on creating a ticket form, please see Zendesk documentation

Cloning a ticket form

For information on cloning a ticket form, please see Zendesk documentation

Editing a ticket form

For information on editing a ticket form, please see Zendesk documentation

Reordering ticket forms

For information on reordering ticket forms, please see Zendesk documentation.

Deactivating a ticket form

For information on deactivating a ticket form, please see Zendesk documentation

Deleting a ticket form

For information on deleting a ticket form, please see Zendesk documentation

Current forms

Zendesk Global

Internal name	Public name	Visibility	Entitlement required?	Direct Link
-----	-----	-----	-----	-----
SaaS	Support for GitLab.com	Public	Y	Link
2FA Removal	2FA Reset	Public	Y	Link
SaaS Account	GitLab.com user accounts and login issues	Public	N	Link
Self-Managed	Support for a self-managed GitLab instance	Public	Y	Link
GitLab Dedicated	Support for GitLab Dedicated instances	Public	Y	Link
L&R	Subscription, License or Customers Portal Problems	Public	N	Link
Billing	Billing inquiries/refunds	Public	N	Link
Alliance Partners	Support for alliance partners	Public	Y	Link
Support Ops	Support portal related matters	Public	N	Link
Emergencies	File an emergency request	Public	N	Link
Support Interval Request		Internal	N	
GitLab Incidents		Internal	N	

Zendesk US Government

Internal name	Public name	Visibility	Entitlement required?	Direct Link
-----	-----	-----	-----	-----
Support	Technical Support Requests	Public	Y	Link
GitLab Dedicated	GitLab Dedicated Technical Support Requests	Public	Y	Link
Upgrade Assistance	Upgrade Planning Assistance Request	Public	Y	Link
Support Ops	Support portal related matters	Public	Y	Link
L&R	License, Subscription, and Renewals Request	Public	Y	Link
Emergency	Emergency Support Request	Public	Y	Link
License Issue		Internal	N	

SECTION: security/customer-support-operations/docs/zendesk/groups.md

{{% alert title="Note" color="primary" %}}

This is an informational page for the Zendesk groups. It may not reflect the way we actually manage Zendesk groups.

If you are looking for information about maintaining groups (creating, editing, etc.), please see Groups workflow

{{% /alert %}}

What are Zendesk groups?

As per Zendesk:

> Groups collect team members together based on criteria those team members have in common. Groups can only contain team members; no end users can be included. All agents must be assigned to at least one group, but they can be members of more than one. Groups can be used to support organizations. You can designate one group as the default group for your account and you can also designate a default group for each team member. All new team members you create will be added to the default group.

Creating a group

For information on creating a group, please see Zendesk documentation.

Adding an agent to a group

For information on adding an agent to a group, please see Zendesk documentation.

Editing a group

For information on editing a group, please see Zendesk documentation.

Deleting a group

For information on deleting a group, please see Zendesk documentation.

SECTION: security/customer-support-operations/docs/zendesk/guide.md

{{% alert title="Note" color="primary" %}}

This is an informational page for the Zendesk Guide. It may not reflect the way we actually manage Zendesk Guide.

- If you are looking for information about maintaining Guide, please see Guide workflow
- If you are looking for information about maintaining themes, please see Themes workflow

{{% /alert %}}

What is Zendesk Guide?

Zendesk Guide is the system that generates the support portal and related matters, such as:

- Help articles
- General appearance
- Built-in integrations

A more general way to think of it is that it is the Help Center.

Accessing Zendesk Guide

The main way to access Zendesk Guide is to click the 4 squares in the top-right of the page and then select Knowledge. This will open up the Zendesk Guide in a new tab.

That all said, where you land after that largely depends on previous actions you have done in Guide. As such, we generally recommend accessing it via:

- Zendesk Global
- Zendesk US Government

Components of Zendesk Guide

On the admin page for Zendesk Guide, you will find several icons on the left-hand side of the page:

| Position | Icon | Meaning | Direct links |

|:-----:|:-----:|:-----:|:-----:|

| 1 |  <svg xmlns="http://www.w3.org/2000/svg" width="26" height="26" viewBox="0 0 26 26" aria-hidden="true" focusable="false" data-garden-id="chrome.navitemicon" data-garden-version="8.76.9" class="StyledNavItemIcon-sc-7w9rpt-0 WqCGj"><path fill="currentColor" d="M8 5H3.5c-.3 0-.5.2-.5.5v13c0 .3.2.5.5.5H7c3 0 4 2 4 2h1V7c0-.1-1-2-4-2zm1 10H6c-.5 0-1-.5-1-1s-.5-1-1-1zm0-4H6c-.5 0-1-.5-1-1s-.5-1-1-1zm5-4v14h1s1-2 4-2h3.5c.3 0 .5-.2.5-.5v-13c0-.3-.2-.5-.5-.5H18c-3 0-4 1.9-4 2zm2 7c0-.5.5-1 1-1h3c.5 0 1 .5 1 1s-.5 1-1 1h-3c-.5 0-1-.5-1-1zm0-4c0-.5.5-1 1-1h3c.5 0 1 .5 1 1s-.5 1-1 1h-3c-.5 0-1-.5-1-1zm0-1z"></path></svg> | Manage articles | Global - US Government |

| 2 |  <svg xmlns="http://www.w3.org/2000/svg" width="26" height="26" viewBox="0 0 26 26" aria-hidden="true" focusable="false" data-garden-id="chrome.navitemicon" data-garden-version="8.76.9" class="StyledNavItemIcon-sc-7w9rpt-0 WqCGj"><path fill="currentColor" d="M13 17.35a1.35 1.35 0 1 1-.001-2.7 1.35 1.35 0 0 1 .001 2.7zM12 8a1 1 0 0 1 2 0v4a1 1 0 1 1-2 0V8zm9-3H5a1 1 0 0 0-1 1v12a1 1 0 0 0 1 1h5v2.545c0 .374.47.588.8.364l4.266-2.91H21a1 1 0 0 0 1 1V6a1 1 0 0 0-1-1z"></path></svg> | Moderate content | Global - US Government |

| 3 |  <svg xmlns="http://www.w3.org/2000/svg" width="26" height="26" viewBox="0 0 26 26" aria-hidden="true" focusable="false" data-garden-id="chrome.navitemicon" data-garden-version="8.76.9" class="StyledNavItemIcon-sc-7w9rpt-0 WqCGj"><path fill="currentColor" d="M7 14v-2a1 1 0 0 1 1-1h13a1 1 0 0 1 1 1v2a1 1 0 0 1-1 1H8a1 1 0 0 1-1 1m-3 6v-2.16a1 1 0 0 1 1-1h13a1 1 0 0 1 1 1V20a1 1 0 0 1-1 1H5a1 1 0 0 1-1 1M4 8.16V6a1 1 0 0 1 1-1h13a1 1 0 0 1 1 1v2.17a1 1 0 0 1-1 1H5a1 1 0 0 1-1 1z"></path></svg> | Arrange content | Global - US Government |

| 4 |  <svg xmlns="http://www.w3.org/2000/svg" width="26" height="26" viewBox="0 0 26 26" aria-

hidden="true" focusable="false" data-garden-id="chrome.navitemicon" data-garden-version="8.76.9" class="StyledNavItemIcon-sc-7w9rpt-0 WqCGj"><g fill="currentColor"><path d="M13 17.36A4.36 4.36 0 1 1 17.36 13 4.36 4.36 0 0 1 13 17.36m9.63-5C21 10.55 17.28 6 13 6s-8 4.54-9.63 6.3a1 1 0 0 0 1 1.37C5 15.45 8.72 20 13 20s8-4.54 9.63-6.3a1 1 0 0 0 1.37"></path><circle cx="13" cy="13" r="2.7"></circle></g></svg> | Customize design | Global - US Government |

| 5 | <svg xmlns="http://www.w3.org/2000/svg" width="26" height="26" viewBox="0 0 26 26" aria-hidden="true" focusable="false" data-garden-id="chrome.navitemicon" data-garden-version="8.76.9" class="StyledNavItemIcon-sc-7w9rpt-0 WqCGj"><g fill="currentColor"><circle cx="10" cy="9" r="4"></circle><path d="M3.968 21A.959.959 0 0 1 3 20.052a.994.994 0 0 1 .008-.134 7.09 7.09 0 0 1 13.984 0 .958.958 0 0 1-.822 1.074 1.049 1.049 0 0 1-.137.008zM19.342 5.005A2.5 2.5 0 0 0 17 7.346v2.075h1.443V7.346a1.057 1.057 0 1 1 2.114 0v2.075H22V7.346a2.5 2.5 0 0 0-2.658-2.341z"></path><rect width="7" height="6" x="16" y="9" rx="1" ry="1"></rect></g></svg> | User permissions | Global - US Government |

| 6 | <svg xmlns="http://www.w3.org/2000/svg" width="26" height="26" viewBox="0 0 26 26" aria-hidden="true" focusable="false" data-garden-id="chrome.navitemicon" data-garden-version="8.76.9" class="StyledNavItemIcon-sc-7w9rpt-0 WqCGj"><path fill="currentColor" d="M13 16.627a3.625 3.625 0 0 1-3.63-3.622A3.633 3.633 0 0 1 13 9.373a3.633 3.633 0 0 1 3.63 3.632A3.625 3.625 0 0 1 13 16.627m8.295-4.902h-.006a2.116 2.116 0 0 1-1.955-1.307l-.031-.075a2.117 2.117 0 0 1 .459-2.306.693.693 0 0 0-.998l-.809-.809a.71.71 0 0 0-.997 0 2.106 2.106 0 0 1-2.295.457l-.08-.033a2.109 2.109 0 0 1-1.302-1.948.705.705 0 0 0-.705-.706h-1.148a.705.705 0 0 0-.705.706c0 .855-.514 1.628-1.306 1.95-.021.009-.043.017-.063.027a2.106 2.106 0 0 1-2.308-.453.72.72 0 0 0-1.006 0l-.81.81a.708.708 0 0 0 .997l.007.006a2.11 2.11 0 0 1 .454 2.305c-.01.022-.018.045-.028.066a2.103 2.103 0 0 1-1.95 1.311h-.006a.706.706 0 0 0-.705.706v1.138c0 .39.316.706.705.706h.002a2.1 2.1 0 0 1 1.949 1.306l.029.069a2.11 2.11 0 0 1-.452 2.31l-.004.003a.708.708 0 0 0 .998l.809.809a.72.72 0 0 0 1.006 0l.005-.005a2.106 2.106 0 0 1 2.307-.452l.059.024a2.104 2.104 0 0 1 1.306 1.95v.007c0 .395.32.706.705.706h1.148c.385 0 .705-.31.705-.706v-.007c0-.855.514-1.627 1.306-1.95l.059-.024a2.106 2.106 0 0 1 2.307.452l.005.005a.71.71 0 0 0 .997 0l.809-.81a.693.693 0 0 0-.997l-.004-.003a2.11 2.11 0 0 1-.452-2.31l.029-.069a2.102 2.102 0 0 1 1.948-1.306h.012a.706.706 0 0 0 .705-.706v-1.138a.706.706 0 0 0-.705-.706"></path></svg> | Settings | Global - US Government |

User permissions

```
{{% alert title="Note" color="danger" %}}
```

This should be the single source of truth for the user permissions used (for all Zendesk instances). Never make changes outside of approved workflows.

Always be cautious of changes. Many of these can have significant downstream impacts.

```
{{% /alert %}}
```

- User segments
 - Signed-in users
 - Agents and admins
- Management permissions
 - Editors and Publishers
 - Not activated

- Administrators
 - Edit permissions: Admins
 - Publish permissions: Admins
- Agents and admins
 - Edit permissions: Admins
 - Publish permissions: Admins
- Community moderators
 - Unused
- Content blocks
 - ☒ Allow agents to update content blocks

Settings

{{% alert title="Note" color="danger" %}}

This should be the single source of truth for the settings used (for all Zendesk instances).
Never make changes outside of approved workflows.

Always be cautious of changes. Many of these can have significant downstream impacts.

{{% /alert %}}

- Guide settings
 - Content management
 - ☒ Anonymous voting on articles
 - ☒ Content moderation
 - Moderate all content
 - ☐ User profiles
 - Security
 - ☒ Display unsafe content
 - ☐ Require sign in
 - ☐ Allow email notifications for restricted articles
 - Requests
 - Set the default sorting for comments in my requests: Sort by oldest comment to newest
 - ☐ Enable agents to manage request from Help Center
 - Integrations
 - ☐ Google Analytics
 - ☐ Powered by Zendesk logo
 - ☐ Turn on anonymous user tracking
 - Article verification
 - None
 - Language settings
 - This will vary from instance to instance depending on dynamic content and localization use
 - Search settings
 - Search sources
 - GitLab, Inc., Help Center
 - GitLab Documentation, External content
 - Features articles
 - None
 - Crawlers

- docs.gitlab.com
 - Sitemap URL: docs.gitlab.com/sitemap.xml
 - Domain ownership verification: REDACTED
 - Name: docs.gitlab.com
 - Owner: Jason Colyer
 - Source: GitLab Documentation
 - Type: Documentation Pages
- Search filters
 - Sources
 - GitLab Documentation
 - Types:
 - Documentation Pages
- Gather settings
 - ☐ Activate community
 - ☐ Enable @mentions
 - ☐ Enable alias
 - ☐ Enable user badges
 - ☐ Allow all users to add content tags to their community posts
- User badges
 - Unused

SECTION: security/customer-support-operations/docs/zendesk/help-center-categories.md

{{% alert title="Note" color="primary" %}}}

This is an informational page for the Zendesk Help Center categories. It may not reflect the way we actually manage Zendesk Help Center categories.

If you are looking for information about maintaining Help Center categories, please see Help Center categories workflow

{{% /alert %}}}

Creating a Help Center category

For information on creating a Help Center category, please see Zendesk documentation.

Editing a Help Center category

For information on editing a Help Center category, please see Zendesk documentation.

Reordering Help Center categories

For information on reordering Help Center categories, please see Zendesk documentation.

Deleting a Help Center category

{{% alert title="Note" color="danger" %}}}

When you delete a Help Center category, it deletes all sections under that category (which then archives all articles containing within those sections).

{{% /alert %}}

For information on deleting a Help Center category, please see Zendesk documentation.

SECTION: security/customer-support-operations/docs/zendesk/help-center-management-permissions-groups.md

{{% alert title="Note" color="primary" %}}

This is an informational page for the Zendesk Help Center management permissions. It may not reflect the way we actually manage Zendesk Help Center management permissions.

If you are looking for information about maintaining Help Center management permissions, please see Help Center management permissions workflow

{{% /alert %}}

What are Help Center management permissions

As per Zendesk:

> Management permissions define editing and publishing permissions for agents. You apply management permissions to an article to determine agent editing and publishing access for that article.

Creating a Help Center management permission

For information on creating a Help Center management permission, please see Zendesk documentation.

SECTION: security/customer-support-operations/docs/zendesk/help-center-sections.md

{{% alert title="Note" color="primary" %}}

This is an informational page for the Zendesk Help Center sections. It may not reflect the way we actually manage Zendesk Help Center sections.

If you are looking for information about maintaining Help Center sections, please see Help Center sections workflow

{{% /alert %}}

Creating a Help Center section

For information on creating a Help Center section, please see Zendesk documentation.

Editing a Help Center section

For information on editing a Help Center category, please see Zendesk documentation.

Moving a Help Center section

For information on moving a Help Center category, please see Zendesk documentation.

Reordering Help Center sections

For information on reordering Help Center sections, please see Zendesk documentation.

Deleting a Help Center section

{{% alert title="Note" color="danger" %}}

When you delete a Help Center section, it deletes all sections under that section (which then archives all articles containing within those sections).

{{% /alert %}}

For information on deleting a Help Center section, please see Zendesk documentation.

SECTION: security/customer-support-operations/docs/zendesk/help-center-user-segments.md

{{% alert title="Note" color="primary" %}}

This is an informational page for the Zendesk Help Center user segments. It may not reflect the way we actually manage Zendesk Help Center user segments.

If you are looking for information about maintaining Help Center user segments, please see Help Center user segments workflow

{{% /alert %}}

What are Help Center user segments

As per Zendesk:

> A user segment is a collection of end users and agents, defined by a specific set of attributes and used to determine access to help center content. User segments are the building blocks for both viewing and management user permissions.

Creating a Help Center user segments

For information on creating a Help Center user segment, please see Zendesk documentation.

How do we populate them

The custom user segments we use are populated using specific tags:

- articleeditor - indicating one is an editor
- articlepublisher - indicating one is a publisher

Thes