

e are put onto an agent's Zendesk profile via the Agent sync.

SECTION: security/customer-support-operations/docs/zendesk/liquid.md

What is the liquid language

Liquid is an open-source template language created by Shopify and written in ruby. It is used to allow for more dynamic content on themes, pages, etc.

How we use liquid in Zendesk

In Zendesk, we utilize liquid most commonly in triggers, automations, and extensions. We utilize this to allow for more dynamic messaging (comments, URLs, etc.). It can take time to learn how to fully utilize the liquid language, especially as there is a lot to it and it gets added to frequently.

Variable interpolation

To insert a value into a text/output, you would use double curly bracks around the name of the variable/function/value.

As an example, to output a ticket requester's name, you might do something like Greetings {{ticket.requester.name}}.

You can also use functions in this manner. As an example, if you wanted to put your role into a message, but ensure it was capitalized, you might do something like My role is {{currentuser.role | capitalize }}.

Code blocks

To use code blocks (common for loops, assignment, conditionals, etc.), you would start the line with {% and end it with %}

As an example, if you wanted to start a loop on ticket comments, you might do something like {% for comment in ticket.comments %}.

Common variables

Object Type	Variable	Description
Current User	currentuser	A user object referring to the current user
User	name	The user's full name
User	firstname	The user's first name
User	lastname	The user's last name
User	email	The user's email address
User	details	The user's details text box
User	notes	The user's notes text box
User	id	The user's Zendesk ID

User	organization	The user's organization object
User	customfields.gitlabuserid	The user's GitLab user ID (a custom user field)
User	customfields.gitlabusername	The user's GitLab username (a custom user field)
User	customfields.xxxxx	The user's value for a user field named xxxxx
Organization	id	The organization's Zendesk ID
Organization	name	The organization's name
Organization	details	The organization's details text box
Organization	notes	The organization's notes text box
Organization	customfields.saleforceid	The Salesforce ID for an organization
Organization	customfields.arr	The ARR for an organization
Organization	customfields.technicalaccountmanager	The CSM for an organization
Organization	customfields.accountowner	The AM for an organization
Organization	customfields.orgregion.title	The organization's region
Organization	customfields.supportlevel.title	The organization's support level
Organization	customfields.xxxxx	The organization's value for a organization field named xxxxx
Agent	name	The agent's name
Agent	role	The agent's role
Agent	email	The agent's email
Agent	signature	The agent's signature
Ticket	assignee	The ticket's assignee (a user object)
Ticket	ccs	An array of users who are CC'd on the ticket
Ticket	duedate	The ticket's due date (date only)
Ticket	duedatewithtimestamp	The ticket's due date (with timestamp)
Ticket	id	The ticket's Zendesk ID
Ticket	inbusinesshours	A boolean if the ticket is currently in it's schedules hours
Ticket	link	The ticket's URL with the HTTP protocol
Ticket	requester	The requester of a ticket (user object)
Ticket	organization	The organization of a ticket (organization object)
Ticket	status	The ticket's status
Ticket	ticketfieldxxxxxx	The ticket's API value for ticket field with ID of xxxxxx
Ticket	ticketfieldoptiontitlexxxxxx	The ticket's dropdown title value for ticket field with ID of xxxxxx
Ticket	ticketfield360019949920	The ticket's unauthorized user field value (Zendesk Global)
Ticket	ticketfield360017383799	The ticket's due date notes (Zendesk Global)
Ticket	ticketfield360012194220	The ticket's partner troubleshooting value (Zendesk Global)
Ticket	ticketfield360020735339	The ticket's request for CCs value (Zendesk Global)
Ticket	ticketfield360012194200	The ticket's Organization email (partners) value (Zendesk Global)
Ticket	ticketfield360018253094	The ticket's preferred region for support value (Zendesk Global)
Ticket	ticketform	The ticket's form
Ticket	url	The ticket's URL without the HTTP protocol
Ticket	title	The ticket's subject
Ticket	comments	An array of the ticket's comments
Ticket	publiccomments	An array of the ticket's public comments
Satisfaction	currentrating	The current satisfaction rating of a ticket
Satisfaction	ratingsection	The formatted block sent to user's request a satisfaction

survey |

| Satisfaction | currentcomment | The current satisfaction comment of a ticket |

There are many more that can be used, these are by far just the most common used at GitLab.

Common functions

| Function | Description |

|-----|-----|

| slice | Returns a substring |

| split | Divides a string into an array based on a separator |

| urlencode | Converts a string into URL encoded characters |

| urldecode | Decodes a string that was encoded by urlencode |

| first | The first item in an array |

| last | The last item in an array |

| join | Combines items in an array |

| capitalize | Sets the first character in the string to uppercase |

| upcase | Sets all characters in the string to uppercase |

| downcase | Sets all characters in the string to lowercase |

| size | Returns the size of the object. If a string, it is number of characters; if an array, the number of items |

| lstrip | Removes whitespace from the left of a string |

| rstrip | Removes whitespace from the right of a string |

| strip | Removes whitespace from both the left and right of a string |

| remove | Removes items in a string |

| replace | Replaces items in a string |

| sort | Sorts items in an array alphabetically |

| truncate | Shortens a string |

| uniq | Removes duplicate items from an array |

Common tags

| Tag | Description |

|----|-----|

| assign | Assigns a value to a variable |

| blank | The same as saying "nil" or "null" |

| capture | Captures text into a variable |

| break | Exit a loop |

| continue | Skip the remaining code in a loop and start the next iteration |

Conditionals

| Conditional | Operators available |

|-----|-----|

| if..elsif..else..endif | == != < <= > >= contains and or |

| unless..endless | == != < <= > >= contains and or |

| case..when..else..endcase | N/A |

Loops

| Loop | Syntax |
|-----|
| for | for x in y, for x in y limit:5, for x in y offset:3, for x in y reversed |
| cycle | cycle "apple", "banana", "cherry" |

Examples

Create documentation issue trigger

We used this in a trigger to determine the author, title, and description of the most recent comment to create a documentation issue.

string

```
{% for comment in ticket.comments limit:1 offset:0 %}  
  {% assign author = comment.author.customfields.gitlabuserid %}  
  {% assign lines = comment | urlencode | split: "%0A" %}  
  {% for line in lines %}  
    {% assign firstfive = line | slice: 0,5 %}  
    {% if firstfive == 'Title' %}  
      {% assign title = line | urldecode | split: ':' | last %}  
    {% endif %}  
  {% endfor %}  
  {% assign description = comment | split: 'Description:' | last | join: '\n' %}  
{% endfor %}
```

Line by line breakdown:

1. Start a for loop on the ticket comments, setting a limit of 1 iteration (meaning only grab the most recent one)
1. Assign a value to the variable author
 - The value should be the comment's author GitLab user ID (a custom user field)
1. Assign a value to the variable lines
 - This passes the comment into the function urlencode, to encode the string into a URL safe format
 - This passed the urlencoded string into the split function, which turns it into an array split by the separate %0A
1. Start a for loop on the array stored in the lines variable
1. Assign a value to the variable firstfive
 - This passes line into the slice function, return the first 5 characters
1. Declare an if block, with the condition being the value of firstfive is Title
1. Assign a value to the variable title
 - This passes the line into the function urldecode, to undo what urlencode previously did
 - This is passed into the split function, which turns it into an array split by the separator :
 - This is passed into the last function, to return the last item in the array
1. Ends the if block
1. Ends for second for loop
1. Assign a value to the variable description

- This passes the comment into the split function, which turns it into an array split by the separator 'Description:'
 - This is passed into the last function, to return the last item in the array
 - This is passed into the join function, to join the items using the separator \n
1. Ends for the first for loop

New ticket confirmation email trigger

We used this to determine is a block of text should display based on if the ticket is currently within business hours or not.

string

```
{% if ticket.inbusinesshours == 'false' %}
  <li>You indicated in this ticket, {{ticket.id}}, a "Preferred Region for Support." The
current time is outside of that region's standard business hours. You can rest assured that
this ticket will be addressed by the next available engineer in the selected region. It is
important that you understand when you may expect a reply regarding this case. Please see the
linked handbook section for more information regarding the <a
href='https://about.gitlab.com/support/effect-on-support-hours-if-a-preferred-region-for-
support-is-chosen' target='blank'>effect of using Preferred Region</a>.<br />During the course
of this ticket if you require assistance outside of the selected region's standard business
hours please feel free to reply asking one of our support engineers to set this ticket's
preferred region to "All regions".</li>
{% endif %}
```

Line by line breakdown:

1. Declare an if block, with the condition being if the ticket is not within business hours
1. Display a block of text
 - This inserts the ticket's ID using a liquid variable via {{ticket.id}}
1. Ends the if block

SSAT Issue Creation trigger

We used this as part of the triggers that create issues based on SSAT ratings customers leave us. This is used to determine the form the ticket is using and set a variable to be used containing the GitLab issue tag that corresponds to the ticket form.

string

```
{% assign form = ticket.ticketform %}

{% if form == 'GitLab.com User Accounts and Login Issues' %}
  {% assign form = 'form::GitLab.com' %}
{% elsif form == 'Support for GitLab.com' %}
  {% assign form = 'form::GitLab.com' %}
{% elsif form == 'Support for a self-managed GitLab instance' %}
  {% assign form = 'form::Self-managed' %}
{% elsif form == 'Licensing and Renewals Problems' %}
  {% assign form = 'form::Upgrades & Renewals' %}
```

```
{% elsif form == 'Contact the Security team' %}
  {% assign form = 'form::Security' %}
{% elsif form == 'Other Request' %}
  {% assign form = 'form::Other' %}
{% else %}
  {% assign form = 'form::GitLab Community Edition' %}
{% endif %}
```

Line by line breakdown:

1. Assign a value to the variable form
 - The value should be the ticket's form
1. A blank line for spacing (not required, just makes it look nicer)
1. Declare an if block, with the condition being if the value of form is GitLab.com User Accounts and Login Issues
 1. Assign a value to the variable form
1. Declare an elsif block, with the condition being if the value of form is Support for GitLab.com
 1. Assign a value to the variable form
1. Declare an elsif block, with the condition being if the value of form is Support for a self-managed GitLab instance
 1. Assign a value to the variable form
1. Declare an elsif block, with the condition being if the value of form is Licensing and Renewals Problems
 1. Assign a value to the variable form
1. Declare an elsif block, with the condition being if the value of form is Contact the Security team
 1. Assign a value to the variable form
1. Declare an elsif block, with the condition being if the value of form is Other Request
 1. Assign a value to the variable form
1. Declare an else block
 1. Assign a value to the variable form
1. Ends the if block

Useful links

- Liquid GitHub repo
- Liquid documentation
- Zendesk placeholders reference

SECTION: security/customer-support-operations/docs/zendesk/macros.md

```
{{% alert title="Note" color="primary" %}}}
```

This is an informational page for the Zendesk macros. It may not reflect the way we actually manage Zendesk macros.

If you are looking for information about maintaining macros (creating, editing, etc.), please see Macros workflow

{{% /alert %}}

What are macros

As per Zendesk:

> A macro is a prepared response or action that an agent can manually apply when they are creating or updating tickets. Macros contain actions that can update ticket properties.

>

> Unlike triggers and automations, macros only contain actions, not conditions. Conditions aren't used because nothing is automatically evaluating tickets to determine if a macro should be applied. Agents evaluate tickets and apply macros manually as needed.

Macro categorization

Macros are a bit unique in Zendesk. They have categorization, but it is not obvious in the UI. Instead, the categorization is determined based on the name of the macro itself. Essentially, every group of words becomes a "folder" of sorts in the macros dropdown selector. The separator currently used by Zendesk is two colons (::).

This can get a bit confusing and hard to learn the ins and outs of, so when in doubt, reach out to your fellow Customer Support Operations team members.

Seeing macro usage information

To see the usage information on macros:

1. Navigate to the admin panel for the Zendesk instance
1. Go to Workspaces > Agent tools > Macros
1. Click the icon to the far right of the list of macros (looks like three vertical rectangles)
1. Click the usage columns you wish to see

Creating a macro in Zendesk

For information on creating a macro in Zendesk, please see the Zendesk documentation

Cloning a macro in Zendesk

To clone a macro in Zendesk:

1. Navigate to the admin panel for the Zendesk instance
1. Go to Workspaces > Agent tools > Macros
1. Locate the macro you wish to clone and click on the name
1. Click the Actions button
1. Click Clone
1. This opens the macro editor page, so you can proceed using the information in the Zendesk documentation

Editing a macro in Zendesk

To edit a macro in Zendesk:

1. Navigate to the admin panel for the Zendesk instance
1. Go to Workspaces > Agent tools > Macros
1. Locate the macro you wish to clone and click on the name
1. This opens the macro editor page, so you can proceed using the information in the Zendesk documentation

Deactivating a macro in Zendesk

To deactivate a macro in Zendesk:

1. Navigate to the admin panel for the Zendesk instance
1. Go to Workspaces > Agent tools > Macros
1. Locate the macro you wish to clone and click on the name
1. Click the Actions button
1. Click Deactivate

Deleting a macro in Zendesk

```
{{% alert title="Note" color="warning" %}}
```

You can only delete a macro if it is deactivated.

```
{{% /alert %}}
```

1. Navigate to the admin panel for the Zendesk instance
1. Go to Workspaces > Agent tools > Macros
1. Locate the macro you wish to clone and click on the name
1. Click the Actions button
1. Click Delete
1. Click Delete macro in the confirmation box

Using a macro in Zendesk

There are two ways to apply a macro to a ticket:

- Via slash commands
- Via the macro selection drop-down

For more information, please see Zendesk documentation

SECTION: security/customer-support-operations/docs/zendesk/metrics-definitions.md

```
{{% alert title="Note" color="primary" %}}
```

These are how Zendesk itself defines various metrics, not how GitLab does. GitLab might define them differently.

{{% /alert %}}

FRT

This is the time a ticket spent from creation until it received its first public reply from an agent.

NRT

This is the time a ticket spent from a public reply from an end-user until it received a public reply from an agent.

Requester wait time

This is the total time a ticket spent in the following statuses:

- New
- Open
- On-hold

Agent work time

This is the total time a ticket spent in the following statuses:

- New
- Open

Agent wait time

This is the total time a ticket spent in the following statuses:

- Pending

On-hold time

This is the total time a ticket spent in the following statuses:

- On-hold

Total resolution time

This is the total time a ticket spent in the following statuses:

- New
- Open
- Pending
- On-hold

Periodic update

This is the time a ticket spends between public agent replies.

Pausable update

This is the time a ticket spends between public agent replies while in the following statuses:

- New
- Open
- On-hold

Futher reading

- Understanding which SLA metrics you can measure
- About native Support time duration metrics

SECTION: security/customer-support-operations/docs/zendesk/org-deletion.md

{{% alert title="Note" color="danger" %}}

This is an informational page for Zendesk organization deletion. This should never be done manually and only as part of automations, unless specifically stated by another process.

{{% /alert %}}

This process relies heavily on the ZD-SFDC sync and custom deletion scripts to work. Please review the following projects so you can better understand the automation/scripting aspect of all this:

- ZD-SFDC sync for Zendesk Global
- ZD-SFDC sync for Zendesk US Government
- Organization Deletion for Zendesk Global
- Organization Deletion for Zendesk US Government

Criteria for standard deletion

As per our Data Retention policy and in accordance with various governing laws/regulations, we delete an organization 3 years after their last valid subscription has expired. So if an organization's last valid subscription expired 2021-12-18, then the date it would be eligible for deletion would be 2024-12-18. For organizations within Zendesk (both instances) that are found to meet this criteria, an organization field named Greatly Expired is marked as true. This results in the tag greatlyexpired being added onto the organization. Through this, organizations that have met the criteria for deletion are marked in a way that is readily findable within Zendesk.

Organizatton deletions

Once a week, on Friday, the Organization Deletion project for the corresponding Zendesk instance will take the list of organizations using the organization tag to be deleted (excluding those with the tag do not delete). With this list, the project will then completely delete the organization, which involves the following:

- Deleting all tickets under the organization
- Deleting all users under the organization
- Deleting the organization itself
- Updating any Redis objects that involve Zendesk organizations, users, and tickets

SECTION: security/customer-support-operations/docs/zendesk/org-fields.md

{{% alert title="Note" color="primary" %}}

This is an informational page for Zendesk organizations. It may not reflect the way we actually manage Zendesk organizations.

If you are looking for information about maintaining organization fields, please see Organization Fields workflow

{{% /alert %}}

Creating organization fields

For information on creating a organization field, please see Zendesk documentation.

Cloning organization fields

For information on cloning a organization field, please see Zendesk documentation.

Editing organization fields

For information on editing a organization field, please see Zendesk documentation.

Reordering user fields

For information on reordering organization fields, please see Zendesk documentation.

Deactivating organization fields

For information on deactivating a organization field, please see Zendesk documentation.

Deleting organization fields

{{% alert title="Note" color="warning" %}}

You can only delete a organization field if it is deactivated.

{{% /alert %}}

For information on deleting a organization field, please see Zendesk documentation.

SECTION: security/customer-support-operations/docs/zendesk/organizations.md

{{% alert title="Note" color="primary" %}}

This is an informational page for Zendesk organizations. It may not reflect the way we actually manage Zendesk organizations.

- If you are looking for information about organization deletions, please see Organization deletions
- If you are looking for information about maintaining organizations, please see ZD-SFDC Sync

{{% /alert %}}

What are Zendesk organizations?

Organizations are simply a collection of users in Zendesk (much like groups). We use them to also store metadata (synced from Salesforce), which is used to determine such things as SLA, ARR, etc.

an organization in Zendesk

Creating an organization in Zendesk

{{% alert title="Note" color="danger" %}}

You can cause some serious issues doing this action. Avoid doing this unless another workflow specifically states to do so.

{{% /alert %}}

For information on creating an organization, please see Zendesk documentation.

Editing an organization in Zendesk

{{% alert title="Note" color="danger" %}}

You can cause some serious issues doing this action. Avoid doing this unless another workflow specifically states to do so.

{{% /alert %}}

For information on editing an organization, please see Zendesk documentation.

Merging an organization in Zendesk

{{% alert title="Note" color="danger" %}}

You can cause some serious issues doing this action. Avoid doing this unless another workflow specifically states to do so.

{{% /alert %}}

For information on merging an organization, please see Zendesk documentation.

Deleting an organization in Zendesk

{{% alert title="Note" color="danger" %}}

You can cause some serious issues doing this action. Avoid doing this unless another workflow specifically states to do so.

{{% /alert %}}

For information on deleting an organization, please see Zendesk documentation.

Organization Notes

Zendesk Global

There are two forms of organization notes we utilize:

- Customer Support Operations organization notes
- Support Team organization notes

Support Operations organizations notes are managed via Zendesk in the Notes and Details fields on the organization itself.

When an organization has a ticket created, the ticket processor runs to parse both of these into internal comments on the ticket itself.

Zendesk US Government

We manage all internal notes on Zendesk itself due to data privacy concerns. As such, we separate them as such:

- Notes are for Support Team organization notes
- Details are for Customer Support Operations organization notes

When an organization has a ticket created, the ticket processor runs to parse both of these into internal comments on the ticket itself.

Permissions

By default, organizations are setup so that the users within it can only see and comment on their own tickets.

For more information on this, please see Shared organizations workflow.

Domain matching

While Zendesk does have the functionality to do domain matching, we have determined that the security risks inherent in this feature outweigh the benefits that would be received from its use.

Because of this decision, as of August 2020, GitLab will not longer apply a domain on a Zendesk organization. Any organization that had this applied prior to this date will have it as a legacy feature.

SECTION: security/customer-support-operations/docs/zendesk/roles.md

{{% alert title="Note" color="primary" %}}

This is an informational page for Zendesk roles. It may not reflect the way we actually manage Zendesk roles.

If you are looking for information about maintaining roles, please see Roles workflow

{{% /alert %}}

What are Zendesk roles?

Zendesk uses Roles as a way to maintain permission sets for agents.

Creating or cloning a role

For information on creating or cloning a role, please see Zendesk documentation.

Assigning an agent to a role

For information on assigning an agent to a role, please see Zendesk documentation.

Editing a role

For information on editing a role, please see Zendesk documentation.

Deleting a role

{{% alert title="Note" color="warning" %}}

You can only delete a role if no one is assigned to it.

{{% /alert %}}

For information on deleting a role, please see Zendesk documentation.

Current roles

{{% alert title="Note" color="danger" %}}

This should be the single source of truth for the roles used. Never make changes outside of approved workflows.

Always be cautious of changes. Many of these can have significant downstream impacts.

{{% /alert %}}

Zendesk Global

- Admin
- Chat-only agent
- Contributor
- GitLab Staff
- GitLab Staff - Explore
- Light agent
- Security Staff
- Support Managers
- Support Staff
- Support Staff - CMOC
- Support Staff - Explore
- Tech Support

Zendesk US Government

- Admin
- Chat-only agent
- Contributor
- GitLab Staff
- Light agent
- Support Managers
- Support US Federal Staff
- Support US Federal Staff w/ Explore

SECTION: security/customer-support-operations/docs/zendesk/round-robin.md

{{% alert title="Note" color="primary" %}}

This is an informational page for the round robin. It may not reflect the way we actually manage the round robin.

If you are looking for information about maintaining round robin, please see Round Robin workflow

{{% /alert %}}

How is it triggered

The round robin runs via gitLab Scheduled pipelines using a specific schedule for each Zendesk instance:

- Global: N/A
- US Government: Every 10 minutes between the hours 0500 to 1700 (Pacific time) Monday through Friday (/10 5-17 1-5)

How it works

Zendesk US Government

- Ruby version: 3.2.2
- Gem list:
 - gitlabsupportreadiness
- CI/CD Images:
 - curlimages/curl:latest
 - ruby:3.2.2

Before each job runs, it performs a few actions to setup the image to perform the needed actions:

- Output the response from running the command `ruby -v`
- Install the bundler gem
- Run the bundle command
- Put the values of the environment variable `SERVICECREDS` into the file `data/config.json`

After this, the `./bin/roundrobin` script is executed.

The script will then determine the currently available agents by checking the support-team information, remove any agents on PTO, and remove any agents not currently within working hours.

Using the list of currently available agents, it will then determine the current workloads of said agents (this is done by looking at assigned tickets with a status lower than solved) using the Ticket Weight field on the tickets it locates.

After gathering the tickets in need of being round robin'd (using the Not round robin'd view), the script will then assign them out to the agent with the lowest workload (incrementing their workload by 1).

Source projects

- Zendesk US Government

SECTION: security/customer-support-operations/docs/zendesk/sandbox.md

What is the Zendesk Sandbox

The Zendesk Sandbox is a replica Zendesk instance you can use to test, learn, replicate, etc. in an environment that is separated from production instances.

We utilize the Zendesk Sandbox in all our change management processes. This allows us a safe and secure place to test changes/updates/etc. so we can ensure the implementations we push into production are both stable and well vetted.

Where are the sandboxes?

You can locate the sandboxes via:

- Global
- US Federal

How to access the Zendesk Sandbox

We have many, many test users with login credentials you can use in the sandbox. You can locate the information for them via the Zendesk Sandbox Test Orgs and Users Google sheet (internal only).

If for some reason the users there will not work in your case, please contact the Fullstack Engineer for Support Operations.

Creating a Sandbox

```
{{% alert title="Note" color="danger" %}}
```

This should never be done freely. This should only ever be planned out and approved by Support Operations leadership.

```
{{% /alert %}}
```

For information on creating a sandbox, please see Zendesk documentation

Deleting a Sandbox

```
{{% alert title="Note" color="danger" %}}
```

This should never be done freely. This should only ever be planned out and approved by Support Operations leadership.

```
{{% /alert %}}
```

For information on deleting a sandbox, please see Zendesk documentation

SECTION: security/customer-support-operations/docs/zendesk/schedules.md

{{% alert title="Note" color="danger" %}}

This is an informational page for the Zendesk schedules. It may not reflect the way we actually manage Zendesk schedules.

You can severely break a contractual obligations if you do not follow established workflows.

If you are looking for information about maintaining schedules, please see Schedules workflow

{{% /alert %}}

What are schedules

Schedules in Zendesk are like schedules in most other things: windows of time. We use these to determine business hours and various regional working hours.

Within Zendesk, these have the ability to use a specific timezone and allow for the setting of holidays.

Creating a schedule

For information on creating a schedule in Zendesk, please see Zendesk documentation.

Editing a schedule

To edit a schedule:

1. Navigate to the admin center of the Zendesk instance
 - Click thhe four squares at the top-right of the page
 - Click Admin Center
1. Navigate to Objects and rules > Business rules > Schedules
1. Locate the schedule to edit and click it
1. Make your changes
1. Click Save at the bottom-right of the page.

Managing holidays

For information on managing holiday on a schedule in Zendesk, please see Zendesk documentation.

Deleting a schedule

For information on deeltling a schedule in Zendesk, please see Zendesk documentation.

SECTION: security/customer-support-operations/docs/zendesk/searching.md

Basic search

To perform a basic search, click the magnifying glass icon in the top-right of any page within

Zendesk. This will reveal a textbox you can type your search into. After typing your search query, hit the enter/return key on your keyboard.

This will bring up the search results page. The results from your search are separated into tabbed sections:

- Tickets
- Articles
- Users
- Organizations

If you wish to share these search results, the white Copy link button can be used to create a link that will replicate the search for you to share.

Advanced searching

This covers searching for more specific information using the Zendesk search language. All results are still shown much like those within a basic search.

Searching by tag

To search for objects with a specific tag, you would simply use the syntax:

`tags:tagname`

As an example, to locate objects using the tag skip2faautomation, you'd use:

`tags:skip2faautomation`

You can search for the negation of this by putting a minus in front of it:

`-tags:tagname`

If you wanted to search for objects with multiple tags, you'd encapsulate them in double quotes:

`tags:"tagname tagname"`

As an example, if you wanted to find all objects that contains the tags gold and sev1, you'd do:

`tags:"gold sev1"`

Searching by status

To search by ticket status, you would use the syntax:

`status{operator}statusname`

The status names (and order) are:

- 1. new
- 1. open
- 1. pending
- 1. hold
- 1. solved
- 1. closed

The comment operators are:

Operator	Meaning
:	Equal to
<	Less than
<=	Less than or equal to
>	Greater than
>=	Greater than or equal to

You can search for the negation of this by putting a minus in front of it:

-status:open

Searching by custom organization field

To search by a custom organization field, you use the format:

fieldapiname:query

The common organization field API names are:

Field	What it is for	Zendesk
Instance		
accountowner	The AM for the org	Both
aar	The ARR of the org	Global
arr	The ARR of the org	US Government
assignedse	The user ID of the ASE for the org	Global
technicalaccountmanager	The CSM for the org	Both
supportlevel	The highest support level of the org	Both
healthscore	The Gainsight health score for the org	Both
seatsdecimal	The highest number of licenses seats for the org	Global
numberofseats	The highest number of licenses seats for the org	US Government

salesforceid	The 18 character SFDC ID for the org	Both
sfdcshortid	The 15 character SFDC ID for the org	Both
solutionsarchitect	The SA for the org	US Government

An example:

Searching for organizations with ARR less than 1000:

aar<1000

You can search for the negation of this by putting a minus in front of any that are text-based.

Searching by custom user field

To search by a custom user field, you use the format:

fieldapiname:query

The common user field API names are:

- gitlabusername - An agent's GitLab.com username
- gitlabuserid - An agent's GitLab.com user ID

As an example, to find one where the GitLab.com username is jcolyer, you would do:

gitlabusername:jcolyer

You can search for the negation of this by putting a minus in front of any that are text-based.

Searching by custom ticket field

To search by a custom user field, you use the format:

customfield{id}:value

where {id} is the ticket field ID. This one can be less intuitive as it requires knowing the ticket field ID. The best resource for this would be to talk to the Support Operations team for assistance in locating the ticket field's ID value.

You can search for the negation of this by putting a minus in front of any that are text-based.

Searching by satisfaction rating

To locate tickets based on satisfaction rating, you would use the format:

satisfaction:value

The possible values are:

- bad - A bad rating without a comment
- badwithcomment - A bad rating with a comment
- good - A good rating without a comment
- goodwithcomment - A good rating with a comment
- offered - The survey has been sent but not responded to

You can search for the negation of this by putting a minus in front of any that are text-based.

Examples

Example 1

Task:

- the preferred region of support is AMER
- the support level of the organization is ultimate
- the satisfaction rating was bad (and had a comment)

customfield360018253094:americasusa tags:ultimate satisfaction:badwithcomment

Example 2

Task:

- all ticket status except new, solved, and closed
- the assignee is Jason
- the SaaS Account problem type is Namesquatting

-status:new -status:solved -status:closed assignee:Jason
customfield360011793260:namesquattingrequests

Example 3

Task:

- locate an organization in Zendesk based off the Salesforce ID

Salesforce accounts actually have two forms of their IDs, the standard 18 character value and the shortened 15 character value. Zendesk organizations have both values within them, so you can use either to locate the account:

- Based off the 18 character ID value:
salesforceid:ABCDEFGH0123456789
- Based off the 15 character ID value:
sfdcshortid:ABCDEFGH0123456

You can also make use of the wildcard search by using an asterisk. So if you have the 15 character value, you could do this as well:

salesforceid:ABCDEFGH0123456

Example 4

Task:

- locate an L&R IR ticket based off the Salesforce ID of the account

As detailed in Example 3, there are two values one could have for a given Salesforce account. With L&R IRs, there is a custom field you can use to locate the Salesforce account it was filed for, but knowing if which of the two was used can be difficult. As such, it is best to use the 15 character value with a wildcard search. If you only have the 18 character value, drop the last 3 characters from the ID (so if it was ABCDEFGH0123456789, drop the last 3 to make it ABCDEFGH0123456). With that, you would do one of the following searches (depending on which Zendesk instance you are looking in):

- Zendesk Global:
customfield6978327875612:ABCDEFGH0123456
- Zendesk US Government:
customfield11717220820372:ABCDEFGH0123456

Useful links

- Zendesk search reference

SECTION: security/customer-support-operations/docs/zendesk/slas.md

{{% alert title="Zendesk calls them service level agreements, we do not" color="danger" %}}

What appears here is all titled service level agreements, or SLAs, but many of these are internal service level objectives, or SLOs, instead. They are titled as service level agreement, or SLA, because that is what Zendesk calls the setting. Nothing detailed herein is an actual, legal service level agreement.

{{% /alert %}}

{{% alert title="Note" color="danger" %}}

This is an informational page for the Zendesk SLAs. It may not reflect the way we actually manage Zendesk SLAs.

You can severely break a contractual obligations if you do not follow established workflows.

If you are looking for information about maintaining SLAs, please see SLAs workflow

{{% /alert %}}

What are Zendesk service level agreements?

As per Zendesk:

> A Service Level Agreement, or SLA, is an agreed upon measure of the response and resolution times that your support team delivers to your customers. Providing support based on service levels ensures that you're delivering measured and predictable service. It also provides greater visibility when problems arise.

Creating a SLA

For more information on creating a SLA, please see Zendesk documentation

Cloning a SLA

For more information on cloning a SLA, please see Zendesk documentation

Editing a SLA

For more information on editing a SLA, please see Zendesk documentation

Reordering SLAs

For more information on reordering SLAs, please see Zendesk documentation

Deleting a SLA

For more information on deleting a SLA, please see Zendesk documentation

SECTION: security/customer-support-operations/docs/zendesk/ssat.md

{{% alert title="Note" color="danger" %}}

Note that as of 2025-05-01, we are no longer using Zendesk satisfaction surveys. We have switched to using CES Surveys

{{% /alert %}}

{{% alert title="Note" color="primary" %}}

This is an informational page for the Zendesk satisfaction surveys. It may not reflect the way we actually manage Zendesk satisfaction surveys.

If you are looking for information about maintaining satisfaction surveys, please see SSAT workflow

{{% /alert %}}

What is the Zendesk satisfaction survey?

As per Zendesk

> One of Zendesk Support's most popular features is our built-in customer satisfaction survey. Customer satisfaction allows you to track how well your agents and customer service organization as a whole are performing on a ticket by ticket basis. Because of our simplified approach, on average our customers see a roughly 21% response rate - which is fantastic! Zendesk Support provides some great defaults for the survey, but we get a lot of questions about how to further customize the customer satisfaction experience.

We shorthand the overall setup (survey and ticket ratings) as SSAT

Activating satisfaction surveys

For information on activating satisfaction surveys, please see Zendesk documentation

Deactivating satisfaction surveys

For information on activating satisfaction surveys, please see Zendesk documentation

End-user experience

For information on the end-user experience, please see Zendesk documentation

SECTION: security/customer-support-operations/docs/zendesk/tags.md

What are Zendesk tags?

As per Zendesk:

> Tags are words, or combinations of words, you can use to add more context to tickets and topics. You can apply tags to tickets, users, and organizations.

At its core, Zendesk relies on tags pretty heavily. As such, it is best to fully understand the tags used and how they correlate to what Zendesk does to the ticket.

What are our tags?

As there are many, many tags, and new ones get added frequently, we maintain it via the Zendesk Tags Google sheet (internal access only).

The Google sheet is populated once a week, at 1200 instance time (UTC for Global, Pacific for US Government) via the following projects:

- Global Tag List Generator
- US Government Tag List Generator

SECTION: security/customer-support-operations/docs/zendesk/themes.md

{{% alert title="Note" color="danger" %}}

This is an informational page for Zendesk themes. It may not reflect the way we actually manage Zendesk themes.

You can severely break a very customer facing item in Zendesk if you do not follow established workflows.

If you are looking for information about managing it, please see themes workflow

{{% /alert %}}

For information on using themes in Zendesk, please see Zendesk documentation.

SECTION: security/customer-support-operations/docs/zendesk/ticket-fields.md

{{% alert title="Note" color="primary" %}}

This is an informational page for Zendesk ticket fields. It may not reflect the way we actually manage Zendesk ticket fields

If you are looking for information about managing it, please see Ticket fields workflow

{{% /alert %}}

What are ticket fields

Ticket fields are the individual components that make up a ticket form. They can be customized to ask for specific information and help generate ticket metadata.

As per Zendesk, there are two types of ticket fields:

- > - Standard ticket fields - predefined fields that agents see in a ticket. Additional standard fields are added to the ticket page when you activate additional Zendesk Support features, such as ticket sharing. You can deactivate and reactivate some (but not all) of the standard fields. See the complete list of standard ticket fields.
- > - Custom ticket fields - created in addition to standard ticket fields to gather additional information from the person who is requesting support. For example, you may add a custom field prompting them to select a product name or model number. See the complete list of custom ticket field types.

Creating a ticket field

For information on creating a ticket field, please see Zendesk documentation.

Cloning a ticket field

For information on cloning a ticket field, please see Zendesk documentation.

Editing a ticket field

For information on editing a ticket field, please see Zendesk documentation.

Reordering ticket fields

For information on reordering ticket fields, please see Zendesk documentation.

Deactivating a ticket field

For information on deactivating a ticket field, please see Zendesk documentation.

Deleting a ticket field

{{% alert title="Note" color="warning" %}}

You can only delete a ticket field if it is deactivated.

{{% /alert %}}

For information on deleting a ticket field, please see Zendesk documentation.

SECTION: security/customer-support-operations/docs/zendesk/ticket-processor.md

{{% alert title="Note" color="primary" %}}

This is an informational page for the ticket processor. It may not reflect the way we actually manage the ticket processor

If you are looking for information about managing it, please see Ticket processor workflow

{{% /alert %}}

What is the ticket processor

The ticket processor is a group of scripts we store on gitlab.com that are activated via CI/CD pipeline triggers. They can do various custom acts on a ticket.

Zendesk Global

Source project

2FA Removal

^{Introduced via gitlab-com/support/support-team-meta6663}

This checks the request itself to determine the eligibility status. Depending on the determination, it adds a tag to the ticket (which will fire a corresponding Zendesk trigger).

- If the request is to remove the requester's 2FA:
 - The user has support entitlement for the request
 - The tag 2fachallengequestions is added, which causes the trigger Post 2FA challenge questions to fire
 - The user does not have support entitlement for the request
 - The tag 2fausernotentitled is added, which causes the trigger Close 2FA ticket due to user not entitled to fire
- If the request is to remove another user's 2FA:
 - Checks the following criteria
 - Does the requester have support entitlement for the request?
 - Is the domain of the requester's email an exact match for the domain of the target's email?
 - Does the requester have a gitlab.com account?
 - Does the target have a gitlab.com account?
 - Is the requester an Owner on a top-level paid namespace?
 - Is the target a member under the top-level paid namespace?
 - If it passed all checks:
 - The tag 2fasnippetverification is added, which causes the trigger Post 2FA snippet verification to fire
 - If it fails any checks:
 - The tag 2faownernotentitled is added, which causes the trigger Close 2FA ticket due to owner not entitled to fire

Account blocked

^{Introduced via gitlab-com/support/support-ops/zendesk-global/trigger!264}

This checks the account status of a gitlab.com user. Depending on the status, different actions can occur:

- If the user does not exist...
 - A public reply is sent to the user stating the account does not exist
 - The Ticket Stage value is set to FRT
 - The ticket's status is set to Pending
- If the user is not blocked...
 - A public reply is sent to the user stating the account is not actually blocked
 - The Ticket Stage value is set to FRT
 - The ticket's status is set to Pending
- If the user is blocked due to embargo policies...
 - A public reply is sent to the user stating they were blocked due to embargo policies. It also tells them the next steps to resolve that.
 - The Ticket Stage value is set to FRT
 - The ticket's status is set to Solved
- If the user is blocked (but not due to embargo policies)...
 - An issue is made within the T&S account reinstatement project
 - An internal reply made on the ticket pointing the SE to the next steps to follow

Account locked

^{Introduced via [gitlab-com/support/support-ops/zendesk-global/trigger!264](https://gitlab.com/support/support-ops/zendesk-global/trigger!264)}

This checks if an email suppression exists within Mailgun. Depending on the results of the check, different actions can occur:

- If a suppression exists...
 - The located suppressions in Mailgun are deleted
 - An internal reply made on the ticket stating that a suppression was found and removed, including the code, error, and timestamp of said suppression
 - A public reply is sent to the user stating a suppression was found, removed, and what next steps the user should take.
 - The ticket's status is set to Solved
- If a suppression does not exist...
 - A public reply is sent to the user stating we did not locate any suppressions and what next steps they can take. policies. It also tells them the next steps to resolve that.
 - The Ticket Stage value is set to FRT
 - The ticket's status is set to Pending

CMP Creation

^{Introduced via [gitlab-com/support/support-ops/support-ops-project2542](https://gitlab.com/support/support-ops/support-ops-project2542)}

This creates a contact management project for the ticket.

Code Request for Advanced SAST

^{Introduced via [gitlab-com/support/support-team-meta6652](https://gitlab.com/support/support-team-meta6652)}

This helps agents work code request for Advanced SAST.

Email Suppressions

^{Introduced via [gitlab-com/support/support-ops/zendesk-global/trigger!264](https://gitlab.com/support/support-ops/zendesk-global/trigger!264)}

This checks if an email suppression exists within Mailgun. Depending on the results of the check, different actions can occur:

- If a suppression exists...
 - The located suppressions in Mailgun are deleted
 - An internal reply made on the ticket stating that a suppression was found and removed, including the code, error, and timestamp of said suppression
 - A public reply is sent to the user stating a suppression was found, removed, and what next steps the user should take.
 - The ticket's status is set to Solved
- If a suppression does not exist...
 - A public reply is sent to the user stating we did not locate any suppressions and what next steps they can take. policies. It also tells them the next steps to resolve that.
 - The Ticket Stage value is set to FRT

- The ticket's status is set to Pending

Link Tagger

^{Introduced via [gitlab-com/support/support-ops/support-ops-project998](https://gitlab.com/support/support-ops/support-ops-project998)}

This checks the passed comment (public and made by an agent) for the various types of items we would want to tag on the ticket. The current kinds of items (and the tag added based on them) are as follows:

- Contains a gitlab.com issue link
 - gitlabissuelink tag is added
 - CUSTOMPATHissuesIID tag is added
 - CUSTOMPATH is the project's slug, IID is the issue ID
 - Example: a link to issue 5 on project jcolyer/mostamazingprojectever would be: jcolyermostamazingprojecteverissues5
 - issue~CUSTOMPATHIID
 - CUSTOMPATH is the project's slug, IID is the issue ID
 - Example: a link to issue 5 on project jcolyer/mostamazingprojectever would be: issue~jcolyermostamazingprojecteverissues5
 - issuePROJECTIDIID
 - PROJECTID is the project's ID, IID is the issue ID
 - Example: a link to issue 5 on project jcolyer/mostamazingprojectever (project ID 123) would be: issue1235
- Contains a gitlab.com merge request link
 - gitlabmergerequestlink tag is added
 - CUSTOMPATHmergerequestsIID tag is added
 - CUSTOMPATH is the project's slug, IID is the merge request ID
 - Example: a link to merge request 27 on project jcolyer/mostamazingprojectever would be: jcolyermostamazingprojectevermergerequests27
 - mergerequest~CUSTOMPATHIID
 - CUSTOMPATH is the project's slug, IID is the issue ID
 - Example: a link to merge request 27 on project jcolyer/mostamazingprojectever would be: mergerequest~jcolyermostamazingprojecteverissues27
 - mergerequestPROJECTIDIID
 - PROJECTID is the project's ID, IID is the merge request ID
 - Example: a link to merge request 27 on project jcolyer/mostamazingprojectever (project ID 123) would be: mergerequest12327
- Contains a docs.gitlab.com link
 - docslink tag is added
- Contains a handbook.gitlab.com link
 - hbblink tag is added
- Contains a KB article link
 - kblink tag is added
- Contains text that indicates the agent offered a call
 - agentofferedcall tag is added
- Search terms used:
 - calendly.com
 - gitlab.zoom.us
 - gitlabmtgs.webex.com

- teams.microsoft.com

Namesquatting

^{Introduced via gitlab-com/support/support-ops/zendesk-global/trigger!264}

This checks if a given namespace is eligible for release based on our various criteria. The result of the check will determine what actions occur:

- If the requester is a free user...
 - A public reply is sent to the user stating these requests are only eligible for paying customers.
 - The Ticket Stage value is set to FRT
- If the namespace is invalid...
 - A public reply is sent to the user stating we could not locate the namespace in question.
 - The Ticket Stage value is set to FRT
- If the namespace is not eligible...
 - A public reply is sent to the user stating the namespace is not eligible for release at this time.
 - The Ticket Stage value is set to FRT
- If the namespace may be eligible...
 - An internal reply made on the ticket stating that the namespace can only be released after contacting the namespace's current owners. It lists the found email addresses of the owners.
 - The Ticket Stage value is set to FRT
- If the namespace is eligible...
 - An internal reply made on the ticket stating that the namespace is eligible for immediate release.
 - The Ticket Stage value is set to FRT

Organization Notes

^{Introduced via gitlab-com/support/support-ops/zendesk-global/trigger!264}

This adds internal notes on a ticket based off information derived from the organization the requester of the ticket is a member of. This has the potential to make 3 different internal notes:

- One derived from organization notes that can contain...
 - A message about the organization being in an escalated state
 - Partner troubleshooting information
 - General organization information
 - Any recent emergency tickets filed under the organization
 - If the organization has a collaboration project
 - If the organization is using a contact management project
 - Support Operations notes (derived from the Notes/Details fields on the organization itself in Zendesk)
 - Support notes (derived from the Zendesk Global Organizations project)
- One detailing the organization's support entitlement and grace period information
 - Only if the organization is expired or a priority prospect
- One about the organization being GitLab Dedicated

If a Support notes file does not exist, this will also create one for the organization.

STAR

^{Introduced via gitlab-com/support/support-ops/support-ops-project957}

This adds the ticket tag starsubmitted onto the ticket.

Weighting

^{Introduced via gitlab-com/support/support-team-meta5134}

This determines the ticket's "weight" based on specific criteria and adds its value to the ticket.

Zendesk US Government

Source project

Code Request for Advanced SAST

^{Introduced via gitlab-com/support/support-team-meta6652}

This helps agents work code request for Advanced SAST.

Organization Notes

^{Introduced via gitlab-support-readiness/zendesk-us-government/triggers@c573f55c}

This adds internal notes on a ticket based off information derived from the organization the requester of the ticket is a member of. This has the potential to make 3 different internal notes:

- One derived from organization notes that can contain...
 - General organization information
 - Any recent emergency tickets filed under the organization
 - If the organization has a collaboration project
 - Support Operations notes (derived from the Notes/Details fields on the organization itself in Zendesk)
- One detailing the organization's support entitlement and grace period information
 - Only if the organization is expired
- One about the organization being GitLab Dedicated

SECTION: security/customer-support-operations/docs/zendesk/tickets.md

{{% alert title="Note" color="primary" %}}

This is an informational page for the Zendesk tickets. It may not reflect the way we actually

manage Zendesk tickets.

- If you are looking for information about maintaining tickets (settings, statuses, etc.), please see Tickets workflow
- If you are looking for information about working tickets, please see Working Tickets workflow

{{% /alert %}}

Ticket settings

{{% alert title="Note" color="danger" %}}

This should be the single source of truth for the settings used. Never make changes outside of approved workflows.

Always be cautious of changes. Many of these can have significant downstream impacts.

{{% /alert %}}

Zendesk Global

- Comments
 - [x] Turn on emoji text replacement
 - [x] Turn on color text
 - [x] Set composed to public channel by default
 - [x] Agent comments via email are public by default
 - [] Allow first comment on tickets to be private
 - Render URIs are hyperlinks: ["[]"]
 - [] Make email comments from CCed end users public (not recommended)
- Attachments
 - [x] Customers can attach files
 - [x] Enable secure downloads
- Tags
 - [x] Enable tags on tickets
 - [] Enable automatic ticket tagging
- CCs
 - [x] Enable CCs on tickets
 - [] Only agents can add CCs
 - [x] Enable CCs for end users on Help Center
 - CC blacklist: noreply@google.com
 - CC email subject: [{{ticket.account}}] Update: {{ticket.title}}
 - CC email text:

plaintext

You are registered as a CC on this support request ({{ticket.link}}). Reply to this email to add a comment to the request.

{{ticket.commentsformatted}}

- Assignment
 - ☒ Auto-assign tickets upon solve
 - ☒ Allow re-assignment back to the general group
- Follow-Ups
 - ☐ Copy original assignee and group to follow-up ticket
- Suspended Ticket Notifications
 - Never How often you want to receive email about new suspended tickets.
 - Email list:
- Ticket IDs
 - Set the ticket ID counter
 - This value is going to change based on ticket volume. Do not touch it
- Modify closed ticket
 - ☐ Turn on
- Email Archiving
 - Archive email address:
- Transcript visibility
 - How conversation transcript is incrementally appended to the ticket: As public reply
- Continuous conversations
 - ☐ Switch messaging conversations to email
- Translations
 - ☒ Agents can translate conversations
- Solved Ticket Reassignment
 - ☐ Turn on solved ticket reassignment
 - ☐ Show solved ticket reassignment
 - Set an account level default for solved ticket reassignment option for newly created groups: To an admin or longest active team member
 - ☐ Force all theh groups to assume the account level default now
- Agent collaboration for messaging
 - ☒ Multiple agents can collaborate in messaging conversations

Zendesk US Government

- Comments
 - ☒ Turn on emoji text replacement
 - ☒ Turn on color text
 - ☒ Set composed to public channel by default
 - ☒ Agent comments via email are public by default
 - ☐ Allow first comment on tickets to be private
 - Render URIs are hyperlinks: ☐
 - ☐ Make email comments from CCed end users public (not recommended)
- Attachments
 - ☒ Customers can attach files
 - ☒ Enable secure downloads
- Tags
 - ☒ Enable tags on tickets
 - ☐ Enable automatic ticket tagging
- CCs
 - ☒ Enable followers

- Follower email subject: {{ticket.title}}
- Follower email template:

plaintext

You are a follower on this request ({{ticket.link}}). {{ticket.followerreplytypemessage}}

{{ticket.commentsformatted}}

- ☐ Enable CCs
- ☐ Automatically make an agent CC a follower
- Requester
 - ☐ Agents can change requester
- Assignment
 - ☒ Auto-assign tickets upon solve
 - ☒ Allow re-assignment back to the general group
- Follow-Ups
 - ☐ Copy original assignee and group to follow-up ticket
- Suspended Ticket Notifications
 - Never How often you want to receive email about new suspended tickets.
 - Email list:
- Ticket IDs
 - Set the ticket ID counter
 - This value is going to change based on ticket volume. Do not touch it
- Modify closed ticket
 - ☐ Turn on
- Email Archiving
 - Archive email address:
- Transcript visibility
 - How conversation transcript is incrementally appended to the ticket: As public reply
- Continuous conversations
 - ☐ Switch messaging conversations to email
- Translations
 - ☒ Agents can translate conversations
- Solved Ticket Reassignment
 - ☐ Turn on solved ticket reassignment
 - ☐ Show solved ticket reassignment
 - Set an account level default for solved ticket reassignment option for newly created groups: To an admin or longest active team member
 - ☐ Force all theh groups to assume the account level default now
- Agent collaboration for messaging
 - ☒ Multiple agents can collaborate in messaging conversations

Ticket sharing

{{% alert title="Note" color="danger" %}}

This should be the single source of truth for the sharing used. Never make changes outside of approved workflows.

Always be cautious of changes. Many of these can have significant downstream impacts.

{{% /alert %}}

Zendesk Global

- Sending agreements: 0
- Receiving agreements
 - Pivotal @ Zendesk Public comments allowed. Sync status and share tags Accepted
- Opt out of sharing
 - [] Decline all sharing agreement invites

Zendesk US Government

- Sending agreements: 0
- Receiving agreements: 0
- Opt out of sharing
 - [] Decline all sharing agreement invites

Statuses

As per Zendesk the various status are defined as:

- New
 - This indicates that no action has been taken on the ticket. Once a New ticket's status has been changed, it can never be set back to New.
- Open
 - This indicates that the ticket is waiting for action by the agent.
- Pending
 - This indicates that the agent is waiting for more information from the requester. When the requester responds and a new comment is added, the ticket status is automatically reset to Open.
- On-hold
 - This indicates that the agent is waiting for information or action from someone other than the requester. It is similar to the Pending status in that you as an agent can't proceed with resolving the ticket until you receive more information from someone else. However, the On-hold is an internal status that the ticket requester never sees. While a ticket is set to On-hold, the requester sees the status as Open.
- Solved
 - This indicates that the agent has submitted a solution or the end-user has marked it as such. A solved ticket can still be edited or re-opened.
- Closed
 - This indicates that the ticket is in a state where it can no longer receive updates. Replying to a closed ticket opens a follow-up ticket, which contains all previous tags and links to the previous ticket.

At GitLab, we define them a bit differently:

- New
 - This is a new ticket. This means it has not yet been worked by GitLab.

- Open
 - This means the ticket is awaiting our reply.
- Pending
 - This means we are waiting on the end-user to reply. We should only use this specifically when the user will reply back to the ticket (or it will auto-solve). If you need to keep a ticket in a "pending" like state for lengthy periods of time, use On-hold.
- On-hold
 - This means the end-user is waiting on us, but we are waiting on something that is blocking us from replying. We should only be using this in situations where we are waiting on something such as a different department, time to pass (namesquatting requests as an example), or some other criteria that fits along the same concept.
- Solved
 - This means the ticket has been resolved, but the end-user might come back to us.
- Closed
 - We use them exactly as Zendesk defines them.

SECTION: security/customer-support-operations/docs/zendesk/triggers.md

{{% alert title="Note" color="primary" %}}

This is an informational page for the Zendesk triggers. It may not reflect the way we actually manage Zendesk triggers.

If you are looking for information about maintaining triggers (creating, editing, etc.), please see Triggers workflow

{{% /alert %}}

What are Zendesk triggers?

As per Zendesk:

> Triggers are business rules you define that run immediately after tickets are created or updated. For example, a trigger can be used to notify the customer when a ticket has been opened. Another can be created to then notify the customer when the ticket is solved.

Trigger categories

As per Zendesk:

> Ticket trigger categories allow you to visually group ticket triggers for easier organization and management.

Creating a trigger category

For information on creating a trigger category, please see Zendesk documentation.

Editing a trigger category

For information on editing a trigger category, please see Zendesk documentation.

Reordering trigger categories

For information on reordering trigger categories, please see Zendesk documentation.

Deleting a trigger category

{{% alert title="Note" color="warning" %}}

You can only delete a trigger category if all triggers within it are deactivated.

{{% /alert %}}

For information on deleting a trigger category, please see Zendesk documentation.

Creating a trigger

For information on creating a trigger, please see Zendesk documentation.

Cloning a trigger

For information on cloning a trigger, please see Zendesk documentation.

Editing a trigger

For information on editing a trigger, please see Zendesk documentation.

Reordering triggers

For information on reordering triggers, please see Zendesk documentation.

Deactivating a trigger

For information on deactivating a trigger, please see Zendesk documentation.

Deleting a trigger

{{% alert title="Note" color="warning" %}}

You can only delete a trigger if it is deactivated.

{{% /alert %}}

For information on deleting a trigger, please see Zendesk documentation.

SECTION: security/customer-support-operations/docs/zendesk/user-fields.md

{{% alert title="Note" color="primary" %}}

This is an informational page for the Zendesk user fields. It may not reflect the way we actually manage Zendesk user fields.

If you are looking for information about maintaining user fields (creating, editing, etc.), please see [User fields workflow](#)

{{% /alert %}}

Creating user fields

For information on creating a user field, please see [Zendesk documentation](#).

Cloning user fields

For information on cloning a user field, please see [Zendesk documentation](#).

Editing user fields

For information on editing a user