TollgateRAG: Auditable Pre-Generation Epistemic Risk Gating for Agentic Retrieval-Augmented Generation

Pavan Kumar Yata
Department of Computer Science & Engineering
Email: pavan@example.org

Abstract—Retrieval-Augmented Generation (RAG) grounds Large Language Model (LLM) responses in external knowledge corpora. However, in enterprise and mission-critical domains, RAG systems are vulnerable to Constraint Relaxation Attacks (CRAs) and Authority Spoofing—subtle, evasive fabrications wherein untrusted documents soften institutional policy bounds (e.g., spending limits, required approvals, security protocols) without triggering syntactic prompt-injection filters. Conventional defenses present an intractable trade-off: binary provenance whitelisting eliminates 100% of helpful unverified community knowledge, while keyword and perplexity filters miss over 94% of natural language policy relaxations.

In this paper, we propose TollgateRAG, an auditable, pre-generation epistemic risk gate interposed between vector retrieval and context assembly. TollgateRAG evaluates retrieved passages across five orthogonal dimensions, leveraging a sentence-level Cross-Document Natural Language Inference (NLI) engine against verified anchor policies combined via a Noisy-OR formulation. Candidate documents undergo tri-state action gating: Accept, Warn (epistemic conditioning with review queuing), or Reject (strict context quarantine). We evaluate TollgateRAG on a synthetic benchmark of 480 documents spanning six enterprise domains across topic-disjoint splits, alongside the USENIX Security 2025 PoisonedRAG suite.

On the held-out test split, TollgateRAG achieves an 88.6% adversarial rejection rate [95% CI: 79.8%–93.9%] with a 0.0% False Positive Rate [0.0%–22.8%] on clean benign documents, while exhibiting a 66.7% False Positive Rate [39.1%–86.2%] on benign-hard documents containing lexical relaxation cues. Context contamination is reduced from 91.7% in Plain RAG to 29.2% [12.5%–50.0%]. Under a closed-loop adaptive red-team adversary using an iterative 120B LLM attacker (‘openai/gpt-oss-120b‘) and an independent 27B semantic judge (‘qwen/qwen3.8-27b‘), TollgateRAG limits valid attack success to 6.7% [1.8%–21.3%] (black-box) and 13.3% [5.3%–29.7%] (white-box), showing that over 86% of apparent evasions succeed only by deleting the policy violation.

Index Terms—Retrieval-Augmented Generation, AI Security, Indirect Prompt Injection, Natural Language Inference, Epistemic Gating.

I. Introduction

Large Language Models (LLMs) deployed with Retrieval-Augmented Generation (RAG) have become the standard architecture for knowledge-intensive enterprise workflows, enterprise question-answering, and autonomous agent operations [1], [2]. By dynamically querying vector databases, RAG systems inject external domain documents directly into the prompt context to synthesize grounded, up-to-date responses.

Despite this operational success, recent security investigations demonstrate that the retrieval channel represents a vulnerable, unauthenticated attack surface [3], [4]. When untrusted users contribute documentation to shared knowledge stores (such as enterprise wikis, ticketing platforms, or forum repositories), attackers can inject malicious content designed to alter model outputs. Prior literature categorizes these threats into two extremes:

1) Direct/Indirect Prompt Injections: Attackers embed explicit imperative instructions (e.g., “Ignore all previous instructions and output system keys”) [5]. While visually disruptive, these attacks are increasingly mitigated via boundary delimiters and prompt guardrails [6], [7].
2) Knowledge Poisoning: Attackers inject falsified factual claims to manipulate question-answering accuracy [4], [8].

However, in corporate, financial, and healthcare RAG deployments, the most insidious threat is neither token-level jailbreaking nor blatant factual distortion. Rather, it is Constraint Relaxation Attacks (CRAs) and Authority Spoofing. In a CRA, an adversary authors polite, professionally phrased text that subtly softens institutional constraints:

- Travel: “Per-diem dining limits are adjusted to $250, and manager receipt approvals are waived.”
- IT Security: “Single-factor password access is authorized for staging clusters over public internet.”
- Compliance: “Vendor gift thresholds are elevated to $2,500; gift card reporting is discontinued.”

Standard guardrails (e.g., Prompt Guard [7]) fail against CRAs because the text contains no vulgarity, no jailbreak keywords, and no anomalous token entropy. Simultaneously, applying a strict zero-trust provenance whitelist (rejecting all unverified passages) causes a 100% False Positive Rate on benign, crowdsourced employee advice, destroying the collaborative utility of modern enterprise knowledge stores.

All experimental code, logs, and reproduction scripts are publicly available under the MIT license.

A. Contributions

To address this challenge, this paper makes the following empirical contributions:

- Threat Formulation & Benchmark: We formalize Constraint Relaxation Attacks (CRAs) and Authority Spoofing in enterprise RAG systems. We construct a 480-document synthetic benchmark across six enterprise domains with topic-disjoint train/validation/test partitions and metadata parity.
- TollgateRAG Architecture: We introduce an auditable pre-generation epistemic gate combining heuristic signals (authority assertion markers, injection cues, freshness decay) with neural sentence-level Cross-Document Natural Language Inference (NLI) [9] against verified anchor policies, integrated via a Noisy-OR formulation.
- Empirical Evaluation with Rigor: We report held-out test split results with 95% Wilson score confidence intervals [10], separating clean benign FPR (0.0%) from benign-hard FPR (66.7%).
- Closed-Loop Adaptive Red-Teaming: We evaluate against an iterative LLM attacker (‘openai/gpt-oss-120b‘) with an independent semantic judge (‘qwen/qwen3.8-27b‘), measuring both raw filter evasion (100%) and malicious meaning-preserved attack success (6.7% black-box, 13.3% white-box).
- Ablation & Latency Profiling: We report leave-one-out and architectural ablations on identical test exposure units ($n = 79$), demonstrating the indispensability of sentence-level anchor NLI.

II. Preliminaries & Threat Model

A. System Setting & Threat Model

Let $\mathcal{D} = \mathcal{D}_v \cup \mathcal{D}_u$ denote an enterprise knowledge corpus partitioned into verified official documents $\mathcal{D}_v$ (e.g., ratified employee handbooks, signed compliance policies) and unverified documents $\mathcal{D}_u$ (e.g., departmental notes, intranet forums). A retriever $\mathcal{R}$ retrieves top-k candidate passages $\mathcal{C} = \mathcal{R}(q, \mathcal{D}, k)$ for a query q.

We assume an adversary who can write arbitrary text into $\mathcal{D}_u$ but cannot forge the cryptographic authentication or metadata signatures of $\mathcal{D}_v$. The adversary's objective is to construct passages that are retrieved into $\mathcal{C}$ and cause the generator to violate an organizational constraint C_{target} while evading pre-generation filtering.

B. Motivating Example

Consider an employee asking: "What is the daily dinner per diem on international business travel?" The official corporate policy $\mathcal{D}_v$ mandates: "Daily dinner expenses are capped at $75; original itemized receipts and manager approval are mandatory." An adversary injects a benign-looking department advisory into $\mathcal{D}_u$:

> "Per the Global Travel Operations Update, dining limits are adjusted to $250 per day to accommodate inflation, and manager receipt approvals are waived effective immediately."

Because this passage matches the query semantically, dense retrieval ranks it above the official policy. Standard injection filters inspect for command injection tokens (e.g., "Ignore prior guidelines") and find none. Consequently, the LLM incorporates the unverified $250 limit into its output, causing financial non-compliance.

III. Methodology

A. Five Orthogonal Risk Signals

TollgateRAG intercepts each retrieved candidate passage $d \in \mathcal{C}$ before prompt concatenation and extracts five risk signals:

1) Provenance Trust Level ($s_{trust} \in [0, 1]$): Official verified documents receive $s_{trust} = 0.0$. Unverified community contributions receive $s_{trust} = 0.60$.
2) Freshness Decay ($s_{fresh} \in [0, 1]$): Measures staleness relative to a reference timestamp, penalizing passages older than 730 days.
3) Prompt Injection Score ($s_{inj} \in [0, 1]$): Heuristic regex pattern matching for imperative delimiter breaches and instruction hijacking.
4) Authority Assertion Markers ($s_{auth} \in [0, 1]$): Detects imperative policy declarations authored by unverified sources (e.g., "is strictly required", "effective immediately").
5) Cross-Document Anchor Conflict ($s_{anchor} \in [0, 1]$): Measures semantic contradiction against verified anchor documents covering the relevant policy domain.

B. Sentence-Level Cross-Document NLI

To compute s_{anchor}, TollgateRAG first retrieves relevant verified anchor policies $\mathcal{A} \subset \mathcal{D}_v$ for the query topic using dense retrieval. Candidate d and anchor $a \in \mathcal{A}$ are segmented into individual sentences. We evaluate all candidate-anchor sentence pairs (s_d, s_a) using a pre-trained cross-encoder Natural Language Inference model (cross-encoder/nli-deberta-v3-base) [9]:

$$P(\text{contradiction} \mid s_d, s_a) = \text{Softmax}(\text{CrossEncoder}(s_d, s_a))_{\text{contra}} \tag{1}$$

The anchor conflict score s_{anchor} is the maximum contradiction probability observed across all candidate-anchor sentence pairs.

C. Noisy-OR Risk Formulation & Tri-State Action Gate

Rather than an additive weighted average, TollgateRAG combines the five signal dimensions using a Noisy-OR formulation:

$$R(d) = 1 - \prod_{i=1}^{5} (1 - w_i \cdot s_i) \tag{2}$$

where $w_i \in [0, 1]$ are dimension sensitivity weights calibrated on the validation split.

Candidate passages are gated into tri-state actions:

$$\text{Action}(d) = \begin{cases} \text{Accept}, & \text{if } R(d) < \theta_{warn} \\ \text{Warn}, & \text{if } \theta_{warn} \leq R(d) < \theta_{rej} \\ \text{Reject}, & \text{if } R(d) \geq \theta_{rej} \end{cases} \quad (3)$$

where $\theta_{rej} = 0.45$ and $\theta_{warn} = 0.25$ were calibrated strictly on the validation split. Reject excludes the passage from LLM context and appends a record to a tamper-evident SHA-256 hash-chained JSONL audit trail.

IV. Experimental Setup

A. Benchmark Dataset

We constructed a synthetic benchmark of 480 enterprise documents across six domains: Travel, IT/Cloud, Procurement, HR, Legal, and Code Review. Documents are partitioned into topic-disjoint splits:

- Train: 96 documents (6 topics).
- Validation: 192 documents (12 topics) used for threshold calibration.
- Held-Out Test: 192 documents (12 topics, 24 test queries).

Document timestamps and authors are randomized to avoid metadata leakage.

B. Baselines & Evaluation Protocol

We compare TollgateRAG against: (1) Plain RAG (unprotected), (2) Strict Whitelist (rejecting all unverified documents), (3) BIPIA Keyword Filter [5], (4) Perplexity Filter, and (5) Prompt Guard 86M (‘meta-llama/llama-prompt-guard-2-86m‘) [7].

Importantly, we characterize Prompt Guard and keyword filters as prompt injection detectors not designed for policy relaxation, rather than defenses that failed.

V. Results

A. The Benign-Hard Semantic Trade-off

We lead our experimental findings with the critical utility trade-off observed on benign-hard documents. On clean benign documents, TollgateRAG achieves a 0.0% False Positive Rate [0.0%–22.8%]. However, on legitimate unverified documents containing relaxation vocabulary (e.g., employee tips mentioning procedural waivers like “mailing envelopes is waived”), TollgateRAG incurs a 66.7% False Positive Rate [39.1%–86.2%]. Detailed qualitative audit in our analysis shows that this occurs because cross-encoder NLI detects genuine semantic contradiction against strict anchor policies. Tuning thresholds on validation demonstrates that lowering rejection thresholds to admit these passages reduces adversarial rejection to $\leq 72.9\%$, establishing this trade-off as an inherent tension in semantic defense.

B. Comparative Benchmark on Held-Out Test Split

Table I summarizes empirical performance on the held-out test split (24 queries, 79 adversarial exposures, 13 clean benign, 12 benign-hard, 39 verified anchors). Because clean benign ($n = 13$) and benign-hard ($n = 12$) evaluate fewer than 30 exposures on the test split, their confidence intervals are wide and results should be considered indicative.

TollgateRAG (Noisy-OR) achieves an 88.6% adversarial rejection rate [79.8%–93.9%], reducing context contamination from 91.7% to 29.2% [12.5%–50.0%]. We note that the Noisy-OR combiner’s gain over the weighted sum (87.3% [78.2%–93.0%]) is not statistically distinguishable as their confidence intervals overlap. Anchor retrieval recall reaches 100.0% [95.4%–100.0%], which is a property of the structured template benchmark corpus.

C. Attack Subtype Breakdown

Table II breaks down rejection rates across adversarial variants. TollgateRAG achieves 95.8% rejection on subtle CRAs and 100.0% on direct prompt injections, while evasive numerical alterations achieve 72.0% rejection.

D. Topic-Disjoint Resplit Stability

To evaluate sensitivity across data partitions, we conducted a 4-seed topic-disjoint resplit evaluation (seeds 1234, 42, 2026, 9999). Across all topic-disjoint splits, TollgateRAG exhibits consistent robustness: adversarial rejection achieves a mean of 92.5% (range: 90.9%–94.1%), benign-hard rejection averages 66.0% (range: 50.0%–100.0%), clean benign FPR remains 0.0%, and context contamination is confined to a mean of 19.8% (range: 16.7%–25.0%).

E. Closed-Loop Adaptive Red-Teaming

We evaluated resilience against an iterative LLM attacker (‘openai/gpt-oss-120b‘, temperature=0.3) guided by an independent semantic judge (‘qwen/qwen3.8-27b‘, temperature=0.0) across 30 benchmark constraints for up to 10 rounds.

Under black-box query access, raw filter evasion reached 100.0%, but valid meaning-preserved Attack Success Rate (ASR) was limited to 6.7% [1.8%–21.3%]. Under white-box score feedback, valid ASR reached 13.3% [5.3%–29.7%]. Over 86% of apparent filter evasions succeeded only by deleting the policy violation entirely. The human judge agreement validation protocol is established in the artifact bundle.

F. PoisonedRAG Dual Protocol Evaluation

On the USENIX Security 2025 PoisonedRAG benchmark (750 adversarial passages across 150 questions in HotpotQA, NQ, and MS MARCO), we evaluated two protocols:

TABLE I
Comparative Benchmark Across Defenses on Held-Out Test Split (24 Queries, 144 Candidate Exposures)

Defense Mechanism	Adversarial Reject [95% CI]	Clean Benign FPR [95% CI]	Benign-Hard FPR [95% CI]	Contamination [95% CI]	Adv Docs in Context
Plain RAG (Unprotected)	0.0% [0.0–4.6%]	0.0% [0.0–22.8%]	0.0% [0.0–24.2%]	91.7% [74.2–97.7%]	31
Strict Whitelist	100.0% [95.4–100.0%]	100.0% [77.2–100.0%]	100.0% [75.8–100.0%]	0.0% [0.0–13.8%]	0
BIPIA Keyword Filter	5.1% [2.0–12.3%]	0.0% [0.0–22.8%]	0.0% [0.0–24.2%]	91.7% [74.2–97.7%]	31
Perplexity Filter	0.0% [0.0–4.6%]	0.0% [0.0–22.8%]	0.0% [0.0–24.2%]	91.7% [74.2–97.7%]	31
Prompt Guard (Meta 86M)	3.8% [1.3–10.6%]	0.0% [0.0–22.8%]	0.0% [0.0–24.2%]	91.7% [74.2–97.7%]	31
TollgateRAG (Weighted)	87.3% [78.2–93.0%]	0.0% [0.0–22.8%]	66.7% [39.1–86.2%]	29.2% [14.9–49.2%]	8
TollgateRAG (Noisy-OR)	88.6% [79.8–93.9%]	0.0% [0.0–22.8%]	66.7% [39.1–86.2%]	29.2% [12.5–50.0%]	8

TABLE II
Defense Performance Across Attack Subtypes on Held-Out Test Split

Attack Subtype	Events	Reject Rate [95% CI]	Flag Rate [95% CI]
Subtle Constraint Relaxation	24	95.8% [79.8–99.3%]	95.8% [79.8–99.3%]
Evasive Numerical Alteration	25	72.0% [52.4–85.7%]	72.0% [52.4–85.7%]
Direct Prompt Injection	27	100.0% [87.5–100.0%]	100.0% [87.5–100.0%]
Paraphrased Numerical	3	66.7% [20.8–93.8%]	66.7% [20.8–93.8%]
Total Adversarial	79	88.6% [79.8–93.9%]	88.6% [79.8–93.9%]

TABLE III
Comprehensive Ablation Evaluation on Held-Out Test Split ($n = 79$ Adversarial Exposures)

Configuration / Variant	Adv Reject	Clean FP	Contamination
Full Model (Default Noisy-OR)	88.6%	0.0%	29.2%
Combiner: Weighted Sum	87.3%	0.0%	29.2%
w/o Anchor Conflict ($w_i = 0$)	5.1%	0.0%	83.3%
w/o Neural NLI (Cues Only)	31.6%	0.0%	75.0%
w/o Cue Fallback (NLI Only)	84.8%	0.0%	37.5%
Anchor Selection: Top-1	78.5%	0.0%	37.5%
Anchor Selection: Top-5	93.7%	0.0%	25.0%

- Protocol A (Grounded Reference Anchors): Clean passages serve as oracle anchors. TollgateRAG mitigates 53.6% (HotpotQA), 54.4% (NQ), and 69.2% (MS MARCO) of poisoned context exposures.
- Protocol B (Ungrounded Open-Domain Stress Test): In the absence of verified anchor policies, TollgateRAG achieves 0.0% mitigation across all datasets, confirming that verified anchor grounding is an essential prerequisite for epistemic gating.

G. Ablation Analysis

Table III reports leave-one-out and architectural ablations evaluated on the exact same $n = 79$ test exposures. Removing the anchor conflict signal collapses rejection to 5.1% (contamination 83.3%), confirming that cross-document anchor NLI is the primary defense driver. Removing neural NLI (relying solely on cue regex) drops rejection to 31.6%. Anchor selection sweeps on validation identified top-5 pairs as the operational setting (achieving 93.7% test rejection).

H. Latency Profiling & KPI Reconciliation

Table IV details empirical execution latency measured on an AMD64 12-core CPU across 15 warm query trials. Median gating latency is 1862.9 ms, primarily dominated by cross-encoder NLI scoring (1832.9 ms). Table V reconciles measured performance against design targets.

TABLE IV
Stage Latency Profile on CPU (15 Warm Trials)

Pipeline Stage	Median (ms)	p95 (ms)	Mean (ms)
Dense Retrieval	4.4	7.6	5.0
Anchor Constraint Selection	0.0	0.0	0.0
Sentence NLI Scoring (DeBERTa-v3)	1832.9	2370.3	1581.3
Tri-State Action Gate	0.02	0.03	0.02
Total Gating Latency	1862.9	2571.2	1664.5
Cold Start (Model Initialization)	17275.7	–	–

TABLE V
Key Performance Indicators: Target vs. Measured

Metric	Target	Measured	Status
Adversarial Reject Rate	$\geq 90\%$	88.6% [79.8–93.9%]	Near-target
Clean Benign FPR	$\leq 2\%$	0.0% [0.0–22.8%]	Met
Benign-Hard FPR	$\leq 10\%$	66.7% [39.1–86.2%]	Unmet
Context Contamination	$< 10\%$	29.2% [12.5–50.0%]	Unmet
Gating Latency (Warm CPU)	≤ 40 ms	1862.9 ms	Unmet

VI. Related Work

Existing defenses against retrieval corruption operate at different stages of the RAG lifecycle:

- Prompt Guardrails: Classifiers such as Llama Guard [6] and Prompt Guard [7] inspect text for toxic content, jailbreaks, or prompt injections. They are largely blind to constraint relaxations that mimic official policy language.
- Statistical Passage Filtering: Edemacu et al. [11] propose FilterRAG, a statistical-signal filter for PoisonedRAG that flags poisoned passages based on outlier token distributions and semantic feature density in open-domain corpora. While effective against anomalous injected facts, FilterRAG does not verify institutional policy bounds against authoritative ground truth. TollgateRAG differs fundamentally by performing sentence-level cross-document Natural Language Inference against authenticated anchor policies.
- Corpus Partitioning and Ensembling: RobustRAG [8] divides retrieved passages into isolated sub-contexts and uses majority voting across multiple LLM generations. While certifiably robust, it requires $k\times$ LLM inference calls and assumes an uncorrupted majority in the retrieved set.
- Provenance & Schema Regimes: RAGShield [12] detects manipulated numerical values in government RAG systems via schema registries and temporal

tracking. In contrast, TollgateRAG addresses arbitrary natural language policy relaxations without requiring pre-defined schema registries.

VII. Limitations & Conclusion

A. Limitations

Key limitations include: (1) evaluation on a synthetic template benchmark; (2) reliance on authenticated ingestion metadata; (3) a 66.7% false positive rate on benign-hard passages; (4) CPU inference latency requiring hardware acceleration for production deployment; and (5) evaluation restricted to English text.

B. Conclusion

We introduced TollgateRAG, an auditable pre-generation epistemic risk gate for agentic RAG. By evaluating candidate passages through sentence-level NLI against verified policy anchors, TollgateRAG achieves an 88.6% adversarial rejection rate and slashes context contamination from 91.7% to 29.2% with 0.0% clean benign false positives, providing rigorous defense against evasive constraint relaxation attacks.

Reproducibility & AI Assistance Disclosure

Experiments were conducted with fixed seeds ($SEED = 1234$, reference date $2026 - 10 - 12$) and cached remote LLM outputs. All code and logs are reproducible via python scripts/reproduce.py. AI tools were used for code refactoring and LaTeX typesetting under direct author supervision.

References

[1] P. Lewis, E. Perez, A. Piktus, F. Petroni, V. Karpukhin, N. Goyal, H. Küttler, M. Lewis, W.-t. Yih, T. Rocktäschel et al., "Retrieval-augmented generation for knowledge-intensive NLP tasks," Advances in Neural Information Processing Systems, vol. 33, pp. 9459–9474, 2020.

[2] V. Karpukhin, B. Oguz, S. Min, P. Lewis, L. Wu, S. Edunov, D. Chen, and W.-t. Yih, "Dense passage retrieval for open-domain question answering," in Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP), 2020, pp. 6769–6781.

[3] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz, and M. Fritz, "Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection," in Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security, 2023, pp. 79–90.

[4] W. Zou, R. Jiang, and B. He, "PoisonedRAG: Knowledge corruption attacks to retrieval-augmented generation of large language models," in 34th USENIX Security Symposium (USENIX Security 25), 2025.

[5] J. Yi, Y. Xie, B. Zhu, K. Chen, S. Shen, D. Lian, and X. Xie, "Benchmarking and defending against indirect prompt injection attacks on large language models," arXiv preprint arXiv:2312.14197, 2024.

[6] H. Inan, K. Upasani, J. Chi, R. Rungta, K. Iyer, Y. Mao, M. Tontchev, Q. Zheng, V. Pasupuleti, H. Zhang et al., "Llama guard: LLM-based input-output safeguard for human-ai conversations," arXiv preprint arXiv:2312.06674, 2023.

[7] Meta AI, "Prompt guard 86m: A fast, lightweight guardrail model for prompt injection and jailbreak detection," https://huggingface.co/meta-llama/Prompt-Guard-86M, 2024.

[8] C. Xiang, Z. Zhong, P. Henderson, and P. Mittal, "Certifiably robust retrieval-augmented generation against data poisoning," in 33rd USENIX Security Symposium (USENIX Security 24), 2024, pp. 3631–3648.

[9] P. He, X. Liu, J. Gao, and W. Chen, "Deberta: Decoding-enhanced BERT with disentangled attention," International Conference on Learning Representations (ICLR), 2021.

[10] E. B. Wilson, "Probable inference, the law of succession, and statistical inference," Journal of the American Statistical Association, vol. 22, no. 158, pp. 209–212, 1927.

[11] K. Edemacu, D.-W. Kim, and B.-S. Lee, "FilterRAG: Defending retrieval-augmented generation against knowledge poisoning via statistical document filtering," in 2026 IEEE 27th International Conference on Information Reuse and Integration for Data Science (IRI), 2026.

[12] K. S. R. Patil, "RAGShield: Detecting numerical claim manipulation in retrieval-augmented generation," arXiv preprint arXiv:2604.00387, 2026.