Gentle clues for typst

Add some beautiful, predefined admonitions or define your own.



Usage

1. Import the package like this:

```
#import "@preview/gentle-clues:0.7.0": *
```

2. Change the default settings for a clue.

```
#show: gentle-clues.with(
  headless: false, // never show any headers
  breakable: false, // default breaking behavior
  header-inset: 0.5em, // default header-inset
  content-inset: lem, // default content-inset
  stroke-width: 2pt, // default left stroke-width
  border-radius: 2pt, // default border-radius
  border-width: 0.5pt, // default boarder-width
)
```

3. Use a predefined clue without any options

```
#info[You will find a list with all
predefined clues at the last page.]
```

Turns into this \rightarrow

rums into tins

4. Or add some options like a custom title

```
#example(title: "Custom title")
[ Content ...]
```

Turns into this \rightarrow

Info

You will find a list with all predefined clues at the last page.



Content ...

New in v0.7.0

- language is detected by #set text(lang: "de"). lang argument is now deprecated.
- Breaking: _color changed to accent-color and can only be of type color or gradient.
- Use border-color and header-color to overwrite calculated header and border colors.

All Options for a clue

All default settings can also be applied to a single clue through passing it as an named argument. Here is a list of accepted arguments:

```
title: auto, // [string] or [none] (none will print headless)
icon: emoji.magnify.l, // [file] or [symbol]
accent-color: navy, // left accent color [color] or [gradient]
width: auto, // total width [length]
radius: auto, // radius of the right border [length]
border-width: auto, // width of the right and down border [length]
content-inset: auto, // [length]
header-inset: auto, // [length]
breakable: auto, // if clue can break onto next page [bool]
```

Breaking news

Clues can now break onto the next page with option: breakable: true

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor

incididunt ut labore et dolore magnam aliquam quaerat voluptatem. Ut enim aeque doleamus animo, cum corpore dolemus, fieri.

This is a two columns layout.

Define your own clue

```
// Define a clue called ghost
#let ghost(title: "Buuuuuh", icon: emoji.ghost , ..args) = clue(
   accent-color: purple, // Define a base color
   title: title, // Define the default title
   icon: icon, // Define the default icon
   ..args // Pass along all other arguments
)
// Use it
#ghost[Huuuuuuh.]
```

The result looks like this.

Buuuuuuh.

Huuuuuuh.




Use the svg-emoji package until emoji support is fully supported in typst

Header title language

The current language which is set by #set text(lang: "de") changes header title to german. Currently supported are en, de, fr and es. This package uses linguify for language settings so you can load your own language data file or feel free to contribute more languages.

List of all predefined clues

#abstract



Make it short. This is all you need.

#question

? Question

How do amonishments work?

#info

i Info

It's as easy as

#info[Whatever you want to say]

#example,

Example

Testing ...

#task

₹ Task

Check out this wonderfull typst package!

#error

× Error

Something did not work here.

#warning

Warning

Still a work in progress.

#success

Success

All tests passed. It's worth a try.

#tip

Tip

Try it yourself

#conclusion

Conclusion

This package makes it easy to add some beatufillness to your documents

#memo

Memorize

Leave a \star on github.

#quote

99 Quote

Keep it simple. Admonish your life.

Headless Variant

just add title: none to any example

Just a short information.