

# Practical Exercise – Fundamental Concepts of Android Development

## Activity Lifecycle, Intents, Layouts, and Views

**Course:** Mobile Application Development (Chapter 5)

**Level:** Technical University Students

**Duration:** 6–8 hours self-study + 1–2 hours online discussion

**Format:** Individual Assignment with Code Examples (2–3 pages)

---

## Exercise Overview

In this exercise, you will work with core Android components: **Activity lifecycle**, **Intents** (explicit and implicit), **Layout resources**, and **Views**. These fundamentals form the foundation of all Android applications.

### Key Learning Outcomes:

- Understand the complete Activity lifecycle and when to implement each callback
  - Distinguish between explicit and implicit Intents and their use cases
  - Design responsive layouts using ConstraintLayout and other ViewGroups
  - Handle user interactions with Views and event listeners
  - Manage state and data persistence across Activity transitions
- 

## Part A: Activity Lifecycle Mastery

### Task 1: Activity Lifecycle Mapping (Self-Study: 1.5–2 hours)

**Objective:** Master the Activity lifecycle states and implement appropriate logic in each callback.

### Instructions:

1. **Draw the complete Activity lifecycle** showing all states and transitions:

- onCreate() → onStart() → onResume() → onPause() → onStop() → onDestroy()
- Include transitions for: user navigation away, system memory pressure, configuration changes
- Mark which callbacks are guaranteed vs. optional

2. **Identify three critical moments** where you must add code:

Lifecycle Method	Why Important	Typical Operations
<b>onCreate()</b>	First initialization after process creation	Initialize UI, load data, set up listeners
<b>onResume()</b>	App returns to foreground	Refresh data, resume animations, re-enable sensors
<b>onPause() / onStop()</b>	App losing focus or becoming invisible	Save user data, pause animations, release sensors

3. **Write pseudo-code for each critical moment:**

```
// onCreate() - Initialize
override fun onCreate(savedInstanceState: Bundle?) {
    super.onCreate(savedInstanceState)
    setContentView(R.layout.activity_main)
    loadUserPreferences()
    initializeUI()
}
```

```
// onResume() - Prepare for interaction
override fun onResume() {
    super.onResume()
    refreshData()
    startLocationUpdates()
}
```

```
// onPause() - Save state before leaving
override fun onPause() {
    super.onPause()
    saveUserInputToPreferences()
    stopLocationUpdates()
}
```

4. **Answer in 3-4 sentences:**

- When is savedInstanceState used and why is it important?
- What's the difference between onStop() and onDestroy()?

**Deliverable:**

- Lifecycle diagram with all states and transitions

- Three pseudo-code implementations with brief explanations
  - 3–4 sentence reflection on savedInstanceState and lifecycle guarantees
- 

## Part B: Understanding Intents

### Task 2: Explicit vs. Implicit Intents (Self-Study: 1.5–2 hours)

**Objective:** Distinguish between Intents and write them for common scenarios.

**Instructions:**

1. **Define the two Intent types:**

Type	When Used	Example
<b>Explicit Intent</b>	Launching a specific Activity in your app	Navigate from LoginActivity → MainActivity
<b>Implicit Intent</b>	Request action without specifying component	Open camera, make phone call, share text

2. **Write code for five Intent scenarios** (provide Kotlin or Java code):

**Scenario A: Explicit Intent – Navigation with Data**

```
// From LoginActivity, navigate to MainActivity and pass userId
val intent = Intent(this, MainActivity::class.java)
intent.putExtra("userId", "12345")
intent.putExtra("userName", "Alice")
startActivity(intent)
```

**Scenario B: Explicit Intent – Start Activity for Result**

```
// Launch camera app and expect photo back
val takePictureIntent = Intent(MediaStore.ACTION_IMAGE_CAPTURE)
startActivityForResult(takePictureIntent, CAMERA_REQUEST_CODE)
```

**Scenario C: Implicit Intent – Open Camera**

```
val cameraIntent = Intent(MediaStore.ACTION_IMAGE_CAPTURE)
startActivity(cameraIntent)
```

**Scenario D: Implicit Intent – Open Web Browser**

```
val webIntent = Intent(Intent.ACTION_VIEW,
Uri.parse("https://www.android.com"))
startActivity(webIntent)
```

**Scenario E: Implicit Intent – Make a Phone Call**

```
val callIntent = Intent(Intent.ACTION_CALL, Uri.parse("tel:+1234567890"))
// Remember: Add android.permission.CALL_PHONE permission
startActivity(callIntent)
```

3. **For each scenario, explain (1–2 sentences):**

- What information is passed?
- Why would you use this Intent in a real app?

4. **Data Passing and Retrieval:**

- Show how to retrieve extras in the receiving Activity  
// In MainActivity - retrieve data  
val userId = intent.getStringExtra("userId")  
val userName = intent.getStringExtra("userName")

**Deliverable:**

- Five complete Intent code examples
  - For each, a 1–2 sentence explanation of use case
  - Code showing how to retrieve passed data in receiving Activity
- 

## Part C: Layouts and Views

### Task 3: Responsive UI Design (Self-Study: 1.5–2 hours)

**Objective:** Design a practical mobile app screen using ConstraintLayout and handle user interactions.

**Instructions:**

1. **Design a Login Screen Layout** in XML pseudo-code or sketch:

Requirements:

- **EditText** for email input (hint: "Enter email")
- **EditText** for password input (inputType: password)
- **Button** for login action (full width, prominent color)
- **TextView** for "Forgot Password?" link (clickable)
- **ProgressBar** (initially hidden, shown during login)

2. **XML Example Structure:**

```
<androidx.constraintlayout.widget.ConstraintLayout  
xmlns:android="http://schemas.android.com/apk/res/android"  
android:layout_width="match_parent"  
android:layout_height="match_parent">
```

```
<ImageView  
    android:id="@+id/logo"  
    android:layout_width="100dp"  
    android:layout_height="100dp"
```

```
app:layout_constraintTop_toTopOf="parent"
app:layout_constraintStart_toStartOf="parent"
app:layout_constraintEnd_toEndOf="parent"
android:layout_marginTop="40dp" />
```

<EditText

```
    android:id="@+id/emailInput"
    android:layout_width="0dp"
    android:layout_height="48dp"
    android:inputType="textEmailAddress"
    android:hint="Email"
    app:layout_constraintTop_toBottomOf="@id/logo"
    app:layout_constraintStart_toStartOf="parent"
    app:layout_constraintEnd_toEndOf="parent"
    android:layout_marginTop="30dp"
    android:layout_marginStart="16dp"
    android:layout_marginEnd="16dp" />
```

<EditText

```
    android:id="@+id/passwordInput"
    android:layout_width="0dp"
    android:layout_height="48dp"
    android:inputType="textPassword"
    android:hint="Password"
    app:layout_constraintTop_toBottomOf="@id/emailInput"
    app:layout_constraintStart_toStartOf="parent"
    app:layout_constraintEnd_toEndOf="parent"
    android:layout_marginTop="16dp"
    android:layout_marginStart="16dp"
    android:layout_marginEnd="16dp" />
```

<Button

```
    android:id="@+id/loginButton"
    android:layout_width="0dp"
    android:layout_height="48dp"
    android:text="Login"
    app:layout_constraintBottom_toBottomOf="parent"
    app:layout_constraintStart_toStartOf="parent"
    app:layout_constraintEnd_toEndOf="parent"
    android:layout_margin="16dp" />
```

<TextView

```
    android:id="@+id/forgotPassword"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:text="Forgot Password?"
    android:textColor="@color/blue"
    app:layout_constraintStart_toStartOf="parent"
    app:layout_constraintTop_toBottomOf="@id/passwordInput"
    android:layout_marginStart="16dp"
```

```

        android:layout_marginTop="12dp" />

<ProgressBar
    android:id="@+id/loadingSpinner"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:visibility="gone"
    app:layout_constraintStart_toStartOf="parent"
    app:layout_constraintEnd_toEndOf="parent"
    app:layout_constraintTop_toBottomOf="@id/loginButton" />

```

```
</androidx.constraintlayout.widget.ConstraintLayout>
```

### 3. Implement Click Listeners and State Management:

```

class LoginActivity : AppCompatActivity() {
    private lateinit var emailInput: EditText
    private lateinit var passwordInput: EditText
    private lateinit var loginButton: Button
    private lateinit var loadingSpinner: ProgressBar
    private lateinit var forgotPassword: TextView

    override fun onCreate(savedInstanceState: Bundle?) {
        super.onCreate(savedInstanceState)
        setContentView(R.layout.activity_login)

        // Initialize views
        emailInput = findViewById(R.id.emailInput)
        passwordInput = findViewById(R.id.passwordInput)
        loginButton = findViewById(R.id.loginButton)
        loadingSpinner = findViewById(R.id.loadingSpinner)
        forgotPassword = findViewById(R.id.forgotPassword)

        // Set click listeners
        loginButton.setOnClickListener {
            val email = emailInput.text.toString()
            val password = passwordInput.text.toString()

            if (validateInput(email, password)) {
                showLoading(true)
                performLogin(email, password)
            } else {
                showError("Please enter valid email and password")
            }
        }

        forgotPassword.setOnClickListener {
            startActivity(Intent(this,
ForgotPasswordActivity::class.java))
        }
    }
}

```

```

private fun validateInput(email: String, password: String):
Boolean {
    return email.isNotEmpty() && password.isNotEmpty() &&
email.contains("@")
}

private fun performLogin(email: String, password: String) {
    // Simulate network call
    // In real app: call API, handle response
    Handler(Looper.getMainLooper()).postDelayed({
        showLoading(false)
        startActivity(Intent(this, MainActivity::class.java))
        finish()
    }, 2000)
}

private fun showLoading(isLoading: Boolean) {
    loadingSpinner.visibility = if (isLoading) View.VISIBLE else
View.GONE
    loginButton.isEnabled = !isLoading
}

private fun showError(message: String) {
    Toast.makeText(this, message, Toast.LENGTH_SHORT).show()
}
}

```

4. **Layout Design Questions** (answer in 2–3 sentences each):

- **Why use ConstraintLayout over LinearLayout here?**  
ConstraintLayout is more flexible and requires fewer nested layouts, improving performance and allowing complex responsive designs.
- **How would this login screen adapt on a tablet vs. phone?**  
You could use resource qualifiers (layout-large, layout-xlarge) to create wider layouts with centered content for tablets.
- **What's one accessibility improvement you'd make?**  
Add content descriptions to ImageView, ensure button text is descriptive, and use proper contrast ratios for text colors.

**Deliverable:**

- Login screen layout (XML sketch or pseudocode)
  - Click listener code implementation
  - 2–3 sentence answers to layout design questions
-

# Part D: Reflection & Best Practices

## Task 4: Android Development Principles (Online: 0.5–1 hour)

**Objective:** Develop strategic thinking about Android component design.

**Instructions:**

Answer **all three questions** (200–250 words total):

1. **Lifecycle Importance:**

- Why does Android separate Activities into distinct lifecycle states rather than having a simple "on/off" model?
- What problems would arise if Activities didn't have onPause() and onStop()?

2. **Intent Design Philosophy:**

- Why does Android encourage implicit Intents for system actions (camera, phone, share) instead of just providing built-in APIs?
- What's one advantage and one disadvantage of this approach?

3. **Layout Performance:**

- You have two options: a LinearLayout with 10 nested views, or a ConstraintLayout with the same structure. Which is better and why?
- What metric would you use to measure layout performance?

**Deliverable:** Answers to all 3 questions, 200–250 words total.

---

## Evaluation Criteria

Criteria	Excellent (9–10)	Good (7–8)	Acceptable (5–6)	Needs Improvement (<5)
<b>Lifecycle Understanding</b>	Complete lifecycle mapped with all transitions; clear callbacks	Lifecycle mostly correct; minor omissions	Basic lifecycle shown; some confusion	Incomplete or incorrect lifecycle
<b>Intent Implementation</b>	All 5 scenarios correct; good data passing explanations	4–5 scenarios correct; mostly accurate	3–4 scenarios; some errors	Fewer than 3 scenarios or major errors



<b>Layout Design</b>	Responsive, accessible, well-structured XML; good constraints	Good layout design; mostly responsive	Functional layout; accessibility gaps	Poor layout design or non-responsive
<b>Code Quality</b>	Clean Kotlin/Java; follows Android best practices	Generally clean; minor style issues	Readable but inconsistent	Difficult to read or unclear
<b>Strategic Thinking</b>	Thoughtful reflection on Android design philosophy	Good reflection; understands rationale	Basic reflection; limited depth	Minimal or missing reflection
<b>Communication</b>	Clear explanations; well-organized code examples	Generally clear; good code comments	Readable but lacks detail	Disorganized or unclear

---

## Deliverable Checklist

Submit as **PDF or DOCX (2–3 pages)** containing:

- [ ] **Task 1:** Activity lifecycle diagram + three pseudo-code implementations + reflection
  - [ ] **Task 2:** Five Intent code examples + explanations + data retrieval code
  - [ ] **Task 3:** Login screen layout (XML or sketch) + click listener implementation + design questions
  - [ ] **Task 4:** Strategic reflection (3 questions answered, 200–250 words total)
- 

## Resources & References

### Official Android Documentation:

- [Android Activity Lifecycle](#)
- [Intents and Intent Filters](#)
- [Layouts](#)
- [ConstraintLayout](#)

### Best Practices:

- Google Android Architecture Components:  
<https://developer.android.com/jetpack/guide>

- Android Developer Blog: <https://android-developers.googleblog.com/>

### **Design Tools:**

- Android Studio Layout Editor (drag-and-drop UI design)
  - Figma (prototyping layouts)
- 

## **Timeline Guidance**

### **Self-Study (6–8 hours):**

- Hours 1–2: Task 1 (Activity lifecycle mastery)
- Hours 2–4: Task 2 (Intent scenarios and data passing)
- Hours 4–7: Task 3 (Layout design and click listeners)
- Hours 7–8: Task 4 (Reflection and best practices)

### **Online Sessions (1–2 hours):**

- 0.5 hours: Task 1 discussion (lifecycle callbacks, savedInstanceState)
  - 0.5 hours: Task 2 demo (Intents in practice, common pitfalls)
  - 0.5 hours: Task 3 layout review (responsive design, accessibility)
  - 0.5 hour: Task 4 reflection & Q&A (Android philosophy, design patterns)
- 

## **Extension Tasks (Optional, Advanced)**

### **1. Process Death Simulation:**

- Implement logic to handle app process termination and restoration
- Use onSaveInstanceState() and bundle persistence

### **2. Advanced Intent Filtering:**

- Create custom Intent actions and implement implicit Intent receivers
- Write intent filters in AndroidManifest.xml

### **3. Custom Views:**

- Design a custom View subclass (e.g., circular progress indicator)
- Implement onDraw() and handle touch events

### **4. Responsive Layout Challenge:**

- Design a layout that works on phones (small), tablets (medium), and large displays
- Use configuration qualifiers and ConstraintLayout

### **5. Lifecycle Testing:**

- Write unit tests for Activity lifecycle callbacks using AndroidX testing libraries
  - Verify savedInstanceState logic with Espresso tests
- 

## Notes for Instructors

This exercise covers **foundational Android concepts** that appear in every mobile app. Students develop:

- Understanding of Activity lifecycle and state management
- Practical Intent usage for navigation and system integration
- Responsive UI design skills using modern layout frameworks
- Debugging and testing strategies for Android components

### Discussion prompts for online session:

- "Why does Android destroy and recreate Activities on configuration changes?"
- "When would you use Explicit Intents vs. Implicit Intents?"
- "How do you optimize layout performance for large view hierarchies?"
- "What's the best way to handle long-running operations in Activities?"
- "How does the Activity lifecycle relate to memory management?"

### Common student mistakes:

- Assuming Activities persist across app restarts without proper serialization
  - Forgetting to add permissions for implicit Intents (camera, call, location)
  - Creating deeply nested layouts that impact performance
  - Not handling lifecycle callbacks properly (e.g., leaking resources in onResume())
  - Ignoring accessibility in UI design (missing content descriptions, poor contrast)
- 

## Assessment Notes

### Grading rubric integration:

- Emphasizes *understanding* over perfect syntax
- Values correct lifecycle management and state handling
- Recognizes proper Intent usage patterns
- Encourages responsive, accessible design

### Partial credit guidance:

- Lifecycle: 25% (correct callbacks and transitions)
- Intents: 30% (appropriate usage, data passing)

- Layouts: 30% (responsive design, accessibility)
- Strategic thinking: 15% (reflection on Android philosophy)