



CENTER FOR  
MACHINE PERCEPTION



CZECH TECHNICAL  
UNIVERSITY IN PRAGUE

BACHELOR THESIS

# Minimal Problem Solver Generator

Pavel Trutman

pavel.trutman@fel.cvut.cz

April 27, 2015

Available at  
<http://cmp.felk.cvut.cz/~trutmpav/theses/bsc-pavel-trutman.pdf>

**Thesis Advisor: Ing. Tomáš Pajdla, PhD.**

Acknowledge grants here. Use centering if the text is too short.

Center for Machine Perception, Department of Cybernetics  
Faculty of Electrical Engineering, Czech Technical University  
Technická 2, 166 27 Prague 6, Czech Republic  
fax +420 2 2435 7385, phone +420 2 2435 7637, www: <http://cmp.felk.cvut.cz>



# **Minimal Problem Solver Generator**

Pavel Trutman

April 27, 2015



Text of acknowledgements. . .

## **Abstract**

Text of abstract...

## Resumé

Text of resumé...





# Contents

<b>1</b>	<b>Introduction</b>	<b>4</b>
<b>2</b>	<b>Polynomial system solving</b>	<b>5</b>
2.1	Buchberger Algorithm . . . . .	5
2.1.1	First implementation . . . . .	5
2.1.2	Improved Buchberger Algorithm . . . . .	6
2.2	$F_4$ Algorithm . . . . .	7
2.2.1	Improved Algorithm $F_4$ . . . . .	7
2.2.2	Function Update . . . . .	10
2.2.3	Function Reduction . . . . .	10
2.2.4	Function Symbolic Preprocessing . . . . .	10
2.2.5	Function Simplify . . . . .	11
2.2.6	Selection strategy . . . . .	11
2.3	$F_5$ Algorithm . . . . .	12
<b>3</b>	<b>Automatic generator</b>	<b>13</b>
3.1	Reimplementation . . . . .	13
3.2	Multiple eliminations solver . . . . .	13
3.3	Removing unnecessary polynomials . . . . .	13
3.4	Matrix partitioning . . . . .	13
3.5	$F_4$ strategy . . . . .	13
<b>4</b>	<b>Experiments</b>	<b>14</b>
<b>5</b>	<b>Conclusion</b>	<b>15</b>
	<b>Bibliography</b>	<b>16</b>

## List of Algorithms

1	Simple Buchberger Algorithm . . . . .	5
2	Improved Buchberger Algorithm . . . . .	6
3	Update . . . . .	8
4	Improved Algorithm $F_4$ . . . . .	9
5	Reduction . . . . .	10
6	Symbolic Preprocessing . . . . .	11
7	Simplify . . . . .	12
8	Sel – The normal strategy for $F_4$ . . . . .	12

## List of Abbreviations

$C(f), C(F)$	Set of all coefficients of the polynomial $f$ or of all polynomials from the set $F$ .
$\overline{f}^F$	Remainder of the polynomial $f$ on division by $F$ .
gcd	Greatest common multiple.
lcm	Least common divisor.
$LC(f), LC(F)$	Leading coefficient(s) of the polynomial $f$ or of all polynomials from the set $F$ .
$LM(f), LM(F)$	Leading monomial(s) of the polynomial $f$ or of all polynomials from the set $F$ .
$LT(f), LT(F)$	Leading term(s) of the polynomial $f$ or of all polynomials from the set $F$ .
$M(f), M(F)$	Set of all monomials of the polynomial $f$ or of all polynomials from the set $F$ .
$S(f_1, f_2)$	S-polynomial of polynomials $f_1$ and $f_2$ .
$T(f), T(F)$	Set of all terms of the polynomial $f$ or of all polynomials from the set $F$ .
$x \mid y$	$x$ divides $y$ .

# 1 Introduction

Here comes introduction.

## 2 Polynomial system solving

Firstly we review the state of the art algorithms for computing Gröbner basis. Better understanding of these algorithms helps us to integrate them into polynomial solving algorithms based on Gröbner basis computation more efficiently.

### 2.1 Buchberger Algorithm

Buchberger Algorithm [2], which was invented by Bruno Buchberger, was the first algorithm for computing Gröbner basis. The algorithm is described in details in [1, 3].

#### 2.1.1 First implementation

The first and easy, but very inefficient implementation of the Buchberger Algorithm, Algorithm 1, is based on the observation that we can extend a set  $F$  of polynomials to a Gröbner basis only by adding all non-zero remainders  $\overline{S(f_i, f_j)}^F$  of all pairs from  $F$  into  $F$  until there is no non-zero remainder generated.

The main disadvantage of this simple algorithm is that so constructed Gröbner basis are often bigger than necessary. This implementation of the algorithm is also very inefficient because many of the S-polynomials that are constructed from the critical pairs are reduced to zero so after spending effort on computing them, there is nothing to add to the Gröbner basis  $G$ . How to decide which pairs need not be generated is described next.

---

**Algorithm 1** Simple Buchberger Algorithm

---

**Input:**

$F$  a finite set of polynomials

**Output:**

$G$  a finite set of polynomials

```
1:  $G \leftarrow F$ 
2:  $B \leftarrow \{\{g_1, g_2\} \mid g_1, g_2 \in G, g_1 \neq g_2\}$ 
3: while  $B \neq \emptyset$  do
4:   select  $\{g_1, g_2\}$  from  $B$ 
5:    $B \leftarrow B \setminus \{\{g_1, g_2\}\}$ 
6:    $h \leftarrow S(g_1, g_2)$ 
7:    $h_0 \leftarrow \overline{h}^G$ 
8:   if  $h_0 \neq 0$  then
9:      $B \leftarrow B \cup \{\{g, h_0\} \mid g \in G\}$ 
10:     $G \leftarrow G \cup \{h_0\}$ 
11:   end if
12: end while
13: return  $G$ 
```

---

### 2.1.2 Improved Buchberger Algorithm

The combinatorial complexity of the simple implementation of the Buchberger Algorithm can be reduced by testing out certain S-polynomials which need not be considered. To know which pairs can be deleted without treatment, we use the first and the second Buchberger's criterion [1]. Sometimes, we can even delete certain polynomials from the set  $G$  completely, knowing that every critical pair they will generate will reduce to zero and hence these polynomials themselves will be superfluous in the output set. In the next few paragraphs we will describe the implementation of the Improved Buchberger Algorithm and of the function *Update*, which deletes superfluous polynomials from  $G$ , according to Gebauer and Möller [5].

The Improved Buchberger Algorithm, Algorithm 2, has the same structure as the Simple Algorithm. The function *Update* is used at the beginning of the Improved Buchberger Algorithm to initialize the set  $B$  of critical pairs and the Gröbner basis  $G$  from the input set  $F$  of polynomials and at every moment when a new non-zero polynomial  $h_0 = \bar{h}^G$  of an S-polynomial  $h$  has been found and the sets  $B$  and  $G$  are about to be updated.

---

**Algorithm 2** Improved Buchberger Algorithm

---

**Input:**
 $F$  a finite set of polynomials

**Output:**
 $G$  a finite set of polynomials

```

1:  $G \leftarrow \emptyset$ 
2:  $B \leftarrow \emptyset$ 
3: while  $F \neq \emptyset$  do
4:   select  $f$  from  $F$ 
5:    $F \leftarrow F \setminus \{f\}$ 
6:    $(G, B) \leftarrow \text{Update}(G, B, f)$ 
7: end while
8: while  $B \neq \emptyset$  do
9:   select  $\{g_1, g_2\}$  from  $B$ 
10:   $B \leftarrow B \setminus \{\{g_1, g_2\}\}$ 
11:   $h \leftarrow S(g_1, g_2)$ 
12:   $h_0 \leftarrow \bar{h}^G$ 
13:  if  $h_0 \neq 0$  then
14:     $(G, B) \leftarrow \text{Update}(G, B, h_0)$ 
15:  end if
16: end while
17: return  $G$ 

```

---

Now, let us look at the function *Update*, Algorithm 3. First, it makes pairs from the new polynomial  $h$  and all polynomials from the set  $G_{old}$  and puts them into the set  $C$ . The first while loop (lines 3 – 9) iterates over all pairs in the set  $C$ . In each iteration it select a pair  $\{h, g_1\}$  from the set  $C$  and removes it from the set. Then it looks for another pair  $\{h, g_2\}$  from the set  $C$  or the set  $D$ . If does not exists a pair  $\{h, g_2\}$  such that  $(h, g_2, g_1)$  is a Buchberger triple, then the pair  $\{h, g_1\}$  is put into the set  $D$ . The triple  $(h, g_2, g_1)$  of polynomials  $h$ ,  $g_1$  and  $g_2$  is a Buchberger triple if the equivalent conditions

$$\text{LM}(g_2) \mid \text{lcm}(\text{LM}(h), \text{LM}(g_1)) \quad (2.1)$$

$$\text{lcm}(\text{LM}(h), \text{LM}(g_2)) \mid \text{lcm}(\text{LM}(h), \text{LM}(g_1)) \quad (2.2)$$

$$\text{lcm}(\text{LM}(g_2), \text{LM}(g_1)) \mid \text{lcm}(\text{LM}(h), \text{LM}(g_1)) \quad (2.3)$$

are satisfied. From the second Buchberger's criterion, we know that if a Buchberger triple  $(h, g_2, g_1)$  shows up in the Buchberger Algorithm and the pairs  $\{g_1, g_2\}$  and  $\{h, g_2\}$  are amongs the critical pairs, then the pair  $\{h, g_1\}$  need not be generated. That means in the code that such a pair is not moved from the set  $C$  to the set  $D$  but it is only removed from the set  $C$ . This while loop keeps all pairs  $\{h, g_1\}$  where  $\text{LM}(h)$  and  $\text{LM}(g_1)$  are disjoint, i.e.  $\text{LM}(h)$  and  $\text{LM}(g_1)$  have no variable in common. The reason of this is that if two or more pairs in  $C$  have the same lcm of their leading monomials, then there is a choice which one should be deleted. So we keep the pair where the leading monomials are disjoint. Pairs with disjoint leading monomials are removed in the second while loop, so we eventually remove them all.

The second while loop (lines 11 – 17) eliminates all pairs with disjoint leading monomials. We can remove such pairs thanks to the first Buchberger's criterion. All remaining pairs are stored in the set  $E$ .

The third while loop (lines 19 – 25) eliminates pairs  $\{g_1, g_2\}$  where  $(g_1, h, g_2)$  is a Buchberger triple from the set  $B_{old}$ . Then the updated set of the old pairs and the new pairs are united into the set  $B_{new}$ .

Finally, the last while loop (lines 28 – 34) removes all polynomials  $g$  whose leading monomial is a multiple of the leading monomial of  $h$  from the set  $G_{old}$ . We can eliminate such polynomials for two reasons. Firstly,  $\text{LM}(h) \mid \text{LM}(g)$  implies  $\text{LM}(h) \mid \text{lcm}(\text{LM}(g), \text{LM}(f))$  for arbitrary polynomial  $f$ . We can see that  $(g, h, f)$  is a Buchberger triple for any  $f$  which in future appears in the set  $G$ . Moreover, polynomial  $g$  will not be missed at the end, because in the Gröbner basis  $G$ , polynomials with leading monomials which are multiples of leading monomials of another polynomial from  $G$  are superfluous, i.e. they will be eliminated in the reduced Gröbner basis.

In the end of the function, the polynomial  $h$  is added into the Gröbner basis  $G_{new}$ . The output of the function *Update* is the Gröbner basis  $G_{new}$  and the set  $B_{new}$  of critical pairs.

## 2.2 $F_4$ Algorithm

The  $F_4$  Algorithm [4] by Jean-Charles Faugère is an improved version of the Buchberger's Algorithm. The  $F_4$  replaces the classical polynomial reduction found in the Buchberger's Algorithm by a simultaneous reduction of several polynomials. This reduction mechanism is achieved by a symbolic precomputation followed by Gaussian elimination implemented using sparse linear algebra methods.  $F_4$  speeds up the reduction step by exchanging multiple polynomial divisions for row-reduction of a single matrix.

### 2.2.1 Improved Algorithm $F_4$

The main function of the  $F_4$  Algorithm, Algorithm 4, consists of two parts. The goal of the first part is to initialize the whole algorithm.

---

**Algorithm 3** Update

---

**Input:**

$G_{old}$  a finite set of polynomials  
 $B_{old}$  a finite set of pairs of polynomials  
 $h$  a polynomial such that  $h \neq 0$

**Output:**

$G_{new}$  a finite set of polynomials  
 $B_{new}$  a finite set of pairs of polynomials

```

1:  $C \leftarrow \{\{h, g\} \mid g \in G_{old}\}$ 
2:  $D \leftarrow \emptyset$ 
3: while  $C \neq \emptyset$  do
4:   select  $\{h, g_1\}$  from  $C$ 
5:    $C \leftarrow C \setminus \{\{h, g_1\}\}$ 
6:   if  $\text{LM}(h)$  and  $\text{LM}(g_1)$  are disjoint or
       ( $\text{lcm}(\text{LM}(h), \text{LM}(g_2)) \nmid \text{lcm}(\text{LM}(h), \text{LM}(g_1))$  for all  $\{h, g_2\} \in C$  and
        $\text{lcm}(\text{LM}(h), \text{LM}(g_2)) \nmid \text{lcm}(\text{LM}(h), \text{LM}(g_1))$  for all  $\{h, g_2\} \in D$ ) then
7:      $D \leftarrow D \cup \{\{h, g_1\}\}$ 
8:   end if
9: end while
10:  $E \leftarrow \emptyset$ 
11: while  $D \neq \emptyset$  do
12:   select  $\{h, g\}$  from  $D$ 
13:    $D \leftarrow D \setminus \{\{h, g\}\}$ 
14:   if  $\text{LM}(h)$  and  $\text{LM}(g)$  are not disjoint then
15:      $E \leftarrow E \cup \{\{h, g\}\}$ 
16:   end if
17: end while
18:  $B_{new} \leftarrow \emptyset$ 
19: while  $B_{old} \neq \emptyset$  do
20:   select  $\{g_1, g_2\}$  from  $B_{old}$ 
21:    $B_{old} \leftarrow B_{old} \setminus \{\{g_1, g_2\}\}$ 
22:   if  $\text{LM}(h) \nmid \text{lcm}(\text{LM}(g_1), \text{LM}(g_2))$  or
       ( $\text{lcm}(\text{LM}(g_1), \text{LM}(h)) = \text{lcm}(\text{LM}(g_1), \text{LM}(g_2))$  or
        $\text{lcm}(\text{LM}(h), \text{LM}(g_2)) = \text{lcm}(\text{LM}(g_1), \text{LM}(g_2))$ ) then
23:      $B_{new} \leftarrow B_{new} \cup \{\{g_1, g_2\}\}$ 
24:   end if
25: end while
26:  $B_{new} \leftarrow B_{new} \cup E$ 
27:  $G_{new} \leftarrow \emptyset$ 
28: while  $G_{old} \neq \emptyset$  do
29:   select  $g$  from  $G_{old}$ 
30:    $G_{old} \leftarrow G_{old} \setminus \{g\}$ 
31:   if  $\text{LM}(h) \nmid \text{LM}(g)$  then
32:      $G_{new} \leftarrow G_{new} \cup \{g\}$ 
33:   end if
34: end while
35:  $G_{new} \leftarrow G_{new} \cup \{h\}$ 
36: return  $(G_{new}, B_{new})$ 

```

---



First, it generates the set  $P$  of critical pairs and initializes the Gröbner basis  $G$ . This is done by taking each polynomial from the input set  $F$  and calling the function *Update* on it, which updates the set  $P$  of pairs and the set  $G$  of basic polynomials.

The second part of the algorithm generates new polynomials and adds them into the set  $G$ . In each iteration, it selects some pairs from  $P$  using the function *Sel*. Many selection strategies are possible and is still an open question how to best select the pairs. Some selection strategies are described in the section 2.2.6 on page 11. Then, it splits each selected pair  $\{f_1, f_2\}$  into two tuples. The first tuple contains the first polynomial  $f_1$  of the pair and the monomial  $m_1$  such that  $\text{LM}(m_1 \times f_1) = \text{lcm}(\text{LM}(f_1), \text{LM}(f_2))$ . The second tuple is constructed in the same way from the second polynomial  $f_2$  of the pair. All tuples from all selected pairs are put into the set  $L$ , i.e. duplicates are removed.

Next, function *Reduction* is called on the set  $L$ . It stores result in the set  $\tilde{F}^+$ . In the end of the algorithm it iterates through all new polynomials in the set  $\tilde{F}^+$  and calls the function *Update* on each of them. This generates new pairs into the set  $P$  of critical pairs and extends the Gröbner basis  $G$ .

This algorithm terminates when the set  $P$  of pairs is empty. Then the set  $G$  is a Gröbner basis and it is the output of the algorithm.

---

**Algorithm 4** Improved Algorithm  $F_4$ 


---

**Input:**

$F$  a finite set of polynomials

*Sel* a function  $\text{List}(\text{Pairs}) \rightarrow \text{List}(\text{Pairs})$  such that  $\text{Sel}(l) \neq \emptyset$  if  $l \neq \emptyset$

**Output:**

$G$  a finite set of polynomials

```

1:  $G \leftarrow \emptyset$ 
2:  $P \leftarrow \emptyset$ 
3:  $d \leftarrow 0$ 
4: while  $F \neq \emptyset$  do
5:   select  $f$  from  $F$ 
6:    $F \leftarrow F \setminus \{f\}$ 
7:    $(G, P) \leftarrow \text{Update}(G, P, f)$ 
8: end while
9: while  $P \neq \emptyset$  do
10:   $d \leftarrow d + 1$ 
11:   $P_d \leftarrow \text{Sel}(P)$ 
12:   $P \leftarrow P \setminus P_d$ 
13:   $L_d \leftarrow \text{Left}(P_d) \cup \text{Right}(P_d)$ 
14:   $(\tilde{F}_d^+, F_d) \leftarrow \text{Reduction}(L_d, G, (F_i)_{i=1, \dots, (d-1)})$ 
15:  for  $h \in \tilde{F}_d^+$  do
16:     $(G, P) \leftarrow \text{Update}(G, P, h)$ 
17:  end for
18: end while
19: return  $G$ 

```

---

### 2.2.2 Function Update

In the  $F_4$  Algorithm the standard implementation of the Buchberger's Criteria such as the Gebauer and Möller installation [5] is used. Details about the function *Update* can be found in the section 2.1.2. The pseudocode of the function is shown in Algorithm 3.

### 2.2.3 Function Reduction

Function *Reduction*, Algorithm 5, performs polynomial division using methods of linear algebra.

Input of the function *Reduction* is a set  $L$  containing tuples of monomial and polynomial. These tuples were constructed in the main function of the  $F_4$  Algorithm from all selected pairs.

First, the function *Reduction* calls the function *Symbolic Preprocessing* on the set  $L$ . This returns a set  $F$  of polynomials to be reduced. To use linear algebra methods to perform polynomial division, the polynomials have to be represented by a matrix. Each column of the matrix corresponds to a monomial. Columns have to be ordered with respect to the monomial ordering used so that the most right column corresponds to "1". Each row of the matrix corresponds to a polynomial from the set  $F$ . The matrix is constructed as follows. On the  $(i, j)$  position in the matrix, we put the coefficient of the term corresponding to  $j$ -th monomial from the  $i$ -th polynomial from the set  $F$ .

We next reduce the matrix to a row echelon form using, for example, Gauss-Jordan elimination. Note that this matrix is typically sparse so we can use sparse linear algebra methods to save computation time and memory. After elimination, we construct resulting polynomials by multiplying the reduced matrix by a vector of monomials from the right.

In the end, the function returns the set  $\tilde{F}^+$  of reduced polynomials such that their leading monomials are not leading monomials of any polynomial from the set  $F$  of polynomials before reduction.

---

#### Algorithm 5 Reduction

---

**Input:**

- $L$  a finite set of tuples of monomial and polynomial
- $G$  a finite set of polynomials
- $\mathcal{F} = (F_i)_{i=1, \dots, (d-1)}$ , where  $F_i$  is finite set of polynomials

**Output:**

- $\tilde{F}^+$  a finite set of polynomials
- $F$  a finite set of polynomials

- 1:  $F \leftarrow \text{Symbolic Preprocessing}(L, G, \mathcal{F})$
  - 2:  $\tilde{F} \leftarrow \text{Reduction to a Row Echelon Form of } F$
  - 3:  $\tilde{F}^+ \leftarrow \left\{ f \in \tilde{F} \mid \text{LM}(f) \notin \text{LM}(F) \right\}$
  - 4: **return**  $(\tilde{F}^+, F)$
- 

### 2.2.4 Function Symbolic Preprocessing

Function *Symbolic Preprocessing*, Algorithm 6, starts with a set  $L$  of tuples each containing a monomial and a polynomial. These tuples were constructed in the main

function of the  $F_4$  Algorithm from the selected pairs. Then, the tuples are simplified by the function *Simplify* and after multiplying polynomials with corresponding monomials, the results are put into the set  $F$ .

Next, the function goes through all monomials in the set  $F$  and for each monomial  $m$  looks for some polynomial  $f$  from the Gröbner basis  $G$  such  $m = m' \times \text{LM}(f)$  where  $m'$  is some monomial. All such polynomials  $f$  and monomials  $m'$  are after simplification multiplied and put into the set  $F$ . The goal of this search is to have for every monomial in  $F$  a polynomial in  $F$  with the same leading monomial. This will ensure that all polynomials from  $F$  will be reduced for  $G$  after polynomial division by linear algebra.

---

**Algorithm 6** Symbolic Preprocessing

---

**Input:**

$L$  a finite set of tuples of monomial and polynomial  
 $G$  a finite set of polynomials  
 $\mathcal{F} = (F_i)_{i=1,\dots,(d-1)}$ , where  $F_i$  is finite set of polynomials

**Output:**

$F$  a finite set of polynomials

```

1:  $F \leftarrow \{\text{multiply}(\text{Simplify}(m, f, \mathcal{F})) \mid (m, f) \in L\}$ 
2:  $\text{Done} \leftarrow \text{LM}(F)$ 
3: while  $\text{M}(F) \neq \text{Done}$  do
4:    $m$  an element of  $\text{M}(F) \setminus \text{Done}$ 
5:    $\text{Done} \leftarrow \text{Done} \cup \{m\}$ 
6:   if  $m$  is top reducible modulo  $G$  then
7:      $m = m' \times \text{LM}(f)$  for some  $f \in G$  and some monomial  $m'$ 
8:      $F \leftarrow F \cup \{\text{multiply}(\text{Simplify}(m', f, \mathcal{F}))\}$ 
9:   end if
10: end while
11: return  $F$ 

```

---

### 2.2.5 Function Simplify

The function *Simplify*, Algorithm 7, simplifies a polynomial  $m \times f$  which is a product of a given monomial  $m$  and a polynomial  $f$ .

The function recursively looks for a monomial  $m'$  and a polynomial  $f'$  such that  $\text{LM}(m' \times f') = \text{LM}(m \times f)$ . The polynomial  $f'$  is selected from all polynomials that have been reduced in previous iterations (sets  $\tilde{F}$ ). We select polynomial  $f'$  such that the total degree of  $m'$  is minimal.

This is done in the function *Symbolic Preprocessing* to insert polynomials that are mostly reduced and have a small number of monomials into the set  $F$  of polynomials to be reduced. This of course speeds up following reduction.

### 2.2.6 Selection strategy

For the speed of the  $F_4$  Algorithm, it is very important how the critical pairs from the list of all critical pairs  $P$  are selected in each iteration. This of course depends on the implementation of the function *Sel*. There are more possible selection strategies:

- The easiest implementation is to select all pairs from  $P$ . In this case we reduce all critical pairs at the same time.

---

**Algorithm 7** Simplify

---

**Input:**

$m$  a monomial

$f$  a polynomial

$\mathcal{F} = (F_i)_{i=1,\dots,(d-1)}$ , where  $F_i$  is finite set of polynomials

**Output:**

$(m', f')$  a non evaluated product of a monomial and a polynomial

```

1: for  $u \in$  list of all divisors of  $m$  do
2:   if  $\exists j$  ( $1 \leq j \leq d$ ) such that  $(u \times f) \in F_j$  then
3:      $\tilde{F}_j$  is the Row Echelon Form of  $F_j$ 
4:     there exists a (unique)  $p \in \tilde{F}_j$  such that  $\text{LM}(p) = \text{LM}(u \times f)$ 
5:     if  $u \neq m$  then
6:       return  $\text{Simplify}(\frac{m}{u}, p, \mathcal{F})$ 
7:     else
8:       return  $(1, p)$ 
9:     end if
10:  end if
11: end for
12: return  $(m, f)$ 

```

---

- If the function *Sel* selects only one critical pair then the  $F_4$  Algorithm is the Buchberger's Algorithm. In this case the *Sel* function corresponds to the selection strategy in the Buchberger's Algorithm.
- The best function that Faugère has tested is to select all critical pairs with a minimal total degree. Faugère calls this strategy the *normal strategy for  $F_4$* . Pseudocode of this function can be found as Algorithm 8.

---

**Algorithm 8** Sel – The normal strategy for  $F_4$

---

**Input:**

$P$  a list of critical pairs

**Output:**

$P_d$  a list of critical pairs

```

1:  $d \leftarrow \min \{ \deg(\text{lcm}(p)) \mid p \in P \}$ 
2:  $P_d \leftarrow \{ p \in P \mid \deg(\text{lcm}(p)) = d \}$ 
3: return  $P_d$ 

```

---

## 2.3 $F_5$ Algorithm

## **3 Automatic generator**

Automatic generators of Gröbner basis solvers are used to easily solve problems leading to systems of polynomial equations. The input of the automatic generator is a system of polynomial equations with a finite number of solutions and the output is a MATLAB or a Maple code that computes solutions of the given system for arbitrary coefficients. One of the goals of this thesis is to improve previous implementation [6] to construct more efficient and numerically stable solvers.

### **3.1 Reimplementation**

### **3.2 Multiple eliminations solver**

### **3.3 Removing unnecessary polynomials**

### **3.4 Matrix partitioning**

### **3.5 F4 strategy**

## 4 Experiments

## 5 Conclusion

## Bibliography

- [1] Thomas Becker and Volker Weispfenning. *Gröbner Bases, A Computational Approach to Commutative Algebra*. Number 141 in Graduate Texts in Mathematics. Springer-Verlag, New York, NY, 1993. 5, 6
- [2] Bruno Buchberger. *Ein Algorithmus zum Auffinden der Basiselemente des Restklassenringes nach einem nulldimensionalen Polynomideal*. PhD thesis, Mathematical Institute, University of Innsbruck, Austria, 1965. 5
- [3] David Cox, John Little, and Donald O’Shea. *Ideals, Varieties, and Algorithms : An Introduction to Computational Algebraic Geometry and Commutative Algebra*. Undergraduate Texts in Mathematics. Springer, New York, USA, 2nd edition, 1997. 5
- [4] Jean-Charles Faugère. A new efficient algorithm for computing gröbner bases ( $f_4$ ). *Journal of pure and applied algebra*, 139(1–3):61–88, 7 1999. 7
- [5] Rüdiger Gebauer and Hans-Michael Möller. On an installation of buchberger’s algorithm. *Journal of Symbolic Computation*, 6(2–3):275–286, 10 1988. 6, 10
- [6] Zuzana Kukelova, Martin Bujnak, and Tomas Pajdla. Automatic generator of minimal problem solvers. In *Proceedings of The 10th European Conference on Computer Vision*, ECCV 2008, October 12–18 2008. 13