Rajalakshmi Engineering College

Name: Pavithra J
Email: 240701381@rajalakshmi.edu.in
Roll no: 240701381
Phone: 9363364978
Branch: REC
Department: I CSE FD
Batch: 2028
Degree: B.E - CSE

Scan to verify results

NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Ravi is developing a student registration system for a college. To efficiently store and manage the student IDs, he decides to implement a doubly linked list where each node represents a student's ID.

In this system, each student's ID is stored sequentially, and the system needs to display all registered student IDs in the order they were entered.

Implement a program that creates a doubly linked list, inserts student IDs, and displays them in the same order.

Input Format

The first line contains an integer N the number of student IDs.

The second line contains N space-separated integers representing the student IDs.

Output Format

The output should display the single line containing N space-separated integers representing the student IDs stored in the doubly linked list.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
10 20 30 40 50
Output: 10 20 30 40 50

Answer

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>

// Node structure
struct Node {
    int data;
    struct Node* prev;
    struct Node* next;
};

struct Node* head = NULL;
struct Node* tail = NULL;

// Function to insert at the end
void insertAtEnd(int data) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = data;
    newNode->prev = NULL;
    newNode->next = NULL;

    if (head == NULL) {
        head = newNode;
        tail = newNode;
```

```
    } else {
        tail->next = newNode;
        newNode->prev = tail;
        tail = newNode;
    }
}

// Function to display the list
void traverse() {
    struct Node* temp = head;
    while (temp != NULL) {
        printf("%d ", temp->data);
        temp = temp->next;
    }
}

int main() {
    int n, id;
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%d", &id);
        insertAtEnd(id);
    }

    traverse();
    return 0;
}
```

Status : Correct ***Marks : 10/10***