

Rajalakshmi Engineering College

Name: Pavithra J
Email: 240701381@rajalakshmi.edu.in
Roll no: 240701381
Phone: 9363364978
Branch: REC
Department: I CSE FD
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 5_COD_Question 5

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In his computer science class, John is learning about Binary Search Trees (BST). He wants to build a BST and find the maximum value in the tree.

Help him by writing a program to insert nodes into a BST and find the maximum value in the tree.

Input Format

The first line of input consists of an integer N, representing the number of nodes in the BST.

The second line consists of N space-separated integers, representing the values of the nodes to insert into the BST.

Output Format

The output prints the maximum value in the BST.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

10 5 15 2 7

Output: 15

Answer

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct TreeNode {  
    int data;  
    struct TreeNode* left;  
    struct TreeNode* right;  
};
```

```
struct TreeNode* createNode(int key) {  
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct  
TreeNode));  
    newNode->data = key;  
    newNode->left = newNode->right = NULL;  
    return newNode;  
}
```

```
struct TreeNode* insert(struct TreeNode* root, int key) {  
    if (root == NULL)  
        return createNode(key);  
  
    if (key < root->data)  
        root->left = insert(root->left, key);  
    else if (key > root->data)  
        root->right = insert(root->right, key);  
  
    return root;  
}
```

```
int findMax(struct TreeNode* root) {  
    if (root == NULL)  
        return -1;  
    while (root->right != NULL)  
        root = root->right;  
    return root->data;  
}
```

```
int main() {  
    int N, rootValue;  
    scanf("%d", &N);  
  
    struct TreeNode* root = NULL;  
  
    for (int i = 0; i < N; i++) {  
        int key;  
        scanf("%d", &key);  
        if (i == 0) rootValue = key;  
        root = insert(root, key);  
    }  
  
    int maxVal = findMax(root);  
    if (maxVal != -1) {  
        printf("%d", maxVal);  
    }  
  
    return 0;  
}
```

Status : Correct

Marks : 10/10