

- Missing closing symbol
- Missing opening symbol
- Mismatched symbol

Input Format:

- A single string representing an expression containing symbols and operands.

Output Format:

Display one of the following messages:

- Symbols are balanced...!
- Missing closing symbol...!
- Missing opening symbol...!
- Mismatched symbol...!

Sample Input 1:

(a+b)

Sample Output 1:

Symbols are balanced...!

Sample Input 2:

((a+b)

Sample Output 2:

Missing closing symbol...!

Sample Input 3:

(a+b))

Sample Output 3:

Missing opening symbol...!

Sample Input 4:

(a+b]

Sample Output 4:

Mismatched symbol...!

For example:

Input	Result
(a+b)	Symbols are balanced...!
((a+b)	Missing closing symbol...!
(a+b))	Missing opening symbol...!
(a+b]	Mismatched symbol...!

Answer: (penalty regime: 0 %)

Reset answer

```

1 #include <stdio.h>
2 #include <string.h>
3
4 #define MAX 20
5 char Stack[MAX];
6 int top = -1;
7
8 int IsEmpty();
9 void Push(char sym);
10 char Pop();
11
12 int main()
13 {
14     char exp[20], c;
15     int i;
16     scanf("%s", exp);
17     for(i = 0; i < strlen(exp); i++)
18     {
19         if(exp[i] == '(' || exp[i] == '[' || exp[i] == '{')
20         {
21             Push(exp[i]);
22         }
23     }
24 }
```

	Input	Expected	Got	
✓	(a+b)	Symbols are balanced...!	Symbols are balanced...!	✓
✓	((a+b)	Missing closing symbol...!	Missing closing symbol...!	✓
✓	(a+b))	Missing opening symbol...!	Missing opening symbol...!	✓
✓	(a+b]	Mismatched symbol...!	Mismatched symbol...!	✓

- Missing closing symbol
- Missing opening symbol
- Mismatched symbol

Input Format:

- A single string representing an expression containing symbols and operands.

Output Format:

Display one of the following messages:

- Symbols are balanced...!
- Missing closing symbol...!
- Missing opening symbol...!
- Mismatched symbol...!

Sample Input 1:

(a+b)

Sample Output 1:

Symbols are balanced...!

Sample Input 2:

((a+b)

Sample Output 2:

Missing closing symbol...!

Sample Input 3:

(a+b))

Sample Output 3:

Missing opening symbol...!

Sample Input 4:

(a+b]

Sample Output 4:

Mismatched symbol...!

For example:

Input	Result
(a+b)	Symbols are balanced...!
((a+b)	Missing closing symbol...!
(a+b))	Missing opening symbol...!
(a+b]	Mismatched symbol...!

Answer: (penalty regime: 0 %)

Reset answer

```

1 #include <stdio.h>
2 #include <string.h>
3
4 #define MAX 20
5 char Stack[MAX];
6 int top = -1;
7
8 int IsEmpty();
9 void Push(char sym);
10 char Pop();
11
12 int main()
13 {
14     char exp[20], c;
15     int i;
16     scanf("%s", exp);
17     for(i = 0; i < strlen(exp); i++)
18     {
19         if(exp[i] == '(' || exp[i] == '[' || exp[i] == '{')
20         {
21             Push(exp[i]);
22         }
23     }
24 }
```

	Input	Expected	Got	
✓	(a+b)	Symbols are balanced...!	Symbols are balanced...!	✓
✓	((a+b)	Missing closing symbol...!	Missing closing symbol...!	✓
✓	(a+b))	Missing opening symbol...!	Missing opening symbol...!	✓
✓	(a+b]	Mismatched symbol...!	Mismatched symbol...!	✓

Fundamentals of Data Structures Using C-2025 Batch

1 Friday, 22 May 2026, 10:49 AM
2 Finished
3 Friday, 22 May 2026, 10:53 AM
4 4 mins 10 secs
5 PAVITHRA B 2025-BME

Write a program to convert a given **Infix Expression** into its equivalent **Postfix Expression** using a **Stack**.

Operators to be Supported:

- + (Addition)
- - (Subtraction)
- * (Multiplication)
- / (Division)
- ^ (Exponentiation)

Operator Precedence & Associativity:

Operator Precedence Associativity

^	Highest	Right to Left
*, /	Medium	Left to Right
+, -	Lowest	Left to Right

Sample Input:

a/b^c+d*e-f*g

Sample Output:

abc^/de*+fg*-

For example:

Input	Result
a/b^c+d*e-f*g	abc^/de*+fg*-

Answer: (penalty regime: 0 %)

Reset answer

```
1 #include <stdio.h>
2 #include <string.h>
3
4 #define MAX 20
5
6 int Stack[MAX], top = -1;
7 char expr[MAX], post[MAX];
8
9 void Push(char sym);
10 char Pop();
11 char Top();
12 int Priority(char sym);
13
14 int main()
15 {
16     int i;
17     scanf("%s", expr);
18     for(i = 0; i < strlen(expr); i++)
19     {
20         if(expr[i] >= 'a' && expr[i] <= 'z')
21             printf("%c", expr[i]);
22         else if(expr[i] == '(')
```

Input	Expected	Got
✓ a/b^c+d*e-f*g	abc^/de*+fg*-	abc^/de*+fg*- ✓

Passed all tests! ✓

Finish review

CS23232-Fundamentals of Data Structures Using C-2025 Batch

Started on Friday, 22 May 2026, 10:49 AM
State Finished
Completed on Friday, 22 May 2026, 10:53 AM
Time taken 4 mins 10 secs
Name PAVITHRA B 2025-BME

Question 1

Correct

Marked out of 1.00

Flag question

Write a program to convert a given **Infix Expression** into its equivalent **Postfix Expression** using a **Stack**.

Operators to be Supported:

- + (Addition)
- - (Subtraction)
- * (Multiplication)
- / (Division)
- ^ (Exponentiation)

Operator Precedence & Associativity:

Operator Precedence Associativity

^	Highest	Right to Left
*, /	Medium	Left to Right
+, -	Lowest	Left to Right

Sample Input:

a/b^c+d*e-f*g

Sample Output:

abc^/de*+fg*-

For example:

Input	Result
a/b^c+d*e-f*g	abc^/de*+fg*-

Answer: (penalty regime: 0 %)

Reset answer

```

1 #include <stdio.h>
2 #include <string.h>
3
4 #define MAX 20
5
6 int Stack[MAX], top = -1;
7 char expr[MAX], post[MAX];
8
9 void Push(char sym);
10 char Pop();
11 char Top();
12 int Priority(char sym);
13
14 int main()
15 {
16     int i;
17     scanf("%s", expr);
18     for(i = 0; i < strlen(expr); i++)
19     {
20         if(expr[i] >= 'a' && expr[i] <= 'z')
21             printf("%c", expr[i]);
22         else if(expr[i] == '(')

```

	Input	Expected	Got	
✓	a/b^c+d*e-f*g	abc^/de*+fg*-	abc^/de*+fg*-	✓

Passed all tests! ✓

Finish review

Quiz navigation

1

Fundamentals of Data Structures Using C-2025 Batch

Friday, 22 May 2026, 10:54 AM
Finished
Friday, 22 May 2026, 10:59 AM
5 mins 28 secs
PAVITHRA B 2025-BME

Write a program to **evaluate a given Postfix Expression** using a **Stack**.

The expression contains operands represented by variables, and their corresponding values will be provided separately.

Input Format:

1. A string representing the **postfix expression**.
2. The integer values of the operands in the **order of their appearance** in the expression.

Output Format:

- Print the **final evaluated result** of the postfix expression.

Sample Input:

abc+*d*

2

3

4

5

Sample Output:

70

For example:

Input	Result
abc+*d*	70
2	
3	
4	
5	

Answer: (penalty regime: 0 %)

Reset answer

```
8
9 void Push(int ele);
10 int Pop();
11
12 int main()
13 {
14     int i, a, b, c, e;
15     scanf("%s", expr);
16     for(i = 0; i < strlen(expr); i++)
17     {
18         if(expr[i]=='+' || expr[i]=='-' || expr[i]=='*' || expr[i]=='/')
19         {
20             b = Pop();
21             a = Pop();
22
23             switch(expr[i])
24             {
25                 case '+':
26                     c = a + b;
27                     Push(c);
28                     break;
29                 case '-':
```

	Input	Expected	Got	
✓	abc+*d*	70	70	✓
	2			
	3			
	4			
	5			

Passed all tests! ✓