



RAJALAKSHMI ENGINEERING COLLEGE

CS23333 - OBJECT ORIENTED PROGRAMMING
USING JAVA

Laboratory Record Note Book

NAME.....	PAYITH RA S
BRANCH.....	B.Tech I.T
UNIVERSITY REGISTER No.	2116241001162
COLLEGE ROLL No.	241001162
SEMESTER	III
ACADEMIC YEAR	2025 - 2026



RAJALAKSHMI
ENGINEERING
COLLEGE

BONAFIDE CERTIFICATE

NAME PAVITHRA S

ACADEMIC YEAR 2025 - 26 SEMESTER III BRANCH...B.Tech..IT

UNIVERSITY REGISTER No. 2116241001162

Certified that this is the bonafide record of work done by the above student in the

CS2333

Object Oriented Laboratory during the year 2025 - 2026

Programming

Using Java

Signature of Faculty - in - Charge


Submitted for the Practical Examination held on

Internal Examiner

External Examiner

INDEX

S.no	Date	Title	QR Code	Sign
1.	15/8/25	Week-1 I/O, Data Types, Operators.		b✓
2.	29/8/25	Week-2 Control Structures		b✓
3.	5/9/25	Week-3 Arrays		b✓
4.	12/9/25	Week-4 Strings		b✓
5.	26/9/25	Week-5 Classes & Objects		b✓
6.	3/10/25	Week-6 Inheritance		b✓

1.	10/10/25	Week-7 Interface		
8.	17/10/25	Week-8 Exceptions		
9.	17/10/25	Week-9 Collections		
10.	24/10/25	Week-10 Collections		
11.	7/11/25	Week-11 Project		
12.	7/11/25	Week-12 Lambda		

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 1_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 15

Section 1 : MCQ

1. What is the output of the following code?

```
class TestClass {  
    public static void main(String[] args) {  
        int count = 8;  
        count = count ^ 1;  
  
        System.out.println(count);  
    }  
}
```

Answer

9

Status : Correct

Marks : 1/1

2. Which of the following data types is used to store floating-point numbers with greater precision?

Answer

double

Status : Correct

Marks : 1/1

3. What will be the output of the following program?

```
class DataTypesMCQ {  
    public static void main(String[] args) {  
        int a = 10;  
        double b = 5;  
        System.out.println(a / b);  
    }  
}
```

Answer

2.0

Status : Correct

Marks : 1/1

4. What will be the output of the following code?

```
import java.util.*;  
  
class TernaryOperatorExample {  
    public static void main(String[] args) {  
        int a = 5, b = 10;  
        int result = (a > b) ? a : b;  
        System.out.println(result);  
    }  
}
```

Answer

10

Status : Correct

Marks : 1/1

5. What is the output of the following code?

```
class TestClass {  
    public static void main(String[] args) {  
        int x = 5;  
        int X = 10;  
  
        int sum = x + X;  
        int bitwiseResult = x | X;  
  
        System.out.println(sum);  
        System.out.println(bitwiseResult);  
    }  
}
```

Answer

1515

Status : Correct

Marks : 1/1

6. What is the output of the following code?

```
class TestClass {  
    public static void main(String[] args) {  
        int a = 10;  
        int b = 3;  
        System.out.println(a / b);  
    }  
}
```

Answer

3

Status : Correct

Marks : 1/1

7. What is the output of the following program?

```
class Demo {  
    public static void main(String[] args) {
```

```
        String text = "Hello, World!";
        System.out.println(text);
    }
}
```

Answer

Hello, World!

Status : Correct

Marks : 1/1

8. What is the output of the following code?

```
import java.util.*;

class RelationalOperatorExample {
    public static void main(String[] args) {
        int x = 8, y = 4;
        boolean result = (x != y);

        System.out.println(result);
    }
}
```

Answer

true

Status : Correct

Marks : 1/1

9. What will be the output of the following code snippet?

```
class DivisionExample {
    public static void main(String[] args) {
        double num1 = 10.5;
        double num2 = 3;
        int result = (int)(num1 / num2);
        System.out.println(result);
    }
}
```

Answer

3

Status : Correct

Marks : 1/1

10. What will be the output of the following code snippet?

```
import java.util.*;  
  
class OperatorPrecedenceExample {  
    public static void main(String[] args) {  
        int a = 5, b = 3, c = 2;  
        int result = a + b * c;  
  
        System.out.println(result);  
    }  
}
```

Answer

11

Status : Correct

Marks : 1/1

11. Which of the following data types is used to store single characters?

Answer

char

Status : Correct

Marks : 1/1

12. What is the result of the following expression?

```
import java.util.*;
```

```
class ComplexExpressionExample {  
    public static void main(String[] args) {  
        int a = 5, b = 2, c = 3, d = 4;  
        int result = a + b * c / d - b;
```

```
        System.out.println(result);
    }
}
```

Answer

4

Status : Correct

Marks : 1/1

13. What is the output of the following code?

```
class TestClass {
    public static void main(String[] args) {
        int a = 5;
        int b = 10;

        int sum = a + b;
        int bitwiseAnd = a & b;
        int bitwiseOr = a | b;

        System.out.println(sum);
        System.out.println(bitwiseAnd);
        System.out.println(bitwiseOr);
    }
}
```

Answer

15015

Status : Correct

Marks : 1/1

14. What is the output of the following program?

```
class Arithmetic {
    public static void main(String[] args) {
        char ch = 'A';
        System.out.println(ch);
    }
}
```

}

Answer

A

Status : Correct

Marks : 1/1

15. Which of the following is not a primitive data type?

Answer

string

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 1_Q1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Gloria is responsible for monitoring the performance of two machines in a factory. She needs to determine which of the two machines is operating closest to the optimal temperature of 100 degrees Celsius using the relational operator.

Assist Gloria in displaying the machine's temperature, which is closer to 100, and the difference from 100.

Input Format

The first line of input consists of an integer N, representing the temperature of the first machine.

The second line consists of an integer M, representing the temperature of the second machine.

Output Format

The output prints "The integer closer to 100 is X with a difference of Y" where X is the temperature of the closer machine and Y is the difference from 100.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 90
80

Output: The integer closer to 100 is 90 with a difference of 10

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;
import java.lang.Math;

class Temperature{
    public static void main(String[] args){
        Scanner sc = new Scanner(System.in);
        int N = sc.nextInt();
        int M = sc.nextInt();
        int d1=Math.abs(100-N);
        int d2 =Math.abs(100-M);
        int X,Y;

        if(d1<d2){
            X=N;
            Y=d1;
        }
        else{
            X=M;
            Y=d2;
        }
        System.out.printf("The integer closer to 100 is %d with a difference of
%d",X,Y);
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 1_Q2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. PROBLEM STATEMENT:

Dave got two students who wants help with their doubt. Each handouts an integer and wants to find if one Integer Positive While the Other is Not Divisible by 3. Write a program to achieve this and conclude for them.

Input Format

The first line of input represents the first integer.

The second line of input represents the second integer.

Output Format

The output should display as "One of the integers is positive while the other is not divisible by 3." or "Neither of the integers meets the condition."

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4

3

Output: One of the integers is positive while the other is not divisible by 3.

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Divisible{
    public static void main(String[] arg){
        Scanner sc=new Scanner(System.in);
        int n1 = sc.nextInt();
        int n2 = sc.nextInt();

        if((n1>0 && n2%3!=0) || (n2>0 && n1%3!=0))
            System.out.println("One of the integers is positive while the other is not
divisible by 3.");

        else
            System.out.println("Neither of the integers meets the condition.");
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 1_Q3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem statement

Manoj, a developer at MoneyMatters Inc., is working on improving the company's financial system. He needs to create a program that takes an integer input, converts it into a double, and displays both the original integer and the converted double value.

Input Format

The input consists of a single integer representing a monetary amount.

Output Format

The first line of the output displays the "Original Integer: ", followed by an integer representation of the input value.

The second line displays the "Converted Double: ", followed by a double value representing the input as a decimal value.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 20

Output: Original Integer: 20

Converted Double: 20.0

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Convert.ToDouble{
    public static void main(String[] args){
        Scanner sc = new Scanner(System.in);
        int n=sc.nextInt();
        double d=(double)n;
        System.out.println("Original Integer: "+n);
        System.out.println("Converted Double: "+d);
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 1_Q4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Vishal and Arun are discussing the properties of numbers. Vishal gives Arun two integers. He asks Arun to check if the sum of these two numbers is a multiple of their product.

Can you assist Arun and determine whether the sum is a multiple of the product?

Input Format

The input consists of two space-separated integers.

Output Format

The output prints:

1. "Sum is Multiple of Product" if the sum of the two numbers is divisible by their product.
2. "Sum is Not Multiple of Product" otherwise.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1 2

Output: Sum is Not Multiple of Product

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class CheckMultiple{
    public static void main(String[] args){
        Scanner sc =new Scanner(System.in);
        int a=sc.nextInt();
        int b=sc.nextInt();

        int sum=a+b;
        int product=a*b;

        if(sum==product)
            System.out.println("Sum is Multiple of Product");
        else
            System.out.println("Sum is Not Multiple of Product");
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 1_Q5

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement:

Emily has a beautiful circular garden in her backyard. She's interested in calculating two important measurements for her garden: the circumference and the area. To do this, she needs a program that can take the radius of her circular garden as input and provide the calculated circumference and area as output. The formulas she should use are as follows:

To calculate the circumference (C) of a circle, you can use the formula:

$$C = 2 * \pi * r$$

$$A = \pi * r^2$$

Where:

C represents the circumference.

A represents the area.

π (pi) is approximately 3.14159.

r is the radius of the circle.

Emily is not a programmer, and she needs your help to create a program that will make these calculations for her garden.

Input Format

The first line of input contains a single double-point number radius, representing the radius of the circle.

Output Format

The output should consist of two lines:

The first line should print the circumference of the circle rounded to 2 decimal places, followed by the unit "meters".

The second line should print the area of the circle rounded to 2 decimal places, followed by the unit "square meters".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3.0

Output: Circumference: 18.85 meters

Area: 28.27 square meters

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;
//import java.lang.Math;

class Garden{
    public static void main(String[] args){
```

```
Scanner sc = new Scanner(System.in);
float r = sc.nextFloat();
float C = 2*3.14159f*r;
float A = 3.14159f*r*r;

System.out.printf("Circumference: %.2f meters\n", C);
System.out.printf("Area: %.2f square meters",A);
}
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 1_Q6

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Joey is learning about bitwise operations and is working on a project that involves extracting specific bits from integers. He needs to write a program that takes an integer and the number of bits N as input and outputs the value of the lowest N bits of the integer.

Help Joey in his project to understand and visualize how bitwise operations work in practical scenarios.

Input Format

The first line of input consists of an integer X, representing the given integer.

The second line consists of an integer N, representing the number of bits to extract.

Output Format

The output displays "Result: " followed by an integer representing the value of the lowest N bits of the given integer.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 85

2

Output: Result: 1

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class LowestBit{
    public static void main(String[] arg){
        Scanner sc = new Scanner(System.in);
        int X=sc.nextInt();
        int N=sc.nextInt();
        String binary=Integer.toBinaryString(X);
        //System.out.println(binary);
        int len=binary.length();
        if(len>N)
        {
            String sub2=binary.substring(len-N,len);
            int res=Integer.parseInt(sub2,2);
            System.out.println("Result: "+res);
        }
        else
        {
            int res=Integer.parseInt(binary,2);
            System.out.println("Result: "+res);
        }
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 1_Q7

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement:

Miles is working on a program that involves analyzing two integers. He wants to check if either one of the integers is both:

Less than or equal to zero, and Odd. Can you help him create a program that identifies whether either of the integers meets these conditions?

Input Format

The input consists of two integers on separate lines, denoted as 'input1' and 'input2'.

Output Format

A single line with a boolean result (either 'true' or 'false') indicating whether either 'input1' or 'input2' is both less than or equal to zero and odd.

Refer to the sample output for format specifications

Sample Test Case

Input: -45

10

Output: true

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] arg){
        Scanner sc=new Scanner(System.in);
        int n1=sc.nextInt();
        int n2=sc.nextInt();

        if((n1<=0 && n1%2!=0) || (n2<=0 && n2%2!=0))
            System.out.println("true");
        else
            System.out.println("false");
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 1_Q8

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In the Kingdom of Finance, the royal treasury is managed by the treasurer, Sir Cedric. Sir Cedric tracks the daily expenses of the kingdom using an expense report that lists three major categories: food, clothing, and utilities. However, the King wants to know if the average daily expense is greater than at least two of these categories to ensure the kingdom is spending wisely.

Your task is to help Sir Cedric determine if the average daily expense is greater than two of the categories. Specifically, you need to calculate the average of the three expenses and check if it is greater than any two categories.

Note: Use the ternary operator

Input Format

Three integers a, b, and c represent the daily expenses for food, clothing, and utilities. Each integer is provided on a single line.

Output Format

The average of the three expenses, rounded to two decimal places.

A message indicating whether the average is greater than at least two of the expense categories.

1. If the average is greater than the two smallest monthly expenses, print "Average is greater than both X and Y," where X and Y are the two smallest expenses.
2. Otherwise, display "Average is not greater than two smallest expenses".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4

6

10

Output: 6.67

Average is greater than both 4 and 6

Answer

```
// You are using Java
import java.io.*;
import java.util.*;
import java.lang.Math;

class Expenses{
    public static void main(String[] args){
        Scanner sc =new Scanner(System.in);
        int a=sc.nextInt();
        int b = sc.nextInt();
        int c=sc.nextInt();

        double avg=(a+b+c)/3.0;
```

```
System.out.printf("%.2f\n",avg);

if(avg>a && avg>b)
    System.out.printf("Average is greater than both %d and %d\n", a, b);
else if(avg>a && avg>c)
    System.out.printf("Average is greater than both %d and %d\n", a, c);
else if(avg>b && avg>c)
    System.out.printf("Average is greater than both %d and %d\n", b, c);
else
    System.out.println("Average is not greater than two smallest expenses");
```

```
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 1_Q9

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Phill is a quality control manager at a manufacturing plant. He needs to verify if a sensor reading at a midpoint station (S2) falls exactly halfway between the readings of the previous station (S1) and the next station (S3). Help him by developing a program that checks if the second sensor reading is the average (midpoint) of the first and third sensor readings.

Use the relational operator to solve the program.

Input Format

The first line of input consists of an integer S1, representing the sensor reading of the first station.

The second line consists of an integer S2, representing the sensor reading of the midpoint station.

The third line consists of an integer S3, representing the sensor reading of the next station.

Output Format

The first line of output displays a boolean value representing whether the sensor reading at the midpoint station is halfway between the readings of the first and the next stations.

The second line displays one of the following:

1. If the result is true, print "The second integer is halfway between the first and third integers."
2. Otherwise, print "The second integer is not halfway between the first and third integers."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

7

10

Output: false

The second integer is not halfway between the first and third integers.

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class SensorReading{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int s1=sc.nextInt();
        int s2=sc.nextInt();
        int s3=sc.nextInt();

        int avg=(s1+s3)/2;
        if(s2==avg){
```

```
        System.out.println("true");
        System.out.println("The second integer is halfway between the first and
third integers.");
    }
else{
    System.out.println("false");
    System.out.println("The second integer is not halfway between the first
and third integers.");
}
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 1_Q10

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Aishu is supervising a construction project that needs to be completed with the help of three workers: A, B, and C.

She knows how many days each of them would take to complete the entire project individually:

A can complete it in x days, B in y days, C in z days.

Initially, all three workers (A, B, and C) work together for d1 days.

After that, C leaves, and only A and B continue for another d2 days.

Then B also leaves, and A works alone to finish the remaining work.

Your tasks is to help aishu to implement this functionality using the class WorkDistribution and Method calculateWork(int x, int y, int z, int d1, int d2)

Calculate the total work completed in the first d_1 days by A, B, and C. Calculate the work completed in the next d_2 days by A and B. Determine the remaining work after these $d_1 + d_2$ days.

Input Format

The first line of input contains five space-separated integers: $x \ y \ z \ d_1 \ d_2$

where:

x represents the Days A takes to complete the work alone

y represents the Days B takes to complete the work alone

z represents the Days C takes to complete the work alone

d_1 represents the Days A, B, and C work together

d_2 represents the Days A and B work together (after C leaves)

Output Format

The first line of output prints "Work done in first d_1 days (A+B+C):" followed by a double value rounded to 2 decimal places.

The second line of output prints "Work done in next d_2 days (A+B):" followed by a double value rounded to 2 decimal places.

The third line prints "Remaining work:" followed by a double value rounded to 2 decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 10 20 30 2 2

Output: Work done in first d_1 days (A+B+C): 0.37

Work done in next d_2 days (A+B): 0.30

Remaining work: 0.33

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class WorkDistribution{
    public static void calculateWork(int x, int y, int z, int d1, int d2){
        double abc=(1.0/x + 1.0/y + 1.0/z)*d1;
        double ab=(1.0/x + 1.0/y)*d2;
        double total=abc+ab;
        double rem=1.0 - total;

        System.out.printf("Work done in first d1 days (A+B+C): %.2f\n",abc);
        System.out.printf("Work done in next d2 days (A+B): %.2f\n",ab);
        System.out.printf("Remaining work: %.2f\n",rem);
    }

    public static void main(String[] arg){
        Scanner sc=new Scanner(System.in);
        int x=sc.nextInt();
        int y=sc.nextInt();
        int z=sc.nextInt();
        int d1=sc.nextInt();
        int d2=sc.nextInt();

        calculateWork(x,y,z,d1,d2);
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 1_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement:

"Write a program that helps identify the type of a triangle based on the lengths of its three sides. The program prompts the user to input the lengths of sides 'a', 'b', and 'c', and then it classifies the triangle as 'Equilateral' if all sides are equal, 'Isosceles' if two sides are equal, or 'Scalene' if all sides are different. Can you provide the Java code for this task?"

Input Format

The first line of the input is an integer 'a' representing the length of side 'a.'

The second line of the input is an integer 'b' representing the length of side 'b.'

The third line of the input is an integer 'c' representing the length of side 'c.'

Output Format

The program outputs a single line that specifies the type of the triangle:
"Equilateral," "Isosceles," or "Scalene."

Sample Test Case

Input: 3

4

5

Output: The triangle is Scalene

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Triangle{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int a=sc.nextInt();
        int b=sc.nextInt();
        int c=sc.nextInt();

        if((a==b)&&(a==c)&&(b==c))
            System.out.println("The triangle is Equilateral");
        else if((a==b)|| (a==c)|| (b==c))
            System.out.println("The triangle is Isosceles");
        else
            System.out.println("The triangle is Scalene");
    }
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Mandy is a software engineer working on a program to analyze two integers based on specific conditions using a logical operator. She needs to determine if both integers are odd or if at least one of them is divisible by 7.

Depending on the result, she wants to print different messages.

If the condition is met, the program should identify and print the first number that is divisible by 7 or indicate that both numbers are odd. If the condition is not met, the program should print a message indicating the condition was not met, along with the input numbers.

Input Format

The first line of input consists of an integer representing the first input number.

The second line consists of an integer representing the second input number.

Output Format

The output displays "Condition met: " followed by an integer representing the first number divisible by 7, or prints "Both numbers are odd" if the two inputs are odd.

If the condition is not met, it displays "Conditions not met: " followed by the two input integers, separated by a space.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 7

14

Output: Condition met: 7

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Numbers{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n1=sc.nextInt();
        int n2=sc.nextInt();
```

```
if((n1%2!=0 && n2%2!=0) ||(n1%7==0 || n2%7==0)){
    System.out.print("Condition met: ");

    if(n1%7==0)
        System.out.println(n1);
    else if(n2%7==0)
        System.out.println(n2);
    else //if(n1%2!=0 && n2%2!=0)
        System.out.println("Both numbers are odd");
}
else
    System.out.printf("Conditions not met: %d %d",n1,n2);
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

In the faraway land of Arithmetica, there exists an ancient calculator that can only perform bitwise operations. The calculator is locked with a secret code that only works when the number is modified using a special operation called right shifting.

The ruler of Arithmetica, King Thales, needs your help to unlock the calculator. The lock on the calculator is encoded with a number, and the calculator will only open if you apply a right shift by 2 on the number. Your task is to help King Thales determine the magic number that will unlock the ancient calculator.

Input Format

The first line of input represents an integer.

Output Format

The output should display the right-shifted value by 2 bits.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 16

Output: 4

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class MagicNumber{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int right=n>>2;
        System.out.println(right);
    }
}
```

Status : Correct

Marks : 10/10

4. Problem Statement:

Tom is tasked with writing a program that determines whether a given integer is the square of another integer. A perfect square is a number that can be expressed as the square of an integer. The program should take an integer as input and determine if it is a perfect square or not.

The task is to implement the logic to check if the provided integer is the square of an integer and return the result.

Input Format

The first line of the input contains an integer, "input", where |input| represents the absolute value of the integer.

Output Format

The output should display a boolean value, "result," which should be set to true if the input is a perfect square (the square of an integer), and false if it is not.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 16

Output: Is the integer a perfect square? true

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;
import java.lang.Math;

class PerfectSquare{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int sq=(int)Math.sqrt(n);

        System.out.print("Is the integer a perfect square? ");
        if(n==sq*sq)
            System.out.println("true");
        else
            System.out.println("false");
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S

Email: 241001162@rajalakshmi.edu.in

Roll no: 241001162

Phone: 8122081287

Branch: REC

Department: IT - Section 2

Batch: 2028

Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 1_PAH

Attempt : 1

Total Mark : 40

Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

In the Kingdom of Delivery Logistics, there is a giant truck used for transporting packages across the kingdom. The truck has a maximum capacity represented by an integer, and each package also has a specific weight. The truck's efficiency and safety depend on whether the weight of the package is below a certain threshold.

The kingdom's delivery service has a rule: if the weight of a package is less than one-third of the truck's total capacity, the package is eligible for quick processing and dispatch. However, if the weight is too heavy, the package will require special handling.

As a logistics manager, you need to check whether the weight of the package is less than one-third of the truck's total capacity.

Write a program using a ternary operator that helps determine whether the package weight meets the requirement for quick processing or if it needs special handling.

Input Format

The first line of input consists of an integer p , representing the weight of the package.

The second line consists of an integer w , representing the total weight capacity of the truck.

Output Format

The first line of output prints "One-third of Truck: X," where X is one-third of the truck's total weight capacity as a double value with two decimal places.

The second line of output displays one of the following:

1. If p is less than one-third of the truck's total weight capacity, print "Package weight is less than one-third of the truck's capacity".
2. Otherwise, print "Package weight is not less than one-third of the truck's capacity".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 13

60

Output: One-third of Truck: 20.00

Package weight is less than one-third of truck's capacity

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Logistics{
    public static void main(String[] args){
```

```
Scanner sc=new Scanner(System.in);
int p=sc.nextInt();
int w=sc.nextInt();

double oneThird=w/3.0;
System.out.printf("One-third of Truck: %.2f\n", oneThird);
if(p<oneThird)
    System.out.println("Package weight is less than one-third of truck's
capacity");
else
    System.out.println("Package weight is not less than one-third of truck's
capacity");
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Mickey and Miney are walking through a magical forest. The forest is full of enchanted stones, each with a unique number. There is a legend that says the magic power of the stones can be revealed by using a special operation. To determine the magic power of a given stone, you need to perform a bitwise AND operation with the number 15.

Each stone's number is represented by an integer, and Mickey needs to find the magic power of each stone by applying this operation.

Your task is to help Mickey compute the result of the bitwise AND operation of the given stone number with 15, and print the result.

Input Format

The input consists of a single integer.

Output Format

The output should display a single integer, which is the result of the bitwise AND operation between input and 15.

Refer to the sample output for format specifications.

Sample Test Case

Input: 25

Output: 9

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class MagicalForest{
    public static void main(String[] args){
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        int res=n & 15;
        System.out.println(res);
    }
}
```

Status : Correct

Marks : 10/10

3. PROBLEM STATEMENT:

Maria, a software developer, is working on a program to determine if two given integers which can be either positive or negative integers have the same parity (both even or both odd). She needs your help in writing this program.

Write a program that takes two integers as input and checks if both integers are either even or odd.

Input Format

The input consists of two lines:

The first line consists of an integer (input1) which can be either positive or negative.

The second line consists of an integer (input2) which can be either positive or negative.

Output Format

The output is displayed in the following format:

If both integers have the same parity (i.e., both even or both odd), print:

"Both integers are either even or odd"

Otherwise, print:

"The integers have different parities"

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 2

-4

Output: Both integers are either even or odd

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class OddEven{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n1=sc.nextInt();
        int n2=sc.nextInt();
```

```
if((n1%2==0 && n2%2==0) || (n1%2!=0 && n2%2!=0))  
    System.out.println("Both integers are either even or odd");  
else  
    System.out.println("The integers have different parities");  
}  
}
```

Status : Correct

Marks : 10/10

4. PROBLEM STATEMENT:

Maria, a software developer, is working on a project to create a simple program to determine which of two integers is closest to zero. The integers can be either positive or negative. The program needs to take two integer inputs and calculate which one is closer to zero. If both integers are equidistant from zero, the program should return 0.

Input Format

The input contains two lines:

The first line of the input contains an integer, which can be either a positive or a negative integer.

The second line of the input contains an integer, which can be either a positive or a negative integer.

Output Format

The output displays the integer that is closest to zero in the following format:

"The integer closest to zero is: [closest_integer]"

Here, [closest_integer] should be replaced with the integer that is closer to zero based on its absolute value.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5

8

Output: The integer closest to zero is: 5

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;
import java.lang.Math;

class Closest{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int closest;
        int n1=sc.nextInt();
        int n2=sc.nextInt();
        int d1=Math.abs(n1);
        int d2=Math.abs(n2);

        if(d1<d2)
            closest=n1;
        else if(d1>d2)
            closest=n2;
        else
            closest=0;
        System.out.println("The integer closest to zero is: "+closest);
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 2_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 15

Section 1 : MCQ

1. What will be the output of the following code?

```
public class Main {  
    public static void main(String[] args) {  
        int sum = 0;  
        for(int i = 1; i <= 5; i++) {  
            sum += i;  
        }  
        System.out.println(sum);  
    }  
}
```

Answer

15

Status : Correct

Marks : 1/1

2. What will be the output of the following code?

```
class LoopTest {  
    public static void main(String[] args) {  
        int i = 1;  
        while (i > 0) {  
            System.out.print(i + " ");  
            i++;  
            if (i == 5) break;  
        }  
    }  
}
```

Answer

1 2 3 4

Status : Correct

Marks : 1/1

3. What will be the output of the following Java code snippet?

```
public class Main {  
    public static void main(String[] args) {  
        int score = 75;  
        if(score >= 90) {  
            System.out.println("Grade: A");  
        } else if(score >= 80) {  
            System.out.println("Grade: B");  
        } else if(score >= 70) {  
            System.out.println("Grade: C");  
        } else {  
            System.out.println("Grade: D");  
        }  
    }  
}
```

Answer

Grade: C

Status : Correct

Marks : 1/1

4. What will be the output of the following code?

```
class Test {  
    public static void main(String[] args) {  
        int a = 4, b = 5;  
        if ((a + b) % 2 == 0)  
            System.out.print("Even");  
        else  
            System.out.print("Odd");  
    }  
}
```

Answer

Odd

Status : Correct

Marks : 1/1

5. What will be the output of the following code?

```
class LoopTest {  
    public static void main(String[] args) {  
        int i = 1;  
        do {  
            System.out.print(i + " ");  
            i *= 2;  
        } while (i <= 8);  
    }  
}
```

Answer

1 2 4 8

Status : Correct

Marks : 1/1

6. What will be the output of the following code?

```
public class Main {  
    public static void main(String[] args) {  
        int i = 1;  
    }  
}
```

```
001162  while(i < 10) {  
001163      i += 2;  
001164  }  
001165  System.out.println(i);  
001166 }
```

Answer

11

Status : Correct

Marks : 1/1

7. What will be the output of the following code?

```
public class Main {  
    public static void main(String[] args) {  
        for(int i = 1; i <= 20; i = i * 2) {  
            System.out.print(i + " ");  
        }  
    }  
}
```

Answer

1 2 4 8 16

Status : Correct

Marks : 1/1

8. What will be the output of the following code?

```
class Main {  
    public static void main(String[] args) {  
        for (int i = 5; i > 0; i--) {  
            System.out.print(i + " ");  
        }  
    }  
}
```

Answer

54321

Status : Correct

Marks : 1/1

9. What will be the output of the following code?

```
class Test {  
    public static void main(String[] args) {  
        int x = 5, y = 2;  
        if (x + y == 10)  
            System.out.print("Ten");  
        else if (x - y == 3)  
            System.out.print("Three");  
        else  
            System.out.print("None");  
    }  
}
```

Answer

Three

Status : Correct

Marks : 1/1

10. What will be the output of the following code?

```
class ConditionTest {  
    public static void main(String[] args) {  
        int x = 10;  
        if (x > 5)  
            System.out.print("High");  
    }  
}
```

Answer

High

Status : Correct

Marks : 1/1

11. What will be the output of the following code?

```
class Test {  
    public static void main(String[] args) {  
        int num = 15;  
        if (num > 10)  
            if (num % 3 == 0)  
                System.out.print("Divisible");  
            else  
                System.out.print("Not Divisible");  
    }  
}
```

Answer

Divisible

Status : Correct

Marks : 1/1

12. What will be the output of the following code?

```
class ConditionTest {  
    public static void main(String[] args) {  
        int a = 7;  
        if (a == 7)  
            System.out.print("Match");  
        else  
            System.out.print("No Match");  
    }  
}
```

Answer

Match

Status : Correct

Marks : 1/1

13. What will be the output of the following Java code snippet?

```
public class Main {  
    public static void main(String[] args) {  
        int day = 4;  
        String result = "";
```

```
switch(day) {  
    case 1:  
        result = "Monday";  
        break;  
    case 2:  
        result = "Tuesday";  
        break;  
    case 3:  
        result = "Wednesday";  
        break;  
    default:  
        result = "Other Day";  
}  
System.out.println(result);  
}
```

Answer

Other Day

Status : Correct

Marks : 1/1

14. What will be the output of the following code?

```
class Loop {  
    public static void main(String[] args) {  
        for (int i = 1; i <= 3; i++) {  
            for (int j = 1; j <= 2; j++) {  
                System.out.print(i + " " + j + " ");  
            }  
        }  
    }  
}
```

Answer

11 12 21 22 31 32

Status : Correct

Marks : 1/1

15. What will be the output of the following code?

```
public class Main {  
    public static void main(String[] args) {  
        int i = 10;  
        do {  
            System.out.print(i + " ");  
            i -= 3;  
        } while(i > 0);  
    }  
}
```

Answer

10 7 4 1

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 2_Q1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Arun is working on a project to automate the process of determining whether a student has passed or failed based on their subject marks.

He aims to create a simple program that takes positive integers as marks for five subjects from the user. If the average of the marks is greater than or equal to 50, the student has passed the exam. Otherwise, the student has failed.

Help Arun to implement the project.

Input Format

The input consists of five space-separated integers, representing the marks in five subjects.

Output Format

The first line of output prints "Average score: " followed by an integer representing the average score.

The second line prints one of the following:

1. If the condition is satisfied, print "The student has passed".
2. Otherwise, the output prints "The student has failed".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 50 60 70 80 90

Output: Average score: 70

The student has passed

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Marks{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int[] arr=new int[5];
        int marks, sum=0;
        for(int i=0;i<5;i++){
            marks=sc.nextInt();
            sum=sum+marks;
        }
        int avg=sum/5;
        System.out.println("Average score: "+avg);
        if(avg>=50)
            System.out.println("The student has passed");
        else
            System.out.println("The student has failed");
    }
}
```

}

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S

Email: 241001162@rajalakshmi.edu.in

Roll no: 241001162

Phone: 8122081287

Branch: REC

Department: IT - Section 2

Batch: 2028

Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 2_Q2

Attempt : 1

Total Mark : 10

Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Samantha is a diligent math student who is exploring the world of programming. She is learning Java and has recently studied conditional statements. One day, her teacher gives her an interesting problem to solve, which takes a number as input and checks whether it is a multiple of 5 or 7.

Help her complete the task.

Input Format

The input consists of a single integer N, representing the number to be checked.

Output Format

If the number is a multiple of 5 but not 7, the output prints "N is a multiple of 5".

If the number is a multiple of 7, the output prints "N is a multiple of 7".

Otherwise the output prints "N is neither multiple of 5 nor 7" where N is an entered integer.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 10

Output: 10 is a multiple of 5

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Multiple{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();

        if(n%5==0 && n%7!=0)
            System.out.println(n+" is a multiple of 5");
        else if(n%7==0)
            System.out.println(n+" is a multiple of 7");
        else
            System.out.println(n+" is neither multiple of 5 nor 7");
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 2_Q3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

John is a fitness trainer, and he wants to use the BMI calculator to assess the body mass index of his clients. He has a list of clients based on their height and weight.

John plans to write a program to quickly determine the BMI and provide a classification for each client.

If BMI is less than 18.5, the program will classify it as "Underweight"
If BMI is between 18.6 and 24.9, the program will classify it as "Normal Weight"
If BMI is between 25.0 and 29.9, the program will classify it as "Overweight"
If BMI is 30.0 or higher, the program will classify it as "Obese"

Note: Formula to calculate BMI = weight/(height*height)

Input Format

The first line of input consists of a double value, representing the height of the person in meters.

The second line consists of a double value, representing the weight of the person in kilograms.

Output Format

The first line of output prints "BMI: " followed by a double (rounded to two decimal places) representing the calculated BMI.

The second line prints "Classification: " followed by a string indicating the BMI category (Underweight, Normal Weight, Overweight, or Obese).

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1.2

45.2

Output: BMI: 31.39

Classification: Obese

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class BMI{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        double h=sc.nextDouble();
        double w=sc.nextDouble();
        double bmi=w/(h*h);

        String c="";
        if(bmi<18.5)
            c="Underweight";
        else if(bmi>18.6 && bmi<24.9)
            c="Normal Weight";
```

```
        else if(bmi>25.0 && bmi<29.9)
            c="Overweight";
        else
            c="Obese";

        System.out.printf("BMI: %.2f\n", bmi);
        System.out.println("Classification: "+c);
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 2_Q4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Amit wants to evaluate the depreciation of his car over time to understand its current value and categorize it based on that value.

Write a program that helps him determine the current value of his car after a certain number of years of depreciation and classify it into one of three categories:

High: If the current value is greater than 10,000.
Medium: If the current value is between 5,000 and 10,000, both inclusive.
Low: If the current value is less than 5,000.

The depreciation rate of the car is 15% per year. The program should calculate the current value of the car after applying this depreciation over the given number of years and print the current value along with the category.

Input Format

The first line of input consists of an integer, representing the initial cost of the car.

The second line consists of an integer, representing the number of years the car has been depreciating.

Output Format

The first line of output prints a double value, representing the current value of the car, rounded off to two decimal places "Current Value: <value>".

The second line prints its category "Category: <categories>".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 20000

5

Output: Current Value: 8874.11

Category: Medium

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;
import java.lang.Math;

class CarValue{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        double cost=sc.nextDouble();
        int n=sc.nextInt();
        double value=cost;
        //double value= cost*Math.pow(1-0.15, n);
        for(int i=0; i<n; i++)
            value-=value*0.15;
```

```
String c="";
if(value>10000)
    c="High";
else if(value>=5000)
    c="Medium";
else
    c="Low";
System.out.printf("Current Value: %.2f\n",value);
System.out.println("Category: "+c);

}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 2_Q5

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Ted, the computer science enthusiast, has accepted the challenge of writing a program that checks if the number of digits in an integer matches the sum of its digits.

Guide Ted in designing and writing the code to solve this problem using a 'do-while' loop.

Input Format

The input consists of an integer N, representing the number to be checked.

Output Format

If the sum is equal to the number of digits, print "The number of digits in N matches the sum of its digits."

Else, print "The number of digits in N does not match the sum of its digits."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 20

Output: The number of digits in 20 matches the sum of its digits.

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int c=0;
        int num=n, sum=0;
        do{
            int i=num%10;

            sum+=i;
            c++;
            num=num/10;

        }while(num>0);
        if(c==sum)
            System.out.printf("The number of digits in %d matches the sum of its
digits.",n);
        else
            System.out.printf("The number of digits in %d does not match the sum of
its digits.",n);
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 2_Q6

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Maya, a student in an arts and crafts class, wants to create a pattern using stars (*) in a specific format. She plans to use a program to help her construct the pattern.

Write a program that takes an integer as input and constructs the following pattern using nested for loops.

Input: 5

Output:

*
**

```
***  
****  
*****  
****  
***  
**  
*
```

Input Format

The input consists of a number (integer) representing the number of rows.

Output Format

The output displays the required pattern.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5

Output: *

```
**  
***  
****  
*****  
***  
**  
*
```

Answer

```
// You are using Java  
import java.io.*;  
import java.util.Scanner;  
  
class Main{
```

```
public static void main(String[] args){  
    Scanner sc=new Scanner(System.in);  
    int n=sc.nextInt();  
  
    for(int i=1;i<=n;i++){  
        for(int j=1;j<=i;j++){  
            System.out.print("* ");  
        }  
        System.out.println();  
    }  
  
    for(int i=n-1; i>=1;i--){  
        for(int j=i; j>=1;j--){  
            System.out.print("* ");  
        }  
        System.out.println();  
    }  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 2_Q7

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

You are taking part in a coding challenge where your task is to design a program that conjures a mesmerizing numerical pyramid pattern. The enchanting pattern is fashioned using a for loop and is customized based on user input.

Participants are prompted to unveil the pyramid's magic by specifying its height - essentially dictating the number of rows in this spellbinding creation.

Write a program that employs to weave this captivating numerical pyramid as shown below.

Example

Input:

4

Output:

Input Format

The input consists of a positive integer n representing the number of rows in the pattern.

Output Format

The output prints the required pyramid pattern, as shown in the sample output.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4

Output: 1

123

12345

1234567

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();

        for(int i=1;i<=n;i++){
            for(int j=1;j<=n-i;j++)
                System.out.print(" ");
            for(int k=1;k<=(2*i)-1;k++)
                System.out.print(k);
        }
    }
}
```

```
        } System.out.println();
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 2_Q8

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

A bank generates secure codes using 3-digit numbers where each digit is unique, and the code must be divisible by 3. You are tasked with generating the first N such codes based on user input, ensuring the digits are unique and the number is divisible by 3.

Note: Use nested for loops to solve.

Input Format

The first line contains an integer N representing the number of valid codes to generate.

Output Format

The output prints N lines, each line contains a valid 3-digit code.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

Output: 102

105

108

120

123

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int count=0;

        for(int i=1;i<=9;i++){
            for(int j=0;j<=9 && count<n;j++){
                if(j==i)
                    continue;

                for(int k=0;k<=9 && count<n;k++){
                    if(i==k || j==k)
                        continue;
                    int num=i*100 + j*10 + k;

                    if(num%3==0){
                        System.out.println(num);
                        count++;
                        if(count==n)
                            continue;
                    }
                }
            }
        }
    }
}
```

```
    } } }
```

Status : Correct

```
241001162
```

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 2_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Raj is solving a physics problem involving projectile motion, where he needs to calculate the time a ball hits the ground using a quadratic equation of the form $ax^2 + bx + c = 0$. Depending on the coefficients, the ball may hit the ground once, twice, or not at all in real time.

Help Raj find all real roots of the equation, if any.

Note: discriminant = $b^2 - 4ac$

Input Format

The input consists of three space-separated doubles a, b, and c, representing the coefficients of the quadratic equation.

Output Format

If there are two real roots, print:

- "Two real solutions:"
- "Root1 = <value>"
- "Root2 = <value>"

If there is one real root, print:

- "One real solution:"
- "Root = <value>"

If there are no real roots, print:

- "There are no real solutions."

Note: values are rounded to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1 6 9

Output: One real solution:

Root = -3.00

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;
import java.lang.Math;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int a=sc.nextInt();
        int b=sc.nextInt();
        int c=sc.nextInt();

        double D=b*b - 4*a*c;
```

```
double r1=(-b + Math.sqrt(D))/(2*a);
double r2=(-b - Math.sqrt(D))/(2*a);

if(D>0){
    System.out.println("Two real solutions:");
    System.out.printf("Root1 = %.2f\n", r1);
    System.out.printf("Root2 = %.2f", r2);
}
else if(D==0){
    System.out.println("One real solution:");
    if(r1==0)
        System.out.printf("Root = %.2f", r2);
    else
        System.out.printf("Root = %.2f", r1);
}
else{
    System.out.println("There are no real solutions.");
}

}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Noah is analyzing numbers within a given range [A, B] and wants to calculate a special sum. For each number in the range, he calculates the product of its odd digits (ignoring even digits). If the number contains no odd digits, it is skipped. The sum of these products for all numbers in the range is the result.

Write a program to compute this sum.

Example

Input:

10 12

Output:

3

Explanation:

For 10, odd digits = 1, product = 1.

For 11, odd digits = 1, 1, product = $1 * 1 = 1$.

For 12, odd digits = 1, product = 1.

Total sum = $1 + 1 + 1 = 3$

Input Format

The input consists of two space-separated integers A and B, representing the inclusive range boundaries.

Output Format

The output prints a single integer representing the sum of the products of odd digits for all numbers in the range.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 10 12

Output: 3

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int a=sc.nextInt();
        int b=sc.nextInt();

        int sum=0;
        for(int i=a;i<=b;i++){
            int num=i;
            int prod=1;
            while(num>0){
                int digit=num%10;
                if(digit%2!=0)
                    prod*=digit;
                num/=10;
            }
            sum+=prod;
        }
        System.out.println(sum);
    }
}
```

```
int p=1;
boolean odd=false;
int temp=i;

while(temp>0){
    int r=temp%10;
    if(r%2!=0){
        p*=r;
        odd=true;
    }
    temp=temp/10;
}

if(odd)
    sum+=p;

}
System.out.println(sum);
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

Ted, the computer science enthusiast, has accepted the challenge of writing a program that checks if the number of digits in an integer matches the sum of its digits.

Guide Ted in designing and writing the code to solve this problem using a 'do-while' loop.

Input Format

The input consists of an integer N, representing the number to be checked.

Output Format

If the sum is equal to the number of digits, print "The number of digits in N matches the sum of its digits."

Else, print "The number of digits in N does not match the sum of its digits."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 20

Output: The number of digits in 20 matches the sum of its digits.

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int c=0, temp=n, sum=0;

        do{
            int r=temp%10;
            c++;
            sum+=r;
            temp/=10;
        }while(temp>0);

        if(c==sum)
            System.out.printf("The number of digits in %d matches the sum of its
digits.",n);
        else
            System.out.printf("The number of digits in %d does not match the sum of
its digits.",n);
    }
}
```

Status : Correct

Marks : 10/10

4. Problem Statement

Samantha is a diligent math student who is exploring the world of programming. She is learning Java and has recently studied conditional statements. One day, her teacher gives her an interesting problem to solve, which takes a number as input and checks whether it is a multiple of 5 or 7.

Help her complete the task.

Input Format

The input consists of a single integer N, representing the number to be checked.

Output Format

If the number is a multiple of 5 but not 7, the output prints "N is a multiple of 5".

If the number is a multiple of 7, the output prints "N is a multiple of 7".

Otherwise the output prints "N is neither multiple of 5 nor 7" where N is an entered integer.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 10

Output: 10 is a multiple of 5

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();

        if(n%5==0 && n%7!=0)
            System.out.println(n+" is a multiple of 5");
    }
}
```

```
        else if(n%7==0)
            System.out.println(n+" is a multiple of 7");
        else
            System.out.println(n+" is neither multiple of 5 nor 7");
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 2_PAH

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Ravi wants to estimate the total utility bill for a household based on the consumption of electricity, water, and gas.

Write a program to calculate the total bill using the following criteria:

The cost per unit for electricity is 0.12, for water is 0.05, and for gas is 0.08. A discount is applied to the total cost based on the following conditions: If the total cost is 100 or more, a 10% discount is applied. If the total cost is between 50 and 99.99, a 5% discount is applied. No discount is applied if the total cost is less than 50.

The program should output the total bill after applying the discount with two decimal places.

Input Format

The input consists of three double values, representing the number of units consumed for electricity, water, and gas respectively.

Output Format

The output prints a double value, representing the total bill after applying the discount, formatted to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1000.0

200.0

100.0

Output: 124.20

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Bill{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        double e=sc.nextDouble();
        double w=sc.nextDouble();
        double g=sc.nextDouble();

        double elec=e*0.12;
        double water=w*0.05;
        double gas=g*0.08;

        double total=elec+water+gas;
        double discount;

        if(total>=100)
            discount=total-total*0.1;
        else if(total>=50 && total<=99.99)
            discount=total-total*0.05;
        else
```

```
        discount=total;  
    }  
    System.out.printf("%.2f",discount);  
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Sampad is a high school teacher who wants to convert numeric grades into letter grades.

Write a program that accepts a numeric grade as input. The program should then convert this numeric grade into a letter grade based on specific conditions. The letter grades are A, B, C, D and F.

The conversion is determined by the following conditions:

If the numeric grade is 90 or higher, it's an "A"
If the numeric grade is between 80 and 89 (inclusive), it's a "B"
If the numeric grade is between 70 and 79 (inclusive), it's a "C"
If the numeric grade is between 60 and 69 (inclusive), it's a "D"
If the numeric grade is below 60, it's an "F"

Input Format

The input consists of an integer representing the numeric grade of the student.

Output Format

The output prints the letter grade corresponding to the input numeric grade as "Letter Grade: <grade>".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 85

Output: Letter Grade: B

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Grades{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int m=sc.nextInt();
        char grade='';

        if(m>=90)
            grade='A';
        else if(m>=80 && m<=89)
            grade='B';
        else if(m>=70 && m<=79)
            grade='C';
        else if(m>=60 && m<=69)
            grade='D';
        else
            grade='F';

        System.out.println("Letter Grade: "+grade);
    }
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

Rohit is tasked with designing a program to analyze the digits of a given integer.

Write a program to help Rohit that takes an integer as input and identifies the minimum odd digit and the maximum even digit present in the number. If no odd or even digits are present, display appropriate messages.

Implement the solution using a 'while' loop to iterate through the digits of the given number.

Input Format

The input consists of an integer n.

Output Format

The first line of output prints the message "Minimum odd digit: " followed by an integer representing the smallest odd digit found in the input number.

If no odd digit exists, it prints "There are no odd digits in the number."

The second line of output prints the message "Maximum even digit: " followed by an integer representing the largest even digit found in the input number.

If no even digit exists, it prints "There are no even digits in the number."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3465

Output: Minimum odd digit: 3

Maximum even digit: 6

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class OddEven{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int[] even=new int[10];
        int[] odd=new int[10];
        int evencount=0, oddcount=0;
        int temp=n;
        while(temp>0){
            int r=temp%10;
            if(r%2==0){
                even[evencount]=r;
            }
            else{
                odd[oddcount]=r;
            }
            temp=temp/10;
        }
        System.out.println("Minimum odd digit: "+odd[0]);
        System.out.println("Maximum even digit: "+even[evencount]);
    }
}
```

```

        evencount++;
    }
    else{
        odd[oddcount]=r;
        oddcount++;
    }
    temp=temp/10;
}

if(oddcount>0){
    int minodd=odd[0];
    for(int i=1;i<oddcount;i++){
        if(odd[i]<minodd)
            minodd=odd[i];
    }
    System.out.println("Minimum odd digit: "+minodd);
}
else
    System.out.println("There are no odd digits in the number.");

if(evencount>0){
    int maxeven=even[0];
    for(int i=1;i<evencount;i++){
        if(even[i]>maxeven)
            maxeven=even[i];
    }
    System.out.println("Maximum even digit: "+maxeven);
}
else
    System.out.println("There are no even digits in the number.");
}
}

```

Status : Correct

Marks : 10/10

4. Problem Statement

You are given a number of distribution centers (rows) and are tasked with generating a zigzag shipment route pattern. Each shipment route should alternate between left-to-right and right-to-left, as described below.

The program should print the zigzag pattern with a tab (\t) separating the columns. For each row, the shipment numbers should follow a diagonal pattern where numbers are placed in a zigzag, left to right on odd rows and right to left on even rows.

Input Format

The input consists of an integer N, which represents the number of distribution centers (rows) for the zigzag pattern.

Output Format

The output prints the zigzag pattern with N rows, formatted with a tab space (\t) separating the columns.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

Output: 1

2 6
3 7 10
4 8 11 13
5 9 12 14 15

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int[][] arr=new int[n][n];
        final String gap=" ";
        for(int i=0; i<n; i++){
            for(int j=0; j<n; j++){
                if((i+j)%2==0)
                    arr[i][j]=i+1;
                else
                    arr[i][j]=n-i;
            }
        }
        for(int i=0; i<n; i++){
            for(int j=0; j<n; j++){
                System.out.print(arr[i][j] + gap);
            }
        }
    }
}
```

```
for(int i=0; i<n; i++){
    for(int t=0; t<n-1-i; t++)
        System.out.print(gap);

    int v=i+1;
    for(int j=0; j<=i; j++){
        System.out.print(v);
        if(j<i)
            System.out.print(gap);
        v+=(n-1-j);
    }
    System.out.println();
}
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 3_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 15

Section 1 : MCQ

1. What will be the output of the following code?

```
class Q {  
    public static void main(String[] args) {  
        int[] a = {1, 2, 3, 4};  
        for (int i = 0; i < a.length; i++) {  
            if (a[i] % 2 == 0)  
                a[i] = 0;  
        }  
        System.out.println(a[1] + " " + a[3]);  
    }  
}
```

Answer

0 0

Status : Correct

Marks : 1/1

2. What will be the output of the following code?

```
public class Test {  
    public static void main(String[] args) {  
        int[] x = {4, 8, 12};  
        int result = x[0] * x[2];  
        System.out.println(result);  
    }  
}
```

Answer

48

Status : Correct

Marks : 1/1

3. What will be the output of the following code?

```
class Q {  
    public static void main(String[] args) {  
        int[] nums = {4, 2, 9, 5};  
        int max = nums[0];  
        for (int i = 1; i < nums.length; i++) {  
            if (nums[i] > max)  
                max = nums[i];  
        }  
        System.out.println(max);  
    }  
}
```

Answer

9

Status : Correct

Marks : 1/1

4. What will be the output of the following code?

```
class Q {  
    public static void main(String[] args) {  
        int[][] a = {  
            {1, 2},  
            {3, 4}  
        };  
        for (int i = 0; i < a.length; i++) {  
            for (int j = 0; j < a[0].length; j++) {  
                System.out.print(a[i][j] + " ");  
            }  
        }  
    }  
}
```

Answer

1234

Status : Correct

Marks : 1/1

5. What will be the output of the following code?

```
class Q {  
    public static void main(String[] args) {  
        int[] a = {1, 2, 1, 3, 1, 4};  
        int count = 0;  
        for (int i = 0; i < a.length; i++) {  
            if (a[i] == 1) count++;  
        }  
        System.out.println(count);  
    }  
}
```

Answer

3

Status : Correct

Marks : 1/1

6. What will be the output of the following code?

```
241001162 class Sample {  
    public static void main(String[] args) {  
        int[][] data = {  
            {1, 2},  
            {3, 4}  
        };  
        int sum = 0;  
  
        for (int[] row : data) {  
            for (int val : row) {  
                sum += val;  
            }  
        }  
        System.out.println("Sum = " + sum);  
    }  
}
```

Answer

Sum = 10

Status : Correct

Marks : 1/1

7. What will be the output of the given code?

```
public class Main {  
    public static void main(String[] args) {  
        int[] arr = {1, 2, 3, 4, 5};  
        int n = arr.length;  
        int temp = arr[0];  
  
        for (int i = 0; i < n - 1; i++) {  
            arr[i] = arr[i + 1];  
        }  
        arr[n - 1] = temp;  
  
        for (int num : arr) {  
            System.out.print(num + " ");  
        }  
    }  
}
```

```
241001162  
    }  
}
```

Answer

2 3 4 5 1

Status : Correct

Marks : 1/1

8. What will be the output of the following code?

```
class M {  
    public static void main(String[] args) {  
        int[][] arr = {  
            {1, 2},  
            {3, 4},  
            {5, 6}  
        };  
  
        for (int i = 0; i < arr.length; i++) {  
            System.out.print(arr[i][0] + " ");  
        }  
    }  
}
```

Answer

1 3 5

Status : Correct

Marks : 1/1

9. What will be the output of the following code?

```
class ReverseArray {  
    public static void main(String[] args) {  
        int[] a = {1, 2, 3, 4};  
        for (int i = 0; i < a.length / 2; i++) {  
            int temp = a[i];  
            a[i] = a[a.length - 1 - i];  
            a[a.length - 1 - i] = temp;  
        }  
    }  
}
```

```
        }
        for (int i : a)
            System.out.print(i + " ");
    }
}
```

Answer

4 3 2 1

Status : Correct

Marks : 1/1

10. What will be the output of the following code?

```
class Q {
    public static void main(String[] args) {
        int[][] arr = {
            {5, 6, 7},
            {8, 9, 10}
        };
        System.out.println(arr[0][2]);
    }
}
```

Answer

7

Status : Correct

Marks : 1/1

11. What will be the output of the following code?

```
class Q {
    public static void main(String[] args) {
        int[] a = {1, 2, 3, 4};
        for (int i = 0; i < a.length / 2; i++) {
            int temp = a[i];
            a[i] = a[a.length - 1 - i];
            a[a.length - 1 - i] = temp;
        }
        System.out.println(a[0]);
    }
}
```

```
}
```

Answer

4

Status : Correct

Marks : 1/1

12. What will be the output of the following code?

```
class Sample {  
    public static void main(String[] args) {  
        int[][] matrix = {  
            {1, 2, 3},  
            {4, 5, 6}  
        };  
        System.out.println(matrix[1][2]);  
    }  
}
```

Answer

6

Status : Correct

Marks : 1/1

13. What will be the output of the following code?

```
class Q {  
    public static void main(String[] args) {  
        int[][] a = {  
            {1, 2},  
            {3, 4}  
        };  
        int sum = 0;  
        for (int i = 0; i < a.length; i++)  
            for (int j = 0; j < a[0].length; j++)  
                sum += a[i][j];  
        System.out.println(sum);  
    }  
}
```

}

Answer

10

Status : Correct

Marks : 1/1

14. What will be the output of the following code?

```
class Q {  
    public static void main(String[] args) {  
        int[] nums = {3, 6, 7, 2, 8};  
        int sum = 0;  
        for (int i = 0; i < nums.length; i++) {  
            if (nums[i] % 2 == 0)  
                sum += nums[i];  
        }  
        System.out.println(sum);  
    }  
}
```

Answer

16

Status : Correct

Marks : 1/1

15. What will be the output of the following code?

```
class Sample {  
    public static void main(String[] args) {  
        int[] a = {1, 2, 3};  
        int product = 1;  
        for (int i = 0; i < a.length; i++) {  
            product *= a[i];  
        }  
        System.out.println(product);  
    }  
}
```

Answer

6

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 3_Q1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Rosh is intrigued by numerical patterns. Today, she stumbled upon a puzzle while working with arrays. She wants to compute the sum of the third-largest and second-smallest elements from a list of integers. She seeks your help to implement a program that solves this for her efficiently.

Input Format

The first line of input is an integer N, representing the size of the array.

The second line of input consists of N space-separated integers, representing the elements of the array.

Output Format

The output displays a single integer representing the sum of the third-largest and second-smallest elements in the array.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 10
10 20 30 40 50 60 70 80 90 100
Output: 100

Answer

```
// You are using Java
import java.io.*;
import java.util.*;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int[] arr=new int[n];
        for(int i=0;i<n;i++){
            arr[i]=sc.nextInt();

        Arrays.sort(arr);
        int sum=arr[n-3]+arr[1];
        System.out.print(sum);
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 3_Q2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Monica is interested in finding a treasure but the key to opening is to get the sum of the main diagonal elements and secondary diagonal elements.

Write a program to help Monica find the diagonal sum of a square 2D array.

Note: The main diagonal of the array consists of the elements traversing from the top-left corner to the bottom-right corner. The secondary diagonal includes elements from the top-right corner to the bottom-left corner.

Input Format

The first line of input consists of an integer N, representing the number of rows and columns.

The following N lines consist of N space-separated integers, representing the 2D array elements.

Output Format

The first line of output prints "Sum of the main diagonal: " followed by an integer, representing the sum of the main diagonal.

The second line prints "Sum of the secondary diagonal: " followed by an integer, representing the sum of the secondary diagonal.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3
1 2 3
4 5 6
7 8 9

Output: Sum of the main diagonal: 15
Sum of the secondary diagonal: 15

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int[][] arr=new int[n][n];
        for(int i=0;i<n;i++){
            for(int j=0;j<n;j++){
                arr[i][j]=sc.nextInt();
            }
        }
        int sumMD=0, sumSD=0;
        for(int i=0;i<n;i++){
            for(int j=0;j<n;j++){
                if(i==j)
                    sumMD+=arr[i][j];
                if(i+j==n-1)
                    sumSD+=arr[i][j];
            }
        }
        System.out.println("Sum of the main diagonal: "+sumMD);
        System.out.println("Sum of the secondary diagonal: "+sumSD);
    }
}
```

```
        sumMD+=arr[i][j];
        if((i+j)==n-1)
            sumSD+=arr[i][j];
    }
}

System.out.println("Sum of the main diagonal: "+sumMD);
System.out.println("Sum of the secondary diagonal: "+sumSD);
}
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 3_Q3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

You are developing a warehouse management system for a shipping company. The system uses an integer array to represent the weights of packages in a specific order. To verify that the weight capacity is not exceeded, the program needs to calculate the sum of the weights of the first and last packages in the list.

Task:

Write a code to calculate the sum of the weights of the first and last packages in the list. The program should take an integer array as input and return the total weight of the first and last packages.

Input Format

The first line of the input is an integer N representing the size of the array.

The second line of the input is N space-separated integer values.

Output Format

The output is displayed in the following format:

"Sum of the first and last elements: <>Sum<>"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
10 20 30 40 50

Output: Sum of the first and last elements: 60

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int[] arr=new int[n];

        for(int i=0;i<n;i++)
            arr[i]=sc.nextInt();

        int sum=arr[0]+arr[n-1];
        System.out.println("Sum of the first and last elements: "+sum);
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 3_Q4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Sesha is developing a weather monitoring system for a region with multiple weather stations. Each weather station collects temperature data hourly and stores it in a 2D array.

Write a program that can add the temperature data from two different weather stations to create a combined temperature record for the region.

Input Format

The first line of input consists of two space-separated integers N and M, representing the number of rows and columns of the matrices, respectively.

The next N lines consist of M space-separated integers, representing the values of the first matrix.

The following N lines consist of M space-separated integers, representing the values of the second matrix.

Output Format

The output prints the addition of the two matrices in N rows and M columns, representing the combined temperature record.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3 3

1 2 3

4 5 6

7 8 9

1 1 1

2 2 2

3 3 3

Output: 2 3 4

6 7 8

10 11 12

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int m=sc.nextInt();
        int[][] arr1=new int[n][m];
        int[][] arr2=new int[n][m];

        for(int i=0;i<n;i++){
            for(int j=0;j<m;j++)
                arr1[i][j]=sc.nextInt();
        }
    }
}
```

```
for(int i=0;i<n;i++){
    for(int j=0;j<m;j++)
        arr2[i][j]=sc.nextInt();
}

int[][] res=new int[n][m];
for(int i=0;i<n;i++){
    for(int j=0;j<m;j++){
        res[i][j] = arr1[i][j] + arr2[i][j];
    }
}

for(int i=0;i<n;i++){
    for(int j=0;j<m;j++)
        System.out.print(res[i][j]+" ");
    System.out.println();
}
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 3_Q5

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Sharon is creating a program that finds the first repeated element in an integer array. The program should efficiently identify the first element that appears more than once in the given array. If no such element is found, it should appropriately display a message.

Help Sharon to complete the program.

Input Format

The first line of input consists of an integer n, representing the number of elements in the array.

The second line consists of n space-separated integers, representing the array elements.

Output Format

If a repeated element is found, print the first element that appears more than once.

If no repeated element is found, print "No repeated element found in the array".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 8
12 21 13 14 21 36 47 21

Output: 21

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int[] arr=new int[n];
        for(int i=0;i<n;i++){
            arr[i]=sc.nextInt();

        int found=0;

        for(int i=0;i<n;i++){
            for(int j=i+1;j<n;j++){
                if(arr[i]==arr[j]){
                    found=arr[i];
                    break;
                }
            }
            if(found!=0)
                break;
        }
    }
}
```

```
        if(found!=0)
            System.out.println(found);
        else
            System.out.println("No repeated element found in the array");
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 3_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement:

Imagine you have an array of integer values, and you're tasked with identifying a pair of elements within the array. This pair of elements should have a sum that is the closest to zero when compared to any other pair in the array.

Your goal is to create a program that solves this problem efficiently. The program should accept an array of integers and return the pair of elements whose sum is closest to zero.

Input Format

The first line of the input is an integer N representing the size of the array.

The second line of the input contains N space-separated integer values.

Output Format

The output is displayed in the following format:

"Pair with the sum closest to zero: {value} and {value}"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

9 10 -3 -5 -2

Output: Pair with the sum closest to zero: 9 and -5

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;
import java.lang.Math;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int[] arr=new int[n];

        for(int i=0;i<n;i++)
            arr[i]=sc.nextInt();

        int minsum=arr[0]+arr[1];
        int n1=arr[0];
        int n2=arr[1];
        for(int i=0;i<n-1;i++){
            for(int j=i+1;j<n;j++){
                int sum=arr[i]+arr[j];
                if(Math.abs(sum)<Math.abs(minsum)){
                    minsum=sum;
                    n1=arr[i];
                    n2=arr[j];
                }
            }
        }
    }
}
```

```
        }
    }
    System.out.println("Pair with the sum closest to zero: "+n1+" and "+n2);
}
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Nikila is working as an intern in a software firm and is practicing with a matrix where each row represents a set of numerical values. Her task is to identify the row with the highest sum of its elements and remove that row from the matrix. After removing the row with the highest sum, Nikila needs to print the updated matrix.

Your task is to help Nikila in implementing the same. If there are two or more rows that have same the highest sum, the firstly encountered row is deleted.

Input Format

The first line of the input consists of two space-separated integers, R and C, representing the number of rows and columns in the matrix, respectively.

The following R lines each contain, C space-separated integers representing the matrix elements.

Output Format

The output prints the matrix after removing the row with the highest sum. Each row should be printed on a new line, with elements separated by a space.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 2 2
1 2

3 4

Output: 1 2

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int r=sc.nextInt();
        int c=sc.nextInt();
        int[][] arr=new int[r][c];

        for(int i=0;i<r;i++){
            for(int j=0;j<c;j++)
                arr[i][j]=sc.nextInt();
        }
        int maxsum=0, index=0;

        for(int i=0;i<r;i++){
            int rowsum=0;
            for(int j=0;j<c;j++)
                rowsum+=arr[i][j];
            if(rowsum>maxsum){
                maxsum=rowsum;
                index=i;
            }
        }
        for(int i=0;i<r;i++){
            if(i==index)
                continue;
            for(int j=0;j<c;j++)
                System.out.print(arr[i][j]+" ");
            System.out.println();
        }
    }
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

Emma is a data analyst working with a grid-based system where each cell contains important numerical data. The grid represents spatial data, inventory records, or structured reports that require periodic updates.

Due to system updates and new requirements, Emma needs to modify the grid in the following ways:

She wants to insert either a new row or a new column at a given position. Later, she needs to delete either a row or a column from the modified matrix.

Input Format

The first line contains two integers rows and cols (the dimensions of the matrix).

The next rows lines contain cols space-separated integers representing the initial matrix.

The next line contains two integers insertType and insertIndex:

- insertType = 0 for row insertion, 1 for column insertion.
- insertIndex is the position where the new row/column should be added.

If inserting a row, the next cols integers represent the new row or If inserting a column, the next rows integers represent the new column.

The next line contains two integers deleteType and deleteIndex:

- deleteType = 0 for row deletion, 1 for column deletion.
- deleteIndex is the position to be deleted.

Output Format

The first line of output prints the string "After insertion" followed by the modified matrix with the inserted row or column.

Each row of the matrix is printed on a new line with space-separated integers.

The next line prints the string "After deletion" followed by the final matrix after the specified deletion operation.

Each row of the resulting matrix is printed on a new line with space-separated integers.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3 3

1 2 3

4 5 6

7 8 9

0 1

10 11 12

1 2

Output: After insertion

1 2 3

10 11 12

4 5 6

7 8 9

After deletion

1 2

10 11

4 5

7 8

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int rows=sc.nextInt();
        int cols=sc.nextInt();
        int[][] arr=new int[rows][cols];
        for(int i=0;i<rows;i++){
            for(int j=0;j<cols;j++)
                arr[i][j]=sc.nextInt();
        }
    }
}
```

```
int insertType=sc.nextInt();
int insertIndex=sc.nextInt();

if(insertType==0){
    int[] newRow=new int[cols];
    for(int i=0; i<cols; i++)
        newRow[i]=sc.nextInt();

    int[][] arr1= new int[rows+1][cols];
    for(int i=0, j=0; i<rows+1; i++){
        if(i==insertIndex)
            arr1[i]=newRow;
        else
            arr1[i]=arr[j++];
    }
    arr=arr1;
    rows++;
}

else{
    int[] newCol=new int[rows];
    for(int i=0;i<rows;i++)
        newCol[i]=sc.nextInt();

    int[][] arr1=new int[rows][cols+1];

    for(int i=0; i<rows; i++){
        for(int j=0,k=0; j<cols+1; j++){
            if(j==insertIndex)
                arr1[i][j]=newCol[i];
            else
                arr1[i][j]=arr[i][k++];
        }
    }
    arr=arr1;
    cols++;
}

System.out.println("After insertion");

for(int i=0;i<rows;i++){
```

```
for(int j=0;j<cols;j++){
    System.out.print(arr[i][j]+" ");
    System.out.println();
}

int deleteType=sc.nextInt();
int deleteIndex=sc.nextInt();

if(deleteType==0){
    int[][] arr1=new int[rows-1][cols];

    for(int i=0,k=0;i<rows;i++){
        if(i==deleteIndex)
            continue;

        else
            arr1[k++]=arr[i];
    }
    arr=arr1;
    rows--;
}

else{
    int[][] arr1=new int[rows][cols-1];
    for(int i=0;i<rows;i++){
        for(int j=0,k=0;j<cols;j++){
            if(j==deleteIndex)
                continue;
            else
                arr1[i][k++]=arr[i][j];
        }
    }
    arr=arr1;
    cols--;
}

System.out.println("After deletion");

for(int i=0;i<rows;i++){
    for(int j=0;j<cols;j++)
        System.out.print(arr[i][j]+" ");
    System.out.println();
}
```

Status : Correct

Marks : 10/10

4. Problem Statement

Rina is managing the inventory for a library, where each row of a 2D matrix represents the number of different genres of books available on each shelf.

She wants to perform the following operations:

Transformation: Replace each element in a row with the sum of all elements in that row.
Merging: After transformation, Rina will provide one additional matrix, and specify whether to merge the transformed matrix with this new matrix row-wise or column-wise.

Input Format

The first line contains two integers R and C, representing the number of rows and columns of the initial matrix.

The next R lines contain C space-separated integers, representing the book counts in the library.

The next line contains two integers MR and MC, representing the dimensions of the second matrix (to be merged).

The next MR lines contain MC space-separated integers, representing the second matrix.

The last line contains an integer mergeType:

- 0 Row-wise merging (append the second matrix below the transformed matrix).
- 1 Column-wise merging (append the second matrix to the right of the transformed matrix).

Output Format

The output prints "Transformed matrix: " followed by the transformed 2D matrix

where each element in a row is replaced with the sum of the elements in that row.

The output prints "Final merged matrix: ", followed by the merging based on mergeType.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3 4

8 2 4 9

4 5 6 1

7 8 9 3

2 4

3 5 7 2

6 1 4 9

0

Output: Transformed matrix:

23 23 23 23

16 16 16 16

27 27 27 27

Final merged matrix:

23 23 23 23

16 16 16 16

27 27 27 27

3 5 7 2

6 1 4 9

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int r=sc.nextInt();
        int c=sc.nextInt();
```

```
int[][] arr1=new int[r][c];
for(int i=0;i<r;i++){
    for(int j=0;j<c;j++)
        arr1[i][j]=sc.nextInt();
}

int mr=sc.nextInt();
int mc=sc.nextInt();

int[][] arr2=new int[mr][mc];
for(int i=0;i<mr;i++){
    for(int j=0;j<mc;j++){
        arr2[i][j]=sc.nextInt();
    }
}
int mergeType=sc.nextInt();

int[][] newArr1=new int[r][c];

for(int i=0;i<r;i++){
    int sum=0;
    for(int j=0;j<c;j++)
        sum+=arr1[i][j];
    for(int j=0;j<c;j++)
        newArr1[i][j]=sum;
}
System.out.println("Transformed matrix:");
for(int i=0;i<r;i++){
    for(int j=0;j<c;j++)
        System.out.print(newArr1[i][j]+" ");
    System.out.println();
}

System.out.println("Final merged matrix:");

if(mergeType==0){
    for(int i=0;i<r;i++){
        for(int j=0;j<c;j++)
            System.out.print(newArr1[i][j]+" ");
        System.out.println();
    }
}
```

```
for(int i=0;i<mr;i++){
    for(int j=0;j<mc;j++){
        System.out.print(arr2[i][j]+" ");
        System.out.println();
    }
}
else{
    for(int i=0;i<r;i++){
        for(int j=0;j<c;j++)
            System.out.print(newArr1[i][j]+" ");

        for(int j=0;j<mc;j++)
            System.out.print(arr2[i][j]+" ");
        System.out.println();
    }
}
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 3_PAH

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Priya is building a system to automate image transformations using matrix operations. To do this, she needs to multiply two matrices representing pixel data and transformation rules.

Help Priya perform matrix multiplication and print the resulting matrix if the operation is valid.

Input Format

The first line of input consists of two int values, representing the number of rows R1 and columns C1 of the first matrix.

The next $R1 \times C1$ integers represent the elements of the first matrix.

The next line consists of two int values, representing the number of rows R2 and

columns C2 of the second matrix.

The next $R_2 \times C_2$ integers represent the elements of the second matrix.

Output Format

If matrix multiplication is possible, print R_1 lines, each containing C_2 space-separated int values representing the resulting matrix.

Otherwise, print "Matrix multiplication not possible".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 2 3

1 2 3

4 5 6

3 2

7 8

9 10

11 12

Output: 58 64

139 154

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int r1=sc.nextInt();
        int c1=sc.nextInt();
        int[][] arr1=new int[r1][c1];
        for(int i=0;i<r1;i++){
            for(int j=0;j<c1;j++)
                arr1[i][j]=sc.nextInt();
        }
    }
}
```

```

int r2=sc.nextInt();
int c2=sc.nextInt();
int[][] arr2=new int[r2][c2];
for(int i=0;i<r2;i++){
    for(int j=0;j<c2;j++)
        arr2[i][j]=sc.nextInt();
}

if(c1==r2){
    int[][] res=new int[r1][c2];
    for(int i=0;i<r1;i++){
        for(int j=0;j<c2;j++){
            for(int k=0;k<c1;k++){
                res[i][j]+=arr1[i][k]*arr2[k][j];
            }
        }
    }
    for(int i=0;i<r1;i++){
        for(int j=0;j<c2;j++)
            System.out.print(res[i][j]+" ");
        System.out.println();
    }
}

else
    System.out.println("Matrix multiplication not possible");
}

```

Status : Correct

Marks : 10/10

2. Problem Statement

In a customer loyalty program, reward points are logged in a sorted array as customers make transactions. Occasionally, due to system errors, duplicate entries for the same transaction may appear. To ensure accurate reward calculations, it's crucial to remove these duplicates from the list.

Write a program to process the array of reward points, removing any duplicates while preserving the order of unique entries. The program

should then display the cleaned list of unique reward points and the total count of these unique points.

Input Format

The first line of input consists of an integer N, representing the number of reward points.

The second line consists of N space-separated integers, representing the reward points in sorted order.

Output Format

The first line of output prints the cleaned list of unique reward points separated by a space.

The second line of output prints an integer representing the total count of unique reward points.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3
100 100 200

Output: 100 200
2

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int[] arr=new int[n];
        for(int i=0;i<n;i++)
            arr[i]=sc.nextInt();
```

```
int count=0;
int[] res=new int[n];

res[count++]=arr[0];

for(int i=1;i<n;i++){
    if(arr[i]!=arr[i-1])
        res[count++]=arr[i];
}

for(int i=0;i<count;i++){
    System.out.print(res[i]+" ");
}
System.out.println();
System.out.println(count);
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

Eminem is a billiard player who enjoys playing billiards and also likes solving mathematical puzzles. He notices that the billiard balls on the table are arranged in a grid, and he is curious to find the sum of the numbers written on each ball.

Write a program to find the sum of all the numbers written on each ball in the grid.

Input Format

The first line of input consists of an integer N, representing the number of rows.

The second line consists of an integer M, representing the number of columns.

The following lines N lines consist of M space-separated integers, representing the numbers written on each ball.

Output Format

The output prints an integer representing the sum of all the numbers written on each ball.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3

3

1 2 3

4 5 6

7 8 9

Output: 45

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int m=sc.nextInt();

        int[][] arr=new int[n][m];
        int sum=0;

        for(int i=0;i<n;i++){
            for(int j=0;j<m;j++){
                arr[i][j]=sc.nextInt();
            }
        }

        for(int i=0;i<n;i++){
            for(int j=0;j<m;j++){
                sum+=arr[i][j];
            }
        }
        System.out.println(sum);
    }
}
```

```
}
```

Status : Correct

Marks : 10/10

4. Problem Statement

Egath is participating in a coding hackathon, and one of the challenges requires him to work with an array of integers. The task is to remove exactly one element from the array such that the sum of the remaining elements is a prime number.

Help Egath find the first possible prime sum by removing one element or determining if no such prime sum can be achieved.

Input Format

The first line of input consists of an integer N, representing the number of elements in the array.

The second line consists of N space-separated integers, representing the array elements.

Output Format

If removing one element results in a prime sum, print the sum.

If no such prime sum can be achieved by removing exactly one element, print "No valid prime sum found".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3

1 2 3

Output: 5

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int[] arr=new int[n];
        int total=0;
        for(int i=0;i<n;i++){
            arr[i]=sc.nextInt();
            total+=arr[i];
        }

        int sum=0, found=0;

        for(int i=0;i<n;i++){
            int count=0;
            sum=total-arr[i];

            for(int j=1;j<=sum;j++){
                if(sum%j==0)
                    count++;
            }
            if(count==2){
                System.out.println(sum);
                found=1;
                break;
            }
        }
        if(found==0)
            System.out.println("No valid prime sum found");
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 4_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 15

Section 1 : MCQ

1. What will be the output of the following program?

```
class Main {  
    public static void main(String[] args) {  
        String s1 = "EDUCATION";  
        String s2 = new String("EDUCATION");  
        String s3 = "EDUCATION";  
        if (s1 == s2) {  
            System.out.println("s1 and s2 equal");  
        }  
        else {  
            System.out.println("s1 and s2 not equal");  
        }  
        if (s1 == s3) {  
            System.out.println("s1 and s3 equal");  
        }  
    }  
}
```

```
        else {
            System.out.println("s1 and s3 not equal");
        }
    }
}
```

Answer

s1 and s2 not equals1 and s3 equal

Status : Correct

Marks : 1/1

2. What will be the output for the following code?

```
class Main {
    public static void main(String[] args) {
        String languages[] = { "C", "C++", "Java", "Python", "Ruby"};
        for (String sample: languages) {
            System.out.println(sample);
        }
    }
}
```

Answer

CC++JavaPythonRuby

Status : Correct

Marks : 1/1

3. What will be the output of the following program?

```
class Main {
    public static void main(String args[]) {
        StringBuffer sb = new StringBuffer("Hello");
        System.out.println("buffer = " + sb);
        System.out.println("length = " + sb.length());
        System.out.println("capacity = " + sb.capacity());
    }
}
```

Answer

buffer = Hello.length = 5 capacity = 21

Status : Correct

Marks : 1/1

4. Predict the output for the following code:

```
public class Main {  
    public static void main(String[] args) {  
        float a = 10.0f;  
        String temp = Float.toString(a);  
        System.out.println(temp);  
    }  
}
```

Answer

10.0

Status : Correct

Marks : 1/1

5. Predict the output for the following code:

```
class Main {  
    public static void main(String args[]) {  
        StringBuffer sb = new StringBuffer("I Java!");  
        sb.insert(5, "like ");  
        System.out.println(sb);  
    }  
}
```

Answer

I Javlike a!

Status : Correct

Marks : 1/1

6. What will be the output of the following program?

```
class Main {  
    public static void main(String args[]) {  
        String name="Work Hard";
```

```
        name.concat("Success");
        System.out.println(name);
    }
}
```

Answer

Work Hard

Status : Correct

Marks : 1/1

7. What will be the output of the following code?

```
class Main {
    public static void main(String args[]) {
        String s1 = "Hello i love java";
        String s2 = new String(s1);
        System.out.println((s1 == s2) + " " + s1.equals(s2));
    }
}
```

Answer

false true

Status : Correct

Marks : 1/1

8. What will be the output of the following code?

```
class Main {
    public static void main(String args[])
    {
        StringBuffer sb = new StringBuffer("Hello");
        System.out.println("buffer before = " + sb);
        System.out.println("charAt(1) before = " + sb.charAt(1));
        sb.setCharAt(1, 'i');
        sb.setLength(2);
        System.out.println("buffer after = " + sb);
        System.out.println("charAt(1) after = " + sb.charAt(1));
    }
}
```

Answer

buffer before = HellocharAt(1) before = ebuffer after = HicharAt(1) after = i

Status : Correct

Marks : 1/1

9. What will be the output of the following code?

```
class Main {  
    public static void main(String args[]) {  
        char c[] = {'j', 'a', 'v', 'a'};  
        String s1 = new String(c);  
        String s2 = new String(s1);  
        System.out.println(s1);  
        System.out.println(s2);  
    }  
}
```

Answer

javajava

Status : Correct

Marks : 1/1

10. What will be the output of the following program?

```
public class Main {  
    public static void main(String[] args) {  
        String str = "1234.34";  
        int a = Integer.parseInt(str);  
        System.out.println(a);  
    }  
}
```

Answer

NumberFormatException

Status : Correct

Marks : 1/1

11. Predict the output for the following code.

```
public class Main {  
    public static void main(String[] args) {  
        String a = "java";  
        char temp = a.charAt(1);  
        System.out.println(temp);  
    }  
}
```

Answer

a

Status : Correct

Marks : 1/1

12. What is the output of the following code?

```
class Main  
{  
    public static void main(String args[])  
    {  
        StringBuffer c = new StringBuffer("Hello");  
        c.delete(0,2);  
        System.out.println(c);  
    }  
}
```

Answer

llo

Status : Correct

Marks : 1/1

13. Predict the output for the following code.

```
class Main {  
    public static void main(String[] fruits) {  
        String fruit1 = new String("apple");  
        String fruit2 = new String("orange");  
        String fruit3 = new String("pear");  
        fruit3 = fruit1;  
    }  
}
```

```
        fruit2 = fruit3;
        fruit1 = fruit2;
        System.out.println(fruit1);
        System.out.println(fruit2);
        System.out.println(fruit3);
    }
}
```

Answer

appleappleapple

Status : Correct

Marks : 1/1

14. What will be the output of the following program?

```
class Main {
    public static void main(String[] args) {
        String greet = "Welcome\n";
        System.out.print("String: " + greet);
        int length = greet.length();
        System.out.print("Length: " + length);
    }
}
```

Answer

String: WelcomeLength: 8

Status : Correct

Marks : 1/1

15. What will be the output of the following program?

```
class Main {
    public static void main(String[] args) {
        String s = new String("5");
        System.out.println(1 + 1111 + s + 1 + 1010);
    }
}
```

Answer

1112511010

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 4_Q1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In a publishing company, editors often need to quickly analyze passages of text to check for punctuation usage. To assist them, you are asked to write a program that counts the number of specific punctuation marks in each passage.

The punctuation marks of interest are:

Commas (,) Periods (.) Question marks (?)

Input Format

The first line of input contains an integer T, representing the number of test cases (passages).

Each of the next T lines contains a single passage of text.

Output Format

For each test case, print three integers separated by spaces, representing the number of commas, periods, and question marks in the passage.

The first line of output corresponds to the first passage, the second line to the second passage, and so on.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

Hello, world. How are you?

Output: 1 1 1

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        sc.nextLine();

        for(int i=0;i<n;i++){
            int comma=0, period=0, question=0;
            String S=sc.nextLine();

            for(char st:S.toCharArray()){
                if(st==',')
                    comma++;
                else if(st=='.')
                    period++;
                else if(st=='?')
                    question++;
            }
            System.out.println(comma+" "+period+" "+question);
        }
    }
}
```

241001162
}{
}

Status : Correct

241001162

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 4_Q2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Anu is developing a tool for a conference registration system. Participants submit keywords related to their fields of interest. The organizer wants to sort these keywords alphabetically to generate tags for session grouping.

Write a program that accepts at least five keywords as input arguments and outputs them in sorted alphabetical order.

Input Format

The first line of input contains an integer n, representing the number of keywords.

The second line of input contains n space-separated keywords (string).

Output Format

The output prints n space separated strings representing the sorted keyword in alphabetical order.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
Blockchain Cloud AI Data Cybersecurity
Output: AI Blockchain Cloud Cybersecurity Data

Answer

```
// You are using Java
import java.io.*;
import java.util.*;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        sc.nextLine();
        String[] words=new String[n];
        for(int i=0;i<n;i++)
            words[i]=sc.next();
        Arrays.sort(words);

        for(int i=0;i<n;i++)
            System.out.print(words[i]+" ");
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 4_Q3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Bechan Chacha is seeking help to filter out valid mobile numbers from a list provided by his crush. He can only pick his crush's number if the list contains valid mobile numbers.

A mobile number is considered valid if:

It has exactly 10 digits. It consists only of numeric values (0–9). It does not begin with zero.

Your task is to determine whether each mobile number in the list is valid or not.

Input Format

The first line contains an integer T, representing the number of mobile numbers

to check.

The next T lines each contain a string S, representing a mobile number.

Output Format

For each mobile number S, the output print "YES" if it is valid.

Otherwise, print "NO".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1
9876543210

Output: YES

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);

        int n=sc.nextInt();
        sc.nextLine();

        int t=0;

        while(t<n){
            String S=sc.nextLine();
            boolean num=true;

            if(S.length()!=10)
                num=false;

            else if(S.charAt(0)=='0')
                num=false;
        }
    }
}
```

```
        else{
            int i=0;
            while(i<S.length()){
                if(!Character.isDigit(S.charAt(i))){
                    num=false;
                    break;
                }
                i++;
            }
            if(num)
                System.out.println("YES");
            else
                System.out.println("NO");
            t++;
        }
    }
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 4_Q4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Arjun is learning how to filter words from a sentence based on grammar rules. He wants to identify the valid words in a sentence.

A word is considered valid if it satisfies all these conditions:

The word contains only alphabets (a–z, A–Z). The word length is at least 2 characters. The word should not contain digits or special characters.

Your task is to read a sentence and print all the valid words in it.

Input Format

The input contains a single line containing a sentence S.

Output Format

The output prints all the valid words separated by spaces.

If no valid word exists, print "No valid words."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: Hello world1 123 ab" @#\$ Hi

Output: Hello Hi

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        String s=sc.nextLine();
        String[] words=s.split(" ");

        String result="";
        boolean found=false;

        for(String i:words){
            boolean valid=true;

            if(i.length()<2)
                valid=false;
            else{
                for(int j=0;j<i.length();j++){
                    if(!Character.isLetter(i.charAt(j))){
                        valid=false;
                        break;
                    }
                }
            }
            if(valid){
                result+=i+" ";
            }
        }
    }
}
```

```
        found=true;
    }
    if(found)
        System.out.println(result);
    else
        System.out.println("No valid words.");
}
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 4_Q5

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In a secure banking system, customers are required to create PIN codes for accessing their accounts. The bank wants to validate these PIN codes before accepting them.

A PIN code is considered valid if:

It consists of exactly 4 digits. All characters must be numeric (0–9). It cannot contain all identical digits (e.g., 1111 is invalid).

Your task is to determine whether each PIN code in the list is valid or not.

Input Format

The first line of input contains an integer T, representing the number of PIN codes to check.

The next T lines each contain a string S, representing a PIN code.

Output Format

For each PIN code S, the output print "YES" if it is valid.

Otherwise, the output print "NO".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1234

Output: YES

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        sc.nextLine();

        for(int i=0;i<n;i++){
            String pin=sc.nextLine();
            boolean valid =true;

            if(pin.length()!=4)
                valid=false;

            else{
                for(int j=0;j<4;j++){
                    if(!Character.isDigit(pin.charAt(j))){
                        valid=false;
                        break;
                    }
                }
            }
        }
    }
}
```

```
        }
        if(valid){
            boolean same=true;
            for(int j=1;j<4;j++){
                if(pin.charAt(j)!=pin.charAt(0)){
                    same=false;
                    break;
                }
            }
            if(same)
                valid=false;
        }
    }
    if(valid)
        System.out.println("YES");
    else
        System.out.println("NO");
}
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 4_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

A bookstore wants to analyze the titles of books to determine their longest word in each title. This helps in designing banners and covers.

Your task is to write a program that, given a sentence (book title), finds and prints the longest word. If multiple words have the same maximum length, print the first one.

Input Format

The input contains a single line containing a sentence representing the book title.

Output Format

The output prints a string representing the longest word in the sentence (book title).

Refer to the sample output for formatting specifications.

Sample Test Case

Input: The Chronicles of Narnia

Output: Chronicles

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        String s=sc.nextLine();
        String[] words=s.split(" ");

        String longest="";
        int max=0;

        for(String i:words){
            if(i.length()>max){
                max=i.length();
                longest=i;
            }
        }
        System.out.println(longest);
    }
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Neha is analyzing text messages to identify words that have repeated characters. A word is considered “repetitive” if any character appears more

than once in that word.

Your task is to write a program that extracts all words that contain repeated characters from a given sentence.

If no such word exists, print "No repetitive words found".

Input Format

The input contains a single line containing a sentence with multiple words.

Output Format

The output prints all words that contain repeated characters separated by a space.

If no word contains repeated characters, print "No repetitive words found".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: letter balloon apple tree

Output: letter balloon apple tree

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        String s=sc.nextLine();
        String[] words=s.split(" ");

        StringBuilder result=new StringBuilder();
        boolean found=false;

        for(String i:words){
            int[] count=new int[256];
```

```
boolean repeat=false;
for(int j=0; j<i.length(); j++){
    char c=i.charAt(j);
    count[c]++;
    if(count[c]>1){
        repeat=true;
        break;
    }
}
if(repeat){
    result.append(i).append(" ");
    found=true;
}
if(found)
    System.out.println(result.toString());
else
    System.out.println("No repetitive words found");
}

}
```

Status : Correct

Marks : 10/10

3. Problem Statement

In a college, students are required to create unique usernames for accessing the digital library.

The librarian needs your help to verify whether the usernames entered by students are valid.

A username is considered valid if:

It contains only letters (a–z, A–Z) and digits (0–9). Its length is between 5 and 15 characters (inclusive). It must start with a letter (not a digit).

Your task is to determine whether each username in the list is valid or not.

Input Format

The first line of input contains an integer T, representing the number of usernames to check.

The next T lines each contain a string S, representing a username.

Output Format

For each username S, the output print "YES" if it is valid.

Otherwise, the output print "NO".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

Alice123

Output: YES

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        sc.nextLine();

        for(int i=0;i<n;i++){
            String s=sc.nextLine();
            boolean valid=true;

            if(!(s.length()>=5 && s.length()<=15))
                valid=false;
            else if(!Character.isLetter(s.charAt(0)))
                valid=false;
            else{
                for(int j=0;j<s.length();j++){
                    if(!Character.isLetterOrDigit(s.charAt(j))){


```

```
        valid=false;
        break;
    }
}
if(valid)
    System.out.println("YES");
else
    System.out.println("NO");

}
}
```

Status : Correct

Marks : 10/10

4. Problem Statement

Meera is practicing her English vocabulary. She wants to focus on words that have more vowels in them, as they help improve her pronunciation. She decides to extract only those words from a sentence that contain at least two vowels.

Your task is to help Meera by writing a program that finds such words from the given sentence.

Input Format

The input contains a string representing the sentence.

Output Format

The output prints all the words that contain at least two vowels, separated by a space.

If no such word exists, print "No words with two vowels".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: This is an example sentence

Output: example sentence

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        String s=sc.nextLine();
        String[] words=s.split(" ");

        String result="";
        boolean found=false;

        for(String ch:words){
            int count=0;
            for(int i=0;i<ch.length();i++){
                char c=Character.toLowerCase(ch.charAt(i));
                if(c=='a'||c=='e'||c=='i'||c=='o'||c=='u')
                    count++;
            }
            if(count>1){
                result+=ch+" ";
                found=true;
            }
        }
        if(found)
            System.out.println(result);

        else
            System.out.println("No words with two vowels");
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 4_PAH

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Ravi is analyzing text messages for his research on typing patterns. He wants to count the number of uppercase letters, lowercase letters, and digits in a sentence to understand typing trends.

Your task is to help Ravi by writing a program that takes a sentence and prints the count of uppercase letters, lowercase letters, and digits.

Input Format

The input contains a single line containing a sentence (string).

Output Format

The output prints three integers separated by spaces:

- Number of uppercase letters
- Number of lowercase letters
- Number of digits

Refer to the sample output for formatting specifications.

Sample Test Case

Input: Hello World 123

Output: 2 8 3

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        String s=sc.nextLine();
        int u=0, l=0, d=0;
        for(int i=0;i<s.length();i++){
            char ch=s.charAt(i);
            if(Character.isUpperCase(ch))
                u++;
            else if(Character.isLowerCase(ch))
                l++;
            else if(Character.isDigit(ch))
                d++;
        }
        System.out.print(u+" "+l+" "+d);
    }
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Riya is preparing a puzzle game for her friends. She wants to include a

feature that highlights special words in a sentence — specifically, palindromic words (words that read the same forward and backward).

Your task is to help Riya by writing a program that extracts all palindrome words from the given sentence. If there are no palindromes, print "No palindromes found".

Input Format

The input contains a single string S representing a sentence.

Output Format

The output prints all palindromic words separated by a space.

If no palindrome exists, print "No palindromes found".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: madam went to school

Output: madam

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        String s=sc.nextLine();
        String[] words=s.split(" ");
        boolean found=false;

        for(String c:words){
            int i=0, j=c.length()-1;
            boolean palindrome=true;
            while(i<j){
                if(c.charAt(i) != c.charAt(j))
                    palindrome=false;
                i++;
                j--;
            }
            if(palindrome)
                System.out.print(c + " ");
        }
    }
}
```

```
        if(c.charAt(i)!=c.charAt(j)){
            palindrome=false;
            break;
        }
        i++;
        j--;
    }
    if(palindrome && c.length()>0){
        System.out.print(c+" ");
        found=true;
    }
}
if(!found)
System.out.println("No palindromes found");
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

At a digital library, the system needs to analyze passages to identify the frequency of vowels, since they are key for linguistic research. You are asked to write a program that counts the number of vowels in each passage of text.

The vowels of interest are:

a, e, i, o, u (both uppercase and lowercase).

Input Format

The first line of input contains an integer T, representing the number of test cases (passages).

Each of the next T lines contains a single passage of text.

Output Format

For each test case, print a single integer representing the total number of vowels in the passage.

The first line of output corresponds to the first passage, the second line to the second passage, and so on.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1
Hello World
Output: 3

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int t=sc.nextInt();
        sc.nextLine();

        for(int i=0;i<t;i++){
            String s=sc.nextLine();
            int count=0;
            for(int j=0;j<s.length();j++){
                char ch=s.charAt(j);
                ch=Character.toLowerCase(ch);
                if(ch=='a'||ch=='e'||ch=='i'||ch=='o'||ch=='u')
                    count++;
            }
            System.out.println(count);
        }
    }
}
```

Status : Correct

Marks : 10/10

4. Problem Statement

Sana is analyzing text for a secret code. She wants to find all words in a sentence that start and end with the same letter. These words are considered "special words" for her analysis.

Your task is to write a program that extracts and prints all words that start and end with the same letter (case-insensitive).

If no such word exists, print "No special words found".

Input Format

The input contains a single line containing a sentence with multiple words.

Output Format

The output prints all words that start and end with the same letter separated by a space.

If no word satisfies the condition, print "No special words found".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: Anna went to the civic center

Output: Anna civic

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        String s=sc.nextLine();
        String[] words=s.split(" ");
        boolean found=false;
```

```
for(String i:words){  
    if(i.length()>0){  
        char c1=Character.toLowerCase(i.charAt(0));  
        char c2=Character.toLowerCase(i.charAt(i.length()-1));  
  
        if(c1==c2){  
            System.out.print(i+" ");  
            found=true;  
        }  
    }  
}  
if(!found)  
    System.out.println("No special words found");  
}  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 5_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 15

Section 1 : MCQ

1. What will be the output of the following code?

```
class Box {  
    int length = 5;  
    int width = 4;  
  
    int area() {  
        return length * width;  
    }  
  
    public static void main(String[] args) {  
        Box b = new Box();  
        System.out.println("Area = " + b.area());  
    }  
}
```

Answer

Area = 20

Status : Correct

Marks : 1/1

2. What will be the output of the following code?

```
class Demo {  
    void printMessage() {  
        System.out.println("Hello from Demo");  
    }  
}  
  
public class Main {  
    public static void main(String[] args) {  
        Demo d = new Demo();  
        d.printMessage();  
    }  
}
```

Answer

Hello from Demo

Status : Correct

Marks : 1/1

3. What will be the output of the following code?

```
class A {  
    int y = 30;  
}  
  
public class Main {  
    public static void main(String[] args) {  
        A a1 = new A();  
        A a2 = new A();  
        a1.y = 50;  
        System.out.println(a2.y);  
    }  
}
```

}

Answer

30

Status : Correct

Marks : 1/1

4. What will be the output of the following code?

```
class Ball {  
    int size = 11;  
}  
  
class Game {  
    public static void main(String[] args) {  
        Ball b1 = new Ball();  
        Ball b2 = new Ball();  
        b2.size = 10;  
        System.out.println(b1.size);  
    }  
}
```

Answer

11

Status : Correct

Marks : 1/1

5. What will be the output of the following code?

```
class Alpha {  
    void greet(String name) {  
        System.out.println("Hello " + name);  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Alpha obj = new Alpha();  
        obj.greet("Anu");  
    }  
}
```

```
}
```

Answer

Hello Anu

Status : Correct

Marks : 1/1

6. What will be the output of the following code?

```
class A {  
    int p = 5;  
    int q = 2;  
}  
  
class Main {  
    public static void main(String[] args) {  
        A obj = new A();  
        System.out.println(obj.p + obj.q);  
    }  
}
```

Answer

7

Status : Correct

Marks : 1/1

7. What will be the output of the following code?

```
class MathUtils {  
    int add(int x) {  
        return x + x;  
    }  
}  
  
public class Main {  
    public static void main(String[] args) {  
        MathUtils m = new MathUtils();  
        System.out.println(m.add(5));  
    }  
}
```

```
}
```

Answer

10

Status : Correct

Marks : 1/1

8. What will be the output of the following code?

```
class A {  
    int x = 50;  
}  
  
public class Main {  
    public static void main(String[] args) {  
        A obj1 = new A();  
        A obj2 = obj1;  
        obj2.x = 100;  
        System.out.println(obj1.x);  
    }  
}
```

Answer

100

Status : Correct

Marks : 1/1

9. What will be the output of the following code?

```
class Test {  
    private int value;  
    Test(int value) {  
        this.value = value;  
    }  
    public int getValue() {  
        return value;  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Test obj = new Test(10);  
        System.out.println(obj.value);  
    }  
}
```

Answer

Compile-time error

Status : Correct

Marks : 1/1

10. What will be the output of the following code?

```
class Person {  
    int age = 18;  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Person p = new Person();  
        p.age += 2;  
        System.out.println("Age: " + p.age);  
    }  
}
```

Answer

Age: 20

Status : Correct

Marks : 1/1

11. What is the output of the following code?

```
class Box {  
    int height;  
    Box(int height) {  
        this.height = height;  
    }  
    void modifyHeight(Box b) {
```

```
b.height += 10;  
}  
}  
public class Main {  
    public static void main(String[] args) {  
        Box b1 = new Box(20);  
        b1.modifyHeight(b1);  
        System.out.println(b1.height);  
    }  
}
```

Answer

30

Status : Correct

Marks : 1/1

12. What will be the output of the following code?

```
class Sample {  
    int x = 10;  
  
    void display() {  
        System.out.println("x = " + x);  
    }  
  
    public static void main(String[] args) {  
        Sample s = new Sample();  
        s.display();  
    }  
}
```

Answer

x = 10

Status : Correct

Marks : 1/1

13. What will be the output of the following code?

```
class Person {
```

```
String name;
void setName(String n) {
    name = n;
}
void printName() {
    System.out.println(name);
}
}
```

```
class Test {
    public static void main(String[] args) {
        Person p = new Person();
        p.printName();
    }
}
```

Answer

null

Status : Correct

Marks : 1/1

14. What will be the output of the following code?

```
class A {
    int val = 20;
}

public class Main {
    public static void main(String[] args) {
        A obj1 = new A();
        A obj2 = obj1;
        obj2.val += 5;
        System.out.println(obj1.val);
    }
}
```

Answer

25

Status : Correct

Marks : 1/1

15. What will be the output of the following code?

```
class Box {  
    int volume(int l, int b, int h) {  
        return l * b * h;  
    }  
}  
  
public class Main {  
    public static void main(String[] args) {  
        Box b = new Box();  
        System.out.println(b.volume(2, 3, 4));  
    }  
}
```

Answer

24

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 5_Q2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

You are working as a developer for CityBank, which wants to build a basic account management system.

Each customer at the bank has:

An Account Number (integer)
A Customer Name (string)
An Initial Balance (double)

The bank allows two types of transactions:

Deposit – increases the balance.
Withdrawal – decreases the balance only if enough funds are available.

If the withdrawal amount is greater than the balance, the withdrawal should not happen, and the balance should remain the same.

You are required to implement this system using:

A class with attributes for account details. A constructor to initialize account details. Setter methods to update details if needed. Getter methods to retrieve details. Objects of the class to represent customers.

Finally, display each customer's account details after all transactions.

Input Format

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the account number (integer).
- The following line contains the customer name (string).
- The next line contains the initial balance (double).
- The next line contains the deposit amount (double).
- The next line contains the withdrawal amount (double).

Output Format

For each customer, print the details in the following format:

1. Account Number: <account_number>
2. Customer Name: <customer_name>
3. Final Balance: <final_balance> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1234

Rahul Sharma

5000

2000

3000

Output: Account Number: 1234

Customer Name: Rahul Sharma

Final Balance: 4000.0

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class CityBank{
    int accNo;
    String custName;
    double Balance;

    public CityBank(int accNo, String custName, double initBalance){
        this.accNo=accNo;
        this.custName=custName;
        this.Balance=initBalance;
    }
    // public int getAcc(int accNo){
    //     return accNo;
    // }
    // public String getName(String custName){
    //     return custName;
    // }
    // public double getBalance(double Balance){
    //     return Balance;
    // }
    public void deposit(double amt){
        if(amt>0)
            Balance+=amt;
    }
    public void withdraw(double amt){
        if(amt>0 && this.Balance>=amt)
            Balance-=amt;
    }
    public void display(){
        System.out.println("Account Number: "+accNo);
        System.out.println("Customer Name: "+custName);
        System.out.println("Final Balance: "+Balance);
    }
}

class Main{
```

```
public static void main(String[] args){  
    Scanner sc=new Scanner(System.in);  
    int n=sc.nextInt();  
    sc.nextLine();  
    for(int i=1;i<=n;i++){  
        int accNo=sc.nextInt();  
        sc.nextLine();  
        String custName=sc.nextLine();  
        double initBalance=sc.nextDouble();  
        double deposit=sc.nextDouble();  
        double withdraw=sc.nextDouble();  
  
        CityBank acc=new CityBank(accNo, custName, initBalance);  
        acc.deposit(deposit);  
        acc.withdraw(withdraw);  
        acc.display();  
    }  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 5_Q3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Neha is working as a developer for CityElectricity Board, which wants to build a household electricity billing system.

Each customer's electricity account has:

A Customer ID (integer) A Customer Name (string) Units Consumed (double)

The electricity bill is calculated based on these rules:

For the first 100 units 5 units charge per unit
For the next 100 units (101–200) 7 units charge per unit
For units above 200 10 units charge per unit
If the total bill exceeds 2000 units, a 5% discount is applied on the final bill.

Neha has been asked to implement this system using:

A class with attributes for customer details.A constructor to initialize customer details.Setter methods to update details if needed.Getter methods to retrieve details.Objects of the class to represent customers.

Finally, display each customer's details and final bill amount.

Input Format

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the Customer ID (integer).
- The following line contains the Customer Name (string).
- The next line contains the Units Consumed (double).

Output Format

For each customer, print the details in the following format:

Customer ID: <customer_id>

Customer Name: <customer_name>

Final Bill: <final_bill> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1001

Ravi Kumar

80

Output: Customer ID: 1001

Customer Name: Ravi Kumar

Final Bill: 400.0

Answer

```
// You are using Java
```

```
import java.io.*;
import java.util.Scanner;

class CityElectricity{
    int custID;
    String custName;
    double units;

    public CityElectricity(int custID, String custName, double units){
        this.custID=custID;
        this.custName=custName;
        this.units=units;
    }

    public int getID(int custID){
        return custID;
    }

    public String getName(String custName){
        return custName;
    }

    public double getUnits(double units){
        return units;
    }

    public double finalBill(){
        double bill=0;
        if(units<=100)
            bill=units*5;
        else if(units>100 && units<=200)
            bill=(100*5) + (units-100)*7;
        else
            bill=(100*5) + (100*7) + (units-200)*10;
        if(bill>2000)
            bill=bill-(bill*0.05);
        return bill;
    }

    public void display(){
        double bill=finalBill();
        System.out.println("Customer ID: "+custID);
        System.out.println("Customer Name: "+custName);
        System.out.printf("Final Bill: %.1f",bill);
    }
}
```

```
class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        sc.nextLine();

        for(int i=1;i<=n;i++){
            int custID=sc.nextInt();
            sc.nextLine();
            String custName=sc.nextLine();
            double units=sc.nextDouble();

            CityElectricity acc = new CityElectricity(custID, custName, units);
            acc.display();
        }
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 5_Q4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

You are working as a developer for CityCab, a taxi service company that wants to build a ride fare management system.

Each customer booking has:

A Booking ID (integer)
A Customer Name (string)
A Distance Travelled in km (double)

The fare calculation rules are:

Base Fare = 50 units (flat charge for every ride). Per km charge = 10 units/km. If the distance is greater than 20 km, a 10% discount is applied on the total fare.

You are required to implement this system using:

A class with attributes for booking details. A constructor to initialize booking details. Setter methods to update details if needed. Getter methods to retrieve details. Objects of the class to represent customer rides.

Finally, display each booking's details and final fare.

Input Format

The first line of input contains an integer N, representing the number of bookings.

For each booking:

- The next line contains the booking ID (integer).
- The following line contains the customer's name (string).
- The next line contains the distance travelled (double).

Output Format

For each booking, print the details in the following format:

1. Booking ID: <booking_id>
2. Customer Name: <customer_name>
3. Final Fare: <final_fare> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1234

Rahul Sharma

15

Output: Booking ID: 1234

Customer Name: Rahul Sharma

Final Fare: 200.0

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;
```

```
class Booking {  
    int bookingId;  
    String customerName;  
    double distance;  
  
    public Booking(int bookingId, String customerName, double distance) {  
        this.bookingId = bookingId;  
        this.customerName = customerName;  
        this.distance = distance;  
  
    }  
  
    public void setBookingId(int bookingId) {  
        this.bookingId = bookingId;  
    }  
  
    public void setCustomerName(String customerName) {  
        this.customerName = customerName;  
    }  
  
    public void setDistance(double distance) {  
        this.distance = distance;  
  
    }  
  
    public int getBookingId() {  
        return bookingId;  
    }  
  
    public String getCustomerName() {  
        return customerName;  
    }  
  
    public double getDistance() {  
        return distance;  
    }  
  
    public double calculateFare() {  
        double fare;  
    }  
}
```

```
fare = 50 + distance * 10;
if (distance > 20) {
    fare = fare - (fare * 0.1);
}
return fare;
}

class CityCabApp {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        sc.nextLine();
        for (int i = 1; i <=n; i++) {
            int id = sc.nextInt();
            sc.nextLine();
            String name = sc.nextLine();
            double distance = sc.nextDouble();
            Booking booking = new Booking(id, name, distance);
            System.out.println("Booking ID: " + booking.getBookingId());
            System.out.println("Customer Name: " + booking.getCustomerName());
            System.out.printf("Final Fare: %.1f\n", booking.calculateFare());
        }
        sc.close();
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 5_Q5

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Ram is working as a developer for BrightEdu Coaching Center, which wants to build a student fee management system.

Each student's enrollment has:

An Enrollment ID (integer) A Student Name (string) The Number of Subjects (integer)

The fee calculation rules are:

Registration Fee = 1000 units (flat for every student). Per Subject Fee = 800 units. If the student enrolls in more than 5 subjects, a 20% scholarship (discount) is applied on the total fee.

Ram has been asked to implement this system using:

A class with attributes for student details. A constructor to initialize student details. Setter methods to update details if needed. Getter methods to retrieve details. Objects of the class to represent student enrollments.

Finally, display each student's details and final fee.

Input Format

The first line of input contains an integer N, representing the number of students.

For each student:

- The next line contains the Enrollment ID (integer).
- The following line contains the student's name (string).
- The next line contains the Number of subjects (integer).

Output Format

For each student, print the details in the following format:

- Enrollment ID: <enrollment_id>
- Student Name: <student_name>
- Final Fee: <final_fee> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1234

Ravi Kumar

3

Output: Enrollment ID: 1234

Student Name: Ravi Kumar

Final Fee: 3400.0

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;
```

```
class BrightEdu{  
    int ID;  
    String name;  
    int subjects;  
  
    public BrightEdu(int ID, String name, int subjects){  
        this.ID=ID;  
        this.name=name;  
        this.subjects=subjects;  
    }  
  
    public int getID(int ID){  
        return ID;  
    }  
    public String getName(String name){  
        return name;  
    }  
    public int getSub(int subjects){  
        return subjects;  
    }  
  
    public double feeCalc(){  
        double total = 1000 + 800*subjects;  
        if(subjects>5)  
            total = total - total*0.2;  
        return total;  
    }  
  
    public void display(){  
        double total=feeCalc();  
        System.out.println("Enrollment ID: "+ID);  
        System.out.println("Student Name: "+name);  
        System.out.printf("Final Fee: %.1f",total);  
    }  
}
```

```
class Main{  
    public static void main(String[] args){  
        Scanner sc=new Scanner(System.in);  
        int n=sc.nextInt();  
        sc.nextLine();
```

```
for(int i=1;i<=n;i++){
    int ID=sc.nextInt();
    sc.nextLine();
    String name=sc.nextLine();
    int subjects=sc.nextInt();

    BrightEdu fee=new BrightEdu(ID, name, subjects);
    fee.display();
}
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 5_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Anjali is now working as a developer for the City Marathon Association, which wants to build a system to track and find the fastest runner among marathon participants.

Each runner's record has:

Runner ID (integer) Runner Name (string) An array of times (in minutes) taken in 5 marathon events (integers)

The system must calculate:

The average time of each runner (sum of all times / 5). Identify the fastest runner (the one with the lowest average time). If two or more runners have the same average time, the one with the lower Runner ID is considered the

fastest runner.

Anjali has been asked to implement this system using:

A class with attributes for runner details. A constructor to initialize runner details. Getter and Setter methods to retrieve and update runner details if required. A method to calculate the average time. Objects of the class to represent runners.

Finally, display each runner's details and announce the Fastest Runner.

Input Format

The first line of input contains an integer N (number of runners).

For each runner:

- The next line contains the Runner ID (integer).
- The following line contains the Runner Name (string).
- The next line contains 5 integers separated by spaces (times in minutes for 5 marathon events).

Output Format

For each runner the output prints the following details:

- Runner ID: <runner_id>
- Runner Name: <runner_name>
- Average Time: <average_time>

Finally, print "Fastest Runner: <runner_name> with <average_time> minutes"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1001

Ravi Kumar

240 250 245 255 260
Output: Runner ID: 1001
Runner Name: Ravi Kumar
Average Time: 250
Fastest Runner: Ravi Kumar with 250 minutes

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Marathon{
    int id;
    String name;
    int[] arr;
    int avg;

    public Marathon(int id, String name, int[] arr){
        this.id=id;
        this.name=name;
        this.arr=arr;
        calcAvg();
    }

    public void setId(int id){
        this.id=id;
    }
    public void setName(String name){
        this.name=name;
    }
    public void setArr(int[] arr){
        this.arr=arr;
    }

    public int getId(){
        return id;
    }
    public String getName(){
        return name;
    }
    public int getAvg(){
        return avg;
    }
}
```

```
}

public void calcAvg(){
    int sum=0;
    for(int i=0;i<5;i++)
        sum+=arr[i];

    avg=sum/5;

}

public void display(){
    System.out.println("Runner ID: "+getId());
    System.out.println("Runner Name: "+getName());
    System.out.println("Average Time: "+getAvg());
}

}

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);

        int n=Integer.parseInt(sc.nextLine());

        Marathon fast=null;

        for(int i=0;i<n;i++){

            int id=Integer.parseInt(sc.nextLine());
            String name=sc.nextLine();

            String[] time=sc.nextLine().split(" ");

            int[] arr=new int[5];

            for(int j=0;j<5;j++)
                arr[j]=Integer.parseInt(time[j]);

            Marathon p=new Marathon( id, name, arr);

            if(fast==null || p.getAvg()<fast.getAvg() || (p.getAvg()==fast.getAvg() &&
p.getId()<fast.getId()))
        }
    }
}
```

```
        fast=p;
        p.display();
    }

    System.out.println("Fastest Runner: "+fast.getName()+" with
"+fast.getAvg()+" minutes");
}
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Arjun is working as a developer for CityWater Supply Board, which wants to build a household water billing system.

Each household's water account has:

A Customer ID (integer)
A Customer Name (string)
Liters Consumed (double)

The water bill is calculated based on these rules:

For the first 500 liters 2 per liter
For the next 500 liters (501–1000) 3 per liter
For liters above 1000 5 per liter
If the total bill exceeds 3000, a 10% discount is applied on the final bill.

Arjun has been asked to implement this system using:

A class with attributes for customer details. A constructor to initialize customer details. Setter methods to update details if needed. Getter methods to retrieve details. Objects of the class to represent customers.

Finally, display each customer's details and final bill amount.

Input Format

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the Customer ID (integer).
- The following line contains the Customer Name (string).
- The next line contains the Liters Consumed (double).

Output Format

For each customer, print the details in the following format:

Customer ID: <customer_id>

Customer Name: <customer_name>

Final Bill: <final_bill> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1
1001
Ravi Kumar
300

Output: Customer ID: 1001
Customer Name: Ravi Kumar
Final Bill: 600.0

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class CityWater{
    int id;
    String name;
    double liters;

    public CityWater(int id, String name, double liters){
        this.id=id;
        this.name=name;
        this.liters=liters;
    }

    public void setId(int id){
        this.id=id;
    }
    public void setName(String name){
        this.name=name;
    }
    public void setLiters(double liters){
        this.liters=liters;
    }

    public int getId(){
        return id;
    }
    public String getName(){
        return name;
    }
    public double getLiters(){
        return liters;
    }
}
```

```
    }

    public double calcBill(){
        double bill=0;

        if(liters<=500)
            bill=liters*2;
        else if(liters>500 && liters<=1000)
            bill = (500*2) + (liters-500)*3;
        else
            bill = (500*2) + (500*3) + (liters-1000)*5;

        if(bill>3000)
            bill=bill-bill*0.1;
        return bill;
    }

}
```

```
class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=Integer.parseInt(sc.nextLine());

        for(int i=1;i<=n;i++){
            int id=Integer.parseInt(sc.nextLine());
            String name=sc.nextLine();
            double liters=Double.parseDouble(sc.nextLine());

            CityWater bill = new CityWater( id, name, liters);

            System.out.println("Customer ID: "+bill.getId());
            System.out.println("Customer Name: "+bill.getName());
            System.out.printf("Final Bill: %.1f\n", bill.calcBill());
        }
    }
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

Meera is working as a developer for CityGas Supply Board, which wants to build a household gas billing system.

Each household's gas account has:

A Customer ID (integer)
A Customer Name (string)
Units Consumed in cubic meters (double)

The gas bill is calculated based on these rules:

For the first 50 units 4 per unit
For the next 100 units (51–150) 6 per unit
For units above 150 8 per unit
If the total bill exceeds 2000, a 15% discount is applied on the final bill.

Meera has been asked to implement this system using:

A class with attributes for customer details.
A constructor to initialize customer details.
Setter methods to update details if needed.
Getter

methods to retrieve details. Objects of the class to represent customers.

Finally, display each customer's details and final bill amount.

Input Format

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the Customer ID (integer).
- The following line contains the Customer Name (string).
- The next line contains the Units Consumed (double).

Output Format

For each customer, print the details in the following format:

Customer ID: <customer_id>

Customer Name: <customer_name>

Final Bill: <final_bill> (The final bill must be rounded to one decimal place.)

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1001

Ravi Kumar

30

Output: Customer ID: 1001

Customer Name: Ravi Kumar

Final Bill: 120.0

Answer

```
// You are using Java  
import java.io.*;  
import java.util.Scanner;
```

```
class CityGas{
    int id;
    String name;
    double units;

    public CityGas(int id, String name, double units){
        this.id=id;
        this.name=name;
        this.units=units;
    }

    public void setId(int id){
        this.id=id;
    }
    public void setName(String name){
        this.name=name;
    }
    public void setUnits(double units){
        this.units=units;
    }

    public int getId(){
        return id;
    }
    public String getName(){
        return name;
    }

    public double calcBill(){
        double bill=0;
        if(units<=50)
            bill=units*4;
        else if(units>50 && units<=150)
            bill=(50*4)+(units-50)*6;
        else
            bill=(50*4)+(100*6)+(units-150)*8;

        if(bill>2000)
            bill = bill - bill*0.15;
    }

    return bill;
}
```

```
}
```

```
class Main{
```

```
    public static void main(String[] args){
```

```
        Scanner sc=new Scanner(System.in);
```

```
        int n=Integer.parseInt(sc.nextLine());
```

```
        for(int i=1;i<=n;i++){
```

```
            int id=Integer.parseInt(sc.nextLine());
```

```
            String name=sc.nextLine();
```

```
            double units=Double.parseDouble(sc.nextLine());
```

```
            CityGas bill=new CityGas( id, name, units);
```

```
            System.out.println("Customer ID: "+bill.getId());
```

```
            System.out.println("Customer Name: "+bill.getName());
```

```
            System.out.printf("Final Bill: %.1f\n",bill.calcBill());
```

```
}
```

```
}
```

Status : Correct

Marks : 10/10

4. Problem Statement

Anjali is working as a developer for the City Basketball Association, which wants to build a system to track and find the top scorer among basketball players.

Each player's record has:

Player ID (integer)Player Name (string)An array of points scored in 5 matches (integers)

The system must calculate:

The total score of each player (sum of all match points). Identify the highest scorer among all players. If two or more players have the same total score, the one with the lower Player ID is considered the top scorer.

Anjali has been asked to implement this system using:

A class with attributes for player details. A constructor to initialize player details. Getter and Setter methods to retrieve and update player details if required. A method to calculate the total score. Objects of the class to represent players.

Finally, display each player's details and announce the Top Scorer.

Input Format

The first line of input contains an integer N (number of players).

For each player:

- The next line contains the Player ID (integer).
- The following line contains the Player Name (string).
- The next line contains 5 integers separated by spaces (points scored in 5 matches).

Output Format

For each player the output prints the following details:

- Player ID: <player_id>
- Player Name: <player_name>
- Total Score: <total_score>

Finally, print "Top Scorer: <player_name> with <total_score> points"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1
1001
Ravi Kumar
10 20 30 40 50

Output: Player ID: 1001
Player Name: Ravi Kumar
Total Score: 150
Top Scorer: Ravi Kumar with 150 points

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class Basketball{
    int id;
    String name;
    int[] arr;
    int total;

    public Basketball(int id, String name, int[] arr){
        this.id=id;
        this.name=name;
```

```
        this.arr=arr;
        calcScore();
    }

    public void setId(int id){
        this.id=id;
    }
    public void setName(String name){
        this.name=name;
    }
    public void setArr(int[] arr){
        this.arr=arr;
    }

    public int getId(){
        return id;
    }
    public String getName(){
        return name;
    }
    public int getTotal(){
        return total;
    }

    public void calcScore(){
        int total=0;
        for(int i=0;i<5;i++)
            total+=arr[i];
        this.total=total;
    }

    public void display(){
        System.out.println("Player ID: "+getId());
        System.out.println("Player Name: "+getName());
        System.out.println("Total Score: "+getTotal());
    }
}

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=Integer.parseInt(sc.nextLine());
```

```
Basketball top=null;

for(int i=1;i<=n;i++){
    int id=Integer.parseInt(sc.nextLine());
    String name=sc.nextLine();

    String[] scores=sc.nextLine().split(" ");
    int[] arr=new int[5];

    for(int j=0;j<5;j++)
        arr[j]=Integer.parseInt(scores[j]);

    Basketball p=new Basketball( id, name, arr);

    if(top==null || p.getTotal()>top.getTotal() || (p.getTotal()==top.getTotal())
    && p.getId()<top.getId())
        top=p;
    p.display();
}

System.out.println("Top Scorer: "+top.getName()+" with "+top.getTotal()+" points");
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 5_PAH

Attempt : 1
Total Mark : 50
Marks Obtained : 50

Section 1 : Coding

1. Problem Statement

Ravi is working as a developer for SecureLogin Systems, which wants to build a system to evaluate the strength of user passwords.

Each user record has:

User ID (integer)User Name (string)Password (string)

The system must calculate whether a password is strong or weak.

A password is considered strong if it meets all of the following conditions:

At least 8 characters long. Contains at least one uppercase letter. Contains at least one lowercase letter. Contains at least one digit. Contains at least one special character (from !@#\$%^&*).

Ravi has been asked to implement this system using:

A class with attributes for user details. A constructor to initialize user details. Getter and setter methods to retrieve or update user details. A method to check whether the password is strong. Objects of the class to represent users.

Finally, display each user's details and indicate whether their password is Strong or Weak.

Input Format

The first line contains an integer N, representing the number of users.

For each user:

The next line contains the User ID (integer).

The next line contains the User Name (string).

The next line contains the Password (string).

Output Format

For each user, print the details in the following format:

User ID: <user_id>

User Name: <user_name>

Password: <password>

Password Strength: <Strong/Weak>

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1001

Ravi Kumar

Abc@1234
Output: User ID: 1001
User Name: Ravi Kumar
Password: Abc@1234
Password Strength: Strong

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class SecureLogin{
    int id;
    String name;
    String pswd;

    public SecureLogin(int id, String name, String pswd){
        this.id=id;
        this.name=name;
        this.pswd=pswd;
    }

    public void setID(int id){
        this.id=id;
    }
    public void setName(String name){
        this.name=name;
    }
    public void setPswd(String pswd){
        this.pswd=pswd;
    }

    public int getID(){
        return id;
    }
    public String getName(){
        return name;
    }
    public String getPswd(){
        return pswd;
    }
}
```

```
public boolean checkPassword(){
    boolean strong=false;
    int u=0, l=0, d=0, s=0;
    for(int i=0;i<pswd.length();i++){
        char ch=pswd.charAt(i);

        if(Character.isUpperCase(ch))
            u++;
        else if(Character.isLowerCase(ch))
            l++;
        else if(Character.isDigit(ch))
            d++;
        else
            s++;

    }
    if(pswd.length()>=8){
        if(u>=1){
            if(l>=1){
                if(d>=1){
                    if(s>=1)
                        strong=true;
                }
            }
        }
    }
    return strong;
}

public void display(){
    boolean strong=checkPassword();
    System.out.println("User ID: "+id);
    System.out.println("User Name: "+name);
    System.out.println("Password: "+pswd);
    if(strong==true)
        System.out.println("Password Strength: Strong");
    else
        System.out.println("Password Strength: Weak");
}
```

```
241001162 class Main{  
    public static void main(String[] args){  
        Scanner sc=new Scanner(System.in);  
        int n=sc.nextInt();  
  
        for(int i=1;i<=n;i++){  
            int id=sc.nextInt();  
            sc.nextLine();  
            String name=sc.nextLine();  
            String pswd=sc.nextLine();  
  
            SecureLogin password=new SecureLogin(id, name, pswd);  
            password.display();  
        }  
    }  
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Neha is working as a developer for CityMovie Theatre, which wants to build a system to calculate total ticket cost for movie-goers based on the number of tickets and type of seats booked.

Each customer's booking has:

Booking ID (integer) Customer Name (string) Number of Tickets (integer)
Seat Type (string: "Standard", "Premium", "VIP")

The ticket prices are:

Standard – 250 units per ticket
Premium – 400 units per ticket
VIP – 600 units per ticket

The calculation rules:

Total Amount = Number of Tickets × Seat Price

If a customer books more than 4 tickets, they get a 10% discount on the

total amount.

If the booking is for VIP seats and the total amount exceeds 3000 units, a 5% luxury tax is added after any discount.

Neha has been asked to implement this system using:

A class with attributes for booking details. A constructor to initialize booking details. Getter and Setter methods to retrieve and update booking details if required. A method to calculate the final ticket cost. Objects of the class to represent bookings.

Finally, display each customer's details and final ticket amount.

Input Format

The first line contains an integer N, representing the number of bookings.

For each booking:

- The next line contains the Booking ID (integer).
- The next line contains the Customer Name (string).
- The next line contains Number of Tickets (integer).
- The next line contains Seat Type ("Standard", "Premium", or "VIP").

Output Format

For each booking, print:

- Booking ID: <booking_id>
- Customer Name: <customer_name>
- Final Ticket Amount: <final_amount> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1001

Ravi Kumar

3

Standard

Output: Booking ID: 1001
Customer Name: Ravi Kumar
Final Ticket Amount: 750.0

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class CityMovie{
    int id;
    String name;
    int tickets;
    String seat;

    public CityMovie(int id, String name, int tickets, String seat){
        this.id=id;
        this.name=name;
        this.tickets=tickets;
        this.seat=seat;
    }

    public void setID(int id){
        this.id=id;
    }
    public void setName(String name){
        this.name=name;
    }
    public void setTickets(int tickets){
        this.tickets=tickets;
    }
    public void setSeat(String seat){
        this.seat=seat;
    }

    public int getID(){
        return id;
    }
    public String getName(){
        return name;
    }
}
```

```
public int getTickets(){
    return tickets;
}
public String getSeat(){
    return seat;
}

public double calcAmt(){
    double amt=0, total;
    if(seat.equals("Standard"))
        amt = 250;
    else if(seat.equals("Premium"))
        amt = 400;
    else if(seat.equals("VIP"))
        amt = 600;

    total = tickets*amt;

    if(tickets>4)
        total=total-total*0.1;
    if(seat.equals("VIP") && total>3000)
        total=total+total*0.05;

    return total;
}

public void display(){
    double total=calcAmt();
    System.out.println("Booking ID: "+id);
    System.out.println("Customer Name: "+name);
    System.out.printf("Final Ticket Amount: %.1f\n", total);
}
}

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=Integer.parseInt(sc.nextLine());

        for(int i=1;i<=n;i++){
            int id=Integer.parseInt(sc.nextLine());
            // Process booking logic here
        }
    }
}
```

```
        String name=sc.nextLine();
        int tickets=Integer.parseInt(sc.nextLine());
        String seat=sc.nextLine();
        CityMovie amt=new CityMovie( id, name, tickets, seat);
        amt.display();
    }
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

Anjali is working as a developer for CityFitness Gym, which wants to build a system to calculate monthly membership fees for gym members based on the type of membership and the number of personal training sessions booked.

Each member's record has:

Member ID (integer) Member Name (string) Membership Type (string: "Basic", "Premium", "Elite") Number of Personal Training Sessions (integer)

The monthly fees are:

Basic – 1000 units Premium – 1500 units Elite – 2000 units

The cost of personal training sessions is 500 units per session.

The calculation rules:

Total Amount = Membership Fee + (Number of Personal Training Sessions × 500)
If the number of sessions is more than 5, a 10% discount is applied on the total amount.
If the member has Elite membership and the total amount exceeds 4000, an additional 5% service tax is added after discount.

Anjali has been asked to implement this system using:

A class with attributes for member details. A constructor to initialize member details. Getter and Setter methods to retrieve and update member details if required. A method to calculate the final monthly fee. Objects of the class to represent members.

Finally, display each member's details and the final monthly fee.

Input Format

The first line contains an integer N, representing the number of members.

For each member:

- Next line contains Member ID (integer)
- Next line contains Member Name (string)
- Next line contains Membership Type ("Basic", "Premium", "Elite")
- Next line contains Number of Personal Training Sessions (integer)

Output Format

For each member, print:

- Member ID: <member_id>
- Member Name: <member_name>
- Final Monthly Fee: <final_fee> (The final fee must be rounded to one decimal place)

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1001

Ravi Kumar

Basic

3

Output: Member ID: 1001

Member Name: Ravi Kumar

Final Monthly Fee: 2500.0

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class CityFitness{
    int id;
    String name;
    String type;
    int sessions;

    public CityFitness(int id, String name, String type, int sessions){
        this.id=id;
        this.name=name;
        this.type=type;
        this.sessions=sessions;
    }
}
```

```
public void setID(int id){  
    this.id=id;  
}  
public void setName(String name){  
    this.name=name;  
}  
public void setType(String type){  
    this.type=type;  
}  
public void setSessions(int sessions){  
    this.sessions=sessions;  
}  
  
public int getID(){  
    return id;  
}  
public String getName(){  
    return name;  
}  
public String getType(){  
    return type;  
}  
public int getSessions(){  
    return sessions;  
}  
  
public double calcAmt(){  
    double amt=0, total;  
  
    if(type.equals("Basic"))  
        amt=1000;  
    else if(type.equals("Premium"))  
        amt=1500;  
    else if(type.equals("Elite"))  
        amt=2000;  
  
    total = amt + sessions*500;  
  
    if(sessions>5)  
        total=total-total*0.1;  
    if(type.equals("Elite") && total>4000)  
        total=total+total*0.05;
```

```
        return total;
    }

    public void display(){
        System.out.println("Member ID: "+getID());
        System.out.println("Member Name: "+getName());
        System.out.printf("Final Monthly Fee: %.1f\n", calcAmt());
    }
}

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=Integer.parseInt(sc.nextLine());

        for(int i=0;i<n;i++){
            int id=Integer.parseInt(sc.nextLine());
            String name=sc.nextLine();
            String type=sc.nextLine();
            int sessions=Integer.parseInt(sc.nextLine());

            CityFitness amt=new CityFitness( id, name, type, sessions);
            amt.display();
        }
    }
}
```

Status : Correct

Marks : 10/10

4. Problem Statement

Neha is working as a developer for CityQuiz Platform, which wants to build a system to calculate quiz scores and identify top scorers among participants.

Each participant's record has:

Participant ID (integer) Participant Name (string) An array of scores in 5 quiz rounds (integers, each between 0 and 100)

The system must calculate:

Total Score = sum of scores in all 5 rounds. Average Score = Total Score ÷ 5. If a participant scores above 80 in all rounds, a bonus of 10 points is added to the total score. Identify the Top Scorer among all participants. If two participants have the same total score, the one with the lower Participant ID is considered the top scorer.

Neha has been asked to implement this system using:

A class with attributes for participant details. A constructor to initialize participant details. Getter and setter methods to retrieve or update participant details. A method to calculate total score and average score (including bonus if applicable). Objects of the class to represent participants.

Finally, display each participant's details and announce the Top Scorer.

Input Format

The first line of input contains an integer N, representing the number of participants.

For each participant:

- Next line: Participant ID (integer)
- Next line: Participant Name (string)
- Next line: 5 integers separated by spaces (scores for 5 quiz rounds)

Output Format

For each participant:

- Participant ID: <participant_id>
- Participant Name: <participant_name>
- Total Score: <total_score>
- Average Score: <average_score>

Finally, print "Top Scorer: <participant_name> with <total_score> points"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1001

Ravi Kumar

85 90 88 92 87

Output: Participant ID: 1001

Participant Name: Ravi Kumar

Total Score: 452

Average Score: 90

Top Scorer: Ravi Kumar with 452 points

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class CityQuiz{
    int id;
    String name;
    int[] arr;
    int total;
    int avg;

    public CityQuiz(int id, String name, int[] arr){
        this.id=id;
        this.name=name;
        this.arr=arr;
        score();
    }

    public void setId(int id){
        this.id=id;
    }
    public void setName(String name){
        this.name=name;
    }
    public void setArr(int[] arr){
        this.arr=arr;
    }

    public int getId(){
        return id;
    }
    public String getName(){
        return name;
    }
    public int getTotal(){
        return total;
    }
    public int getAvg(){
        return avg;
    }
}
```

```
public void score(){
    int total=0, avg;
    boolean above80=true;
    for(int i=0;i<5;i++){
        total+=arr[i];
        if(arr[i]<=80)
            above80=false;
    }
    if(above80)
        total+=10;
    avg=total/5;
    this.total=total;
    this.avg=avg;
}
public void display(){
    System.out.println("Participant ID: "+getId());
    System.out.println("Participant Name: "+getName());
    System.out.println("Total Score: "+total);
    System.out.println("Average Score: "+avg);
}
```

```
class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);

        int n=Integer.parseInt(sc.nextLine());
        CityQuiz top=null;

        for(int i=0;i<n;i++){
            int id=Integer.parseInt(sc.nextLine());
            String name=sc.nextLine();
            String[] score=sc.nextLine().split(" ");
            int[] arr=new int[5];

            for(int j=0;j<5;j++)
                arr[j]=Integer.parseInt(score[j]);

            CityQuiz p=new CityQuiz( id, name, arr);
```

```
        if(top==null || p.getTotal()>top.getTotal())
            top=p;

        p.display();
    }

    System.out.println("Top Scorer: "+top.getName()+" with "+top.getTotal()+" points");
}
}
```

Status : Correct

Marks : 10/10

5. Problem Statement

Each customer at the bank has an Account Number, Customer Name, and an Initial Balance. The bank allows two types of transactions:

Deposit – Increases the balance. Withdrawal – Decreases the balance, but only if enough funds are available. If the withdrawal amount exceeds the available balance, the transaction should be skipped, and the balance should remain unchanged.

You are required to implement this banking system by:

Creating a class with the necessary attributes to store account details.

Using a constructor to initialize the account details when a new account is created. Providing setter methods to update the details if required. Providing getter methods to retrieve account details. Creating objects of this class to represent different customers, where each customer can perform deposits and withdrawals.

Instructions:

Implement the class to store account details. Implement the logic for performing deposit and withdrawal transactions. Ensure that withdrawals don't exceed the available balance. After performing the transactions, print the account number, customer name, and final balance.

Input Format

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the account number (integer).
- The following line contains the customer name (string).
- The next line contains the initial balance (double).
- The next line contains the deposit amount (double).
- The next line contains the withdrawal amount (double).

Output Format

For each customer, print the details in the following format:

1. Account Number: <account_number>
2. Customer Name: <customer_name>

3. Final Balance: <final_balance> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

1234

Rahul Sharma

5000

2000

3000

Output: Account Number: 1234

Customer Name: Rahul Sharma

Final Balance: 4000.0

Answer

```
// You are using Java
import java.util.Scanner;

class Account {
    private int accountNumber;
    private String customerName;
    private double balance;

    public Account(int accountNumber, String customerName, double balance) {
        this.accountNumber = accountNumber;
        this.customerName = customerName;
        this.balance = balance;
    }

    public void setAccountNumber(int accountNumber) {
        this.accountNumber = accountNumber;
    }

    public void setCustomerName(String customerName) {
        this.customerName = customerName;
    }

    public void setBalance(double balance) {
```

```
this.balance = balance;
}

public int getAccountNumber() {
    return accountNumber;
}

public String getCustomerName() {
    return customerName;
}

public double getBalance() {
    return balance;
}

public void deposit(double amount) {
    if (amount >= 0) balance += amount;
}

public void withdraw(double amount) {
    if (amount <= balance) balance -= amount;
}
}

class CityBankApp {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());
        for (int i = 0; i < n; i++) {
            int accNo = Integer.parseInt(sc.nextLine());
            String name = sc.nextLine();
            double initBal = Double.parseDouble(sc.nextLine());
            double deposit = Double.parseDouble(sc.nextLine());
            double withdraw = Double.parseDouble(sc.nextLine());

            Account acc = new Account(accNo, name, initBal);
            acc.deposit(deposit);
            acc.withdraw(withdraw);

            System.out.println("Account Number: " + acc.getAccountNumber());
            System.out.println("Customer Name: " + acc.getCustomerName());
            System.out.println("Final Balance: " + acc.getBalance());
        }
    }
}
```

```
    } } sc.close();  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 6_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 15

Section 1 : MCQ

1. Which of the following is the correct way for class B to inherit from class A?

Answer

class B extends A {}

Status : Correct

Marks : 1/1

2. What will be the output of the following Java program?

```
class Parent {  
    void show() {  
        System.out.println("Parent class");  
    }  
}
```

```
class Child extends Parent {  
    void show() {  
        System.out.println("Child class");  
    }  
}  
class Test {  
    public static void main(String[] args) {  
        Parent obj = new Child();  
        obj.show();  
    }  
}
```

Answer

Child class

Status : Correct

Marks : 1/1

3. What will be the output of the following code?

```
class A {  
    int sum(int x) {  
        return x + 2;  
    }  
}
```

```
class B extends A {  
    int sum(int x) {  
        return super.sum(x) * 2;  
    }  
}
```

```
class C extends B {  
    int sum(int x) {  
        return super.sum(x) - 3;  
    }  
}
```

```
class Test {  
    public static void main(String[] args) {
```

```
C obj = new C();
    System.out.println(obj.sum(4));
}
}
```

Answer

9

Status : Correct

Marks : 1/1

4. What will be the output of the following program?

```
class A {
    int x = 10;
}
```

```
class B extends A {
    int x = 20;
}
```

```
class C extends B {
    int x = 30;
```

```
void display() {
    System.out.println(x);
    System.out.println(super.x);
}
```

```
class Test {
    public static void main(String[] args) {
        C obj = new C();
        obj.display();
    }
}
```

Answer

3020

Status : Correct

Marks : 1/1

5. What will be the output of the following Java program?

```
class Vehicle {  
    void start() {  
        System.out.println("Vehicle starts");  
    }  
}  
class Car extends Vehicle {  
  
    void start() {  
        System.out.println("Car starts");  
    }  
}  
class ElectricCar extends Car {  
    void start() {  
        System.out.println("Electric Car starts silently");  
    }  
}  
class Test {  
    public static void main(String[] args) {  
        Vehicle v = new ElectricCar();  
        v.start();  
    }  
}
```

Answer

Electric Car starts silently

Status : Correct

Marks : 1/1

6. What will be the output of the following program?

```
class A {  
    public int i;  
    private int j;  
}  
class B extends A {  
    void display() {  
        super.j = super.i + 1;  
    }  
}
```

```
        System.out.println(super.i + " " + super.j);
    }
}
class inheritance {
    public static void main(String args[]) {
        B obj = new B();
        obj.i=1;
        obj.j=2;
        obj.display();
    }
}
```

Answer

Compile Time Error

Status : Correct

Marks : 1/1

7. What will be the output of the following code?

```
class A {
    void display() {
        System.out.println("Display A");
    }
}

class B extends A {
    void display() {
        System.out.println("Display B");
    }
}

class C extends B {
    void display() {
        super.display();
    }
}

class Test {
    public static void main(String[] args) {
```

```
    C obj = new C();
    obj.display();
}
}
```

Answer

Display B

Status : Correct

Marks : 1/1

8. What will be the output of the following Java program?

```
class Test {
    void show(int a) {
        System.out.println("Integer method");
    }
    void show(String s) {
        System.out.println("String method");
    }
    public static void main(String[] args) {
        Test obj = new Test();
        obj.show(null);
    }
}
```

Answer

String method

Status : Correct

Marks : 1/1

9. What will be the output of the following program?

```
class Vehicle {
    String type = "Vehicle";
}
```

```
class Car extends Vehicle {
    String type = "Car";
}
```

```
class Test {  
    public static void main(String[] args) {  
        Car c = new Car();  
        System.out.println(c.type);  
    }  
}
```

Answer

Car

Status : Correct

Marks : 1/1

10. What will be the output of the following Java program?

```
class A {  
    void display() {  
        System.out.println("Class A");  
    }  
}
```

```
class B extends A {  
    void show() {  
        System.out.println("Class B");  
    }  
}
```

```
class C extends B {  
    void print() {  
        System.out.println("Class C");  
    }  
}
```

```
class Test {  
    public static void main(String[] args) {  
        C obj = new C();  
        obj.display();  
        obj.show();  
        obj.print();  
    }  
}
```

```
}
```

Answer

Class A Class B Class C

Status : Correct

Marks : 1/1

11. What will be the output of the following Java program?

```
class Vehicle {  
    void startEngine() {  
        System.out.println("Vehicle engine started");  
    }  
}
```

```
class Car extends Vehicle {  
    void startEngine() {  
        System.out.println("Car engine started");  
    }  
}
```

```
class Main {  
    public static void main(String[] args) {  
        Vehicle myVehicle = new Car();  
        myVehicle.startEngine();  
    }  
}
```

Answer

Car engine started

Status : Correct

Marks : 1/1

12. What will be the output of the following Java program?

```
class Test {  
    void display(int a, int b){  
        System.out.println("Method 1");  
    }  
}
```

```
001162    }  
001162 void display(double a, double b) {  
001162     System.out.println("Method 2");  
001162 }  
001162 public static void main(String[] args) {  
001162     Test obj = new Test();  
001162     obj.display(10, 10.0);  
001162 }
```

Answer

Method 2

Status : Correct

Marks : 1/1

13. Which of the following is true about method overriding in Java?

Answer

The method must have the same name, same parameters, and must be in different classes with an inheritance relationship

Status : Correct

Marks : 1/1

14. Select the correct keyword for implementing inheritance through the class.

Answer

extends

Status : Correct

Marks : 1/1

15. What will be the output of the following Java program?

```
class A {
```

```
class A {  
    int value = 10;  
    void display() {  
        System.out.println("A's display: " + value);  
    }  
}
```

```
}

class B extends A {
    int value = 20;
    void display() {
        System.out.println("B's display: " + value);
    }
}

class Test {
    public static void main(String[] args) {
        A obj = new B();
        obj.display();
        System.out.println("Value: " + obj.value);
    }
}
```

Answer

B's display: 20 Value: 10

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 6_Q1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Elsa subscribes to a premium service with a base monthly cost, a service tax and an extra feature cost. Assist her in writing an inheritance program that takes input for these values and calculates the total monthly cost.

Refer to the below class diagram:

Input Format

The first line of input consists of a double value, representing the base monthly cost.

The second line consists of a double value, representing the service tax.

The third line consists of a double value, representing the extra feature cost.

Output Format

The output prints "Rs. X" where X is a double value, rounded off to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 10.0

2.5

5.0

Output: Rs. 17.50

Answer

```
import java.util.Scanner;

// You are using Java
class Subscription{
    double monthlyCost;
    double serviceTax;
    double extraFeatureCost;

    public Subscription(double monthlyCost, double serviceTax, double
extraFeatureCost){
        this.monthlyCost=monthlyCost;
        this.serviceTax=serviceTax;
        this.extraFeatureCost=extraFeatureCost;
    }
}

class PremiumSubscription extends Subscription{
    public PremiumSubscription(double monthlyCost, double serviceTax, double
extraFeatureCost){
        super(monthlyCost, serviceTax, extraFeatureCost);
    }
    public double calculateMonthlyCost(){
        double cost=monthlyCost + serviceTax + extraFeatureCost;
        return cost;
    }
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
  
        double baseMonthlyCost = scanner.nextDouble();  
        double serviceTax = scanner.nextDouble();  
        double extraFeatureCost = scanner.nextDouble();  
  
        PremiumSubscription premiumSubscription = new  
        PremiumSubscription(baseMonthlyCost, serviceTax, extraFeatureCost);  
  
        double totalMonthlyCost = premiumSubscription.calculateMonthlyCost();  
  
        System.out.printf("Rs. %.2f%n", totalMonthlyCost);  
        scanner.close();  
    }  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 6_Q2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Alice is managing an online store and wants to implement a program using inheritance to calculate the selling price of products after applying discounts.

Guide her by following the instructions:

Create a base class called Product with a public double attribute price. Create a subclass called DiscountedProduct, which extends Product and includes a private double attribute discount rate. This subclass has a method called calculateSellingPrice() to determine the final selling price after applying the discount.

Formula: Discounted selling price = price * (1 - discount rate)

Input Format

The first line of input consists of a double value p , the initial price of the product.

The second line consists of a double value d , the discount rate.

Output Format

The output prints "Rs. X", where X is a double value, representing the calculated discounted selling price, rounded off to two decimal places.

If the discount rate is greater than 1, print "Not applicable".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 50.00

0.20

Output: Rs. 40.00

Answer

```
import java.util.Scanner;  
  
// You are using Java  
class Product{  
    double price;  
  
    public Product(double price){  
        this.price=price;  
    }  
}  
  
class DiscountedProduct extends Product{  
    private double discountRate;  
    public DiscountedProduct(double price, double discountRate){  
        super(price);  
        this.discountRate=discountRate;  
    }  
  
    public double calculateSellingPrice(){  
        double total=price*(1-discountRate);  
        return total;  
    }  
}
```

```
    }
}

class ProductPricing {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        double initialPrice = scanner.nextDouble();
        double discountRate = scanner.nextDouble();
        DiscountedProduct discountedProduct = new
DiscountedProduct(initialPrice, discountRate);
        double sellingPrice = discountedProduct.calculateSellingPrice();

        if (sellingPrice >= 0) {
            System.out.printf("Rs. %.2f%n", sellingPrice);
        } else {
            System.out.println("Not applicable");
        }
        scanner.close();
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 6_Q3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Preethi is working on a project to automate sales tax calculations for items in a store. She wants to create a program that takes the price of an item and the sales tax rate as input and calculates the final price of the item after applying the sales tax.

Write a program using the class SalesTaxCalculator, which contains an overloaded method named calculateFinalPrice to handle both integer and double inputs. The program should also include a Main class that takes user input, calls the appropriate method from SalesTaxCalculator, and prints the final price of the item.

Formula Used: Final price = price + ((price * sales tax rate) / 100)

Input Format

The first line of input consists of an integer price (the price of the item for integer inputs).

The second line of input consists of an integer taxRate (the sales tax rate for integer inputs).

The third line of input consists of a double price (the price of the item for double inputs).

The fourth line of input consists of a double taxRate (the sales tax rate for double inputs).

Output Format

The first line of output prints an integer, representing the final price of the item after applying the sales tax for integer inputs (a and b).

The second line prints a double value, representing the final price of the item after applying the sales tax for double-value inputs (m and n), rounded to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 100

10

100.0

5.0

Output: 110

105.00

Answer

```
import java.util.Scanner;  
  
// You are using Java  
class SalesTaxCalculator{  
  
    public static int calculateFinalPrice(int intPrice, int intTaxRate){  
        int intFinal = intPrice + ((intPrice*intTaxRate)/100);  
        return intFinal;  
    }  
}
```

```
    }
    public static double calculateFinalPrice(double doublePrice, double
doubleTaxRate){
        double doubleFinal= doublePrice + ((doublePrice*doubleTaxRate)/100);
        return doubleFinal;
    }
}

class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        int intPrice = scanner.nextInt();
        int intTaxRate = scanner.nextInt();
        double doublePrice = scanner.nextDouble();
        double doubleTaxRate = scanner.nextDouble();

        int finalPriceInt = SalesTaxCalculator.calculateFinalPrice(intPrice,
intTaxRate);
        double finalPriceDouble =
SalesTaxCalculator.calculateFinalPrice(doublePrice, doubleTaxRate);

        System.out.println(finalPriceInt);
        System.out.format("%.2f", finalPriceDouble);
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 6_Q4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Mr.Kapoor wants to create a program to calculate the volume of a Cuboid and a Cube using method overriding.

Implements a base class Cuboid with attributes for length, width, and height. Include a method calculateVolume() that computes the volume of the cuboid.

Extends the base class with a subclass Cube representing a cube, where all sides are equal. Override the calculateVolume() method in the Cube class to compute the volume of the cube.

The program should take user input for the dimensions of the cuboid and the side length of the cube and display the calculated volumes with two decimal places.

Input Format

The first line of input consists of 3 space-separated double values, representing the cuboid length, width, and height, respectively.

The second line consists of a double value, representing the side length of the cube.

Output Format

The first line of output prints the volume of the cuboid, rounded off to two decimal places.

The second line prints the volume of the cube, rounded off to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 60.0 60.0 60.0
50.0

Output: Volume of Cuboid: 216000.00
Volume of Cube: 125000.00

Answer

```
import java.util.Scanner;  
  
// You are using Java  
class Cuboid{  
    double length;  
    double width;  
    double height;  
  
    public Cuboid(double length, double width, double height){  
        this.length=length;  
        this.width=width;  
        this.height=height;  
    }  
  
    public double calculateVolume(){
```

```

        double volume=length*width*height;
        return volume;
    }

}

class Cube extends Cuboid{
    double side;
    public Cube(double side){
        super(side, side, side);
    }
    public double calculateVolume(){
        return super.calculateVolume();
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        double cuboidLength = scanner.nextDouble();
        double cuboidWidth = scanner.nextDouble();
        double cuboidHeight = scanner.nextDouble();

        // Regular object instantiation for Cuboid
        Cuboid cuboid = new Cuboid(cuboidLength, cuboidWidth, cuboidHeight);
        System.out.printf("Volume of Cuboid: %.2f\n", cuboid.calculateVolume());

        double cubeSide = scanner.nextDouble();

        // Upcasting - Using superclass reference for subclass object (DMD)
        Cuboid cube = new Cube(cubeSide); // Upcasting
        System.out.printf("Volume of Cube: %.2f", cube.calculateVolume()); // Calls
        Cube's method dynamically

        scanner.close();
    }
}

```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 6_Q5

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem statement:

Tim was tasked with developing a grocery shopping app. You have a class hierarchy that includes Item, Produce, and OrganicProduce. Your goal is to calculate the total cost of a shopping list, which may contain a mix of regular produce and organic produce items. Additionally, you need to apply discounts to organic items. Apply a 10% discount on organic produce items

Class Hierarchy:

Item: Base class for all items.

Produce: Subclass of Item for regular produce items.

OrganicProduce: Subclass of Produce for organic produce items.

Input Format

The first line of input consists of an integer, 'n'.

For each 'n' item, the user will provide:

- A string 'type' representing the item type ('Regular' or 'Organic').
- A string 'name' represents the item name.
- A double 'price' represents the item price.

Output Format

The output will display the total cost of the shopping list, including discounts on organic items.

Refer to the sample output for format specifications.

Sample Test Case

Input: 1

Regular Banana 1.99

Output: 1.99

Answer

```
import java.util.Scanner;  
// You are using Java  
class Item{  
    String name;  
    double price;  
  
    Item(String name, double price){  
        this.name=name;  
        this.price=price;  
    }  
    public double calculateCost(){  
        return this.price;  
    }  
}  
class Produce extends Item{
```

```
Produce(String name, double price){  
    super(name, price);  
}  
public double calculateCost(){  
    return super.calculateCost();  
}  
}  
  
class OrganicProduce extends Produce{  
    OrganicProduce(String name, double price){  
        super(name, price);  
    }  
    public double calculateCost(){  
        double discount=price-price*0.1;  
        return discount;  
    }  
}  
  
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
  
        int n = sc.nextInt();  
        sc.nextLine(); // Consume newline  
  
        double totalCost = 0.0;  
  
        for (int i = 0; i < n; i++) {  
            String type = sc.next();  
            String name = sc.next();  
            double price = sc.nextDouble();  
  
            if (type.equals("Regular")) {  
                Item item = new Produce(name, price);  
                totalCost += item.calculateCost();  
            } else if (type.equals("Organic")) {  
                Item item = new OrganicProduce(name, price);  
                totalCost += item.calculateCost();  
            }  
        }  
        System.out.printf("%.2f%n", totalCost);  
    }  
}
```

}

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 6_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Arun wants to calculate the age gap between the grandfather and the son and determine the father's age after 5 years.

Your task is to assist him in developing a program using three classes: GrandFather, Father, and Son, where the GrandFather stores the grandfather's age, the Father extends GrandFather to include the father's age and calculates his age after 5 years, and Son extends Father to include the son's age and calculate the age difference between the grandfather and the son.

Input Format

The input consists of three integers representing the ages of the grandfather, father, and son, one per line.

Output Format

The first line of output prints "Grandfather and son's age gap:" followed by an integer representing the age gap between the grandfather and the son, ending with "years".

The second line prints "Father's Age:" followed by an integer representing the father's age after 5 years, ending with "years".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 50
30
3

Output: Grandfather and son's age gap: 47 years
Father's Age: 35 years

Answer

```
import java.util.Scanner;  
  
// You are using Java  
class GrandFather{  
    int grandFatherAge;  
  
    public void setGrandfatherAge(int grandFatherAge){  
        this.grandFatherAge=grandFatherAge;  
    }  
  
    class Father extends GrandFather{  
        int fatherAge;  
  
        public void setFatherAge(int fatherAge){  
            this.fatherAge=fatherAge;  
        }  
  
        public int calculateFatherAgeAfter5Years(){  
            return (fatherAge+5);  
        }  
    }  
}
```

```

    }

class Son extends Father{
    int sonAge;

    public void setSonAge(int sonAge){
        this.sonAge=sonAge;
    }

    public int calculateGrandfatherSonAgeDifference(){
        return (grandFatherAge-sonAge);
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        Son son = new Son();

        int grandfatherAge = scanner.nextInt();
        son.setGrandfatherAge(grandfatherAge);

        int fatherAge = scanner.nextInt();
        son.setFatherAge(fatherAge);

        int sonAge = scanner.nextInt();
        son.setSonAge(sonAge);

        System.out.println("Grandfather and son's age gap: "+
        son.calculateGrandfatherSonAgeDifference() + " years");

        int fatherAgeAfter5Years = son.calculateFatherAgeAfter5Years();
        System.out.println("Father's Age: " + fatherAgeAfter5Years + " years");
    }
}

```

Status : Correct

Marks : 10/10

2. Problem Statement

A bank provides two types of deposit schemes: Fixed Deposits (FD) and Recurring Deposits (RD). Customers want to calculate the interest they can earn based on their selected scheme.

Develop a Java program using inheritance to compute the interest for FD and RD. The program should include:

A base class Account with attributes accountHolder and principalAmount, along with a method for interest calculation. A subclass FixedDeposit that calculates interest for FD. A subclass RecurringDeposit that calculates interest for RD.

Formulas Used:

Interest for FD: $(\text{principal amount} * \text{duration in years} * \text{rate of interest}) / 100$

Interest for RD: $(\text{maturity amount} * \text{duration in months} * \text{rate of interest}) / (12 * 100)$, where maturity amount = monthly deposit * duration in months.

Input Format

The first line of input consists of the choice (1 for FD, 2 for RD).

If the choice is 1, the following lines consist of account holder (string), principal amount (double), duration in years (int), and rate of interest (double).

If the choice is 2, the following lines consist of account holder (string), monthly deposit (int), duration in months (int), and rate of interest (double).

Output Format

The output prints the calculated interest with one decimal place in the following format.

For choice 1: "Interest for FD: <calculated interest >"

For choice 2: "Interest for FD: <calculated interest >"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1
Alice
50000.56
5
6.5

Output: Interest for FD: 16250.2

Answer

```
import java.util.Scanner;  
  
// You are using Java  
abstract class Account{  
    String accHolder;  
    double principal;  
  
    Account(String accHolder, double principal){  
        this.accHolder=accHolder;  
        this.principal=principal;  
    }  
  
    public abstract double calculateInterest();  
  
}  
  
class FixedDeposit extends Account{  
    int duration;  
    double rate;  
  
    FixedDeposit(String accHolder, double principal, int duration, double rate){  
        super(accHolder, principal);  
        this.duration=duration;  
        this.rate=rate;  
    }  
  
    public double calculateInterest(){  
        return ((principal*duration*rate)/100);  
    }  
}  
  
class RecurringDeposit extends FixedDeposit{  
    double monthlyDeposit;
```

```
int monthlyDuration;
double rate;

RecurringDeposit(String accHolder, double monthlyDeposit, int
monthlyDuration, double rate){
    super(accHolder, monthlyDeposit*monthlyDuration, monthlyDuration, rate);
    this.monthlyDeposit=monthlyDeposit;
    this.monthlyDuration=monthlyDuration;
    this.rate=rate;
}

public double calculateInterest(){
    double maturity = principal;
    return ((maturity*monthlyDuration*rate)/(12*100));
}
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int choice = sc.nextInt();

        switch (choice) {
            case 1:
                sc.nextLine();
                String fdName = sc.nextLine();
                double fdPrincipal = sc.nextDouble();
                int fdDuration = sc.nextInt();
                double fdRate = sc.nextDouble();

                FixedDeposit fd = new FixedDeposit(fdName, fdPrincipal, fdDuration,
fdRate);
                System.out.printf("Interest for FD: %.1f", fd.calculateInterest());
                break;

            case 2:
                sc.nextLine();
                String rdName = sc.nextLine();
                int rdDeposit = sc.nextInt();
                int rdDuration = sc.nextInt();
                double rdRate = sc.nextDouble();
```

```

        RecurringDeposit rd = new RecurringDeposit(rdName, rdDeposit,
rdDuration, rdRate);
        System.out.printf("Interest for RD: %.1f", rd.calculateInterest());
        break;

    default:
        System.out.println("Invalid Choice");
    }
}
}

```

Status : Correct

Marks : 10/10

3. Problem Statement

Mary is managing a business and wants to analyze its profitability. She operates both a regular business model and a seasonal business model. To assess profitability, she uses a program that calculates and compares the profit margins for both models based on revenue and cost.

The program defines:

BusinessUtility class with a method calculateMargin(double revenue, double cost).SeasonalBusinessUtility (inherits from BusinessUtility) and overrides calculateMargin(double revenue, double cost), adding a seasonal adjustment of 10% to the base margin.ProfitabilityChecker class with a method checkProfitability(double regularMargin), which prints "Business is profitable." if the regular margin is 10% or more, otherwise prints "Business is not profitable.".

Mary inputs revenue and cost, and the program compute and display the regular and seasonal margins using:

$$\text{Margin} = ((\text{Revenue} - \text{Cost}) / \text{Revenue}) \times 100$$

$$\text{Seasonal Margin} = \text{Margin} + 10$$

Input Format

The first line of input consists of a double value r, representing the revenue.

The second line consists of a double value c, representing the cost.

Output Format

The first line prints a double value, representing the regular profit margin, rounded to two decimal places, in the format: "Regular Margin: X. XX%", where X.XX denotes the calculated regular margin.

The second line prints a double value, representing the seasonal profit margin, rounded to two decimal places, in the format: "Seasonal Margin: X. XX%", where X.XX denotes the calculated seasonal margin.

The third line prints a string, indicating whether the business is profitable or not profitable, based on the regular margin.

If the regular margin is less than 10, print "Business is not profitable.". If it is 10 or greater, print "Business is profitable."

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1000.0

800.0

Output: Regular Margin: 20.00%

Seasonal Margin: 30.00%

Business is profitable.

Answer

```
import java.util.Scanner;  
  
// You are using Java  
class BusinessUtility{  
  
    public double calculateMargin(double revenue, double cost){  
        double margin = ((revenue-cost)/revenue)*100;  
        return margin;  
    }  
}  
  
class SeasonalBusinessUtility extends BusinessUtility{
```

```

public double calculateMargin(double revenue, double cost){
    double margin = super.calculateMargin(revenue, cost);
    return (margin+10);
}

class ProfitabilityChecker{
    public void checkProfitability(double regularMargin){

        if(regularMargin>=10)
            System.out.println("Business is profitable.");

        else
            System.out.println("Business is not profitable.");
    }
}

class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        double revenue = scanner.nextDouble();
        double cost = scanner.nextDouble();
        BusinessUtility business = new BusinessUtility();
        SeasonalBusinessUtility seasonalBusiness = new
SeasonalBusinessUtility();
        double regularMargin = business.calculateMargin(revenue, cost);
        double seasonalMargin = seasonalBusiness.calculateMargin(revenue,
cost);

        System.out.printf("Regular Margin: %.2f%%\n", regularMargin);
        System.out.printf("Seasonal Margin: %.2f%%\n", seasonalMargin);

        ProfitabilityChecker checker = new ProfitabilityChecker();
        checker.checkProfitability(regularMargin);
        scanner.close();
    }
}

```

Status : Correct

Marks : 10/10

4. Problem Statement

Bob has been tasked with creating a program using CircleUtils class to calculate and display the circumference and area of the circle.

The program should allow Bob to input the radius of a circle as both an integer and a double and compute both the circumference and area of the circle using separate overloaded methods:

calculateCircumference- To calculate the circumference using the formula
 $2 * 3.14 * \text{radius}$
calculateArea- To calculate the area $3.14 * \text{radius} * \text{radius}$

Write a program to help Bob.

Input Format

The first line of input consists of an integer m, representing the radius of the circle as a whole number.

The second line consists of a double value n, representing the radius of the circle as a decimal number.

Output Format

The first line of output displays two space-separated double values, rounded to two decimal places, representing the circumference of the circle with the integer radius and the double radius, respectively.

The second line displays two space-separated double values, rounded to two decimal places, representing the area of the circle with the integer radius and the double radius, respectively.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

3.50

Output: 31.40 21.98

78.50 38.47

Answer

```
import java.util.Scanner;
// You are using Java
class CircleUtils{
    public double calculateCircumference(int radius){
        return (2*3.14*radius);
    }

    public double calculateCircumference(double radius){
        return (2*3.14*radius);
    }

    public double calculateArea(int radius){
        return (3.14*radius*radius);
    }

    public double calculateArea(double radius){
        return (3.14*radius*radius);
    }
}

class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        int radiusInt = scanner.nextInt();
        double radiusDouble = scanner.nextDouble();

        CircleUtils circleUtils = new CircleUtils();

        double circumferenceInt = circleUtils.calculateCircumference(radiusInt);
        double circumferenceDouble =
            circleUtils.calculateCircumference(radiusDouble);
        double areaInt = circleUtils.calculateArea(radiusInt);
        double areaDouble = circleUtils.calculateArea(radiusDouble);

        System.out.format("%.2f %.2f\n", circumferenceInt, circumferenceDouble);
        System.out.format("%.2f %.2f", areaInt, areaDouble);

        scanner.close();
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 6_PAH

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Ram is designing a program to calculate the Body Mass Index (BMI). Your task is to assist him by following the given specifications.

Create a base class BMIcalculator with a method calculateBMI() to compute BMI using the formula weight / (height * height).

Extend the class with a subclass CustomBMIcalculator that overrides the method calculateBMI() to calculate BMI based on custom criteria, assigning categories such as "Underweight," "Normal Weight," "Overweight," or "Obese."

BMI < 18.5, category = "Underweight"
BMI >= 18.5 < 24.9, category = "Normal Weight"
BMI >= 25 < 29.9, category = "Overweight"
else category = "Obese"

Implement user input for weight and height and display both the standard and custom BMI calculations.

Input Format

The first line of input consists of a double value, representing the weight in kgs.

The second line consists of a double value, representing the height in meters.

Output Format

The first line of output prints: "Standard BMI Calculation:"

The second line of output prints: "BMI: " followed by the calculated BMI value (to two decimal places).

The third line of output prints: "Custom BMI Calculation:"

The fourth line of output prints: "Category: " followed by the BMI category.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 69.7

2.6

Output: Standard BMI Calculation:

BMI: 10.31

Custom BMI Calculation:

Category: Underweight

Answer

```
import java.util.Scanner;  
  
// You are using Java  
class BMIcalculator{  
    double weight;  
    double height;  
  
    BMIcalculator(double weight, double height){  
        this.weight=weight;
```

```
        this.height=height;
    }

    public double calculateBMI(){
        double bmi=weight/(height*height);
        return bmi;
    }

    public void displayBMI(){
        double bmi=calculateBMI();
        System.out.printf("BMI: %.2f\n",bmi);
    }
}

class CustomBMIcalculator extends BMIcalculator{
    CustomBMIcalculator(double weight, double height){
        super(weight, height);
    }

    public String calculateCategory(){
        double bmi=super.calculateBMI();
        if(bmi<18.5)
            return "Underweight";
        else if(bmi>=18.5 && bmi<24.9)
            return "Normal Weight";
        else if(bmi>=25 && bmi<29.9)
            return "Overweight";
        else
            return "Obese";
    }

    public void displayCustomBMI(){
        String category=calculateCategory();
        System.out.println("Category: "+category);
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        double weight = scanner.nextDouble();
```

```
        double height = scanner.nextDouble();

        BMIcalculator bmiCalculator = new BMIcalculator(weight, height);
        System.out.println("Standard BMI Calculation:");
        bmiCalculator.displayBMI();

        CustomBMIcalculator customBMIcalculator = new
        CustomBMIcalculator(weight, height);
        System.out.println("Custom BMI Calculation:");
        customBMIcalculator.displayCustomBMI();

        scanner.close();
    }
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Sharon, a software developer, is working on a project to automate velocity calculations for various objects. She wants to create a class named VelocityCalculator with overloaded methods calculateVelocity to calculate the velocity. One method will accept distance in meters and time in seconds as integers, while another will accept distance and time as doubles.

Help her in completing the project.

Formula: Velocity = distance / time

Input Format

The first line of input consists of an integer, representing the distance in meters (for the integer method).

The second line consists of an integer, representing the time in seconds (for the integer method).

The third line consists of a double value, representing the distance in meters (for the double method).

The fourth line consists of a double value, representing the time in seconds (for the double method).

Output Format

The first line prints the velocity calculated using the integer inputs in the format:

Velocity with integer inputs: <velocity> m/s

The second line prints the velocity calculated using the double inputs in the format:

Velocity with double inputs: <velocity> m/s

Note:

The velocity for the double inputs should be printed with two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 100
10
100.5
10.2

Output: Velocity with integer inputs: 10 m/s

Velocity with double inputs: 9.85 m/s

Answer

```
import java.util.Scanner;  
  
// You are using Java  
class VelocityCalculator{  
  
    public static int calculateVelocity(int distInt, int timeInt){  
        int velocityInt=distInt/timeInt;  
        return velocityInt;
```

```

    }

    public static double calculateVelocity(double distDouble, double timeDouble){
        double velocityDouble=distDouble/timeDouble;
        return velocityDouble;
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        int distanceInt = scanner.nextInt();
        int timeInt = scanner.nextInt();

        double distanceDouble = scanner.nextDouble();
        double timeDouble = scanner.nextDouble();

        int velocityInt = VelocityCalculator.calculateVelocity(distanceInt, timeInt);
        double velocityDouble =
VelocityCalculator.calculateVelocity(distanceDouble, timeDouble);

        System.out.println("Velocity with integer inputs: " + velocityInt + " m/s");
        System.out.printf("Velocity with double inputs: %.2f m/s", velocityDouble);

        scanner.close();
    }
}

```

Status : Correct

Marks : 10/10

3. Problem Statement

John is planning a long road trip and wants to calculate the distance his car can travel based on its speed and fuel capacity. As John knows that different cars have different fuel efficiencies, he wants a program that can help him estimate the travel distance for any given car.

To do this, you are tasked with creating a program that calculates the travel distance of a car based on its speed and fuel capacity. The calculation is simple and follows the formula:

Travel Distance = Speed * Fuel Capacity

You need to model this system using a Vehicle class and a Car class. The Vehicle class will have attributes for the speed and fuel capacity, while the Car class will inherit from the Vehicle class and include a method to calculate the travel distance.

Input Format

The first line of input consists of a double value representing the speed of the car in km/h.

The second line of input consists of a double value representing the fuel capacity of the car in liters.

Output Format

The first line should print "Speed: X km/h", where X is the speed of the car, rounded to two decimal places.

The second line should print "Fuel Capacity: Y liters", where Y is the fuel capacity of the car, rounded to two decimal places.

The third line should print "Travel Distance: Z km", where Z is the total travel distance the car can cover, rounded to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 10.0

1.0

Output: Speed: 10.00 km/h

Fuel Capacity: 1.00 liters

Travel Distance: 10.00 km

Answer

```
import java.util.Scanner;
```

```
// You are using Java  
class Vehicle{
```

```

        double speed;
        double fuelCapacity;

        Vehicle(double speed, double fuelCapacity){
            this.speed=speed;
            this.fuelCapacity=fuelCapacity;
        }
    }

    class Car extends Vehicle{
        Car(double speed, double fuelCapacity){
            super(speed, fuelCapacity);
        }

        public double calculateTravelDistance(){
            double distance = speed*fuelCapacity;
            return distance;
        }
    }

    public class Main {
        public static void main(String[] args) {
            Scanner scanner = new Scanner(System.in);

            double speed = scanner.nextDouble();
            double fuelCapacity = scanner.nextDouble();

            Car car = new Car(speed, fuelCapacity);

            System.out.println("Speed: " + String.format("%.2f", car.speed) + " km/h");
            System.out.println("Fuel Capacity: " + String.format("%.2f", car.fuelCapacity)
+ " liters");
            System.out.println("Travel Distance: " + String.format("%.2f",
car.calculateTravelDistance()) + " km");

            scanner.close();
        }
    }

```

Status : Correct

Marks : 10/10

4. Problem Statement

In a company, each manager has a unique employee ID and a monthly salary. You are required to design a program that will calculate and display the annual(12 months) salary of a manager based on the input details provided by the user.

Implement the solution using a single inheritance approach.

Employee: The base class with attributes name and employeeID.

Manager: The derived class inheriting from Employee, with an additional attribute salary.

Input Format

The first line of input consists of a string name, representing the manager's name.

The second line of input consists of an integer employeeID, representing the manager's employee ID.

The third line of input consists of a double salary, representing the manager's monthly salary.

Output Format

The first line of output prints: Name: <name>

The second line of output prints: Annual Salary: Rs. <annual_salary> (rounded to two decimal places).

Refer to the sample output for formatting specifications.

Sample Test Case

Input: Davis

234

28750.75

Output: Name: Davis

Annual Salary: Rs. 345009.00

Answer

```
import java.util.Scanner;
import java.text.DecimalFormat;

// You are using Java
class Employee{
    String name;
    int employeeID;

    Employee(String name, int employeeID){
        this.name=name;
        this.employeeID=employeeID;
    }
}

class Manager extends Employee{
    double salary;
    Manager(String name, int employeeID, double salary){
        super(name, employeeID);
        this.salary=salary;
    }

    public double calculateAnnualSalary(){
        double annual=salary*12;
        return annual;
    }
}

class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        DecimalFormat df = new DecimalFormat("0.00");

        String name = scanner.nextLine();
        int employeeID = scanner.nextInt();
        double salary = scanner.nextDouble();

        Manager manager = new Manager(name, employeeID, salary);

        System.out.println("Name: " + manager.name);
        System.out.println("Annual Salary: Rs. " +
df.format(manager.calculateAnnualSalary()));
    }
}
```

```
        scanner.close();  
    }  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 7_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 15

Section 1 : MCQ

1. Can a Java interface contain both default and static methods?

Answer

Yes, an interface can have both default and static methods.

Status : Correct

Marks : 1/1

2. What is the output of the following code?

```
interface MathOperations {  
    static int square(int x) {  
        return x * x;  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        System.out.println(MathOperations.square(5));  
    }  
}
```

Answer

25

Status : Correct

Marks : 1/1

3. Consider a class implementing an interface and extending a class, both having a method with the same name. Which method gets called?

Answer

The method from the superclass

Status : Correct

Marks : 1/1

4. What is the output of the following code?

```
interface A {  
    default void show() {  
        System.out.println("A's Default Method");  
    }  
}
```

```
interface B {  
    default void show() {  
        System.out.println("B's Default Method");  
    }  
}
```

```
class C implements A, B {  
    public void show() {  
        A.super.show();  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        C obj = new C();  
        obj.show();  
    }  
}
```

Answer

A's Default Method

Status : Correct

Marks : 1/1

5. What is the output of the following code?

```
interface A {  
    static void display() {  
        System.out.println("Static method in A");  
    }  
}
```

```
class B implements A {  
    static void display() {  
        System.out.println("Static method in B");  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        B.display();  
    }  
}
```

Answer

Static method in B

Status : Correct

Marks : 1/1

6. What is the output of the following code?

```
interface A {  
    default void show() {  
        System.out.println("A's Default Method");  
    }  
}
```

```
class B {  
    public void show() {  
        System.out.println("B's Method");  
    }  
}
```

```
class C extends B implements A {  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        C obj = new C();  
        obj.show();  
    }  
}
```

Answer

B's Method

Status : Correct

Marks : 1/1

7. How can a class explicitly call a default method from an interface if there is a naming conflict?

Answer

Using InterfaceName.super.methodName();

Status : Correct

Marks : 1/1

8. Which of the following is the correct way to declare an interface in Java?

Answer

```
interface Vehicle { void start();}
```

Status : Correct

Marks : 1/1

9. What is the primary purpose of static methods in Java interfaces?

Answer

They allow an interface to provide helper methods without requiring an implementing class.

Status : Correct

Marks : 1/1

10. What happens when an implementing class does not override a default method from an interface?

Answer

The default method's implementation from the interface will be used.

Status : Correct

Marks : 1/1

11. Which of the following statements about Java interfaces is true?

Answer

A class can implement multiple interfaces.

Status : Correct

Marks : 1/1

12. Which of the following statements is true regarding default methods in Java interfaces?

Answer

A default method can be overridden in a class implementing the interface.

Status : Correct

Marks : 1/1

13. What is the output of the following code?

```
interface X {  
    default void show() {  
        System.out.println("X's Default Method");  
    }  
}
```

```
interface Y {  
    default void show() {  
        System.out.println("Y's Default Method");  
    }  
}
```

```
class Z implements X, Y {  
    public void show() {  
        System.out.println("Z's Method");  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Z obj = new Z();  
        obj.show();  
    }  
}
```

Answer

Z's Method

Status : Correct

Marks : 1/1

14. If a class implements two interfaces that have the same default method, what must the class do?

Answer

The class must override the method to resolve ambiguity.

Status : Correct

Marks : 1/1

15. How do you call a static method from an interface MyInterface?

Answer

MyInterface.staticMethod();

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 7_Q1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement:

Rajiv is analyzing the energy consumption in his household and wants to calculate the total cost based on the daily energy usage. He is given the rate per unit of electricity and the energy consumed for multiple days. To structure this calculation efficiently, he decides to use an interface-based approach.

Implement an interface CostCalculator with the necessary methods to retrieve energy details and compute the cost. The calculations should be handled in the EnergyConsumptionTracker class, while the EnergyConsumptionApp class should only handle input and output.

Formula

Energy Cost for one day = Energy Consumed per day * Rate Per Unit

Input Format

The first line of input consists of the rate per unit as an 'R' (a double value).

The second line of input consists of the number of days 'N' (an integer).

The third line of input consists of the daily energy consumption values for each day 'D' (double values), separated by space.

Output Format

The first line of the output prints: "Day-wise Energy Cost:"

The next N lines of the output print the day-wise energy costs(double type) and the total energy cost (double type) in Indian Rupees in the following format: "Day [day_number]: Rs. [energy_cost]"

The last line of the output prints: "Total Energy Cost: Rs. [total_cost]"

Note: energy_cost and total_cost are rounded off to two decimal points

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 0.01

3

10.0 20.0 30.0

Output: Day-wise Energy Cost:

Day 1: Rs. 0.10

Day 2: Rs. 0.20

Day 3: Rs. 0.30

Total Energy Cost: Rs. 0.60

Answer

```
import java.util.Scanner;
```

```
// You are using Java
```

```
interface CostCalculator{
    void getEnergyDetails(Scanner sc);
    void calculateAndDisplayCost();
}

class EnergyConsumptionTracker implements CostCalculator{
    double rate;
    int n;
    double[] energy;

    EnergyConsumptionTracker(double rate, int n){
        this.rate=rate;
        this.n=n;
        this.energy=new double[n];
    }

    public void getEnergyDetails(Scanner sc){
        for(int i=0;i<n;i++){
            energy[i]=sc.nextDouble();
        }
    }

    public void calculateAndDisplayCost(){
        double total=0;
        double dayWise;
        System.out.println("Day-wise Energy Cost:");
        for(int i=0;i<n;i++){
            dayWise=energy[i]*rate;
            System.out.printf("Day %d: Rs. %.2f\n", i+1, dayWise);
            total+=dayWise;
        }
        System.out.printf("Total Energy Cost: Rs. %.2f", total);
    }
}

class EnergyConsumptionApp {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        double ratePerUnit = scanner.nextDouble();
        int numDays = scanner.nextInt();

        CostCalculator tracker = new EnergyConsumptionTracker(ratePerUnit,
        numDays);
```

```
        tracker.getEnergyDetails(scanner);
        tracker.calculateAndDisplayCost();

        scanner.close();
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 7_Q2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Jaheer is working on a health monitoring system to help individuals calculate their Body Mass Index (BMI). He has implemented a basic BMI calculator and an interface called HealthCalculator. It should have a method called calculateBMI.

You are tasked with creating a program that takes weight and height as input, calculates the BMI using the BMICalculator class, and displays the result. If the height or weight is less than or equal to zero, then return -1.

Formula: $BMI = \text{weight} / (\text{height} * \text{height})$

Input Format

The first line of input consists of a double value W, the person's weight in kilograms.

The second line consists of a double value H, the height of the person in meters.

Output Format

The output displays "BMI: " followed by a double value, representing the calculated BMI, rounded off to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 70.0

1.75

Output: BMI: 22.86

Answer

```
import java.util.Scanner;  
  
// You are using Java  
interface HealthCalculator{  
    double calculateBMI(double height, double weight);  
}  
  
class BMICalculator implements HealthCalculator{  
    double height;  
    double weight;  
  
    BMICalculator(){  
        this.height=height;  
        this.weight=weight;  
    }  
  
    public double calculateBMI(double weight, double height){  
        if((height<=0) || (weight <=0))  
            return -1;  
        double bmi=weight/(height*height);  
        return bmi;  
    }  
}  
class Main {
```

```
public static void main(String[] args) {  
    Scanner scanner = new Scanner(System.in);  
  
    double weight = scanner.nextDouble();  
    double height = scanner.nextDouble();  
  
    BMICalculator bmiCalculator = new BMICalculator();  
  
    double bmi = bmiCalculator.calculateBMI(weight, height);  
  
    System.out.printf("BMI: %.2f\n", bmi);
```

```
    scanner.close();  
}  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 7_Q3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

A financial analyst, Alex, needs a program to calculate simple interest for various financial transactions. He requires a straightforward tool that takes in the principal amount, interest rate, and time in years and computes the interest.

The formula to be used is: $\text{Interest} = \text{Principal} \times \text{Rate} \times \text{Time} / 100$

Implement this functionality using the `InterestCalculator` interface and the `SimpleInterestCalculator` class.

Input Format

The first line of input consists of the principal amount `P` as a double value.

The second line of input consists of the annual interest rate r as a double value.

The third line of input consists of the number of years t as a positive integer, which is an integer value.

Output Format

The output displays the calculated simple interest in the following format:
"Simple Interest: [interest_value]", Here, [interest_value] should be replaced with the actual interest value calculated by the program.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1000.00
5.00
2

Output: Simple Interest: 100.0

Answer

```
import java.util.Scanner;

// You are using Java
interface InterestCalculator{
    double simpleInterest(double principal, double rate, int time);
}

class SimpleInterestCalculator implements InterestCalculator{
    double principal;
    double rate;
    int time;

    public double simpleInterest(double principal, double rate, int time){
        double interest = (principal*rate*time)/100;
        return interest;
    }
}

class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
```

```
        double principal = scanner.nextDouble();

        double rate = scanner.nextDouble();

        int time = scanner.nextInt();

        InterestCalculator calculator = new SimpleInterestCalculator();

        double interest = calculator.simpleInterest(principal, rate, time);

        System.out.println("Simple Interest: " + interest);

    }

}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 7_Q4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Maria, a software developer, is working on an inventory management system project using Java that utilizes an inventory interface to manage a store's products.

The interface should define two methods: addProduct, which adds a product by accepting its name, price, and quantity, and calculateTotalValue, which computes the total value of all products in the inventory. Implement the interface in a class called SimpleInventory, which internally manages a list of Product objects.

Each Product object should encapsulate the product's name, price, and quantity and include a method to calculate its value as price × quantity. The system should allow users to dynamically add products to the inventory and calculate the total value of all products stored.

Help Maria achieve the task.

Input Format

The first line of input consists of an integer to choose one of the following options:

1 - to add a product to the inventory.

2 - to calculate and view the total inventory value.

3 - to exit the program.

For Choice 1 (Add Product):

The next input line is the string representing the product name as a string (single or multi-word, without quotes).

The next line is a double value representing the price as a decimal value

The next line is an integer value representing the quantity as an integer

For Choices 2 and 3, no additional input is required

Output Format

The output displays the results of the commands as follows:

- For the addProduct command, the program should display "Product added to inventory."
- For choice 2, the program should display "Total inventory value [totalvalue]."
The total value should be displayed with one decimal place. If there is no product in the inventory, print the total as 0.0.
- For choice 3, the program should exit

If the choice is not 1, 2, or 3, then print "Invalid choice. Please select a valid option (1/2/3).".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1

Laptop

800.0

3

2

5

3

Output: Product added to inventory.

Total inventory value: \$2400.0

Invalid choice. Please select a valid option (1/2/3).

Answer

```
import java.util.Scanner;  
  
// You are using Java  
interface Inventory{  
    void addProduct(String name, double price, int quantity);  
    double calculateTotalValue();  
}  
  
class Product{  
    String name;  
    double price;  
    int quantity;  
  
    Product(String name, double price, int quantity){  
        this.name=name;  
        this.price=price;  
        this.quantity=quantity;  
    }  
    public double value(){  
        return price*quantity;  
    }  
}  
class SimpleInventory implements Inventory{  
    public Product[] products;  
    int count;  
    SimpleInventory(int n){  
        products=new Product[n];  
        count=0;  
    }  
}
```

```

public void addProduct(String name, double price, int quantity){
    if(count<products.length){
        products[count]=new Product(name, price, quantity);
        count++;
        System.out.println("Product added to inventory.");
    }
}

public double calculateTotalValue(){
    double total=0;
    for(int i=0;i<count;i++)
        total+=products[i].value();
    return total;
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        Inventory inventory = new SimpleInventory(10);
        while (true) {
            int choice = scanner.nextInt();
            if (choice == 1) {
                scanner.nextLine();
                String productName = scanner.nextLine();
                double price = scanner.nextDouble();
                int quantity = scanner.nextInt();
                inventory.addProduct(productName, price, quantity);
            } else if (choice == 2) {
                double totalValue = inventory.calculateTotalValue();
                System.out.println("Total inventory value: $" + totalValue);
            } else if (choice == 3) {
                break;
            } else {
                System.out.println("Invalid choice. Please select a valid option
(1/2/3).");
            }
        }
        scanner.close();
    }
}

```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 7_Q5

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Raj is curious about how old he is in the current year.

He has asked you to create a simple program that calculates a person's age based on their birth year. You decide to implement this functionality using the AgeCalculator interface and the HumanAgeCalculator class.

Note: The current year is 2024. Calculate the current age by using the formula: current year - birth year.

Input Format

The input consists of an integer representing the birth year.

Output Format

The output displays "You are X years old." where X is an integer representing the calculated age based on the entered birth year.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1934

Output: You are 90 years old.

Answer

```
import java.util.Scanner;  
  
// You are using Java  
interface AgeCalculator{  
    int calculateAge(int birthYear);  
}  
  
class HumanAgeCalculator implements AgeCalculator{  
    int birthYear;  
    int currentYear=2024;  
  
    HumanAgeCalculator(){  
        this.birthYear=birthYear;  
    }  
  
    public int calculateAge(int birthYear){  
        return currentYear-birthYear;  
    }  
}  
  
class AgeCalculatorApp {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
  
        AgeCalculator ageCalculator = new HumanAgeCalculator();  
  
        int birthYear = scanner.nextInt();  
        int age = ageCalculator.calculateAge(birthYear);  
  
        System.out.println("You are " + age + " years old.");
```

}

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 7_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

A developer aims to create a budget management system using two interfaces, ExpenseRecorder for recording expenses and BudgetCalculator for calculating remaining budgets.

The ExpenseTracker class implements these interfaces, allowing users to input an initial budget and record expenses iteratively until entering 0.0 as a sentinel value.

The program then computes and displays the remaining budget or notifies of budget exceedance.

Example

Input

100.0

20.0 30.0 10.0 0.0

Output

Remaining budget: Rs. 40.00

Explanation

The initial budget is 100.0. Expenses of 20.0, 30.0, and 10.0 are recorded.

Remaining budget is calculated ($100.0 - 20.0 - 30.0 - 10.0 = 40.0$).

Input Format

The first line of input is the initial budget as a double-point number (double type).

The budget is a positive number.

The second line of input consists of individual expenses as double-point numbers. Each expense is separated by space.

To end the input, an expense of 0.0 is used.

Output Format

The output displays the remaining budget, formatted to two decimal places, in the following format:

If the remaining budget (double type) is non-negative, it prints "Remaining budget: Rs. [remainingBudget]".

If the remaining budget is negative, it prints "No remaining budget, You've exceeded your budget!".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 100.0

20.0 30.0 10.0 0.0
Output: Remaining budget: Rs. 40.00

Answer

```
import java.util.Scanner;  
  
// You are using Java  
interface ExpenseRecorder{  
    void recordExpense(double expense);  
}  
  
interface BudgetCalculator{  
    double calculateRemainingBudget();  
}  
  
class ExpenseTracker implements ExpenseRecorder, BudgetCalculator{  
    double budget;  
    double total=0;  
  
    ExpenseTracker(double budget){  
        this.budget=budget;  
        this.total=total;  
    }  
  
    public void recordExpense(double expense){  
        total+=expense;  
    }  
  
    public double calculateRemainingBudget(){  
        return budget-total;  
    }  
}  
  
class Main {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
        double budget = scanner.nextDouble();  
  
        ExpenseTracker tracker = new ExpenseTracker(budget);  
        double expense;  
        do {
```

```
        expense = scanner.nextDouble();
        tracker.recordExpense(expense);
    } while (expense != 0.0);

    double remainingBudget = tracker.calculateRemainingBudget();
    if (remainingBudget >= 0) {
        System.out.printf("Remaining budget: Rs. %.2f", remainingBudget);
    } else {
        System.out.println("No remaining budget, You've exceeded your
budget!");
    }
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Alex and Bob are designing a control system for household appliances, and one of the appliances is a washing machine. You want to create a program to help them that models the washing machine as a motor and calculates its electricity consumption based on its capacity.

Define an interface named Motor with the following methods:

void run() double consume(double capacity)

Create a class called WashingMachine that implements the Motor interface.

In the WashingMachine class:

Implement the run() method to print "Washing machine is running." Implement a consume() method to print "Washing machine is consuming electricity." Implement the consume(double capacity) method to calculate the electricity consumption (in kWh) of the washing machine based on its capacity. The formula for electricity consumption is (capacity * 0.05).

Input Format

The input consists of a double value representing the capacity of the washing

machine in kW.

Output Format

The first line of output prints "Washing machine is running."

The second line prints "Washing machine is consuming electricity."

The third line prints "Electricity consumption: X kWh" where X is a double value, rounded off to two decimal places, representing the electricity consumption.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 2.5

Output: Washing machine is running.

Washing machine is consuming electricity.

Electricity consumption: 0.13 kWh

Answer

```
import java.util.Scanner;

// You are using Java
interface Motor{
    void run();
    double consume(double capacity);
}

class WashingMachine implements Motor{

    public void run(){
        System.out.println("Washing Machine is running.");
    }

    public void consume(){
        System.out.println("Washing Machine is consuming electricity.");
    }

    public double consume(double capacity){
        return capacity*0.05;
    }
}
```

```

    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        WashingMachine washingMachine = new WashingMachine();

        double capacity = scanner.nextDouble();

        washingMachine.run();
        washingMachine.consume();

        double consumption = washingMachine.consume(capacity);
        System.out.printf("Electricity consumption: %.2f kWh", consumption);

        scanner.close();
    }
}

```

Status : Correct

Marks : 10/10

3. Problem Statement:

Sam is developing a geometry application and needs a class for trapezoid calculations. Create a "Trapezoid" class implementing a "ShapeInput" interface with a method to input trapezoid dimensions.

Also, implement a "ShapeCalculator" interface with methods to compute area and perimeter. In the "Main" class, instantiate Trapezoid, gather user input, and display the calculated area and perimeter with two decimal places.

Note

$$\text{Area of Trapezoid} = \frac{1}{2} * (\text{base1} + \text{base2}) * \text{height}$$

$$\text{Perimeter of Trapezoid} = \text{base1} + \text{base2} + \text{side1} + \text{side2}$$

Input Format

The first line of input is a double-point value representing base1 of the trapezoid.

The second line of input is a double-point value representing base2 of the trapezoid.

The third line of input is a double-point value representing the height of the trapezoid.

The fourth line of input is a double-point value representing side1 of the trapezoid.

The fifth line of input is a double-point value representing side2 of the trapezoid.

Output Format

The output displays the two lines of the calculated area (double type) and perimeter (double type) of the trapezoid, each rounded to two decimal places in the following format:

"Area of the Trapezoid: <<calculated area>>".

Perimeter of the Trapezoid: <<calculated perimeter>>".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1.0

2.0

1.0

3.0

1.0

Output: Area of the Trapezoid: 1.50

Perimeter of the Trapezoid: 7.00

Answer

```
import java.util.Scanner;
// You are using Java
interface ShapeInput{
    void getInput();
}

interface ShapeCalculator{
    double calculateArea();
    double calculatePerimeter();
}

class Trapezoid implements ShapeInput, ShapeCalculator{

    double base1;
    double base2;
    double height;
    double side1;
    double side2;

    public void getInput(){
        Scanner sc=new Scanner(System.in);
        base1=sc.nextDouble();
        base2=sc.nextDouble();
        height=sc.nextDouble();
        side1=sc.nextDouble();
        side2=sc.nextDouble();
    }

    public double calculateArea(){
        return (1/2.0)*(base1+base2)*height;
    }

    public double calculatePerimeter(){
        return base1+base2+side1+side2;
    }
}

public class Main {
    public static void main(String[] args) {
        Trapezoid trapezoid = new Trapezoid();
        trapezoid.getInput();
    }
}
```

```
        double area = trapezoid.calculateArea();
        double perimeter = trapezoid.calculatePerimeter();

        System.out.println("Area of the Trapezoid: " + String.format("%.2f", area));
        System.out.println("Perimeter of the Trapezoid: " + String.format("%.2f",
perimeter));
    }
}
```

Status : Correct

Marks : 10/10

4. Problem Statement

Maria, an online store owner, is looking to implement a pricing system that calculates the final price of products after applying discounts. She needs a program that takes the original price of a product and the discount percentage as input and computes the final discounted price. The discount is applied as a percentage of the original price. Maria wants to ensure that the final price is formatted to display exactly two decimal places.

Implement this functionality using the PriceCalculator interface and the DiscountCalculator class.

Input Format

The first line of input consists of the original price (a double value).

The second line of input consists of a discount percentage (a double value).

Output Format

The output displays the final price after the discount, adhering to the following format: "Final Price after discount: \$[final_price]".

Here, [final_price] should be replaced with the calculated final price, formatted as a currency value with two decimal places.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 100.0
10.0

Output: Final Price after discount: \$90.00

Answer

```
import java.util.Scanner;

// You are using Java
interface PriceCalculator{
    double calculatePrice(double originalPrice, double discount);
}

class DiscountCalculator implements PriceCalculator{

    public double calculatePrice(double originalPrice, double discount){
        return originalPrice-originalPrice*(discount/100.0);
    }
}

class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        double originalPrice = scanner.nextDouble();
        double discount = scanner.nextDouble();
        PriceCalculator calculator = new DiscountCalculator();
        double finalPrice = calculator.calculatePrice(originalPrice, discount);
        System.out.printf("Final Price after discount: $%.2f%n", finalPrice); // Formats output to 2 decimal places
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 7_PAH

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Develop a program for managing employee information that caters to both full-time and part-time employees. The program should be capable of computing the salary for each category of employee and presenting their particulars. To achieve this, create two classes, FullTimeEmployee and PartTimeEmployee, that adhere to the Employee interface.

The program is expected to accept input data, including the name and monthly salary for full-time employees, as well as the name, hourly rate, and hours worked for part-time employees. Subsequently, it should calculate and exhibit the employee details and their respective salaries.

For Full-Time employees, the annual salary should be calculated as 12 times the monthly salary.

For Part-Time employees, the salary calculation should be based on the formula: hourly rate * hours worked.

Input Format

The first line of input should be a string representing the name of a full-time employee.

The second line of input should be an integer representing the monthly salary of the full-time employee.

The third line of input should be a string representing the name of a part-time employee.

The fourth line of input should be an integer representing the hourly rate of the part-time employee.

The fifth line of input should be an integer representing the number of hours worked by the part-time employee.

Output Format

The output displays the following details:

Full-Time Employee Details:

Name: [Full-Time Employee Name] (string)

Monthly Salary: \$[Monthly Salary] (integer)

Annual Salary: \$[12 times Monthly Salary] (integer)

Part-Time Employee Details:

Name: [Part-Time Employee Name] (string)

Hourly Rate: \$[Hourly Rate] (integer)

Hours Worked: [Hours Worked] hours (integer)

Monthly Salary: \$[Calculated Monthly Salary] (integer)

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: John Smith

15000

Mary Johnson

100

100

Output: Full-Time Employee Details:

Name: John Smith

Monthly Salary: \$15000

Annual Salary: \$180000

Part-Time Employee Details:

Name: Mary Johnson

Hourly Rate: \$100

Hours Worked: 100 hours

Monthly Salary: \$10000

Answer

```
import java.util.Scanner;
```

```
// You are using Java
```

```
interface Employee{
```

```
    void displayDetails();
```

```
}
```

```
class FullTimeEmployee implements Employee{
```

```
    String fullName;
```

```
    int fullTimeSalary;
```

```
    FullTimeEmployee(String fullName, int fullTimeSalary){
```

```
        this.fullName=fullName;
```

```
        this.fullTimeSalary=fullTimeSalary;
```

```
}

public int calculateFullTime(){
    return fullTimeSalary*12;
}

public void displayDetails(){
    System.out.println("Full-Time Employee Details:");
    System.out.println("Name: "+fullName);
    System.out.printf("Monthly Salary: $%d\nAnnual Salary: $%d",
fullTimeSalary, calculateFullTime());
    System.out.println();
}

class PartTimeEmployee implements Employee{
    String partTimeName;
    int hourlyRate;
    int hoursWorked;

    PartTimeEmployee(String partTimeName, int hourlyRate, int hoursWorked){
        this.partTimeName=partTimeName;
        this.hourlyRate=hourlyRate;
        this.hoursWorked=hoursWorked;
    }

    public int calculatePartTime(){
        return hourlyRate*hoursWorked;
    }

    public void displayDetails(){
        System.out.println("Part-Time Employee Details:");
        System.out.println("Name: "+partTimeName);
        System.out.printf("Hourly Rate: $%d\nHours Worked: %d hours\nMonthly
Salary: $%d", hourlyRate, hoursWorked, calculatePartTime());
    }
}

class EmployeeInheritanceDemo {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        String fullName = scanner.nextLine();
```

```

        int fullTimeSalary = scanner.nextInt();
        scanner.nextLine();
        String partTimeName = scanner.nextLine();
        int hourlyRate = scanner.nextInt();
        int hoursWorked = scanner.nextInt();
        FullTimeEmployee fullTimeEmployee = new FullTimeEmployee(fullName,
        fullTimeSalary);
        PartTimeEmployee partTimeEmployee = new
        PartTimeEmployee(partTimeName, hourlyRate, hoursWorked);
        fullTimeEmployee.displayDetails();
        System.out.println();
        partTimeEmployee.displayDetails();
        scanner.close();
    }
}

```

Status : Correct

Marks : 10/10

2. Problem Statement:

Alice has been tasked with implementing a simple calculator interface and a corresponding class for performing basic addition and subtraction operations. The task is to create an interface called Calculator with two methods: add and subtract. The add method should take two numbers as input and return their sum, while the subtract method should take two numbers as input and return their difference.

Implement a class called SimpleCalculator that implements the Calculator interface. This class should provide the functionality for adding and subtracting numbers. Write a code that satisfies the above requirements.

Input Format

The first line of input consists of a single integer, representing the choice

If the choice is 1 or 2, the next two lines consist of 2 double values, representing the numbers to do addition or subtraction.

Output Format

The output prints a float-value with one decimal value representing the sum of

two number or difference of two number.

Refer to the sample output for format specification.

Sample Test Case

Input: 1

5.5

3.5

Output: Result: 9.0

Answer

```
import java.util.Scanner;  
// You are using Java  
interface Calculator {  
    //Type your code here  
    double add(double num1, double num2);  
    double subtract(double num1, double num2);  
}  
  
class SimpleCalculator implements Calculator {  
    //Type your code here  
    double num1;  
    double num2;  
  
    SimpleCalculator(){  
        this.num1=num1;  
        this.num2=num2;  
    }  
  
    public double add(double num1, double num2){  
        return num1+num2;  
    }  
  
    public double subtract(double num1, double num2){  
        return num1-num2;  
    }  
}
```

```
class MathOperationsProgram {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
  
        SimpleCalculator calculator = new SimpleCalculator();  
  
        int choice = scanner.nextInt();  
  
        if (choice == 1) {  
            double num1 = scanner.nextDouble();  
            double num2 = scanner.nextDouble();  
            double result = calculator.add(num1, num2);  
            System.out.println("Result: " + result);  
        } else if (choice == 2) {  
            double num1 = scanner.nextDouble();  
            double num2 = scanner.nextDouble();  
            double result = calculator.subtract(num1, num2);  
            System.out.println("Result: " + result);  
        } else {  
            System.out.println("Invalid choice. Please choose 1 for addition or 2 for  
subtraction.");  
        }  
  
        scanner.close();  
    }  
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

Sophia is developing a matrix analysis tool for a data analytics company. The tool needs to analyze square matrices and extract insights from the matrix diagonals.

To organize the code properly, Sophia creates an interface named Matrix that declares a method for finding the smallest and largest elements along the principal and secondary diagonals of the matrix.

Sophia then creates a class named MatrixAnalyzer that implements the Matrix interface. This class provides the logic to process a given square matrix and print:

The smallest and largest elements in the principal diagonal (from top-left to bottom-right).The smallest and largest elements in the secondary diagonal (from top-right to bottom-left).

Your task is to implement the Matrix interface and the MatrixAnalyzer class. The main driver program (in the class Main) will read the input matrix, create an instance of MatrixAnalyzer, and invoke its method to display the results.

Input Format

The first line contains an integer n, representing the size of the square matrix.

The next n lines each contain n integers separated by spaces, representing the elements of the matrix.

Output Format

The output prints the four lines:

"Smallest Element - 1: <smallest element in the principal diagonal>" (integer)

"Largest Element - 1: <largest element in the principal diagonal>" (integer)

"Smallest Element - 2: <smallest element in the secondary diagonal>" (integer)

"Largest Element - 2: <largest element in the secondary diagonal>" (integer)

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5

7 8 9 0 1

2 3 4 5 6

5 4 2 0 8

23 5 6 8 9
12 5 6 7 32
Output: Smallest Element - 1: 2
Largest Element - 1: 32
Smallest Element - 2: 1
Largest Element - 2: 12

Answer

```
import java.util.Scanner;  
// You are using Java  
import java.util.Arrays;  
  
interface Matrix{  
    void diagonalsMinMax(int[][] matrix);  
}  
  
class MatrixAnalyzer implements Matrix{  
  
    public void diagonalsMinMax(int[][] matrix)  
    {  
        int n=matrix.length;  
        int[] main=new int[n];  
        int[] sec=new int[n];  
        int count=0;  
        for(int i=0;i<n;i++){  
            main[i]=matrix[i][i];  
            sec[i]=matrix[i][n-i-1];  
        }  
        Arrays.sort(main);  
        Arrays.sort(sec);  
  
        System.out.println("Smallest Element - 1: "+main[0]);  
        System.out.println("Largest Element - 1: "+main[n-1]);  
        System.out.println("Smallest Element - 2: "+sec[0]);  
        System.out.println("Largest Element - 2: "+sec[n-1]);  
    }  
}  
  
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
        int n = sc.nextInt();  
        int[][] matrix = new int[n][n];  
        for (int i = 0; i < n; i++) {  
            for (int j = 0; j < n; j++) {  
                matrix[i][j] = sc.nextInt();  
            }  
        }  
        MatrixAnalyzer analyzer = new MatrixAnalyzer();  
        analyzer.diagonalsMinMax(matrix);  
    }  
}
```

```
        for (int i = 0; i < n; i++) {  
            for (int j = 0; j < n; j++) {  
                matrix[i][j] = sc.nextInt();  
            }  
        }  
        MatrixAnalyzer analyzer = new MatrixAnalyzer();  
        analyzer.diagonalsMinMax(matrix);  
    }  
}
```

Status : Correct

Marks : 10/10

4. Problem Statement

Oviya is fascinated by automorphic numbers and wants to create a program to determine whether a given number is an automorphic number or not.

An automorphic number is a number whose square ends with the same digits as the number itself. For example, $25 = (25)^2 = 625$

Oviya has defined two interfaces: NumberInput for taking user input and AutomorphicChecker for checking if a given number is automorphic. The class AutomorphicNumber implements both interfaces.

Help her complete the task.

Input Format

The input consists of a single integer n .

Output Format

If the input number is an automorphic number, print " n is an automorphic number". Otherwise, print " n is not an automorphic number".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 25

Output: 25 is an automorphic number

Answer

```
import java.util.Scanner;  
  
// You are using Java  
interface NumberInput{  
    int getInput();  
}  
  
interface AutomorphicChecker{  
    boolean checkAutomorphic(int n);  
}  
  
class AutomorphicNumber implements NumberInput, AutomorphicChecker{  
  
    public int getInput(){  
        Scanner sc=new Scanner(System.in);  
        int n=sc.nextInt();  
        return n;  
    }  
  
    public boolean checkAutomorphic(int n){  
        int sq=n*n;  
        int temp=n;  
        boolean isAutomorphic=true;  
  
        while(temp>0){  
            if(temp%10!=sq%10){  
                isAutomorphic=false;  
                break;  
            }  
            temp/=10;  
            sq/=10;  
        }  
        return isAutomorphic;  
    }  
}  
  
public class Main {  
    public static void main(String[] args) {  
        AutomorphicNumber automorphicNumber = new AutomorphicNumber();  
    }  
}
```

```
int inputNumber = automorphicNumber.getInput();
boolean isAutomorphic =
automorphicNumber.checkAutomorphic(inputNumber);

if (isAutomorphic) {
    System.out.println(inputNumber+" is an automorphic number");
} else {
    System.out.println(inputNumber+" is not an automorphic number");
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 8_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 14

Section 1 : MCQ

1. What will be the output for the following code?

```
import java.io.*;  
  
class TemperatureTooHighException extends Exception {  
    public TemperatureTooHighException(String message) {  
        super(message);  
    }  
}  
  
class Test {  
    public static void main(String[] args) {  
        try {  
            int temperature = 110;  
            if (temperature > 100) {  
                throw new TemperatureTooHighException("Temperature too  
high");  
            }  
        } catch (TemperatureTooHighException e) {  
            System.out.println(e.getMessage());  
        }  
    }  
}
```

```
        }
    } catch (TemperatureTooHighException e) {
        System.out.println(e.getMessage());
    }
}
```

Answer

Temperature too high

Status : Correct

Marks : 1/1

2. What will be the output for the following code?

```
class InvalidVotingAgeException extends Exception {
    public InvalidVotingAgeException(String message) {
        super(message);
    }
}
```

```
class Test {
    public static void main(String[] args) {
        try {
            int age = 15;
            if (age < 18) {
                throw new InvalidVotingAgeException("You are not eligible to
vote");
            }
            System.out.println("Eligible to vote");
        } catch (InvalidVotingAgeException e) {
            System.out.println(e.getMessage());
        }
    }
}
```

Answer

You are not eligible to vote

Status : Correct

Marks : 1/1

3. What will be the output for the following code?

```
import java.io.*;

class UnderageException extends Exception {
    public UnderageException(String message) {
        super(message);
    }
}

class Test {
    public static void main(String[] args) {
        try {
            int age = 17;
            if (age < 18) {
                throw new UnderageException("Underage, cannot proceed");
            }
        } catch (UnderageException e) {
            System.out.println(e.getMessage());
        }
    }
}
```

Answer

Underage, cannot proceed

Status : Correct

Marks : 1/1

4. What will be the output for the following code?

```
class NegativeBalanceException extends Exception {
    public NegativeBalanceException(String message) {
        super(message);
    }
}

class Test {
    public static void main(String[] args) {
        try {

```

```
        double balance = -500;
        if (balance < 0) {
            throw new NegativeBalanceException("Balance cannot be
negative");
        }
    } catch (NegativeBalanceException e) {
        System.out.println("Error: " + e.getMessage());
    }
}
```

Answer

Error: Balance cannot be negative

Status : Correct

Marks : 1/1

5. What will be the output for the following code?

```
class InvalidUsernameException extends Exception {
    public InvalidUsernameException(String message) {
        super(message);
    }
}

class Test {
    public static void main(String[] args) {
        try {
            String username = "abc";
            if (username.length() < 5) {
                throw new InvalidUsernameException("Username must be at
least 5 characters long");
            }
        } catch (InvalidUsernameException e) {
            System.out.println(e.getMessage());
        }
    }
}
```

Answer

Username must be at least 5 characters long

Status : Correct

Marks : 1/1

6. What is the purpose of a custom exception in Java?

Answer

To create user-defined exceptions for specific scenarios

Status : Correct

Marks : 1/1

7. What will be the output of the following code?

```
class MyException extends Exception {  
    public MyException() {  
        super("Default Exception Message");  
    }  
}
```

```
class Test {  
    public static void main(String[] args) {  
        try {  
            throw new MyException();  
        } catch (MyException e) {  
            System.out.println(e.getMessage());  
        }  
    }  
}
```

Answer

Default Exception Message

Status : Correct

Marks : 1/1

8. What will be the output for the following code?

```
import java.io.*;
```

```
241001162 class OutOfStockException extends Exception {  
241001162     public OutOfStockException(String message) {  
241001162         super(message);  
241001162     }  
241001162 }  
241001162  
241001162 class Test {  
241001162     public static void main(String[] args) {  
241001162         try {  
241001162             int stock = 0;  
241001162             if (stock == 0) {  
241001162                 throw new OutOfStockException("Item is out of stock");  
241001162             }  
241001162         } catch (OutOfStockException e) {  
241001162             System.out.println(e.getMessage());  
241001162         }  
241001162     }  
241001162 }
```

Answer

Item is out of stock

Status : Correct

Marks : 1/1

9. what is the output of the following code?

```
241001162 class MyException extends Exception {  
241001162     public MyException(String message) {  
241001162         super(message);  
241001162     }  
241001162 }  
241001162  
241001162 class Test {  
241001162     public static void main(String[] args) {  
241001162         try {  
241001162             throw new MyException("Error occurred");  
241001162         } catch (MyException e) {  
241001162             System.out.println(e);  
241001162         }  
241001162 }
```

```
}
```

Answer

Compilation Error

Status : Wrong

Marks : 0/1

10. How do you create an unchecked custom exception?

Answer

By extending RuntimeException

Status : Correct

Marks : 1/1

11. Which of the following is true about custom exceptions?

Answer

Custom exceptions must extend either Exception or RuntimeException

Status : Correct

Marks : 1/1

12. What will happen if a checked custom exception is thrown inside a method without being caught or declared?

Answer

Compilation Error

Status : Correct

Marks : 1/1

13. what is the output of the following code?

```
class MyException extends Exception {  
    public MyException(String message) {  
        super(message);  
    }  
}
```

```
class Test {  
    static void check() throws MyException {  
        throw new MyException("Custom Exception Occurred");  
    }  
  
    public static void main(String[] args) {  
        try {  
            check();  
        } catch (Exception e) {  
            System.out.println(e.getMessage());  
        }  
    }  
}
```

Answer

Custom Exception Occurred

Status : Correct

Marks : 1/1

14. Which keyword is used to explicitly throw a custom exception?

Answer

throw

Status : Correct

Marks : 1/1

15. What will be the output for the following code?

```
import java.io.*;
```

```
class NegativeAgeException extends Exception {  
    public NegativeAgeException(String message) {  
        super(message);  
    }  
}
```

```
class Test {
```

```
public static void main(String[] args) {  
    try {  
        int age = -5;  
        if (age < 0) {  
            throw new NegativeAgeException("Age cannot be negative");  
        }  
    } catch (NegativeAgeException e) {  
        System.out.println(e.getMessage());  
    }  
}
```

Answer

Age cannot be negative

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 8_Q1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Write a program to validate the email address and display suitable exceptions if there is any mistake.

Create 3 custom exception classes as below

DotExceptionAtTheRateExceptionDomainException

A typical email address should have a ". " character, and a "@" character, and also the domain name should be valid. Valid domain names for practice be 'in', 'com', 'net', or 'biz'.

Display Invalid Dot usage, Invalid @ usage, or Invalid Domain message based on email id.

Get the email address from the user, validate the email by checking the

above-mentioned criteria, and print the validity status of the input email address.

Input Format

The first line of input contains the email to be validated.

Output Format

The output prints a Valid email address or an Invalid email address along with the suitable exception

If email ends with . or contains not exactly one . after @, it throws:

DotException: Invalid Dot usage

Invalid email address

If @ appears not exactly once, it throws:

AtTheRateException: Invalid @ usage

Invalid email address

If the part after the last dot is not among accepted domains:

DomainException: Invalid Domain

Invalid email address

If all conditions satisfied then print:

Valid email address

Refer to the sample input and output for format specifications.

Sample Test Case

Input: sample@gmail.com

Output: Valid email address

Answer

```
// You are using Java
import java.util.*;

class DotException extends Exception {
    public DotException(String message) {
        super(message);
    }
}

class AtTheRateException extends Exception {
    public AtTheRateException(String message) {
        super(message);
    }
}

class DomainException extends Exception {
    public DomainException(String message) {
        super(message);
    }
}

class EmailValidator {

    public static void validateEmail(String email) throws DotException,
AtTheRateException, DomainException {

        if (email.startsWith(".") || email.endsWith(".") || email.startsWith("@") || email.endsWith("@"))
            throw new DotException("Invalid Dot usage");

        int atCount = email.length() - email.replace("@", "").length();
        if (atCount != 1)
```

```
throw new AtTheRateException("Invalid @ usage");

String[] parts = email.split("@");
if (parts.length != 2)
    throw new AtTheRateException("Invalid @ usage");

String localPart = parts[0];
String domainPart = parts[1];

if (email.contains(..) || email.contains(@@) || email.contains(.@) ||
email.contains(@.))
    throw new DotException("Invalid Dot usage");

if (!domainPart.contains(.))
    throw new DotException("Invalid Dot usage");

int dotAfterAtCount = domainPart.length() - domainPart.replace(".", "").length();
if (dotAfterAtCount != 1)
    throw new DotException("Invalid Dot usage");

String domain = domainPart.substring(domainPart.lastIndexOf(.) + 1);
List<String> validDomains = Arrays.asList("com", "in", "net", "biz");

if (!validDomains.contains(domain))
    throw new DomainException("Invalid Domain");

}

public static void main(String[] args) {
    Scanner sc = new Scanner(System.in);
    String email = sc.nextLine();

    try {
        validateEmail(email);
        System.out.println("Valid email address");
    }
    catch(DotException e) {
        System.out.println("DotException: " + e.getMessage());
        System.out.println("Invalid email address");
    }
    catch(AtTheRateException e) {
```

```
        System.out.println("AtTheRateException: " + e.getMessage());
        System.out.println("Invalid email address");
    }
    catch(DomainException e) {
        System.out.println("DomainException: " + e.getMessage());
        System.out.println("Invalid email address");
    }
    catch(Exception e) {
        System.out.println("Invalid email address");
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 8_Q2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Elsa, a busy professional, is using a scheduling application to plan her meetings efficiently. The application requires users to input meeting durations in minutes, ensuring that the duration is a positive integer and does not exceed 240 minutes (4 hours). Elsa needs a program to assist her in scheduling meetings securely with proper exception handling.

Create a Java class named ElsaMeetingScheduler. Implement a custom exception: InvalidDurationException for invalid meeting duration entries. Implement the main method to interactively take user input for a meeting duration. Implement the validateMeetingDuration method to validate the meeting duration based on the specified rules and throw a custom exception if the validation fails. Print appropriate success or error messages based on the meeting duration.

Implement a custom exception, `InvalidDurationException`, to handle cases where the entered meeting duration does not meet the specified criteria.

Input Format

The input consists of an integer value '`n`', representing the meeting duration.

Output Format

The output is displayed in the following format:

If the entered meeting duration meets the specified criteria, the program outputs
"Meeting scheduled successfully!"

If the entered meeting duration is invalid, the program outputs an error message indicating the issue.

"Error: Invalid meeting duration. Please enter a positive integer not exceeding 240 minutes (4 hours)."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 120

Output: Meeting scheduled successfully!

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class InvalidDurationException extends Exception{
    public InvalidDurationException(String message){
        super(message);
    }
}
class ElsaMeetingScheduler {
```

```
public static void validateMeetingDuration(int minutes) throws  
    InvalidDurationException {  
    if (minutes<= 0 || minutes > 240)  
        throw new InvalidDurationException("Error: Invalid meeting duration.  
Please enter a positive integer not exceeding 240 minutes (4 hours).");  
}  
  
public static void main(String[] args) {  
    Scanner sc = new Scanner(System.in);  
    int minutes = sc.nextInt();  
  
    try {  
        validateMeetingDuration(minutes);  
        System.out.println("Meeting scheduled successfully!");  
    }  
    catch (InvalidDurationException e) {  
        if (minutes <= 0 || minutes > 240)  
            System.out.println(e.getMessage());  
    }  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 8_Q3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In a user registration system, there is a requirement to implement a username validation module. Users attempting to register must adhere to specific criteria for their usernames to be considered valid.

Your task is to develop a program that takes user input for a desired username and validates it according to the following rules:

The username must not contain any spaces. The username must be at least 5 characters long.

Implement a custom exception, InvalidUsernameException, to handle cases where the entered username does not meet the specified criteria.

Input Format

The input consists of a string S, representing the desired username.

Output Format

If the username is valid, print "Username is valid: [S]" .

If the username is invalid:

1. If the username is short, print "Invalid Username: Username must be at least 5 characters long"
2. If the username contains spaces, print "Invalid Username: Username cannot contain spaces"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: John

Output: Invalid Username: Username must be at least 5 characters long

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class InvalidUsernameException extends Exception{
    public InvalidUsernameException(String message){
        super(message);
    }
}

class Main{
    public static void validateUsername(String username) throws
    InvalidUsernameException{

        if (username.contains(" "))
            throw new InvalidUsernameException("Invalid Username: Username
cannot contain spaces");

        else if (username.length()<5)
            throw new InvalidUsernameException("Invalid Username: Username must
be at least 5 characters long");
    }
}
```

```
    be at least 5 characters long");
}

public static void main(String[] args) {
    Scanner sc=new Scanner(System.in);
    String username=sc.nextLine();

    try {
        validateUsername(username);
        System.out.println("Username is valid: " + username);
    }
    catch(InvalidUsernameException e) {
        System.out.println(e.getMessage());
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 8_Q4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

A local municipality is implementing an online voting system for a community event and wants to ensure that only eligible voters (those aged 18 or older) can participate.

Your task is to develop a program that validates the age of individuals attempting to vote online. If the user's age is below 18, the program should throw a custom exception, `InvalidAgeException`, preventing them from casting their vote. If the input is invalid, catch the appropriate `InputMismatchException` and print the in-built exception message.

Input Format

The input consists of an integer representing the age.

Output Format

If the age is 18 or older, print "Eligible to vote"

If the age is below 18, print "Exception occurred: InvalidAgeException: Age is not valid to vote"

If there is any other type of exception, print "An error occurred: " followed by the in-built exception message.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 20

Output: Eligible to vote

Answer

```
// You are using Java
import java.io.*;
import java.util.*;

class InvalidAgeException extends Exception{
    public InvalidAgeException(String message){
        super(message);
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner sc=new Scanner(System.in);
        try{
            int age=sc.nextInt();
            if(age<18)
                throw new InvalidAgeException("Age is not valid to vote");
            else
                System.out.println("Eligible to vote");
        }
        catch(InvalidAgeException e){
            System.out.println("Exception occurred: InvalidAgeException:
"+e.getMessage());
        }
    }
}
```

```
        catch(InputMismatchException e){
            System.out.println("An error occurred: java.util.InputMismatchException");
        }
        catch(Exception e){
            System.out.println("An error occurred: "+e.getMessage());
        }
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 8_Q5

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In a file management system, users are required to provide a valid file name when creating new files. The system enforces specific rules for file names to maintain consistency and avoid potential issues. Your task is to implement a Java program named FileNameValidator that takes user input for a file name and validates it according to the specified rules.

Rules for Valid File Name:

The file name must consist of alphanumeric characters (letters and digits) only. The file name must have a minimum length of 3 characters.

Implement a custom exception, FileNameValidator, to handle cases where the entered filename does not meet the specified criteria.

Input Format

The input consists of a string S, representing the desired filename.

Output Format

The output is displayed in the following format:

If the entered file name meets the specified criteria, the program outputs
"Valid file name"

If the entered file name does not meet the criteria and triggers the
InvalidFileNameException, the program outputs

"Error: Invalid file name. It must be alphanumeric and have a minimum length of
3 characters."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: myfile123

Output: Valid file name

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class InvalidFileNameException extends Exception{
    public InvalidFileNameException(String s){
        super(s);
    }
}

class FileNameValidator{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        String name=sc.nextLine();

        try{
            if(name.length()<3)
```

```
        throw new InvalidFileNameException("Error: Invalid file name. It must  
be alphanumeric and have a minimum length of 3 characters.");  
  
        for(int i=0;i<name.length();i++){  
            char ch=name.charAt(i);  
            if(!Character.isLetterOrDigit(ch))  
                throw new InvalidFileNameException("Error: Invalid file name. It must  
be alphanumeric and have a minimum length of 3 characters.");  
        }  
        System.out.println("Valid file name");  
    }  
    catch(InvalidFileNameException e) {  
        System.out.println(e.getMessage());  
    }  
    catch(Exception e){  
        System.out.println(e.getMessage());  
    }  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 8_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

In an online shopping cart system, users can apply coupon codes during checkout to avail of discounts. However, to ensure the validity and security of coupon codes, the system enforces specific rules for their format. Your task is to implement a Java program named CouponCodeValidator that takes user input for a coupon code and validates it according to the specified rules.

Rules for Valid Coupon Code:

The coupon code must consist of exactly 10 characters. The coupon code must contain at least one alphabet (uppercase or lowercase) and at least one digit (0-9). Special characters are not allowed in the coupon code.

Implement a custom exception, InvalidCouponException, to handle cases where the entered coupon code does not meet the specified criteria.

Input Format

The input consists of a string s, representing the coupon code.

Output Format

The output is displayed in the following format:

If the entered coupon code meets the specified criteria, the program outputs

"Coupon code applied successfully!"

If the entered coupon code has less than or more than 10 characters it outputs

"Error: Invalid coupon code length. It must be exactly 10 characters."

If the entered coupon code contains only numeric or only alphabets it outputs

"Error: Invalid coupon code format. It must contain at least one alphabet and one digit."

If the entered coupon code contains special characters it outputs

"Error: Coupon code should not contain special characters."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: ABCD123456

Output: Coupon code applied successfully!

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class InvalidCouponException extends Exception{
    public InvalidCouponException(String s){
        super(s);
    }
}
```

```
}

class CouponCodeValidator{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        String code=sc.next();

        try{
            if(code.length()!=10)
                throw new InvalidCouponException("Invalid coupon code length. It must
be exactly 10 characters.");

            boolean hasAlpha=false;
            boolean hasDigit=false;
            boolean hasSpecial=false;

            for(int i=0;i<code.length();i++){
                char ch=code.charAt(i);
                if(Character.isLetter(ch))
                    hasAlpha=true;
                else if(Character.isDigit(ch))
                    hasDigit=true;
                else{
                    hasSpecial=true;
                    break;
                }
            }
            if(hasSpecial)
                throw new InvalidCouponException("Coupon code should not contain
special characters.");
            if(!hasAlpha || !hasDigit)
                throw new InvalidCouponException("Invalid coupon code format. It
must contain at least one alphabet and one digit.");

            System.out.println("Coupon code applied successfully!");
        }

        catch(InvalidCouponException e){
            System.out.println("Error: "+e.getMessage());
        }
    }
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Theo is trying to update his payment information on a subscription-based streaming service. To proceed, the system requires Theo to provide a valid credit card number consisting of 16 digits. However, Theo wants to make sure that the credit card number he enters meets the specified criteria with proper exception handling.

The credit card number must consist of exactly 16 digits. If the entered credit card number does not meet the specified criteria, the program should throw a custom exception, `InvalidCreditCardException`, and provide Theo with specific error messages: If the length of the credit card number is not 16 digits, the exception message should be: "Invalid credit card number length." If the credit card number contains non-numeric characters, the exception message should be: "Invalid credit card number format."

Implement a custom exception, `InvalidCreditCardException`, to fulfill Theo's requirements and keep his payment information secure.

Input Format

The input consists of a string value 's', consisting of the 16-digit credit card number.

Output Format

The output is displayed in the following format:

If the entered credit card number is valid, the program should output a success message:

"Payment information updated successfully!"

If the entered credit card has more than 16 digits or less than 16 digits it displays

"Error: Invalid credit card number length."

If the entered 16-digit credit card has non-integers it displays
"Error: Invalid credit card number format."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1234567890123456

Output: Payment information updated successfully!

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class InvalidCreditCardException extends Exception{
    public InvalidCreditCardException(String s){
        super(s);
    }
}

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        String s=sc.next();

        try{
            if(s.length()!=16)
                throw new InvalidCreditCardException("Invalid credit card number
length.");
        }

        boolean hasDigits=true;
        for(int i=0;i<s.length();i++){
            char ch=s.charAt(i);

            if(!Character.isDigit(ch)){
                hasDigits=false;
                break;
            }
        }
    }
}
```

```

        }
        if(!hasDigits)
            throw new InvalidCreditCardException("Invalid credit card number
format.");
        System.out.println("Payment information updated successfully!");
    }

    catch(InvalidCreditCardException e){
        System.out.println("Error: "+e.getMessage());
    }
}
}

```

Status : Correct

Marks : 10/10

3. Problem Statement

Faustus is managing his bank account and wants to create a program to update his account balance based on certain conditions. However, he needs to handle specific scenarios related to invalid inputs and insufficient balances. Faustus wants to update his account balance. He inputs the current balance and the amount to be updated.

The initial account balance should be positive. If Faustus enters a negative initial balance, the program should throw an InvalidAmountException with the message "Invalid amount. Please enter a positive initial balance." If the amount to be updated is negative, the program should check if the subtraction results in a negative balance. If so, it should throw an InsufficientBalanceException with the message "Insufficient balance." If the amount to be updated is positive, it should be added to the current balance, and the new balance should be printed.

Implement a custom exception, InvalidAmountException, and InsufficientBalanceException, to manage his bank account.

Input Format

The first line of input consists of a double value 'd', representing the initial account balance.

The second line of input consists of a double value 'd1', representing the amount

to be updated.

Output Format

The output is displayed in the following format:

If the validation passes, print

"Account balance updated successfully! New balance: {new_balance}"

where {new_balance} is the updated account balance.

If the initial bank amount is negative it displays

"Error: Invalid amount. Please enter a positive initial balance."

If the updated amount exceeds the initial account balance in withdrawal it displays

"Error: Insufficient balance."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1000

500

Output: Account balance updated successfully! New balance: 1500.0

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class InvalidAmountException extends Exception{
    public InvalidAmountException(String s){
        super(s);
    }
}

class InsufficientBalanceException extends Exception{
```

```

        public InsufficientBalanceException(String s){
            super(s);
        }

class BankAccount{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        double initBal=sc.nextDouble();
        double updAmt=sc.nextDouble();

        try{
            if(initBal<0)
                throw new InvalidAmountException("Invalid amount. Please enter a
positive initial balance.");

            else if((initBal+updAmt)<0){

                throw new InsufficientBalanceException("Insufficient balance.");
            }
            else
                System.out.printf("Account balance updated successfully! New
balance: %.1f", (initBal+updAmt));
        }
        catch(InvalidAmountException e){
            System.out.println("Error: "+e.getMessage());
        }
        catch(InsufficientBalanceException e){
            System.out.println("Error: "+e.getMessage());
        }
    }
}

```

Status : Correct

Marks : 10/10

4. Problem Statement

Hemanth is designing a banking system for XYZ Bank. The system should allow customers to perform deposit, withdrawal, and balance inquiry operations. Implement exception handling for scenarios involving invalid transaction amounts or insufficient funds.

Create two custom exception classes, InvalidAmountException and InsufficientFundsException, both extending the Exception class. Throw an InvalidAmountException with a message if the deposit amount is less than or equal to zero. Throw an InsufficientFundsException if the withdrawal amount is greater than the available balance. Deduct the withdrawal amount from the balance if the withdrawal is successful.

Assist Hemanth in designing the program.

Input Format

The first line of input consists of a double value B, representing the initial balance.

The second line consists of a double value D, representing the deposit amount.

The third line consists of a double value W, representing the withdrawal amount.

Output Format

If the withdrawal is successful, print the amount withdrawn and the current balance, rounded off to one decimal place.

If an InvalidAmountException occurs, print "Error: [D] is not valid".

If an InsufficientFundsException occurs, print "Error: Insufficient funds".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1050.1

270.2

150.3

Output: Amount Withdrawn: 150.3

Current Balance: 1170.0

Answer

```
// You are using Java  
import java.io.*;
```

```
import java.util.Scanner;

class InvalidAmountException extends Exception{
    public InvalidAmountException(String s){
        super(s);
    }
}

class InsufficientFundsException extends Exception{
    public InsufficientFundsException(String s){
        super(s);
    }
}

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        double balance=sc.nextDouble();
        double deposit=sc.nextDouble();
        double withdraw=sc.nextDouble();

        try{
            if(deposit<=0)
                throw new InvalidAmountException(deposit+"is not valid");
            else
                balance+=deposit;

            if(withdraw>balance)
                throw new InsufficientFundsException("Insufficient funds");
            else{
                balance-=withdraw;
                System.out.printf("Amount Withdrawn: %.1f\n", withdraw);
                System.out.printf("Current Balance: %.1f\n", balance);
            }
        }
        catch(InvalidAmountException e){
            System.out.println("Error: "+e.getMessage());
        }
        catch(InsufficientFundsException e){
            System.out.println("Error: "+e.getMessage());
        }
    }
}
```

}

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 8_PAH

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

An HR software system is being developed to process employee payrolls. During payroll processing, the system must ensure that no employee has a negative salary and that no employee's salary exceeds 2,00,000. If either condition occurs, the system should throw a custom exception.

Create a custom exception `InvalidSalaryException` and a class `Employee` that processes salary according to the following rules:

If `salary < 0`, throw `InvalidSalaryException` with the message: "Salary cannot be negative". If `salary > 200000`, throw `InvalidSalaryException` with the message: "Salary exceeds threshold limit". Otherwise, display: "Salary processed successfully for <empName>: <salary>".

The payroll processing should always display: "Payroll process completed"

at the end, regardless of whether an exception occurs.

Input Format

The first line of input contains an integer representing the employee ID.

The second line contains a string representing the employee's name.

The third line contains a floating-point number representing the salary of the employee.

Output Format

If the salary is valid: "Salary processed successfully for <empName>: <salary>"

"Payroll process completed"

If the salary is invalid: "<Exception Message>"

"Payroll process completed"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 101

Rahul

150000.0

Output: Salary processed successfully for Rahul: 150000.0

Payroll process completed

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class InvalidSalaryException extends Exception{
    public InvalidSalaryException(String s){
        super(s);
    }
}
```

```

class Employee{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int empID=sc.nextInt();
        String name=sc.next();
        double salary=sc.nextDouble();

        try{
            if(salary<0)
                throw new InvalidSalaryException("Salary cannot be negative");
            else if(salary>200000)
                throw new InvalidSalaryException("Salary exceeds threshold limit");
            else
                System.out.println("Salary processed successfully for "+ name +":"
                        "+salary);
        }
        catch(InvalidSalaryException e){
            System.out.println(e.getMessage());
        }
        catch(Exception e){
            System.out.println(e.getMessage());
        }
        finally{
            System.out.println("Payroll process completed");
        }
    }
}

```

Status : Correct

Marks : 10/10

2. Problem Statement

Enigma is developing a simple web application that takes a user-input URL, validates it, and throws a custom exception `InvalidURLException` if the URL does not start with "http://" or "https://".

The main method prompts the user for input, validates the URL, and prints

whether it is valid or not.

Input Format

The input consists of a string, representing the URL entered by the user.

Output Format

The output displays one of the following results:

If the entered URL is valid according to the specified format, the program prints:

"[URL] is a valid URL"

If the entered URL is not valid according to the specified format, the program prints:

"Invalid URL format: [URL]"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: http://www.example.com

Output: http://www.example.com is a valid URL

Answer

```
// You are using Java
import java.util.Scanner;

class InvalidURLException extends Exception {
    public InvalidURLException(String message) {
        super(message);
    }
}

class Main {
    public static void main(String[] args) {
```

```
Scanner sc = new Scanner(System.in);
String url = sc.nextLine();

try {
    if(!(url.startsWith("http://") || url.startsWith("https://")))
        throw new InvalidURLException("Invalid URL format: "+url);
    System.out.println(url + " is a valid URL");
}

catch (InvalidURLException e) {
    System.out.println(e.getMessage());
}
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

Daniel is developing a program to verify the age of users. He wants to ensure that the entered age is within a valid range. Write a program to help Daniel implement this age-checking feature using custom exceptions.

Daniel needs a program that takes an integer input representing a person's age. If the age is between 0 and 150 (inclusive), the program should print "Age is valid!". If the age is less than 0 or greater than 150, the program should throw a custom exception (InvalidAgeException) with the message "Invalid age. Please enter an age between 0 and 150."

Implement a custom exception, InvalidAgeException, to handle cases where the entered age does not meet the specified criteria.

Input Format

The input consists of an integer value 'n', representing the age.

Output Format

The output is displayed in the following format:

If the age is valid (between 0 and 150, inclusive), print

"Age is valid!".

If the age is invalid, print

"Error: Invalid age. Please enter an age between 0 and 150."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 45

Output: Age is valid!

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class InvalidAgeException extends Exception{
    public InvalidAgeException(String s){
        super(s);
    }
}

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int age=sc.nextInt();

        try{
            if(age>=0 && age<=150)
                System.out.println("Age is valid!");
            else
                throw new InvalidAgeException("Invalid age. Please enter an age
between 0 and 150.");
        }

        catch(InvalidAgeException e){
            System.out.println("Error: "+e.getMessage());
        }
    }
}
```

```
}
```

Status : Correct

Marks : 10/10

4. Problem Statement

You are tasked to create a program that defines a custom exception GradeException. The program should include a Student class with fields for the student's name, age, and grade. Implement a method in the Student class that checks the grade, and if the grade is below 40, it should throw a GradeException. Otherwise, it should display the student's details.

Input Format

The input consists of three parameters in separate lines:

1. A string representing the student's name.
2. An integer representing the student's age.
3. An integer representing the student's grade.

Output Format

The output will display the student's details if the grade is valid.

If the grade is below 40, the program will display an error message "Grade is below 40".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: Alice

20

85

Output: Name: Alice

Age: 20

Grade: 85

Answer

```
// You are using Java
import java.io.*;
import java.util.Scanner;

class GradeException extends Exception{
    public GradeException(String s){
        super(s);
    }
}

class Student{
    public static void checkGrade(int grade, String name, int age) throws
GradeException{
        if(grade>=40){
            System.out.println("Name: "+name);
            System.out.println("Age: "+age);
            System.out.println("Grade: "+grade);
        }
        else{
            throw new GradeException("Grade is below 40");
        }
    }

    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        String name=sc.next();
        int age=sc.nextInt();
        int grade=sc.nextInt();

        try{
            checkGrade(grade,name,age);
        }
        catch(GradeException e){
            System.out.println(e.getMessage());
        }
        catch(Exception e){
            System.out.println(e.getMessage());
        }
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 9_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 14

Section 1 : MCQ

1. What will be the output of the following code?

```
import java.util.ArrayList;

public class Main {
    public static void main(String[] args) {
        ArrayList<String> list = new ArrayList<>();
        list.add("Apple");
        list.add("Banana");
        list.remove("Apple");
        System.out.println(list);

    }
}
```

Answer

[Banana , Apple]

Status : Wrong

Marks : 0/1

2. What is the correct way to create an ArrayList in Java?

Answer

ArrayList<String> list = new ArrayList<>();

Status : Correct

Marks : 1/1

3. What does the addFirst() method of LinkedList do?

Answer

Adds an element to the beginning of the list

Status : Correct

Marks : 1/1

4. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        ArrayList<String> list = new ArrayList<>();
        list.add("Java");
        list.add("Python");
        list.add("Java");
        list.add("C++");
        System.out.println(list.indexOf("Java"));
    }
}
```

Answer

0

Status : Correct

Marks : 1/1

5. What will be the output of the following code?

```
import java.util.*;
public class Main {
    public static void main(String[] args) {
        Stack<Integer> s = new Stack<>();
        s.push(10);
        s.push(20);
        s.push(30);
        System.out.println(s.peek());
    }
}
```

Answer

30

Status : Correct

Marks : 1/1

6. Which method is used to add an element to the top of the stack?

Answer

push()

Status : Correct

Marks : 1/1

7. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        ArrayList<Integer> list = new ArrayList<>();
        list.add(10);
        list.add(20);
        list.add(30);
        list.remove(1);
        System.out.println(list);
    }
}
```

Answer

[10, 30]

Status : Correct

Marks : 1/1

8. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        ArrayList<Integer> list = new ArrayList<>();
        list.add(1);
        list.add(2);
        list.add(3);
        list.add(4);
        list.set(2, 10);
        System.out.println(list);
    }
}
```

Answer

[1, 2, 10, 4]

Status : Correct

Marks : 1/1

9. What will be the output of the following code?

```
import java.util.*;
public class Main {
    public static void main(String[] args) {
        Stack<Integer> stack = new Stack<>();
        for (int i = 1; i <= 3; i++)
            stack.push(i * 2);
        stack.pop();
        stack.push(10);
        System.out.println(stack.peek());
    }
}
```

Answer

10

Status : Correct

Marks : 1/1

10. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        ArrayList<String> list = new ArrayList<>();
        list.add("apple");
        list.add("banana");
        list.add("cherry");
        list.add("banana");
        System.out.println(list.lastIndexOf("banana"));
    }
}
```

Answer

3

Status : Correct

Marks : 1/1

11. What will be the output of the following code?

```
import java.util.ArrayList;

public class Main {
    public static void main(String[] args) {
        ArrayList<Integer> list = new ArrayList<>();
        list.add(10);
        list.add(20);
        list.add(30);
        System.out.println("Size of the list: " + list.size());
    }
}
```

Answer

Size of the list: 3

Status : Correct

Marks : 1/1

12. How can you access the first element of an ArrayList named as list?

Answer

list.get(0);

Status : Correct

Marks : 1/1

13. What is Collection in Java?

Answer

A group of objects

Status : Correct

Marks : 1/1

14. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        ArrayList<Integer> list = new ArrayList<>();
        list.add(1);
        list.add(2);
        list.add(3);
        list.add(4);
        list.add(5);
        System.out.println(list.get(3));
    }
}
```

Answer

4

Status : Correct

Marks : 1/1

15. Which of the following methods removes and returns the last element

from a LinkedList?

Answer

`removeLast()`

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 9_Q1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Bobby is tasked with processing a sequence of numbers from a monitoring system. He needs to extract a strictly increasing subsequence using an ArrayList. The program should dynamically add numbers to the ArrayList only if they are greater than the last number currently stored in the list. Bobby aims to efficiently utilize the dynamic resizing and indexing features of the ArrayList to solve this problem.

Help Bobby implement this solution.

Input Format

The first line of input consists of an integer N, representing the number of elements.

The second line consists of N space-separated integers, representing the elements.

Output Format

The output prints the list of integers in increasing sequence, ignoring out-of-order elements.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 7
3 5 9 1 11 7 13
Output: [3, 5, 9, 11, 13]

Answer

```
// You are using Java
import java.io.*;
import java.util.*;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();

        ArrayList<Integer> list = new ArrayList<>();

        for(int i=0;i<n;i++){
            int num=sc.nextInt();

            if(list.isEmpty())
                list.add(num);

            else if(num>list.get(list.size()-1))
                list.add(num);
        }
        System.out.println(list);
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 9_Q2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Vikram loves listening to music and wants to create a simple playlist manager using Java Collections. The playlist supports the following operations:

"ADD <song>" Adds the song to the end of the playlist."REMOVE <song>" Removes the first occurrence of the song from the playlist. If the song is not found, do nothing."SHOW" Displays all songs in the playlist in order. If the playlist is empty, print "EMPTY".NEXT" Moves to the next song in the playlist and prints its name. If the playlist is empty, print "EMPTY".

The playlist maintains a "current song" position that starts at the first song when it's added. The NEXT command moves to the next song and prints it, wrapping around to the first song after reaching the last song. When removing songs, the current position adjusts accordingly to maintain

proper navigation.

Help Vikram implement this playlist manager.

Input Format

The first line of the input consists of an integer n , the number of operations.

The next n lines, each containing a command:

- "ADD <song>"
- "REMOVE <song>"
- "SHOW"
- "NEXT"

Output Format

For each "SHOW" command, print the songs in order, separated by spaces.

For each "NEXT" command, print the next song in the playlist.

If no song exists, print "EMPTY".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 7

ADD song1

ADD song2

SHOW

NEXT

REMOVE song2

SHOW

NEXT

Output: song1 song2

song2

song1

song1

Answer

```
// You are using Java
import java.io.*;
import java.util.*;

public class Main {
    public static void main(String[] args) {
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        sc.nextLine();
        LinkedList<String> playlist=new LinkedList<>();
        int currentIndex=-1;

        for(int i=0;i<n;i++) {
            String command=sc.nextLine().trim();

            if(command.startsWith("ADD")) {
                String song=command.substring(4);
                playlist.add(song);
                if(currentIndex==-1)
                    currentIndex=0;

            }
            else if(command.startsWith("REMOVE")) {
                String song=command.substring(7);
                int removeIndex=playlist.indexOf(song);
                if(removeIndex!=-1) {
                    playlist.remove(removeIndex);

                    if(playlist.isEmpty())
                        currentIndex=-1;
                    else if(removeIndex<currentIndex)
                        currentIndex--;
                    else if(removeIndex==currentIndex) {
                        if (currentIndex>=playlist.size())
                            currentIndex=0;
                    }
                }
            }
            else if(command.equals("SHOW")){
                if(playlist.isEmpty())
                    System.out.println("EMPTY");
            }
        }
    }
}
```

```
        else{
            for (String song : playlist)
                System.out.print(song + " ");
            System.out.println();
        }

    }
else if(command.equals("NEXT")) {
    if(playlist.isEmpty())
        System.out.println("EMPTY");
    else {
        currentIndex = (currentIndex + 1) % playlist.size();
        System.out.println(playlist.get(currentIndex));
    }
}
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 9_Q3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Assist Pranitha in developing a program that takes an integer N as input, representing the number of names to be read. Then read N names and store them in an ArrayList. Finally, input a search string and output the frequency of that string in the list of names.

Note: Some parts of the code are provided as snippets, and you need to complete the remaining sections by writing the necessary code.

Input Format

The first line of input consists of an integer N, representing the number of names to be read.

The following N lines consist of N names, as a string.

The last line consists of a string, representing the name to be searched.

Output Format

The output prints a single integer, representing the frequency of the specified name in the given list.

If the specified name is not found, print 0.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

Alice

Bob

Ankit

Alice

Pranitha

Alice

Output: 2

Answer

```
// You are using Java
import java.io.*;
import java.util.*;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        sc.nextLine();

        ArrayList<String> names=new ArrayList<>();

        for(int i=0;i<n;i++){
            String name=sc.nextLine();
            names.add(name);
        }
        String name1=sc.nextLine();
```

```
int count=0;
for(String name:names){
    if(name.equals(name1))
        count++;
}
System.out.println(count);
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 9_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Aarav is developing a music playlist application where users can manage their favorite songs. He wants to implement a feature that allows users to reorder the playlist by moving a song from one position to another.

You need to implement a function that performs the following operations using a LinkedList:

Add songs to the playlist in the given order. Move a song from a specified position to another position in the playlist. Print the final playlist after all operations.

Input Format

The first line of the input consists of an integer n representing the number of songs.

The next n lines, each containing a string representing a song name.

After the songs are given the next line contains an integer m, the number of move operations.

The next m lines, each containing two integers x and y representing the move operation where the song at position x (0-based index) should be moved to position y.

Output Format

The output prints the final playlist, each song on a new line.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

SongA

SongB

SongC

SongD

SongE

2

2 4

0 3

Output: SongB

SongD

SongE

SongA

SongC

Answer

```
// You are using Java
import java.io.*;
import java.util.*;
```

```
class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
```

```
int n=sc.nextInt();
sc.nextLine();

LinkedList<String> playlist=new LinkedList<>();

for(int i=0;i<n;i++){
    String song=sc.nextLine();
    playlist.add(song);
}

int m=sc.nextInt();

for(int i=0;i<m;i++){
    int x=sc.nextInt();
    int y=sc.nextInt();

    String s=playlist.remove(x);
    playlist.add(y, s);
}

for(int i=0;i<n;i++)
    System.out.println(playlist.get(i));
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Sanjay is working on a program to merge two sorted linked lists into a single sorted list using Java's `LinkedList` class from the Collections framework. Given two sorted linked lists, he wants to merge them while maintaining the sorted order.

Write a Java program that:

Reads two sorted linked lists. Merges them into a single sorted linked list. Prints the merged list in ascending order.

Input Format

The first line contains an integer m (the size of the first linked list).

The second line contains m space-separated integers (sorted).

The third line contains an integer n (the size of the second linked list).

The fourth line contains n space-separated integers (sorted).

Output Format

The output prints the merged linked list as space-separated integers.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 2

5 10

3

1 3 8

Output: 1 3 5 8 10

Answer

```
import java.util.*;
class MergeSortedLinkedLists {
    // You are using Java

    public static void main(String[] args) {
        Scanner sc=new Scanner(System.in);

        int m=sc.nextInt();
        LinkedList<Integer> l1=new LinkedList<>();

        for(int i=0;i<m;i++){
            int v=sc.nextInt();
            l1.add(v);
        }

        int n=sc.nextInt();
        LinkedList<Integer> l2=new LinkedList<>();
```

```
for(int i=0;i<n;i++){
    int v=sc.nextInt();
    l2.add(v);
}

l1.addAll(l2);
Collections.sort(l1);

for(int i:l1)
    System.out.print(i+" ");
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

Rahul is working on a list manipulation problem where he needs to reverse a specific subarray using a stack. Given an array and two indices l and r, he wants to reverse only the portion of the array from index l to r (both inclusive) while keeping the rest of the array unchanged.

Since Rahul wants to solve this problem efficiently, he decides to use a stack to reverse the subarray in $O(r - l)$ time.

Your task is to help Rahul by implementing this functionality.

Input Format

The first line contains an integer n, the size of the array.

The second line contains n space-separated integers arr[i].

The third line contains two integers l and r, denoting the start and end indices of the subarray to reverse.

Note: The array follows 0-based indexing.

Output Format

The output prints the modified array after reversing the subarray between indices

l and r.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 6
1 2 3 4 5 6
1 4

Output: 1 5 4 3 2 6

Answer

```
import java.util.*;  
  
public class Main {  
  
    // You are using Java  
  
    public static void main(String[] args) {  
        Scanner sc=new Scanner(System.in);  
  
        int n=sc.nextInt();  
        int[] arr=new int[n];  
  
        for(int i=0;i<n;i++)  
            arr[i]=sc.nextInt();  
  
        int l=sc.nextInt();  
        int r=sc.nextInt();  
  
        Stack<Integer> stack=new Stack<>();  
  
        for(int i=l;i<=r;i++)  
            stack.push(arr[i]);  
  
        for(int i=l;i<=r;i++)  
            arr[i]=stack.pop();  
  
        for(int i=0;i<n;i++)  
            System.out.print(arr[i]+" ");
```

}

Status : Correct

Marks : 10/10

4. Problem Statement

Rahul, a stock trader, wants to analyze the stock prices of a company over several days. For each day, he wants to determine the stock span, which is the number of consecutive days (including the current day) where the stock price is less than or equal to the price on that day.

The stock span helps him understand how long a stock has been continuously increasing or staying the same. You need to help Rahul by computing the stock span for each day using a Stack data structure efficiently.

Example:

Input:

7

100 80 60 70 60 75 85

Output:

1 1 1 2 1 4 6

Explanation:

For each day:

Day 1: Price = 100 Span = 1 (Only this day)
Day 2: Price = 80 Span = 1 (Only this day)
Day 3: Price = 60 Span = 1 (Only this day)
Day 4: Price = 70 Span = 2 (Includes today and previous day)
Day 5: Price = 60 Span = 1 (Only this day)
Day 6: Price = 75 Span = 4 (Includes today and previous three days)
Day 7: Price = 85 Span = 6 (Includes today and previous five days)

Input Format

The first line contains an integer n, the number of days.

The second line contains n space-separated integers prices[i], where prices[i] represents the stock price on the i-th day.

Output Format

The output prints n space-separated integers representing the stock span for each day.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 7
100 80 60 70 60 75 85
Output: 1 1 1 2 1 4 6

Answer

```
// You are using Java
import java.io.*;
import java.util.*;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int[] arr=new int[n];
        Stack<Integer> stack=new Stack<>();

        for(int i=0;i<n;i++)
            arr[i]=sc.nextInt();

        int[] span=new int[n];

        for(int i=0;i<n;i++){

            while(!stack.isEmpty() && arr[stack.peek()]<=arr[i])
                stack.pop();

            if(stack.isEmpty())
                span[i]=i+1;
            else
                span[i]=i-stack.peek();
        }
    }
}
```

```
        else
            span[i]=i-stack.peek();

        stack.push(i);
    }
    for(int i=0;i<n;i++)
        System.out.print(span[i]+" ");
}
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 9_PAH

Attempt : 1
Total Mark : 30
Marks Obtained : 30

Section 1 : Coding

1. Problem Statement

Rekha is a teacher who wants to calculate the average of marks scored by her students in a test. She needs to store all the marks dynamically because the number of students may vary each time. Using an ArrayList allows her to easily add any number of marks without worrying about the initial size.

Help her implement the task.

Input Format

The first line of input is an integer n, representing the number of students..

The second line of input consists of n double values, representing the marks of each student, separated by a space.

Output Format

The output prints: "Average of the list: " followed by the average value formatted to two decimal places.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5
1.0 2.0 3.0 4.0 5.0

Output: Average of the list: 3.00

Answer

```
// You are using Java
import java.io.*;
import java.util.*;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();

        ArrayList<Double> arr=new ArrayList<>();
        double total=0.0;
        for(int i=0;i<n;i++){
            double marks=sc.nextDouble();
            arr.add(marks);
            total+=marks;
        }
        double avg=total/n;
        System.out.printf("Average of the list: %.2f", avg);
    }
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Aditi is analyzing stock market trends and wants to find the Next Greater Element (NGE) for each stock price in a list. The Next Greater Element for an element x in an array is the first element to the right that is greater than x . If no greater element exists, return -1 for that position.

Your task is to help Aditi by efficiently computing the Next Greater Element for each element in the given array using a Stack.

Example:

Input:

6

4 5 2 10 8 6

Output:

5 10 10 -1 -1 -1

Explanation:

For each element:

4 5 (next greater element) 5 10 2 10 10 -1 (No greater element) 8 -16 -1

Input Format

The first line contains an integer n , representing the number of elements.

The second line contains n space-separated integers $\text{arr}[i]$, where $\text{arr}[i]$ is the stock price on the i -th day.

Output Format

The output prints n space-separated integers representing the Next Greater Element for each element in the array.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 6

4 5 2 10 8 6

Output: 5 10 10 -1 -1 -1

Answer

```
// You are using Java
import java.io.*;
import java.util.*;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int[] arr=new int[n];
        int[] result=new int[n];
        Stack<Integer> stack=new Stack<>();

        for(int i=0;i<n;i++){
            arr[i]=sc.nextInt();

            for(int i=n-1;i>=0;i--){
                while(!stack.isEmpty() && stack.peek()<=arr[i])
                    stack.pop();

                if(stack.isEmpty())
                    result[i]=-1;
                else
                    result[i]=stack.peek();

                stack.push(arr[i]);
            }

            for(int i=0;i<n;i++)
                System.out.print(result[i]+" ");
        }
    }
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

Arun is building a task manager to keep track of tasks using a LinkedList.

The task manager supports the following operations:

"ADD <task>" Adds the given task to the end of the list.
"REMOVE" Removes the first task from the list.
"SHOW" Displays all tasks in the list in order. If the list is empty, print "EMPTY".

Help Arun implement this functionality using a `LinkedList`.

Input Format

The first line of the input consists of an integer n , the number of operations.

The next n lines, each containing a command:

- "ADD <task>"
- "REMOVE"
- "SHOW"

Output Format

For each "SHOW" command, the output prints the tasks in order, separated by spaces.

If no tasks exist, print "EMPTY".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
ADD homework
ADD project
SHOW
REMOVE
SHOW

Output: homework project
project

Answer

```
// You are using Java
import java.io.*;
```

```
import java.util.*;  
  
class Main{  
    public static void main(String[]args){  
        Scanner sc=new Scanner(System.in);  
        int n=sc.nextInt();  
        sc.nextLine();  
  
        LinkedList<String> tasks=new LinkedList<>();  
  
        for(int i=0;i<n;i++){  
            String command=sc.nextLine();  
  
            if(command.startsWith("ADD")){  
                String task=command.substring(4);  
                tasks.add(task);  
            }  
  
            else if(command.equals("SHOW")){  
                if(tasks.isEmpty())  
                    System.out.println("EMPTY");  
                else{  
                    for(int j=0;j<tasks.size();j++){  
                        System.out.print(tasks.get(j));  
                        if(j<tasks.size()-1)  
                            System.out.print(" ");  
                    }  
                    System.out.println();  
                }  
            }  
  
            else if(command.equals("REMOVE")){  
                if(!tasks.isEmpty())  
                    tasks.removeFirst();  
            }  
        }  
    }  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 10_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 15

Section 1 : MCQ

1. What will happen if you add a null element to a TreeSet?

Answer

An exception occurs

Status : Correct

Marks : 1/1

2. Which statement is true about HashSet and TreeSet?

Answer

TreeSet provides sorted elements

Status : Correct

Marks : 1/1

3. Which method removes all elements from a Set?

Answer

clear()

Status : Correct

Marks : 1/1

4. What is the time complexity of retrieving an element from a HashSet?

Answer

O(1)

Status : Correct

Marks : 1/1

5. What will happen if you add elements in descending order in a TreeSet?

Answer

They are sorted in ascending order

Status : Correct

Marks : 1/1

6. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        HashMap<String, Integer> map = new HashMap<>();
        map.put("X", 10);
        map.put("Y", 20);
        map.put("Z", 30);
        map.remove("Y");
        System.out.println(map);
    }
}
```

Answer

{X=10, Z=30}

Status : Correct

Marks : 1/1

7. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        HashMap<String, Integer> map = new HashMap<>();
        map.put("A", 1);
        map.put("B", 2);
        map.put("C", 3);
        System.out.println(map.containsKey("B"));
    }
}
```

Answer

true

Status : Correct

Marks : 1/1

8. Which of the following allows null keys in Java?

Answer

HashMap

Status : Correct

Marks : 1/1

9. Which of the following is true about HashMap?

Answer

It is not synchronized

Status : Correct

Marks : 1/1

10. Which of the following is true about TreeMap?

Answer

It maintains natural ordering

Status : Correct

Marks : 1/1

11. How does HashSet check for duplicate elements?

Answer

Using equals() and hashCode()

Status : Correct

Marks : 1/1

12. What happens if two keys have the same hash code in a HashMap?

Answer

A linked list is used to store values with the same hash

Status : Correct

Marks : 1/1

13. What happens when you add duplicate elements to a HashSet?

Answer

The duplicate is ignored

Status : Correct

Marks : 1/1

14. Which method retrieves the lowest key in a TreeMap?

Answer

firstKey()

Status : Correct

Marks : 1/1

15. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
```

```
001162 241001162  
HashMap<String, String> map = new HashMap<>();  
map.put("A", "Apple");  
map.put("B", "Banana");  
map.put("C", "Cherry");  
map.replace("B", "Blueberry");  
System.out.println(map);  
}  
}
```

Answer

{A=Apple, B=Blueberry, C=Cherry}

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 10_Q1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : COD

1. Problem Statement

A city traffic management system needs to track vehicles entering a toll booth. Each vehicle is uniquely identified by its registration number. The system should allow adding vehicles to a record, ensuring that no duplicate registration numbers exist. The vehicles should be stored in a HashSet, which does not guarantee any specific order.

Your task is to implement a program using a HashSet that allows adding vehicle details and displaying the records.

Input Format

The first line of input contains an integer N - the number of vehicles.

The next N lines contain details of each vehicle in the format: "RegNumber

OwnerName VehicleType"

1. RegNumber (String) - A unique registration number (Alphanumeric).
2. OwnerName (String) - The name of the vehicle owner.
3. VehicleType (String, Car, Bike, or Truck) - The type of vehicle.

If a vehicle with the same registration number is already present, ignore the duplicate entry.

Output Format

The output prints the unique vehicle records in any order (since HashSet does not maintain order).

Output format: "RegNumber OwnerName VehicleType"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

KA01AB1234 John Car
MH02CD5678 Alice Bike
DL03EF9012 Bob Truck
TN04GH3456 Mike Car
KA01AB1234 John Car

Output: TN04GH3456 Mike Car
KA01AB1234 John Car
MH02CD5678 Alice Bike
DL03EF9012 Bob Truck

Answer

```
// You are using Java
import java.io.*;
import java.util.*;
```

```
class Vehicle{
    String regNo;
    String name;
    String type;
```

```
public Vehicle(String regNo, String name, String type){  
    this.regNo=regNo;  
    this.name=name;  
    this.type=type;  
}  
  
public boolean equals(Object obj){  
    if(this==obj)  
        return true;  
    if(obj==null || getClass()!=obj.getClass())  
        return false;  
    Vehicle v=(Vehicle)obj;  
    return regNo.equals(v.regNo);  
}  
  
public int hashCode(){  
    return regNo.hashCode();  
}  
  
public String toString(){  
    return regNo+" "+name+" "+type;  
}  
}  
  
class Main{  
    public static void main(String[] args){  
        Scanner sc=new Scanner(System.in);  
        int n=sc.nextInt();  
  
        HashSet<Vehicle> set=new HashSet<>();  
  
        for(int i=0;i<n;i++){  
            String regNo=sc.next();  
            String name=sc.next();  
            String type=sc.next();  
            set.add(new Vehicle(regNo, name, type));  
        }  
  
        for(Vehicle v:set)  
            System.out.println(v);  
    }  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 10_Q2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : COD

1. Problem Statement

John is organizing a fruit festival, and the quantities of various fruits are stored in a HashMap where fruit names are keys and quantities are values.

Help him develop a program to find the total quantity of fruits for the festival by summing up the values in the HashMap.

Input Format

The input consists of fruit quantities in the format 'fruitName:quantity', where fruitName is the name of the fruit(a string), and quantity is a double value representing the quantity.

The input is terminated by entering "done".

Output Format

The output prints a double value, representing the sum of values in the HashMap, rounded off to two decimal places.

If the value is not numeric, print "Invalid input".

If any special characters other than ':' are entered, print "Invalid format".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: Banana:15.2

Orange:56.3

Mango:47.3

done

Output: 118.80

Answer

```
// You are using Java
import java.io.*;
import java.util.*;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        double total=0;

        HashMap<String, Double> fruits=new HashMap<>();

        boolean invalidInput=false;
        boolean invalidFormat=false;

        while(true){
            String input=sc.nextLine();
            if(input.equals("done"))
                break;

            if(!input.contains(":") || input.startsWith(":") || input.endsWith(":")){
                invalidFormat=true;
                break;
            }

            String[] parts=input.split(":");
            String fruitName=parts[0];
            String valueStr=parts[1];
            double value;
            try {
                value=Double.parseDouble(valueStr);
            } catch (NumberFormatException e) {
                invalidInput=true;
                break;
            }

            if(invalidInput)
                break;

            fruits.put(fruitName, value);
            total+=value;
        }

        System.out.println("Output: "+total);
    }
}
```

```
        }

        for(char ch: input.toCharArray()){
            if(!(Character.isDigit(ch) || Character.isLetter(ch) || ch=='.' || ch==',')){
                invalidFormat=true;
                break;
            }
        }
        if(invalidFormat)
            break;

        String[] parts=input.split(":");
        if((parts.length!=2)){
            invalidFormat=true;
            break;
        }
        String fruitName=parts[0];
        String quantity=parts[1];

        try{
            double quan=Double.parseDouble(quantity);
            if(quan<=1 || quan>=100){
                invalidInput=true;
                break;
            }
            fruits.put(fruitName, quan);
        }
        catch(NumberFormatException e){
            invalidInput=true;
            break;
        }
    }

    if(invalidFormat)
        System.out.println("Invalid format");
    else if(invalidInput)
        System.out.println("Invalid input");
    else{
        for(double val: fruits.values())
            total+=val;
        System.out.printf("%.2f", total);
    }
}
```

}

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 10_Q3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : COD

1. Problem Statement

Priya is analyzing encrypted messages in a research project. She wants to analyze the frequency of each character in a given paragraph. The characters should be stored in a TreeMap so that the output is sorted in ascending order of characters automatically.

You are required to build a Java program that:

Uses a TreeMap<Character, Integer> to count how many times each character appears in the message.Ignores spaces and considers only alphabets (case-sensitive).Outputs the frequencies of characters in sorted order.

You must use a TreeMap in the class named MessageAnalyzer.

Input Format

The first line of input contains an integer n, the number of lines in the message.

The next n lines each contain a string (the encrypted message line).

Output Format

The first line of output prints: "Character Frequency:"

Then print each character and its frequency in the format: "<character>: <count>"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 2
Hello World
Java

Output: Character Frequency:

H: 1
J: 1
W: 1
a: 2
d: 1
e: 1
l: 3
o: 2
r: 1
v: 1

Answer

```
// You are using Java
import java.io.*;
import java.util.*;

class MessageAnalyzer{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        sc.nextLine();

        TreeMap<Character, Integer> msg=new TreeMap<>();
```

```
for(int i=0;i<n;i++){
    String s=sc.nextLine();

    for(char ch: s.toCharArray()){
        if(Character.isLetter(ch)){
            msg.put(ch, msg.getOrDefault(ch,0)+1);
        }
    }

    System.out.println("Character Frequency:");
    for(Map.Entry<Character,Integer> entry : msg.entrySet()){
        System.out.println(entry.getKey()+" : "+entry.getValue());
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 10_Q4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : COD

1. Problem Statement

In a ticket reservation system, you store the available seat numbers in a TreeSet. Users input their desired seat number, and the program checks whether the chosen seat is available.

Using a TreeSet ensures quick and efficient verification of seat availability, ensuring a smooth and organized ticket booking process.

Input Format

The first line of input contains a single integer n, representing the number of available seats.

The second line contains n space-separated integers, representing the available seat numbers.

The third line contains an integer m, representing the seat number that needs to be searched.

Output Format

The output displays "[m] is present!" if the given seat is available. Otherwise, it displays "[m] is not present!"

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4

2 4 5 6

5

Output: 5 is present!

Answer

```
// You are using Java
import java.io.*;
import java.util.*;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        TreeSet<Integer> seats=new TreeSet<>();

        for(int i=0;i<n;i++){
            int s=sc.nextInt();
            seats.add(s);
        }

        int m=sc.nextInt();

        if(seats.contains(m))
            System.out.println(m+" is present!");
        else
            System.out.println(m+" is not present!");
    }
}
```

}

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 10_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : COD

1. Problem Statement

Arjun is working on a program that checks if one set of numbers is a subset of another. If Set B is a subset of Set A, the program should print "YES" followed by the sorted elements of Set B. If Set B is not a subset of Set A, the program should print "NO" followed by the average of all elements from both sets combined, rounded to two decimal places.

Implement a class Solution with the required method to perform the subset check using TreeSet in Java.

Input Format

The first line contains an integer n - the number of elements in Set A.

The second line contains n space-separated integers - the elements of Set A.

The third line contains an integer m - the number of elements in Set B.

The fourth line contains m space-separated integers - the elements of Set B.

Output Format

If Set B is a subset of Set A, print "YES" followed by the sorted values of Set B.

Otherwise, print "NO" followed by the average of all numbers in both sets (rounded to two decimal places).

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

1 2 3 4 5

3

2 3 5

Output: YES 2 3 5

Answer

```
import java.util.*;  
  
// You are using Java  
class Solution {  
    //Type your code here  
    public static void checkSubset(TreeSet<Integer> setA, TreeSet<Integer> setB,  
    int count, long sum){  
  
        if(setA.containsAll(setB)){  
            System.out.print("YES ");  
            for(int i: setB)  
                System.out.print(i+" ");  
        }  
  
        else{  
            System.out.print("NO ");  
            double avg=(double)sum/count;  
            System.out.printf("%.2f", avg);  
        }  
    }  
}
```

```
241001162
}
}

class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        TreeSet<Integer> setA = new TreeSet<>();
        long sum = 0;
        for (int i = 0; i < n; i++) {
            int num = sc.nextInt();
            setA.add(num);
            sum += num;
        }
        int m = sc.nextInt();
        TreeSet<Integer> setB = new TreeSet<>();
        for (int i = 0; i < m; i++) {
            int num = sc.nextInt();
            setB.add(num);
            sum += num;
        }
        Solution.checkSubset(setA, setB, n + m, sum);
        sc.close();
    }
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Bob wants to develop a score-tracking application for a gaming tournament. Each player's score is stored in a `HashMap` with the player's name as the key and the score as the value.

Write a program to assist Bob that takes user input to enter player scores, calculates the maximum score from the HashMap, and prints the player with the highest score.

Input Format

The input consists of strings representing player details in the format "playerName:score".

The input is terminated by entering "done".

Output Format

The output displays a string, representing the player's name who scored the maximum.

If the value is not numeric, print "Invalid input".

If any special characters other than ':' are given, print "Invalid format".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: Alice:15

Bob:56

done

Output: Bob

Answer

```
import java.util.*;
// You are using Java
class ScoreTracker {
    //type your code here
    HashMap<String, Integer> scoreMap=new HashMap<>();

    public boolean processInput(String s){

        if(!s.contains(":") || s.startsWith(":") || s.endsWith(":")){
            System.out.println("Invalid format");
            return false;
        }

        for(char ch: s.toCharArray()){
            if(!(Character.isLetterOrDigit(ch) || ch==':')){
                System.out.println("Invalid format");
            }
        }
    }
}
```

```
        return false;
    }

String[] parts=s.split(":");
String name=parts[0];
String scoreStr=parts[1];

if(parts.length!=2){
    System.out.println("Invalid format");
    return false;
}
for(char i: scoreStr.toCharArray()){
    if(!Character.isDigit(i)){
        System.out.println("Invalid input");
        return false;
    }
}

int score=Integer.parseInt(scoreStr);
scoreMap.put(name, score);
return true;
}

public String findTopPlayer(){
    String topScorer="";
    int max=Collections.max(scoreMap.values());
    for(Map.Entry<String, Integer> entry : scoreMap.entrySet()){
        if(entry.getValue()==max)
            topScorer= entry.getKey();
    }
    return topScorer;
}
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        ScoreTracker tracker = new ScoreTracker();
        boolean validInput = true;

        while (true) {
            String input = scanner.nextLine();
```

```
        if (input.toLowerCase().equals("done")) {
            break;
        }

        if (!tracker.processInput(input)) {
            validInput = false;
            break;
        }
    }

    if (validInput && !tracker.scoreMap.isEmpty()) {
        System.out.println(tracker.findTopPlayer());
    }

    scanner.close();
}
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

The city library maintains a record of books available for lending. Each book is uniquely identified by its ISBN number, along with its title and author. The librarian wants to efficiently store and manage these records, ensuring books can be listed in the order they were added.

Your task is to implement a Library Management System using HashSet where:

The librarian adds books with ISBN, title, and author. The librarian can remove books by providing an ISBN. Finally, the librarian displays the available books in the order they were added.

Implement a class Library that will handle these operations. The main function should manage user input and interact with the Library class accordingly.

Input Format

The first line contains an integer n – the number of books to be added.

The next n lines contain three values: ISBN (integer), Title (string without spaces), and Author (string without spaces).

1. An integer employee_id
2. A string title
3. A string author name

The next line contains an integer m – the number of books to be removed.

The next m lines follow, each contains an ISBN number to remove.

Output Format

The output prints a list of books available in the library after performing all operations in the format:

"ISBN: <isbn>, Title: <title>, Author: <author>"

If no books remain, print: "No books available"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3
1234 JavaCompleteGuide JohnDoe
5678 PythonBasics JaneDoe
9012 DataStructures AliceSmith
1
5679

Output: ISBN: 1234, Title: JavaCompleteGuide, Author: JohnDoe
ISBN: 9012, Title: DataStructures, Author: AliceSmith
ISBN: 5678, Title: PythonBasics, Author: JaneDoe

Answer

```
import java.util.*;  
// You are using Java  
class Book {
```

```
int isbn;
String title;
String author;

public Book(int isbn, String title, String author){
    this.isbn=isbn;
    this.title=title;
    this.author=author;
}

public boolean equals(Object obj){
    if(this==obj)
        return true;
    if(obj==null || getClass()!=obj.getClass())
        return false;
    Book book=(Book) obj;
    return this.isbn==book.isbn;
}

public int hashCode(){
    return Objects.hash(isbn);
}
}

class Library {
    //Type your code here
    HashSet<Book> books=new HashSet<>();
    public void addBook(int isbn, String title, String author){
        books.add(new Book(isbn, title, author));
    }

    public void removeBook(int isbn){
        books.removeIf(book->book.isbn==isbn);
    }
    public void displayBooks(){
        if(books.isEmpty()){
            System.out.println("No books available");
            return;
        }
        for(Book b:books)
            System.out.println("ISBN: "+b.isbn+", Title: "+b.title+", Author: "+b.author);
    }
}
```

```
        }
    }

class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        Library library = new Library();
        int n = sc.nextInt();
        for (int i = 0; i < n; i++) {
            int isbn = sc.nextInt();
            String title = sc.next();
            String author = sc.next();
            library.addBook(isbn, title, author);
        }
        int m = sc.nextInt();
        for (int i = 0; i < m; i++) {
            int isbn = sc.nextInt();
            library.removeBook(isbn);
        }
        library.displayBooks();
        sc.close();
    }
}
```

Status : Correct

Marks : 10/10

4. Problem Statement

Tony is an e-learning platform administrator, he oversees the user ratings for various online courses offered in the platform.

To enhance user experience, you should assist him in utilizing a HashMap to store course ratings given by learners. Regularly, he analyzes this data to identify the highest and lowest-rated courses, enabling targeted improvements and ensuring the quality of the educational content. This process assists in maintaining a competitive and engaging online learning environment for the users.

Input Format

The input consists of a string representing the course name followed by a

double value representing the course's rating, in separate lines.

The input is terminated by entering "done".

Output Format

The first line of output prints the string "Highest Rated Course: " followed by the highest-rated course.

The second line prints the string "Lowest Rated Course: " followed by the lowest-rated courses.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: DSA

4.0

OOPS

4.2

C

3.2

done

Output: Highest Rated Course: OOPS

Lowest Rated Course: C

Answer

```
import java.util.HashMap;  
import java.util.Map;  
import java.util.Scanner;
```

```
// You are using Java
```

```
import java.util.*;
```

```
class CourseAnalyzer {
```

```
 //type your code here
```

```
    public Map<String, String>  
identifyHighestAndLowestRatedCourses(Map<String,Double> courseRatings){
```

```
        Map<String, String> result = new HashMap<>();
```

```
double max=Collections.max(courseRatings.values());
double min=Collections.min(courseRatings.values());

String highest="";
String lowest="";

for(Map.Entry<String, Double> entry : courseRatings.entrySet()){
    if(entry.getValue()==max)
        highest= entry.getKey();

    if(entry.getValue()==min)
        lowest= entry.getKey();
}

result.put("highest", highest);
result.put("lowest", lowest);

return result;
}
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        Map<String, Double> courseRatings = new HashMap<>();

        while (true) {
            String courseName = scanner.nextLine();
            if (courseName.equalsIgnoreCase("done")) {
                break;
            }
            double rating = Double.parseDouble(scanner.nextLine().trim());
            courseRatings.put(courseName, rating);
        }

        CourseAnalyzer analyzer = new CourseAnalyzer();
        Map<String, String> result =
analyzer.identifyHighestAndLowestRatedCourses(courseRatings);

        System.out.printf("Highest Rated Course: %s\n", result.get("highest"));
        System.out.printf("Lowest Rated Course: %s", result.get("lowest"));
    }
}
```

```
        scanner.close();  
    }  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 10_PAH

Attempt : 3
Total Mark : 30
Marks Obtained : 30

Section 1 : Coding

1. Problem Statement

Sarah is working on a spam detection system that analyzes incoming messages for unique patterns. Spammers often use repetitive character sequences, making it important to identify the first non-repeating character in a message.

Given a string, Sarah needs to determine the first character that appears only once. If all characters repeat, the system should return -1.

She decides to use a HashMap to efficiently track character frequencies and find the solution.

Input Format

The first line contains an integer N representing , the length of the string.

The second line contains a string of N lowercase English letters (a-z).

Output Format

The output prints a character representing the first non-repeating character. If none exist, print -1.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 10
abacabadac
Output: d

Answer

```
// You are using Java
import java.io.*;
import java.util.*;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        String str=sc.next();
        HashMap<Character, Integer> map=new HashMap<>();

        for(char ch: str.toCharArray())
            map.put(ch, map.getOrDefault(ch,0)+1);

        char result='-';
        for(char ch: str.toCharArray()){
            if(map.get(ch)==1){
                result=ch;
                break;
            }
        }
        if(result=='-')
            System.out.println(-1);
        else
```

```
        System.out.println(result);
    }
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

A university maintains a list of student records and wants to store them in a sorted manner based on their GPA. If two students have the same GPA, they should be further sorted by their name in lexicographical order.

Implement a program that uses a TreeSet to store student records and ensures unique student IDs.

Input Format

The first line contains an integer N - the number of students.

The next N lines contain details of each student in the format: "StudentID Name GPA"

- StudentID (Integer) - A unique identifier.
- Name (String) - The student's name (can contain spaces).
- GPA (Double) - The Grade Point Average.

Output Format

The output prints the list of students in ascending order of GPA.

If two students have the same GPA, sort them by name.

Print details in the format: "StudentID Name GPA" in the output, GPA is rounded to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
101 John 8.5

102 Alice 9.1
103 Bob 8.5
104 Zoe 7.3
105 Charlie 9.1
Output: 104 Zoe 7.30
103 Bob 8.50
101 John 8.50
102 Alice 9.10
105 Charlie 9.10

Answer

```
// You are using Java
import java.io.*;
import java.util.*;

class Student implements Comparable<Student>{
    int studentID;
    String name;
    double gpa;

    Student(int studentID, String name, double gpa){
        this.studentID=studentID;
        this.name=name;
        this.gpa=gpa;
    }

    public int compareTo(Student other){
        if(this.gpa<other.gpa)
            return -1;
        else if(this.gpa>other.gpa)
            return 1;
        else{
            int nameCompare=this.name.compareTo(other.name);
            if(nameCompare!=0)
                return nameCompare;
            else
                return Integer.compare(this.studentID, other.studentID);
        }
    }

    public String toString(){
        return studentID+" "+name+" "+String.format("%.2f",gpa);
    }
}
```

```
        }  
    }  
  
class Main{  
    public static void main(String[] args){  
        Scanner sc=new Scanner(System.in);  
        int n=sc.nextInt();  
        sc.nextLine();  
        TreeSet<Student> students=new TreeSet<>();  
  
        for(int i=0;i<n;i++){  
            int id=sc.nextInt();  
            String name=sc.next();  
            double gpa=sc.nextDouble();  
            students.add(new Student(id, name, gpa));  
        }  
  
        for(Student s: students)  
            System.out.println(s);  
    }  
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

Riya is building a calendar event scheduler where each event is stored in chronological order using a TreeMap. The key represents the event time in 24-hour format (HH:MM), and the value is the event description.

She wants the system to:

Automatically sort events by time. Avoid duplicate time entries – if a duplicate time is entered, ignore the new entry. Print all scheduled events in order.

Implement this logic using a class named EventManager.

Input Format

The first line of the input contains an integer n, representing the number of events.

The next n lines each contain a string in the format: "HH:MM Description"

(Example: 09:00 TeamMeeting).

Output Format

The first line of the output prints "Scheduled Events:"

The next k lines print each event in the format: "HH:MM - Description"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

09:00 TeamMeeting

13:30 LunchBreak

11:00 ProjectUpdate

09:00 Standup

15:00 ClientCall

Output: Scheduled Events:

09:00 - TeamMeeting

11:00 - ProjectUpdate

13:30 - LunchBreak

15:00 - ClientCall

Answer

```
// You are using Java
import java.io.*;
import java.util.*;

class EventManager{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        sc.nextLine();
        TreeMap<String, String> events=new TreeMap<>();
        for(int i=0;i<n;i++){
            String s=sc.nextLine();
```

```
String[] parts=s.split(" ");
String time=parts[0];
String event=parts[1];

if(!events.containsKey(time))
    events.put(time, event);
}
System.out.println("Scheduled Events:");
for(Map.Entry<String, String> entry:events.entrySet())
    System.out.println(entry.getKey()+" - "+entry.getValue());
}
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 11

Attempt : 1
Total Mark : 20
Marks Obtained : 20

Section 1 : Project

1. Problem Statement

Create a JDBC-based Inventory Management System that handles runtime input to manage items in an inventory. The system should allow users to:

Add a new item (item ID, name, quantity, price).

Restock an item by increasing its quantity.

Reduce the stock of an item, ensuring sufficient quantity.

Display all items in the inventory in a sorted order by item ID.

Exit the application.

Half of the code is given here; Only the remaining part should be completed.

The system should connect to a MySQL database using the following default credentials:

DB URL: jdbc:mysql://localhost/ri_db

USER: test

PWD: test123

The items table has already been created with the following structure:

Table Name: items

Input Format

The first line of input consists of an integer choice, representing the operation to be performed (1 for Add Item, 2 for Restock item, 3 for reduce item, 4 for Display, 5 for Exit).

For choice 1 (Add Item):

- The second line consists of an integer item_id.
- The third line consists of a string name.
- The fourth line consists of an integer quantity.
- The fifth line consists of a double price.

For choice 2 (Restock Item):

- The second line consists of an integer item_id.
- The third line consists of an integer quantity_to_add (must be positive).

For choice 3 (Reduce Stock):

- The second line consists of an integer item_id.
- The third line consists of an integer quantity_to_remove (must be positive).

For choice 4 (Display Inventory):

- No additional inputs are required.

For choice 5 (Exit):

- No additional inputs are required.

Output Format

For choice 1 (Add Item):

- Print "Item added successfully" if the item was added.
- Print "Failed to add item." if the insertion failed.

For choice 2 (Restock Item):

- Print "Item restocked successfully" if the restock was successful.
- Print "Item not found." if the specified item ID does not exist.

For choice 3 (Reduce Stock):

- Print "Stock reduced successfully" if the stock reduction was successful.
- Print "Not enough stock to remove." if there is insufficient quantity.
- Print "Item not found." if the specified item ID does not exist.

For choice 4 (Display Inventory):

- Display each item on a new line in the format:
- ID | Name | Quantity | Price
- If no items are available, print nothing (or handle with an appropriate message if desired).

For choice 5 (Exit):

- Print "Exiting Inventory Management System."

For invalid input:

- Print "Invalid choice. Please try again."

Sample Test Case

Input: 1

101

Laptop

50

1200.00
4
5
Output: Item added successfully
ID | Name | Quantity | Price
101 | Laptop | 50 | 1200.00
Exiting Inventory Management System.

Answer

```
import java.sql.*;  
import java.util.Scanner;  
  
class InventoryManagementSystem {  
    public static void main(String[] args) {  
        try (Connection conn = DriverManager.getConnection("jdbc:mysql://  
localhost/ri_db", "test", "test123");  
        Scanner scanner = new Scanner(System.in)) {  
  
            boolean running = true;  
  
            while (running) {  
  
                int choice = scanner.nextInt();  
  
                switch (choice) {  
                    case 1:  
                        addItem(conn, scanner);  
                        break;  
                    case 2:  
                        restockItem(conn, scanner);  
                        break;  
                    case 3:  
                        reduceStock(conn, scanner);  
                        break;  
                    case 4:  
                        displayInventory(conn);  
                        break;  
                    case 5:  
                        System.out.println("Exiting Inventory Management System.");  
                        running = false;  
                        break;  
                    default:
```

```
        System.out.println("Invalid choice. Please try again.");
    }
}
} catch (SQLException e) {
    e.printStackTrace();
}
}

// You are using Java
public static void addItem(Connection conn, Scanner scanner) {
    // write your code here
    try{
        int item_id=scanner.nextInt();
        scanner.nextLine();
        String name=scanner.nextLine();
        int quantity=scanner.nextInt();
        double price=scanner.nextDouble();

        String query="insert into items(item_id, name, quantity, price)
values(?, ?, ?, ?)";
        PreparedStatement ps=conn.prepareStatement(query);
        ps.setInt(1, item_id);
        ps.setString(2, name);
        ps.setInt(3, quantity);
        ps.setDouble(4, price);

        int rows=ps.executeUpdate();
        if(rows>0)
            System.out.println("Item added successfully");
        else
            System.out.println("Failed to add item.");
    }

    catch(SQLException e){
        System.out.println("Failed to add item.");
    }
}

public static void restockItem(Connection conn, Scanner scanner) {
    try{
        int item_id=scanner.nextInt();
        int quantity_to_add=scanner.nextInt();
        String checkQuery="select quantity from items where item_id=?";
```

```
PreparedStatement psCheck=conn.prepareStatement(checkQuery);

psCheck.setInt(1,item_id);
ResultSet rs=psCheck.executeQuery();

if(rs.next()){
    int currentQuantity=rs.getInt("quantity");
    int newQuantity=currentQuantity+quantity_to_add;
    String updateQuery="update items set quantity=? where item_id=?";

    PreparedStatement psUpdate=conn.prepareStatement(updateQuery);
    psUpdate.setInt(1, newQuantity);
    psUpdate.setInt(2, item_id);
    psUpdate.executeUpdate();
    System.out.println("Item restocked successfully");
}

else
    System.out.println("Item not found.");
}

catch(SQLException e){
    System.out.println("Item not found");
}
}

public static void reduceStock(Connection conn, Scanner scanner) {
try{
    int item_id=scanner.nextInt();
    int quantity_to_remove=scanner.nextInt();

    String checkQuery="select quantity from items where item_id=?";
    PreparedStatement psCheck=conn.prepareStatement(checkQuery);
    psCheck.setInt(1, item_id);
    ResultSet rs=psCheck.executeQuery();

    if(rs.next()){
        int currentQuantity=rs.getInt("quantity");

        if(currentQuantity>=quantity_to_remove){
            int newQuantity=currentQuantity-quantity_to_remove;
            String updateQuery="update items set quantity=? where item_id=?";
            PreparedStatement psUpdate=conn.prepareStatement(updateQuery);
```

```
        psUpdate.setInt(1, newQuantity);
        psUpdate.setInt(2, item_id);
        psUpdate.executeUpdate();
        System.out.println("Stock reduced successfully");
    }
    else
        System.out.println("Not enough stock to remove.");
}
else
    System.out.println("Item not found.");
}

catch(SQLException e){
    System.out.println("Item not found");
}
}

public static void displayInventory(Connection conn) {
try{
    String query="select * from items order by item_id";
    PreparedStatement ps=conn.prepareStatement(query);
    ResultSet rs=ps.executeQuery();

    boolean hasItems=false;
    System.out.println("ID | Name | Quantity | Price");
    while(rs.next()){
        hasItems=true;
        int id=rs.getInt("item_id");
        String name=rs.getString("name");
        int quantity=rs.getInt("quantity");
        double price=rs.getDouble("price");

        System.out.printf("%d | %s | %d | %.2f\n", id, name, quantity, price);
    }

}
catch(SQLException e){
    e.printStackTrace();
}
}
```

2. Problem Statement

In Café Central, the menu is cataloged and stored in a database.

To efficiently manage the restaurant's menu using Java and JDBC, you must build a Restaurant Management System that supports:

Adding new menu items

Updating menu item prices

Viewing details of a menu item

Displaying all menu items in sorted order

You are given two files:

File 1: MenuItem.java (POJO Class)

This class represents the MenuItem entity.

A MenuItem contains the following details:

Field Description

itemId Unique Menu Item ID (Integer)

name Item Name (String)

category Item Category (String)

price Item Price (Double)

Students must write code in the marked area:

```
class MenuItem {  
    private int itemId;  
    private String name;  
    private String category;  
    private double price;
```

```
public MenuItem() {}  
public MenuItem(int itemId, String name, String category, double price) {  
    // write your code here  
}  
  
// Include getters and setters  
}
```

Expected in this part:

Assign parameter values to instance variables inside the constructor.

Add getters and setters for all attributes.

File 2: MenuItemDAO.java (Data Access Layer)

This class handles all database operations using JDBC.

Students must complete the missing JDBC logic in the following methods:

```
class MenuItemDAO {
```

```
    public void addMenuItem(Connection conn, MenuItem menuItem)  
throws SQLException {
```

// write your code here

```
}
```

```
    public void updateItemPrice(Connection conn, int itemId, double  
newPrice) throws SQLException {
```

// write your code here

```
}
```

```
    public void deleteMenuItem(Connection conn, int itemId) throws  
SQLException {
```

// write your code here

```
}

public MenuItem viewItemDetails(Connection conn, int itemId) throws
SQLException {
    // write your code here
}

public List<MenuItem> displayAllMenuItems(Connection conn) throws
SQLException {
    // write your code here
}

private MenuItem mapToMenuItem(ResultSet rs) throws SQLException {
    return new MenuItem(
        // write your code here
    );
}

}
```

Expected in this part:

Write SQL queries for INSERT, UPDATE, DELETE, SELECT.

Execute queries using PreparedStatement or Statement.

Map ResultSet rows to MenuItem objects using mapToMenuItem().

Return a List<MenuItem> where required.

The system should connect to a MySQL database using the following default credentials:

DB URL: jdbc:mysql://localhost/ri_db

USER: test

PWD: test123

The menu table has already been created with the following structure:

Table Name: menu

Input Format

The first line of input consists of an integer choice, representing the operation to be performed (1 for Add Item, 2 for Restock item, 3 for reduce item, 4 for Display, 5 for Exit).

For choice 1 (Add Menu Item):

- The second line consists of an integer item_id.
- The third line consists of a string name.
- The fourth line consists of a string category.
- The fifth line consists of a double price.

For choice 2 (Update Item Price):

- The second line consists of an integer item_id.
- The third line consists of a double new_price.

For choice 3 (View Item Details):

- The second line consists of an integer item_id.

For choice 4 (Display All Menu Items):

- No additional inputs are required.

For choice 5 (Exit):

- No additional inputs are required.

Output Format

For choice 1 (Add Menu Item):

- Print "Menu item added successfully" if the item was added.
- Print "Failed to add item." if the insertion failed.

For choice 2 (Update Item Price):

- Print "Item price updated successfully" if the price update was successful.
- Print "Item not found." if the specified item ID does not exist.

For choice 3 (View Item Details):

- Display the item details in the format:
- ID: [item_id] | Name: [name] | Category: [category] | Price: [price]
- Print "Item not found." if the specified item ID does not exist.

For choice 4 (Display All Menu Items):

- Display each item on a new line in the format:
- ID | Name | Category | Price
- If no items are available, print nothing (or handle with an appropriate message if desired).

For choice 5 (Exit):

- Print "Exiting Restaurant Management System."

For invalid input:

- Print "Invalid choice. Please try again."

Sample Test Case

Input: 1

11

Margherita Pizza

Main Course

12.99

4

5

Output: Menu item added successfully

ID | Name | Category | Price

11 | Margherita Pizza | Main Course | 12.99

Exiting Restaurant Management System.

Answer

```
import java.sql.*;  
import java.util.Scanner;
```

```
class RestaurantManagementSystem {  
    public static void main(String[] args) {  
        try (Connection conn = DriverManager.getConnection("jdbc:mysql://  
localhost/ri_db", "test", "test123");  
            Scanner scanner = new Scanner(System.in)) {  
  
            boolean running = true;  
  
            while (running) {  
                int choice = scanner.nextInt();  
  
                switch (choice) {  
                    case 1:  
                        addMenuItem(conn, scanner);  
                        break;  
                    case 2:  
                        updateItemPrice(conn, scanner);  
                        break;  
                    case 3:  
                        viewItemDetails(conn, scanner);  
                        break;  
                    case 4:  
                        displayAllMenuItems(conn);  
                        break;  
                    case 5:  
                        System.out.println("Exiting Restaurant Management System.");  
                        running = false;  
                        break;  
                    default:  
                        System.out.println("Invalid choice. Please try again.");  
                }  
            }  
        } catch (SQLException e) {  
            e.printStackTrace();  
        }  
    }  
  
    // You are using Java  
    public static void addMenuItem(Connection conn, Scanner scanner) {  
        try{  
            int itemId=scanner.nextInt();  
            scanner.nextLine();  
            String name=scanner.nextLine();  
        }  
    }  
}
```

```
String category=scanner.nextLine();
double price=scanner.nextDouble();

String sql="insert into menu(item_id, name, category, price) values
(?, ?, ?, ?)";
PreparedStatement ps=conn.prepareStatement(sql);

ps.setInt(1, itemId);
ps.setString(2, name);
ps.setString(3, category);
ps.setDouble(4, price);

int rows=ps.executeUpdate();

if(rows>0)
    System.out.println("Menu item added successfully");
else
    System.out.println("Failed to add item.");
}

catch (SQLException e){
    System.out.println("Failed to add item.");
}
}

public static void updateItemPrice(Connection conn, Scanner scanner) {
//Write your code here
try{
    int itemId=scanner.nextInt();
    double newPrice=scanner.nextDouble();

    String sql="update menu set price=? where item_id=?";
    PreparedStatement ps=conn.prepareStatement(sql);

    ps.setDouble(1, newPrice);
    ps.setInt(2, itemId);

    int rows=ps.executeUpdate();

    if(rows>0)
        System.out.println("Item price updated successfully");
    else

```

```
        System.out.println("Item not found.");
    }

    catch(SQLException e){
        System.out.println("Item not found.");
    }
}

public static void viewItemDetails(Connection conn, Scanner scanner) {
    //Write your code here
    try{
        int itemId=scanner.nextInt();

        String sql="select * from menu where item_id=?";
        PreparedStatement ps=conn.prepareStatement(sql);

        ps.setInt(1, itemId);
        ResultSet rs=ps.executeQuery();

        if(rs.next()){
            int id=rs.getInt("item_id");
            String name=rs.getString("name");
            String category=rs.getString("category");
            double price=rs.getDouble("price");

            System.out.println("ID: "+id+" | Name: "+name+" | Category: "+category
+" | Price: "+price);
        }
        else
            System.out.println("Item not found.");
    }
    catch(SQLException e){
        System.out.println("Item not found.");
    }
}

public static void displayAllMenuItems(Connection conn) {
    try{
        String sql="select * from menu order by item_id";
        PreparedStatement ps=conn.prepareStatement(sql);
```

```
ResultSet rs=ps.executeQuery();

System.out.println("ID | Name | Category | Price");

while(rs.next()){
    int id=rs.getInt("item_id");
    String name=rs.getString("name");
    String category=rs.getString("category");
    double price=rs.getDouble("price");

    System.out.printf("%d | %s | %s | %.2f\n", id, name, category, price);
}
}

catch(SQLException e){
    e.printStackTrace();
}

}

class MenuItem {
    private int itemId;
    private String name;
    private String category;
    private double price;

    // Constructor
    public MenuItem(int itemId, String name, String category, double price) {
        this.itemId = itemId;
        this.name = name;
        this.category = category;
        this.price = price;
    }

    //Include getters and setters

    public int getItemId(){
        return itemId;
    }
    public void setItemId(int itemId){
        this.itemId=itemId;
    }
    public String getName(){
        return name;
```

```
}

public void setName(String name){
    this.name=name;
}

public String getCategory(String category){
    return category;
}

public void setCategory(String category){
    this.category=category;
}

public double getPrice(){
    return price;
}

public void setPrice(double price){
    this.price=price;
}

//
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_Week 12_Java_Lambda Expressions_MCQ

Attempt : 1

Total Mark : 10

Marks Obtained : 9

Section 1 : MCQ

1. Which of the following is a valid lambda expression in Java?

Answer

(x) -> x * 2

Status : Wrong

Marks : 0/1

2. Which of the following interfaces is NOT a functional interface in Java?

Answer

Iterable

Status : Correct

Marks : 1/1

3. Which functional interface is commonly used with lambda expressions in Java?

Answer

Runnable

Status : Correct

Marks : 1/1

4. What is the return type of a lambda expression in Java?

Answer

The return type is inferred from the context

Status : Correct

Marks : 1/1

5. Can a lambda expression in Java have a body with multiple statements?

Answer

Yes, if the statements are enclosed in curly braces

Status : Correct

Marks : 1/1

6. What is the syntax for a basic lambda expression in Java?

Answer

(parameters) -> expression

Status : Correct

Marks : 1/1

7. Which functional interface in Java takes two arguments and returns a result?

Answer

BiFunction

Status : Correct

Marks : 1/1

8. Can a lambda expression have more than one parameter?

Answer

Yes, it can have multiple parameters

Status : Correct

Marks : 1/1

9. What is a lambda expression in Java?

Answer

A way to define anonymous methods

Status : Correct

Marks : 1/1

10. Can a lambda expression in Java have a body with multiple statements?

Answer

Yes, if the statements are enclosed in curly braces

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 12_Q1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Sabrina is working on a project that involves analyzing a set of numbers. In her exploration, she encounters scenarios where extracting even numbers and finding their sum is essential.

Create a program that calculates the sum of even numbers from a given array of integers using a lambda expression.

Input Format

The first line of input consists of an integer N, representing the size of the array.

The second line consists of N space-separated integers, representing the elements of the array.

Output Format

The output prints the sum of the even integers from the array.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3

29 37 45

Output: 0

Answer

```
// You are using Java
import java.io.*;
import java.util.*;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int[] arr=new int[n];

        for(int i=0;i<n;i++)
            arr[i]=sc.nextInt();

        int sum=Arrays.stream(arr).filter(x -> x%2==0).sum();
        System.out.println(sum);
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 12_Q2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Alex is learning about Java's functional interfaces and lambda expressions.

He wants to write a simple program that prints the square of each number in an array using a predefined functional interface.

Help Alex complete this task using the Consumer functional interface.

Input Format

- The first line contains an integer N, the number of elements in the array.
- The second line contains N space-separated integers.

Output Format

- Print the squares of all elements in the array, separated by a space.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4

1 2 3 4

Output: 1 4 9 16

Answer

```
// You are using Java
import java.io.*;
import java.util.*;
import java.util.function.Consumer;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int[] arr=new int[n];
        for(int i=0;i<n;i++)
            arr[i]=sc.nextInt();

        Consumer<Integer> squares= x->System.out.print((x*x)+" ");
        for(int i:arr)
            squares.accept(i);
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 12_Q3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In the mystical realm of programming, there exists a magical incantation to reveal hidden words.

Elara, the skilled enchantress, wishes to summon a word using her spell and then reverse its characters to uncover its enchanted reflection.

Write a program that uses the predefined functional interface Supplier<String> and a lambda expression to:

Supply (generate) a string, and

Display its reversed form.

Input Format

No input is required from the user.

The string must be supplied internally using a Supplier<String>.

Output Format

Print the reversed version of the supplied string.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: Wizard!!

Output: !!dرازW

Answer

```
// You are using Java
import java.io.*;
import java.util.*;
import java.util.function.Supplier;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        String s=sc.nextLine();

        Supplier<String> supplier=()->s;

        String str=supplier.get();

        String reverse=new StringBuilder(str).reverse().toString();

        System.out.println(reverse);
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

2028_REC_OOPS using Java_Week 12_Q4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Abi is working on a text analysis project where she needs to categorize words based on their length.

Words that have three or fewer characters are considered “Short”, while words with more than three characters are classified as “Long.”

Write a Java program that takes a sentence as input, analyzes each word, and prints a list showing whether each word is “Short” or “Long.”

Use the predefined functional interface Function<String, String> along with a lambda expression for categorization.

Input Format

A single line containing a sentence (words separated by spaces).

Output Format

- A single line with each word categorized as "Short" or "Long", separated by spaces.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: I love my cat

Output: Short Long Short Short

Answer

```
// You are using Java
import java.io.*;
import java.util.*;
import java.util.function.Function;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        String s=sc.nextLine();

        Function<String, String> str=word->word.length()<=3? "Short":"Long";

        String[] words=s.split(" ");
        for(String word: words)
            System.out.print(str.apply(word)+" ");
    }
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_Week 12_Java_Lambda Expressions_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Riya is developing a college admission system that assigns unique roll numbers to each newly admitted student.

Each roll number should follow this fixed format:

<DEPT>-<YEAR>-<4-digit-sequence>

where:

<DEPT> is the department code (in uppercase, e.g., CSE, ECE, MECH).<YEAR> is the admission year (e.g., 2025).<4-digit-sequence> starts from a given number and increases sequentially for each student. Write a Java program using a Supplier<String> lambda to generate and print the roll numbers for n students.

Input Format

First line: integer n – number of roll numbers to generate

Second line: string DEPT – department code (uppercase letters only)

Third line: integer YEAR – admission year

Fourth line: integer start – starting sequence number ($0 \leq \text{start} \leq 9999$)

Output Format

Print n roll numbers, one per line, in the required format

Sequence must be zero-padded to 4 digits

If sequence exceeds 9999, wrap around to 0000

Sample Test Case

Input: 5

CSE

2025

98

Output: CSE-2025-0098

CSE-2025-0099

CSE-2025-0100

CSE-2025-0101

CSE-2025-0102

Answer

```
// You are using Java
import java.io.*;
import java.util.*;
import java.util.function.Supplier;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        String dept=sc.next();
        int year=sc.nextInt();
        int start=sc.nextInt();
        int[] seq={start};
```

```
Supplier<String> rollSupplier=()-> {
    String roll=String.format("%s-%d-%04d", dept, year, seq[0]);
    seq[0]=(seq[0]+1)%10000;
    return roll;
};

for(int i=0;i<n;i++)
    System.out.println(rollSupplier.get());
}
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Problem Statement

Sophia, a data analyst, is studying experimental results collected from various lab sensors. Each sensor provides a list of numeric readings, and Sophia wants to calculate the average of these readings to analyze consistency.

She decides to use lambda expressions and the Function functional interface to compute the average of all the recorded values efficiently.

Your Task

Write a Java program that:

Reads the total number of measurements. Reads all the measurement values as doubles. Uses a `Function<double[], Double>` lambda expression to calculate the average value. Displays the final average, formatted to two decimal places.

Input Format

The first line of input consists of an integer N, representing the number of measurements.

The second line contains N space-separated double values.

Output Format

Print the average of the entered values, rounded to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 6
2.2 1.2 5.4 4.6 2.9 55.7

Output: 12.00

Answer

```
// You are using Java
import java.io.*;
import java.util.*;
import java.util.function.Function;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        double[] readings=new double[n];

        for(int i=0;i<n;i++)
            readings[i]=sc.nextDouble();

        Function<double[], Double> avgFunc=arr->{
            double sum=0;
            for(double val:arr)
                sum+=val;
            return sum/arr.length;
        };

        double avg=avgFunc.apply(readings);
        System.out.printf("%.2f",avg);
    }
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

A company named TechNova is collecting feedback from its customers. Each customer gives a feedback score (an integer between 1 and 10) along with their name.

The company wants to:

Display each customer's name along with their feedback in a formatted way using a lambda expression and a Consumer functional interface. After displaying all feedbacks, calculate and display the average feedback score. You need to implement this functionality using Java lambda expressions and streams, emphasizing the Consumer interface for displaying formatted output.

Input Format

The first line of input contains an integer n, representing the number of customers.

The next n lines each contain a String (customer name) followed by an int (feedback score).

Output Format

- Each line prints a customer's name and feedback in the format:
 - Customer: <name>, Feedback Score: <score>
-
- After all customers are displayed, print the average feedback as:
 - Average Feedback: <average_value>

(Average should be displayed up to two decimal places.)

Sample Test Case

Input: 3
Ravi 7
Ananya 9

Kiran 8

Output: Customer: Ravi, Feedback Score: 7
Customer: Ananya, Feedback Score: 9
Customer: Kiran, Feedback Score: 8
Average Feedback: 8.00

Answer

```
// You are using Java
import java.io.*;
import java.util.*;
import java.util.function.Consumer;
import java.util.stream.Collectors;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        sc.nextLine();

        List<String> names=new ArrayList<>();
        List<Integer> scores=new ArrayList<>();

        for(int i=0;i<n;i++){
            String name=sc.next();
            int score=sc.nextInt();
            names.add(name);
            scores.add(score);
        }

        Consumer<Integer> displayFeedback=i->System.out.println("Customer: "+names.get(i)+", Feedback Score: "+scores.get(i));

        for(int i=0;i<n;i++)
            displayFeedback.accept(i);

        double avg=scores.stream().collect(Collectors.averagingInt(Integer::intValue));

        System.out.printf("Average Feedback: %.2f", avg);
    }
}
```

4. Problem Statement

Nethra is a researcher working on a project that involves analyzing experimental data. As part of her analysis, she needs to determine whether a given word is a palindrome or not.

Create a Java program that allows Nethra to input a word, and then check and display whether the entered word is a palindrome. Use lambda expressions to perform the palindrome check.

Input Format

The first line of input consists of a word.

Output Format

The output prints whether the given word is a palindrome or not in the following format:

"<input> is palindrome" or "<input> is not palindrome".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: malayalam

Output: malayalam is palindrome

Answer

```
// You are using Java
import java.io.*;
import java.util.*;
import java.util.function.Predicate;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
```

```
String word=sc.nextLine();  
  
    Predicate<String> isPalin=s->s.equalsIgnoreCase(new  
StringBuilder(s).reverse().toString());  
  
    if(isPalin.test(word))  
        System.out.println(word+" is palindrome");  
    else  
        System.out.println(word+" is not palindrome");  
}  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Pavithra S
Email: 241001162@rajalakshmi.edu.in
Roll no: 241001162
Phone: 8122081287
Branch: REC
Department: IT - Section 2
Batch: 2028
Degree: B.E - IT

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_Week 12_Java_Lambda Expressions_PAH

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : COD

1. Problem Statement

Rishi is working as an HR analyst in a software company. He wants to filter a list of employees based on their salary using modern Java techniques. He has a list of employee names and salaries and wants to use lambda expressions to filter those who earn more than a specific threshold.

Implement a program using lambda expressions and functional interfaces to print the names of employees whose salary is greater than or equal to 50,000.

Input Format

The first line of input consists of an integer n, representing the number of employees.

The next n lines. Each line contains a String (employee name) and an int (salary).

Output Format

The output prints the names of employees whose salary is greater than or equal to 50000, each on a new line.

If no employee found with salary greater than 50000, print: No employee found with salary >= 50000

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
Amit 45000
Sneha 50000
Ravi 60000
Priya 30000

Output: Sneha
Ravi

Answer

```
// You are using Java
import java.io.*;
import java.util.*;
import java.util.function.Predicate;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        String[] names=new String[n];
        int[] salaries=new int[n];

        for(int i=0;i<n;i++){
            names[i]=sc.next();
            salaries[i]=sc.nextInt();
        }

        Predicate<Integer> isHighSalary = salary->salary>=50000;
    }
}
```

```
        boolean found=false;  
        for(int i=0;i<n;i++){  
            if(isHighSalary.test(salaries[i])){  
                System.out.println(names[i]);  
                found=true;  
            }  
        }  
        if(!found)  
            System.out.println("No employee found with salary >= 50000");  
    }  
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Emily, an analyst at a data processing firm, is tasked with cleaning up datasets to remove duplicate values from lists of integers.

Create a Java program that allows Emily to input a series of integers, with the program then utilizing a lambda expression to efficiently remove any duplicates.

Input Format

The first line of input consists of an integer N, representing the size of the array.

The second line consists of N space-separated integers, each denoting an array element.

Output Format

The output prints the array elements after removing the duplicates inside the square bracket separated by a comma and space.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 15
1 2 3 4 3 2 1 2 3 4 4 4 5 5 6
Output: [1, 2, 3, 4, 5, 6]

Answer

```
// You are using Java
import java.util.*;
import java.util.function.Function;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();

        Integer[] arr=new Integer[n];

        for(int i=0;i<n;i++)
            arr[i]=sc.nextInt();

        Function<Integer[], List<Integer>> removeDuplicates = (numbers)->{
            Set<Integer> set=new LinkedHashSet<>(Arrays.asList(numbers));
            return new ArrayList<>(set);
        };

        List<Integer> uniqueList=removeDuplicates.apply(arr);
        System.out.println(uniqueList);
    }
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

Aditya is developing a reading app that recommends books to users based on a predefined list.

Each time a user opens the app, it should supply the next book title in the list, one at a time, using a lambda expression and the Supplier functional interface.

When all books have been recommended, the list should start again from the beginning.

Input Format

The first line contains an integer n – the total number of available book titles.

The next n lines each contain a book title (a string).

The next line contains an integer m – the number of times users open the app (i.e., the number of recommendations to be made).

Output Format

Print the supplied book title for each recommendation, one per line.

If m > n, repeat the list from the start.

Sample Test Case

Input: 3

The Alchemist

Atomic Habits

Ikigai

5

Output: The Alchemist

Atomic Habits

Ikigai

The Alchemist

Atomic Habits

Answer

```
// You are using Java
import java.io.*;
import java.util.*;
import java.util.function.Supplier;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        sc.nextLine();
```

```
List<String> books=new ArrayList<>();  
  
for(int i=0;i<n;i++)  
    books.add(sc.nextLine());  
  
int m=sc.nextInt();  
int[] index={0};  
  
Supplier<String> bookSupplier=()->{  
    String book=books.get(index[0]);  
    index[0]=(index[0]+1)%books.size();  
    return book;  
};  
  
for(int i=0;i<m;i++)  
    System.out.println(bookSupplier.get());  
}  
}
```

Status : Correct

Marks : 10/10

4. Problem Statement

Sneha is developing a feature for an e-commerce application that helps display product details after applying a seasonal discount.

She decides to use lambda expressions with the Consumer functional interface to print each product's name, original price, and discounted price neatly.

The program should:

Accept a list of product names and their prices. Apply a 15% discount on all products. Use a Consumer lambda expression to display the details in a formatted manner.

Input Format

The first line of input consists of an integer n, representing the number of products.

The next n lines each contain a String (product name) and a double (price) separated by a space.

Output Format

For each product, print the details in the format:

Product: <name>, Original Price: <price>, Discounted Price: <discounted price>

If there are no products, print:

No products available

Sample Test Case

Input: 1

Phone 60000

Output: Product: Phone, Original Price: 60000.0, Discounted Price: 51000.0

Answer

```
// You are using Java
import java.io.*;
import java.util.*;
import java.util.function.Consumer;

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();

        if(n==0){
            System.out.println("No products available");
            return;
        }

        List<String> names=new ArrayList<>();
        List<Double> prices=new ArrayList<>();

        for(int i=0;i<n;i++){
            String name=sc.next();
            double price=sc.nextDouble();
            names.add(name);
            prices.add(price);
        }
    }
}
```

```
Consumer<Integer> printProduct = i->{
    String name=names.get(i);
    double price=prices.get(i);
    double discounted=price-(price*0.15);
    System.out.printf("Product: %s, Original Price: %.1f, Discounted Price: %.1f
\n", name, price, discounted);
};

for(int i=0;i<n;i++)
    printProduct.accept(i);
}
```

Status : Correct

Marks : 10/10