

SathiMarket

Complete API Documentation

Customer + Merchant — Mobile App Guide

Source: [villagesathi-ui/src/pages/SathiMarket](#)

Generated: 16/5/2026

<https://api.villagesathi.in/api>

1. SathiMarket Folder Structure

```
src/pages/SathiMarket/
% % %   C u s t o m e r /
%       % % %   C a r t . j s x                !'   M a n a g e A d d r e s s ,   P l a c e O r d e r
%       % % %   C u s t o m e r D a s h B o a r d . j s x    !'   G e t B y U s e r   o r d e r s
%       % % %   C u s t o m e r L o g i n . j s x           !'   C u s t o m e r / L o g i n
%       % % %   C u s t o m e r R e g i s t e r . j s x      !'   C u s t o m e r / R e g i s t e r
%       % % %   M a n a g e A d d r e s s e s . j s x        !'   C u s t o m e r / M a n a g e A d d r e s s
%       % % %   M y O r d e r s . j s x                   !'   O r d e r s / G e t B y U s e r
%       % % %   P r o d u c t D e t a i l s M o d a l . j s x !'   ( n o   A P I   -   U I   m o d a l )
%       % % %   S a t h i M a r k e t . j s x              !'   S h o p s / G e t A l l
%       % % %   S h o p D e t a i l s . j s x              !'   S h o p s / G e t B y I d ,   S h o p I t e m s / G e t
%       % % %   W i s h L i s t . j s x                   !'   E X C L U D E D   ( n o   b a c k e n d )
% % %   M e r c h a n t /
%       % % %   M a n a g e I n v e n t o r y . j s x        !'   S h o p I t e m s   C R U D
%       % % %   M a n a g e P r o f i l e . j s x           !'   S h o p s   G e t B y I d ,   U p d a t e S h o p
%       % % %   M e r c h a n t D a s h B o a r d . j s x    !'   O r d e r s ,   S h o p I t e m s
%       % % %   M e r c h a n t L o g i n . j s x           !'   A u t h / L o g i n
%       % % %   M e r c h a n t R e g i s t e r . j s x      !'   A u t h   r e g i s t e r ,   r o l e s ,   c a t e g o
%       % % %   S h o p O r d e r s . j s x                !'   O r d e r s   G e t B y S h o p ,   U p d a t e S t a t
```

2. Base Configuration

Base URL: <https://api.villagesathi.in/api>
Images: <https://api.villagesathi.in> (VITE_IMAGE_URL)
Headers: Content-Type: application/json
Accept: */*
Protected: Authorization: Bearer <token>

RoleId	Role	Login API
1	Admin	POST /Auth/Login
2	Merchant / Shopkeeper	POST /Auth/Login + RoleId=2
3	Customer	POST /Customer/Login + RoleId=3

3. Master API Index (All Endpoints)

Method	Endpoint	Used In
GET	/Auth/get-roles	MerchantRegister
POST	/Auth/register	MerchantRegister
POST	/Auth/Login	MerchantLogin
GET	/Categories/GetAll	MerchantRegister
POST	/Customer/Register	CustomerRegister
POST	/Customer/Login	CustomerLogin
POST	/Customer/ManageAddress	ManageAddresses, Cart
GET	/Shops/GetAll	SathiMarket
GET	/Shops/GetById/{id}	ShopDetails, ManageProfile

Method	Endpoint	Used In
POST	/Shops/UpdateShop	ManageProfile
GET	/ShopItems/GetByShop/{shopId}	ShopDetails, ManageInventory, Dashboard
POST	/ShopItems/AddItem	ManageInventory (multipart)
DELETE	/ShopItems/DeleteItem/{itemId}	ManageInventory
POST	/Orders/PlaceOrder	Cart
GET	/Orders/GetByUser/{userId}	MyOrders, CustomerDashBoard
GET	/Orders/GetByShop/{shopId}	ShopOrders, MerchantDashBoard
POST	/Orders/UpdateStatus	ShopOrders

4. Auth APIs (Merchant Register & Login)

GET /Auth/get-roles

Load Account Type dropdown.

Auth: No

Request:
(none)

Response (expected):
[{ "id": 2, "roleName": "Merchant" }, ...]

GET /Categories/GetAll

Shop category dropdown when roleId=2.

Auth: No

Response (expected):
{ "Data": [{ "categoryID": 1, "categoryName": "Grocery" }] }

POST /Auth/register

Register user + shop (merchant).

Auth: No

Request:
{
 "name": "Owner Name",
 "mobileNo": "9876543210",
 "password": "****",
 "villageId": 1,
 "roleId": "2",
 "shopName": "Sathi Store", // required if roleId=2
 "categoryId": "1",
 "shopAddress": "Full address"
}

Response (expected):
{ "success": true, "message": "..." }

UI: isBusiness = Number(roleId)===2 shows Shop Information block (shopName, categoryId, shopAddress).

POST /Auth/Login

Merchant login (unified auth).

Auth: No

Request:
{ "mobileNo": "9876543210", "password": "****" }

Response (expected):

```
{ "Success": 1, "token": "...", "Data": {  
  "RoleId": 2, "ShopId": 15, "shopName": "...", "mobileNo": "..."  
} }
```

Reject if RoleId !== 2. Store shopId for all merchant APIs.

5. Customer Module — APIs by Page

Page: CustomerLogin

Route: /customer-login

File: src/pages/SathiMarket/Customer/CustomerLogin.jsx

Method	Endpoint	Purpose
POST	/Customer/Login	Customer sign-in

POST /Customer/Login

Authenticate customer; flat response at root level.

Request:
{ "mobileNo": "10 digits", "password": "****" }

Response (expected):
{ "Success": 1, "UserId": 101, "Name": "...", "RoleId": 3,
"RoleName": "Customer", "City": "...", "VillageId": 1 }

Save to customerUser: userId, name, mobileNo, roleId, roleName, city, villageId. RoleId must be 3.

Page: CustomerRegister

Route: /customer-register

File: src/pages/SathiMarket/Customer/CustomerRegister.jsx

Method	Endpoint	Purpose
POST	/Customer/Register	New customer account

POST /Customer/Register

undefined

Request:
{ "name", "mobileNo", "password", "villageId": 0,
"fullAddress", "landmark", "city", "state", "pincode" }

Response (expected):
{ "Success": 1, "Message": "Account created..." }

Page: SathiMarket (Home)

Route: /sathi-market

File: src/pages/SathiMarket/Customer/SathiMarket.jsx

Method	Endpoint	Purpose
GET	/Shops/GetAll	List all shops on marketplace

GET /Shops/GetAll

Public shop listing with search/filter by categoryName.

```
Response (expected):  
Array or { Data: [ { shopID, shopName, categoryName,  
  shopAddress, shopImage, isOpen, ... } ] }
```

Wishlist toggle is local state only — no API.

Page: ShopDetails

Route: /shop/:id

File: src/pages/SathiMarket/Customer/ShopDetails.jsx

Method	Endpoint	Purpose
GET	/Shops/GetById/{id}	Shop header info
GET	/ShopItems/GetByShop/{id}	Products in shop

GET /Shops/GetById/{shopId}

undefined

```
Response (expected):  
{ shopName, categoryName, shopAddress, isOpen, ownerName, ... }
```

GET /ShopItems/GetByShop/{shopId}

undefined

```
Response (expected):  
[ { itemID, itemName, price, itemDescription,  
  mediaList: [ { mediaURL, isPrimary, mediaType } ] } ]
```

ProductDetailsModal opens from this data — no separate API.

Page: ProductDetailsModal

Route: (modal)

File: src/pages/SathiMarket/Customer/ProductDetailsModal.jsx

Displays item from ShopDetails. Add to cart uses CartContext (localStorage sathiCart). No HTTP calls.

No backend API calls — UI-only component.

Page: Cart

Route: /cart

File: src/pages/SathiMarket/Customer/Cart.jsx

Method	Endpoint	Purpose
POST	/Customer/ManageAddress	actionType=3 fetch addresses
POST	/Orders/PlaceOrder	Checkout

POST /Customer/ManageAddress

Cart loads saved addresses (same API as ManageAddresses).

Request:

```
{ "actionType": 3, "userId": 101, "addressId": 0,  
  "fullAddress": "", "landmark": "", "city": "", "state": "", "pincode": "" }
```

Response (expected):

```
[ { "Id", "FullAddress", "City", "Pincode", "Landmark", "State" } ]
```

actionType: 1=Add, 2=Update, 3=Get, 4=Delete

POST /Orders/PlaceOrder

Place order from cart. One shop per order.

Request:

```
{  
  "userId": 101,  
  "shopId": 15,  
  "addressId": 5,  
  "totalAmount": 500,  
  "orderStatus": 0,  
  "isActive": true,  
  "orderItems": [  
    { "itemId": 1, "quantity": 2, "unitPrice": 100, "totalPrice": 200 }  
  ]  
}
```

Response (expected):

```
{ "orderId": 123 } or message containing success
```

Success if orderId/OrderID present. Cart must be single-shop.

Page: ManageAddresses

Route: /manage-addresses

File: src/pages/SathiMarket/Customer/ManageAddresses.jsx

Method	Endpoint	Purpose
POST	/Customer/ManageAddress	CRUD addresses

POST /Customer/ManageAddress

Single endpoint for all address operations via actionTypes.

Request:

Add (1): { actionTypes:1, userId, addressId:0, fullAddress, landmark, city, state, pincode }

Update (2): { actionTypes:2, userId, addressId, fullAddress, ... }

Get (3): { actionTypes:3, userId, addressId:0, empty strings }

Delete (4): { actionTypes:4, userId, addressId, empty strings }

Response (expected):

Get !' array of addresses . Add / Update / Delete !' { Success , Message }

Page: CustomerDashBoard

Route: /customer-dashboard

File: src/pages/SathiMarket/Customer/CustomerDashBoard.jsx

Method	Endpoint	Purpose
GET	/Orders/GetByUser/{userId}?page=1&pageSize=3	Recent orders

GET /Orders/GetByUser/{userId}

Dashboard fetches 3 recent orders.

Request:

Query: page=1, pageSize=3

Response (expected):

{ Data: [...orders], TotalCount?: number }

Requires customerUser in localStorage with userId.

Page: MyOrders

Route: /my-orders

File: src/pages/SathiMarket/Customer/MyOrders.jsx

Method	Endpoint	Purpose
GET	/Orders/GetByUser/{userId}?page&pageSize=5	Order history

GET /Orders/GetByUser/{userId}

undefined

Request:

Query: page (default 1), pageSize (5)

Response (expected):

Order object fields: orderID, orderStatus, orderDate, totalAmount,
orderItems: [{ itemName, quantity, unitPrice, totalPrice }]

orderStatus: 0=Pending, 1=Completed, 2=Cancelled (merchant view). Invoice is client-side PDF.

WishList.jsx — EXCLUDED: wishlist uses localStorage customerWishlist only; no backend API implemented.

6. Merchant Module — APIs by Page

Page: MerchantRegister

Route: /merchant-register

File: src/pages/SathiMarket/Merchant/MerchantRegister.jsx

Method	Endpoint	Purpose
GET	/Auth/get-roles	Roles dropdown
GET	/Categories/GetAll	Category dropdown
POST	/Auth/register	Submit registration

Page: MerchantLogin

Route: /merchant-login

File: src/pages/SathiMarket/Merchant/MerchantLogin.jsx

Method	Endpoint	Purpose
POST	/Auth/Login	Merchant sign-in

Page: MerchantDashBoard

Route: /merchant/dashboard

File: src/pages/SathiMarket/Merchant/MerchantDashBoard.jsx

Method	Endpoint	Purpose
GET	/Orders/GetByShop/{shopId}	Orders + stats
GET	/ShopItems/GetByShop/{shopId}	Active item count

GET /Orders/GetByShop/{shopId}

All orders for merchant shop. Stats: pending(0), completed(1), cancelled(2).

Response (expected):
[{ orderId, userID, totalAmount, orderStatus, orderDate, ... }]

shopId from login Data.ShopId. Requires Bearer token if API protected.

Page: ManageProfile

Route: /merchant/profile

File: src/pages/SathiMarket/Merchant/ManageProfile.jsx

Method	Endpoint	Purpose
GET	/Shops/GetById/{shopId}	Load shop profile
POST	/Shops/UpdateShop	Toggle isOpen / update shop

GET /Shops/GetById/{shopId}

undefined

```
Response (expected):
{ shopName, categoryName, shopAddress, ownerName,
  isOpen, openingTime, closingTime, shopImage, ... }
```

POST /Shops/UpdateShop

Update shop — UI sends full shop object with isOpen toggled.

```
Request:
{ ...shopFields, shopId, isOpen: true|false }
```

```
Response (expected):
Success implied by no error; UI updates local state
```

Page: ManageInventory

Route: /merchant/inventory

File: src/pages/SathiMarket/Merchant/ManageInventory.jsx

Method	Endpoint	Purpose
GET	/ShopItems/GetByShop/{shopId}	List products
POST	/ShopItems/AddItem	Add product (multipart)
DELETE	/ShopItems/DeleteItem/{itemId}	Remove product

POST /ShopItems/AddItem

multipart/form-data — NOT JSON.

```
Request:
FormData fields:
  ShopID (number)
  ItemName, ItemDescription, Price (float)
  IsAvailable: true, IsActive: true
  mediaFiles: (file[]) – one or more images
```

Header: Content-Type: multipart/form-data

DELETE /ShopItems/DeleteItem/{itemId}

Delete product by itemID.

Page: ShopOrders

Route: /merchant/orders

File: src/pages/SathiMarket/Merchant/ShopOrders.jsx

Method	Endpoint	Purpose
GET	/Orders/GetByShop/{shopId}	List orders
POST	/Orders/UpdateStatus	Complete or cancel

POST /Orders/UpdateStatus

undefined

```
Request:  
{ "orderId": 123, "status": 1 }  
// status: 1=Complete, 2=Cancel
```

Pending orders have orderStatus=0. Confirm dialog before update.

7. Mobile App — Implementation Checklist

Step	Customer App	Merchant App
1	POST /Customer/Register	GET roles + categories
2	POST /Customer/Login	POST /Auth/register (roleId=2 + shop)
3	GET /Shops/GetAll	POST /Auth/Login
4	GET shop + items	GET /Shops/GetById, inventory
5	ManageAddress + Cart checkout	GET/POST orders, UpdateStatus

8. Order Status Reference

orderStatus	Meaning	Merchant action
0	Pending	Can Complete (1) or Cancel (2)
1	Completed	—
2	Cancelled	—

9. Local Storage Keys (Web Reference)

Key	User	Content
customerUser	Customer	userId, name, mobileNo, roleId, city, villageId
user + token	Merchant	shopId, RoleId, token from Auth/Login
sathiCart	Customer	Cart items (local until PlaceOrder)
customerWishlist	Customer	Local only — no API