

# Topic: FORTRAN Programming

---

## Objectives

- Basics of FORTRAN programming

# Topic: FORTRAN Programming

---

## Subroutines

- Invoked by *call* statement
- Can be written in the same file (both as a part of the same program or after the end program line) as the main program or in a separate file
- If the subroutine is written a separate file, care need to be taken during compilation. For eg: main.f90 and sub.f90

**gfortran main.f90 sub.f90 OR**

**gfortran -c main.f90**

**gfortran -c sub.f90**

**gfortran main.o sub.o -o main.x**

# Topic: FORTRAN Programming

## Subroutines – Hello World

```
program test
  implicit none

  call hello

end program test

subroutine hello
  implicit none

  write(*,*) "Hello World"

end subroutine hello
```

```
program test
  implicit none

  call hello

contains
  subroutine hello
    implicit none

    write(*,*) "Hello World"

  end subroutine hello
end program test
```

# Topic: FORTRAN Programming

```
program test
  implicit none

  integer :: i
  real    :: s(100), total

! initialize the variable s

  do i = 1, 100

    s(i) = i

  enddo

! main part of the program

  call testsub(s,total)

  write(*,*) ' Sum ', total

end program test
```

```
subroutine testsub(a,total)
  implicit none

  real :: a(*)
  real :: total
  integer :: i

  total=0
  do i = 1, 100

    total = total + a(i)

  enddo

end subroutine testsub
```

Subprogram(s)

# Topic: FORTRAN Programming

```
program test
  implicit none

  integer :: i
  real    :: s(100), total

! initialize the variable s

  do i = 1, 100
    s(i) = i
  enddo

! main part of the program

  total=sum(s)

  write(*,*) ' Sum ', total
end program test
```

Output

Sum 5050.00000

sum is an internal  
function

Introducing internal functions

# Topic: FORTRAN Programming

## Internal functions

- Internal functions

ABS(A)	Returns the absolute value of A. If complex returns $\sqrt{real^2 + imag^2}$
ACOS(X)	Returns the arcosine of X.
AIMAG(Z)	Returns the imaginary part of the complex argument Z.
ASIN(X)	Returns the arcsine of X.
ATAN(X)	Returns the arctan of X.
ATAN2(Y,X)	Returns the arctan of Y/X in the range of $-\pi$ to $\pi$
COS(X)	Returns the cosine of X.
COSH(X)	Returns the hyperbolic cosine of X.
DIM(X,Y)	Returns X-Y if $> 0$ , otherwise returns 0. Both X and Y must be of the same type and kind.
DOT_PRODUCT(Vector_1,Vector_2)	Performs the mathematical dot product of the two rank 1 arrays.
DPROD(X,Y)	Returns the double precision product of X and Y.
EXP(X)	Returns $e^x$ .
FLOOR(A,kind)	Returns the largest integer $\leq A$ .
LOG(X)	Returns the natural logarithm of X

# Topic: FORTRAN Programming

---

## Dynamic memory allocation

- Use allocate statement

```
real, allocatable :: coor(:, :)
```

```
n=10
```

```
m=10
```

```
allocate(coor(n,m))
```

```
deallocate(coor)
```

# Topic: FORTRAN Programming

## Dynamic memory allocation

```
program test
  implicit none

  integer :: i
  real    :: s(100), total

! initialize the variable s

  do i = 1, 100
    s(i) = i
  enddo

! main part of the program

  total=0.0
  do i = 1, 100
    total = total + s(i)
  enddo

  write(*,*) ' Sum ', total

end program test
```

```
program test
  implicit none

  integer :: i,N,total

  real,allocatable :: s(:)

! initialize the variable s

  write(*,*) "Enter the size of the array"
  read(*,*) N

  allocate(s(N))

  do i = 1, N
    s(i) = i
  enddo

! main part of the program

  total=0
  do i = 1, N
    total = total + s(i)
  enddo

  write(*,*) ' Sum ', total

  deallocate(s)

end program test
```



# Topic: FORTRAN Programming

```
do atom = 1, natoms  
    write(101,"(a5,2x,3F15.7)") atm_name(atom), atm_coor(atom,:)   
enddo
```

OR

format  
statement

```
do atom = 1, natoms  
    write(101,100) atm_name(atom), atm_coor(atom,:)   
enddo  
  
100 format(a5,2x,3F15.7)
```

Descriptors: separated by commas and in parentheses.

## Syntax

- Integer: iw
- Real: fw.d, ew.d
- Character: aw
- Space: x

## Examples:

- 10 FORMAT(1X, A5, 2X, I3, 4X, A6, 2X, F6.2)
- 1001 format (i5, f5.2, e12.3)
- 2001 format ( 3(i5,e15.3))

# Topic: FORTRAN Programming

## Integer format descriptor

```
program test
  implicit none

  integer :: ii,ij

  ii=12345; ij=12345
  write(*,"(i4,i4)") ii,ij
  write(*,"(i6,i6)") ii,ij
  write(*,"(i6,2x,i6)") ii,ij
  write(*,"(i6,2x,i6)") ii,ij
  write(*,"(i10,2x,i10)") ii,ij
  write(*,"(2(i10,2x))") ii,ij

end program test
```

### Output

\*\*\*\*\*

12345 12345

12345    12345

12345    12345

      12345            12345

      12345            12345

# Topic: FORTRAN Programming

## Real format descriptor

```
program test
  implicit none

  real(kind=8) :: ri, rj

  ri=12345; rj=12345.12345d0

  write(*,"(f10.3,f10.3)") ri,rj
  write(*,"(2(f10.3,2x))") ri,rj
  write(*,"(f10.7,2x,f14.7)") ri,rj
  write(*,*)
  write(*,"(e10.3,e10.3)") ri,rj
  write(*,"(e12.6,2x,e12.6)") ri,rj

end program test
```

### Output

```
12345.000 12345.123
12345.000    12345.123
*****    12345.1234500

 0.123E+05 0.123E+05
0.123450E+05 0.123451E+05
```

# Topic: FORTRAN Programming

## character format descriptor

```
program test
  implicit none

  character(len=8) :: ca

  ca='hpc-cour'

  write(*,"(a8,a8)") ca,ca
  write(*,"(2x,a8,2x,a8)") ca,ca
  write(*,"(2(a5))") ca,ca
  write(*,"(2(a,2x))") ca,ca

end program test
```

### Output

```
hpc-courhpc-cour
  hpc-cour  hpc-cour
hpc-chpc-c
hpc-cour  hpc-cour
```

# Topic: FORTRAN Programming

---

## hands-on

Write a program to read pdb file (file is available in the "general" channel) and write the output using the format statements (the output should look the same as input file)

Write a program to calculate the roots of a quadratic function. Use subroutine in the program. Read the value of three input variables from the terminal.

# Topic: FORTRAN Programming

---

## Tips

- Don't worry about declaring variables initially. Identify the main part of the program and start writing
- All real numbers should be in double precision (add d0 in the end), eg. 10.0d0
- Always use indentation, leave black spaces to improve readability
- Always use 'parameter' in case when assigning the values to integer datatype
- Use internal functions to convert datatypes, eg. real(x)
- Read compiler error messages more carefully
- For debugging, use 'write' statement at several places in the program and check for the output
-

# Topic: FORTRAN Programming

---

## FORTRAN – Reading material

- Please go through this FORTRAN program for a quick overview,
  - <https://learnxinyminutes.com/docs/fortran95/>
- Please go through this document for quick overview of FORTRAN
  - <https://www.ideo.columbia.edu/~mspieg/mmm/Fortran.pdf>
- For a video on FORTRAN programming, look at  
[https://www.youtube.com/watch?v=\\_\\_2UgFNYgf8](https://www.youtube.com/watch?v=__2UgFNYgf8)
- Book: Computer Programming in Fortran 90 and 95, V. Rajaraman