

Cryptohack General

-

Challenge Room Walkthrough

Paweł Murdzek

Warsaw University of Technology

November 4, 2025

Contents

Introduction	2
1. Modular Math	2
1.1. Quadratic Residues	2
1.2. Legendre Symbol	2
1.3. Modular Square Root	3
1.4. Chinese Remainder Theorem	4
2. Brainteasers Part 1	5
2.1. Successive Powers	5
2.2. Adrien's Signs	6
2.3. Modular Binomials	7
2.4. Broken RSA	8
2.5. No Way Back Home	9
3. Brainteasers Part 2	10
3.1. Ellipse Curve Cryptography	10
3.2. Roll your Own	10
3.3. Unencryptable	11
3.4. Cofactor Cofantasy	12
3.5. Real Eisenstein	12
4. Primes	13
4.1. Prime and Prejudice	13

Introduction

This document provides a walkthrough for the "Mathematics" challenge category on the Cryptohack platform.

1. Modular Math

1.1. Quadratic Residues

— Code:

```
# Set the given values
p = 29
numbers_to_check = [14, 6, 11]

# memory
found_residue = None
root1 = None
root2 = None

# Loop through all possible roots 'a' from 1 to p-1
for a in range(1, p):
    # Calculate the square of 'a' modulo p
    square = (a * a) % p

    # Check if this square is one of the numbers we're looking for
    if square in numbers_to_check:
        found_residue = square
        root1 = a
        root2 = p - a
        break

# Print the results
if found_residue is not None:
    print(f"p = {p}")
    print(f"List of numbers = {numbers_to_check}")
    print("-----")
    print(f"Found Quadratic Residue: {found_residue}")
    print(f"The square roots are: {root1} and {root2}")

    # Calculate the smaller root for the flag
    flag = min(root1, root2)
    print(f"The smaller square root (the flag) is: {flag}")
else:
    print("Could not find a quadratic residue in the list.")
```

— Flag: 8

- **Explanation:** The code implements a "brute-force" method to find a **quadratic residue**. A quadratic residue x modulo p is a number for which there exists a number a such that $a^2 \equiv x \pmod{p}$. The loop `for a in range(1, p)` iterates through all possible values of a (from 1 to $p - 1$). Inside the loop, the square is calculated: `square = (a * a) % p`. The code then checks if this calculated square is on the list of candidates (`numbers_to_check`). If the square a^2 is equal to one of the target numbers, it means that number is a quadratic residue. The code then saves both square roots: a and $p - a$. This is the correct second root because $(p - a)^2 \equiv (-a)^2 \equiv a^2 \pmod{p}$. The flag is the smaller of these two roots.

1.2. Legendre Symbol

— Code:

```
import ast

def solve_qr_large(p, candidates):
    """Finds quadratic residue and calculates its largest square root modulo p."""
    if p % 4 != 3:
        print(f"Error: p={p} does not satisfy p % 4 == 3")
        return

    print(f"Prime p = {p} (p % 4 = {p % 4})\n")

    # Find quadratic residue using Euler's Criterion
    exponent_test = (p - 1) // 2
    found_residue = None

    for a in candidates:
        result = pow(a, exponent_test, p)
        if result == 1:
            print(f"[+] Found QR: {a}")
            found_residue = a
            break
        print(f"[-] Not QR: {a}")

    if not found_residue:
        print("No quadratic residue found")
        return

    # Calculate square roots:  $a^{\frac{p+1}{4}} \pmod{p}$ 
    root1 = pow(found_residue, (p + 1) // 4, p)
    root2 = p - root1
    flag = max(root1, root2)

    print(f"\nRoots: {root1}, {root2}")
    print(f"Flag (larger root): {flag}")
    return flag

def parse_input_file(filename="output.txt"):
```

```

"""Reads and parses p and list of integers from file."""
try:
    with open(filename, 'r') as f:
        lines = [line.strip() for line in f if line.strip()]

    if len(lines) < 2:
        print(f"Error: File must contain at least 2 lines")
        return None, None

    p_line = next((line for line in lines if line.startswith(('p =', 'p='))), None)
    ints_line = next((line for line in lines if line.startswith(('ints =', 'ints='))), None)

    if not p_line or not ints_line:
        print("Error: Could not find 'p =' or 'ints =' in file")
        return None, None

    p = int(p_line.split('=')[1].strip())
    candidates = ast.literal_eval(ints_line.split('=')[1].strip())

    print(f"Successfully parsed '{filename}'")
    return p, candidates

except FileNotFoundError:
    print(f"Error: File '{filename}' not found")
    return None, None
except Exception as e:
    print(f"Error parsing file: {e}")
    return None, None

if __name__ == "__main__":
    p, candidates = parse_input_file("output.txt")
    if p and candidates:
        solve_qr_large(p, candidates)

```

— **Flag:** 93291799125366706806545638475797430512104976066103610269938025709952247020061090804870186195285

— **Explanation:** This code uses **Euler's Criterion** to quickly check if a number a is a quadratic residue modulo p . Instead of calculating all squares $x^2 \pmod{p}$, it calculates the **Legendre Symbol** $\left(\frac{a}{p}\right)$, which is defined as:

$$\left(\frac{a}{p}\right) \equiv a^{(p-1)/2} \pmod{p}$$

In the code, this corresponds to `exponent_test = (p - 1) // 2` and `result = pow(a, exponent_test, p)`.

— If `result == 1`, a is a quadratic residue.

— If `result == p - 1` (which is -1), a is a quadratic non-residue.

When a quadratic residue a is found, the code must calculate its square roots. It uses a special property of prime numbers p that satisfy the condition $p \equiv 3 \pmod{4}$. For such primes, there is a simple formula to calculate the square roots of a :

$$x \equiv \pm a^{(p+1)/4} \pmod{p}$$

In the code, this corresponds to `root1 = pow(found_residue, (p + 1) // 4, p)`, and the second root is `root2 = p - root1`. The flag is the larger of the calculated roots.

1.3. Modular Square Root

— **Code:**

```

import re

def tonelli_shanks(a, p):
    """Tonelli-Shanks algorithm for finding modular square root when p % 4 == 1."""
    if pow(a, (p - 1) // 2, p) != 1:
        return None

    # Factor p - 1 as Q * 2^S
    Q, S = p - 1, 0
    while Q % 2 == 0:
        Q //= 2
        S += 1

    # Find quadratic non-residue
    z = 2
    while pow(z, (p - 1) // 2, p) == 1:
        z += 1

    # Initialize
    c = pow(z, Q, p)
    R = pow(a, (Q + 1) // 2, p)
    t = pow(a, Q, p)
    M = S

    while t != 1:
        # Find smallest i where t^(2^i) == 1
        i, temp_t = 0, t
        while temp_t != 1:
            temp_t = pow(temp_t, 2, p)
            i += 1

        # Update values
        b = pow(c, 1 << (M - i - 1), p)
        R = (R * b) % p
        t = (t * b * b) % p
        c = (b * b) % p
        M = i

    return R

```

```

def find_modular_sqrt(a, p):
    """Find modular square root. Returns the smaller of the two roots."""
    a = a % p
    if a == 0:
        return 0

    if p % 4 == 3:
        r = pow(a, (p + 1) // 4, p)
    elif p % 4 == 1:
        r = tonelli_shanks(a, p)
    else:
        return None

    return min(r, p - r) if r else None

def main():
    with open('output.txt', 'r') as f:
        content = f.read()

    # Parse a and p from file
    a = int(re.search(r'a\s*=\s*(\d+)', content).group(1))
    p = int(re.search(r'p\s*=\s*(\d+)', content).group(1))

    print(f"a = {str(a)[:60]}...")
    print(f"p = {str(p)[:60]}...")
    print(f"p % 4 = {p % 4} ({'Tonelli-Shanks' if p % 4 == 1 else 'Simple formula'})\n")

    # Calculate modular square root
    result = find_modular_sqrt(a, p)

    if result is None:
        print("No square root exists")
    else:
        print(f"The smaller of the two roots is: {result}")
        print(f"Verification: {result}^2 % p == a ? {pow(result, 2, p) == a % p}")

if __name__ == "__main__":
    main()

```

— **Flag:** 23623393076830486383277732985804892989321375055205003883382710520537347478623517796473141768179

— **Explanation:** This code calculates the modular square root modulo p for any prime number p .

1. **Case $p \equiv 3 \pmod{4}$:** This is the simple case, the same as in the previous task. The roots are calculated directly from the formula $x \equiv \pm a^{(p+1)/4} \pmod{p}$.
2. **Case $p \equiv 1 \pmod{4}$:** In this situation, the simple formula does not work. The code must implement the **Tonelli-Shanks algorithm**, which is a general method for finding square roots modulo a prime number.

- First, the algorithm checks if a is a quadratic residue at all, using Euler's Criterion ($\text{pow}(a, (p - 1) // 2, p) \neq 1$).
- Then, it factors $p - 1$ into $Q \cdot 2^S$, where Q is odd.
- It finds z , any **quadratic non-residue** modulo p .
- It initializes the variables c, R, t, M .
- In the main loop **while** $t \neq 1$, the algorithm iteratively updates these variables, "correcting" the root candidate R , until t becomes 1. The final value of R is the desired root.

Finally, the code returns the smaller of the two roots: R and $p - R$.

1.4. Chinese Remainder Theorem

— **Code:**

```

from functools import reduce
from operator import mul

def solve_crt(remainders, moduli):
    """Solves system of congruences using Chinese Remainder Theorem."""
    N = reduce(mul, moduli)
    return sum(a * (N_i := N // n) * pow(N_i, -1, n) for a, n in zip(remainders, moduli)) % N

remainders = [2, 3, 5]
moduli = [5, 11, 17]

result = solve_crt(remainders, moduli)

print(f"System: z {remainders[0]} (mod {moduli[0]}), z {remainders[1]} (mod {moduli[1]}), z {remainders[2]} (mod {moduli[2]})")
print(f"Solution: {result}\n")
print(f"Verification: {result} % {moduli[0]} = {result % moduli[0]}, {result} % {moduli[1]} = {result % moduli[1]}, {result} % {moduli[2]} = {result % moduli[2]}")

```

— **Flag:** 872

— **Explanation:** The code is a direct, constructive implementation of the **Chinese Remainder Theorem (CRT)**. The goal is to find a single number z that satisfies a system of congruences (gives specific remainders a_i when divided by different, pairwise coprime moduli n_i).

$$\begin{cases} z \equiv 2 \pmod{5} \\ z \equiv 3 \pmod{11} \\ z \equiv 5 \pmod{17} \end{cases}$$

The formula used in the code is the standard solution to CRT:

$$z \equiv \sum_i a_i \cdot N_i \cdot M_i \pmod{N}$$

Where:

- **a** (a_i) is the required remainder (e.g., 2, 3, 5).
 - **n** (n_i) is the modulus (e.g., 5, 11, 17).
 - **N** is the product of all moduli: $N = \prod n_i = 5 \cdot 11 \cdot 17$.
 - **N_i** (in code `N_i := N // n`) is N/n_i (e.g., $N_1 = N/5 = 11 \cdot 17$).
 - **pow(N_i, -1, n)** is M_i , which is the **modular inverse** of N_i modulo n_i (e.g., $M_1 = (11 \cdot 17)^{-1} \pmod{5}$).
- Each term in the sum $a_i \cdot N_i \cdot M_i$ is constructed such that it is equal to $a_i \pmod{n_i}$ and simultaneously 0 $\pmod{n_j}$ for all $j \neq i$. Summing these terms gives the final solution z , which satisfies all conditions at the same time.

2. Brainteasers Part 1

2.1. Successive Powers

- **Pen-and-Paper Solution:** Let the given sequence be $S = \{s_1, s_2, s_3, \dots\}$. The problem states that these are successive powers of an integer z modulo a prime p . This gives the relation:

$$s_{i+1} \equiv s_i \cdot z \pmod{p}$$

The sequence is: $\{588, 665, 216, 113, 642, 4, 836, 114, \dots\}$

Finding z

The "on paper" hint suggests looking for a simple relationship. Let's check the sixth and seventh terms:

- $s_6 = 4$
- $s_7 = 836$

Using our relation:

$$s_7 \equiv s_6 \cdot z \pmod{p}$$

$$836 \equiv 4 \cdot z \pmod{p}$$

This congruence means that $836 = 4z + k \cdot p$ for some integer k . The simplest case, and the one suggested by the hint, is to assume $k = 0$.

$$836 = 4z$$

$$z = \frac{836}{4}$$

$$\mathbf{z = 209}$$

Finding p

Now that we have $z = 209$, we can find p . The relation $s_{i+1} \equiv s_i \cdot z \pmod{p}$ can be rewritten as:

$$s_i \cdot z - s_{i+1} \equiv 0 \pmod{p}$$

This means that p must be a divisor of the integer $s_i \cdot z - s_{i+1}$ for every i . Therefore, p must be a common divisor of all such expressions. We can find p by calculating the Greatest Common Divisor (GCD) of a few of these expressions.

Expression 1 (using $s_1 = 588$ and $s_2 = 665$)

$$X_1 = s_1 \cdot z - s_2$$

$$X_1 = 588 \cdot 209 - 665$$

$$X_1 = 122892 - 665 = 122227$$

Expression 2 (using $s_4 = 113$ and $s_5 = 642$)

$$X_2 = s_4 \cdot z - s_5$$

$$X_2 = 113 \cdot 209 - 642$$

$$X_2 = 23617 - 642 = 22975$$

Calculating GCD

Now we find $p = \text{GCD}(122227, 22975)$ using the Euclidean Algorithm.

$$122227 = 5 \cdot 22975 + 7352$$

$$22975 = 3 \cdot 7352 + 919$$

$$7352 = 8 \cdot 919 + 0$$

The GCD is 919. This is a three-digit prime number, which matches the problem description.

Conclusion

The solution is:

$$\mathbf{p = 919}$$

$$\mathbf{z = 209}$$

— **Flag:** crypto{919,209}

— **Explanation:** (Explanation is already included in the problem text)

2.2. Adrien's Signs

— **Code:**

```
from random import randint

a = 288260533169915
p = 1007621497416261

FLAG = b'crypto{????????????????}'

def encrypt_flag(flag):
    ciphertext = []
    plaintext = ''.join([bin(i)[2:].zfill(8) for i in flag])
    for b in plaintext:
        e = randint(1, p)
        n = pow(a, e, p)
        if b == '1':
            ciphertext.append(n)
        else:
            n = -n % p
            ciphertext.append(n)
    return ciphertext

# Legendre symbol function
def legendre(a, p):
    """Compute the Legendre symbol (a/p)"""
    return pow(a, (p - 1) // 2, p)

def decrypt_flag(ciphertext, p):
    """Decrypt the ciphertext using Legendre symbol"""
    binary_string = ''
    for n in ciphertext:
        # Check if n is a quadratic residue using Legendre symbol
        leg = legendre(n, p)
        if leg == 1:
            # Quadratic residue -> bit is '1'
            binary_string += '1'
        else:
            # Not a quadratic residue -> bit is '0'
            binary_string += '0'

    # Convert binary string to bytes
    flag = ''
    for i in range(0, len(binary_string), 8):
        byte = binary_string[i:i+8]
        flag += chr(int(byte, 2))

    return flag

# Read ciphertext from output.txt
with open('output.txt', 'r') as f:
    content = f.read().strip()
    ciphertext = eval(content)

decrypted_flag = decrypt_flag(ciphertext, p)
print(f"Decrypted flag: {decrypted_flag}")
```

— **Flag:** crypto{p4tterns_1n_re5idu3s}

— **Explanation:** Encryption and decryption are based entirely on the properties of the **Legendre Symbol** $\left(\frac{a}{p}\right)$.

1. **Configuration of p :** The challenge uses a prime p such that $p \equiv 3 \pmod{4}$. This has a key consequence: $(p-1)/2$ is an odd number. From Euler's Criterion, it follows that $\left(\frac{-1}{p}\right) \equiv (-1)^{(p-1)/2} \equiv -1 \pmod{p}$. This means that -1 is a **quadratic non-residue** modulo p .
2. **Configuration of a :** The value a must be a **quadratic residue** (its Legendre symbol $\left(\frac{a}{p}\right) = 1$). Consequently, $n \equiv a^e \pmod{p}$ is *always* a quadratic residue, regardless of e , because $\left(\frac{n}{p}\right) = \left(\frac{a^e}{p}\right) = \left(\frac{a}{p}\right)^e = 1^e = 1$.
3. **Encrypting bit '1'** (per `encrypt_flag`): Ciphertext $c = n$. We calculate the Legendre symbol of c : $\left(\frac{c}{p}\right) = \left(\frac{n}{p}\right) = 1$.
4. **Encrypting bit '0'** (per `encrypt_flag`): Ciphertext $c = -n \pmod{p}$. We calculate the Legendre symbol of c : $\left(\frac{c}{p}\right) = \left(\frac{-n}{p}\right) = \left(\frac{-1}{p}\right) \left(\frac{n}{p}\right) = (-1) \cdot (1) = -1$.
5. **Decryption** (`decrypt_flag`): The code reverses this process. For each number n (which is c) in the ciphertext, it calculates its Legendre symbol `leg = legendre(n, p)` (using Euler's Criterion: `pow(a, (p - 1) // 2, p)`).
 - If `leg == 1`, it means it's a quadratic residue, and thus bit '1'.
 - If `leg != 1` (meaning it's equal to $p-1$, which corresponds to -1), it means it's a quadratic non-residue, and thus bit '0'.

2.3. Modular Binomials

— **Code:**

```
from math import gcd
"""
c1 = (2p + 3q) ^ e1 % N
c2 = (5p + 7q) ^ e2 % N

-----
N = pq => Binomial: mid elements % N == 0
-> c1 = (2p) ^ e1 + (3q) ^ e1 % N
    c2 = (5p) ^ e2 + (7q) ^ e2 % N

-----
raise c1 to e2 and c2 to e1: to create similar exponent
c1 ^ e2 = (2p) ^ (e1e2) + (3q) ^ (e1e2) % N (1)
c2 ^ e1 = (5p) ^ (e1e2) + (7q) ^ (e1e2) % N (2)

-----
Let (1) * 5 ^ (e1e2) - (2) * 2 ^ (e1e2) to get rid of p:
-> t = 5 ^ (e1e2) * c1 ^ e2 - 2 ^ (e1e2) * c2 ^ e1 = ( 15 ^ (e1e2) - 14 ^ (e1e2)) * q

-----
=> t % q == 0 and we have N % q == 0:
=> q = gcd(t, N)
p = N / q
"""

N = 1490562257842714057932724129575002825405393502650869767115942606408600343380327866258982402447992564988466588305174271674657844352454543958847568190372446723549627752274442789184236490768272313
e1 = 12886657667389660800780796462970504910193928992888518978200029826975978624718627799215564700096007849924866627154987365059524315097631111242449314835868137
e2 = 12110586673991788415780355139635579057920926864887110308343229256046868242179445444897790171351302575188607117081580121488253540215781625598048021161675697
c1 = 140107294187032282343524658830412706111137358983875343329547849576340905613673415561215693467398834488262954120498590965043381920529893987783731414508240352805588475207921915073984999292139350
c2 = 1438699713863797886074827898694509864850714286458411112420258036510379316581166698766485121023000937526739895797949406688029641801334500697765474230344103000849081623930639449216851627832885151

x1 = pow(5, e1 + e2, N) + pow(c1, e2, N)
x2 = pow(2, e1 + e2, N) + pow(c2, e1, N)

# t = z1 - z2
q = gcd(x1 - x2, N)

p = N // q
print("crypto{" + str(p) + "," + str(q) + "}")
```

— **Flag:** `crypto{1122740001692584863902620644419912006085563761274089527015149626443409218991960915575193}`

— **Explanation:** This code uses the **Binomial Expansion** (Newton's Binomial Theorem) in the ring modulo $N = pq$.

1. **Key observation:** For $N = pq$, the expression $(ap + bq)^e \pmod{N}$ simplifies significantly. According to the binomial theorem:

$$(ap + bq)^e = \sum_{k=0}^e \binom{e}{k} (ap)^k (bq)^{e-k}$$

2. All terms in this sum, except for the first ($k = e$) and the last ($k = 0$), contain both a factor of p (from $(ap)^k$, where $k \geq 1$) and q (from $(bq)^{e-k}$, where $e - k \geq 1$). This means that all "middle" terms are divisible by $pq = N$, so they vanish (are equal to 0 \pmod{N}).
3. Only the outermost terms remain: $(ap)^e + (bq)^e$.
4. Hence we have the simplified congruences: $c_1 \equiv (2p)^{e_1} + (3q)^{e_1} \pmod{N}$ $c_2 \equiv (5p)^{e_2} + (7q)^{e_2} \pmod{N}$

5. **Elimination of p :** To isolate q , the code brings both expressions to a common exponent e_1e_2 by exponentiating:

$$\begin{aligned} &— c_1^{e_2} \equiv (2p)^{e_1e_2} + (3q)^{e_1e_2} \pmod{N} \\ &— c_2^{e_1} \equiv (5p)^{e_1e_2} + (7q)^{e_1e_2} \pmod{N} \end{aligned}$$

6. It then creates a linear combination that will remove the p term. It multiplies the first equation by $5^{e_1e_2}$ and the second by $2^{e_1e_2}$ and subtracts them (in the code $t = x1 - x2$):

$$\begin{aligned} t &= 5^{e_1e_2}c_1^{e_2} - 2^{e_1e_2}c_2^{e_1} \\ t &\equiv [5^{e_1e_2}(2p)^{e_1e_2} + 5^{e_1e_2}(3q)^{e_1e_2}] - [2^{e_1e_2}(5p)^{e_1e_2} + 2^{e_1e_2}(7q)^{e_1e_2}] \pmod{N} \\ t &\equiv [(10p)^{e_1e_2} + (15q)^{e_1e_2}] - [(10p)^{e_1e_2} + (14q)^{e_1e_2}] \pmod{N} \end{aligned}$$

7. The terms containing p (i.e., $(10p)^{e_1e_2}$) cancel out:

$$t \equiv (15q)^{e_1e_2} - (14q)^{e_1e_2} \equiv q^{e_1e_2}(15^{e_1e_2} - 14^{e_1e_2}) \pmod{N}$$

8. This equation shows that t is a multiple of q . Since N is also a multiple of q , q must be a common divisor of t and N .
9. By calculating the **Greatest Common Divisor** $\text{GCD}(t, N)$ (in the code $q = \text{gcd}(x1 - x2, N)$), we recover the factor q . With q , we calculate $p = N/q$.

2.4. Broken RSA

— Code:

```
# Import the long_to_bytes function from the Crypto.Util.number module
from Crypto.Util.number import long_to_bytes

# p is a large prime number, which serves as the modulus in the RSA-like scheme
p = 27772857409875257529415990911214211975844307184430241451899407838750503024323367895540981606586709985980003435082116995888017731426634845808624796292507989171497629109450825818587383112280639037
# c is the ciphertext, which is the result of encrypting the message m (c = m^e mod p)
c = 113031747618944311467356975694891347472349751441621721624016745672730348313919369163972340683461154591346024439636040636793792859193022257190501935590179240191429612072131629779948379821039610415
# e is the public exponent
e = 16

# This function calculates the modular square root of a number 'a' modulo a prime 'p'.
# It implements the Tonelli-Shanks algorithm.
def modular_sqrt(a, p):
    # First, check if a has a square root modulo p using the Legendre symbol.
    # If legendre_symbol(a, p) is not 1, 'a' is a quadratic non-residue and has no square root.
    if legendre_symbol(a, p) != 1:
        return 0
    elif a == 0:
        return 0
    elif p == 2:
        return 0
    # A simpler case for primes p congruent to 3 modulo 4.
    elif p % 4 == 3:
        return pow(a, (p + 1) // 4, p)

    # Tonelli-Shanks algorithm for other primes.
    # 1. Decompose p-1 into s * 2^e where s is odd.
    s = p - 1
    e_s = 0
    while s % 2 == 0:
        s //= 2
        e_s += 1

    # 2. Find a quadratic non-residue 'n' modulo p.
    n = 2
    while legendre_symbol(n, p) != -1:
        n += 1

    # 3. Initialize the variables for the main loop.
    x = pow(a, (s + 1) // 2, p)
    b = pow(a, s, p)
    g = pow(n, s, p)
    r = e_s

    # 4. Main loop of the algorithm to find the square root.
    while True:
        t = b
        m = 0
        for m in range(r):
            if t == 1:
                break
            t = pow(t, 2, p)

        if m == 0:
            return x

        gs = pow(g, 2 ** (r - m - 1), p)
        g = (gs * gs) % p
        x = (x * gs) % p
        b = (b * g) % p
        r = m

def legendre_symbol(a, p):
    ls = pow(a, (p - 1) // 2, p)
    return -1 if ls == p - 1 else ls

for i in range(e):
    f = c
    chk = i
```



```

for j in range(4):
    f = modular_sqrt(f, p)
    if f == 0:
        break
    if chk%2 == 1:
        f = p - f
    chk //= 2
if f > 0:
    try:
        print(long_to_bytes(f))
    except Exception:
        pass # Ignore conversion errors for non-flag candidates

```

— **Flag:** `crypto{m0dul4r_squ4r3_r00t}`

— **Explanation:** The encryption is $c \equiv m^{16} \pmod{p}$. To recover m , we must calculate the **16th root** of c modulo p .

1. **Problem:** We cannot use the standard RSA mechanism (calculating the private key $d \equiv e^{-1} \pmod{\phi(p)}$), because $e = 16$ is not coprime to $\phi(p) = p - 1$ (both are even). $\text{GCD}(16, p - 1) \neq 1$.
2. **Solution:** We use the fact that $16 = 2^4$. Calculating the 16th root is equivalent to **calculating the square root four times**:

$$m \equiv c^{1/16} \equiv \left(\left(\left(c^{1/2} \right)^{1/2} \right)^{1/2} \right)^{1/2} \pmod{p}$$

3. **Ambiguity:** Each square root operation $x = \sqrt{y} \pmod{p}$ (performed by the `modular_sqrt` function using the Tonelli-Shanks algorithm) has two solutions: r and $p - r$ (i.e., $\pm r$).
4. After four such operations, we get $2^4 = 16$ possible candidates for the original message m .
5. **Implementation:** The code systematically checks all 16 possibilities.
 - The loop for `i in range(e)` (where `e=16`) iterates through numbers from 0 to 15.
 - The loop for `j in range(4)` performs four successive square root calculations.
 - The variable `i` (copied to `chk`) acts as a binary counter (from 0000 to 1111). Its bits (checked by `chk%2 == 1`) decide whether to choose the "positive" root f or the "negative" root $p - f$ at each step.
6. In this way, the code tests all 16 possible combinations of \pm signs, until it finds the one that, when converted to bytes (`long_to_bytes`), yields a readable flag.

2.5. No Way Back Home

— **Code:**

```

from Crypto.Cipher import AES
from Crypto.Util.Padding import unpad
from Crypto.Util.number import inverse, long_to_bytes
from hashlib import sha256

p, q = (10699940648196411028170713430726559470427113689721202803392638457920771439452897032229838317321639599506283870585924807089941510579727013041135771337631951, 119566763878365121514807449798691)
vka = 124641741967121300068241280971408306625050636261192655845274494695382484894973990899018981438824398885984003880665335336872849819983045790478166909381968949910717906136475842568208640203811766
vkab = 11477824518409167756134046724609868204771151114464578705248434143568974794737396272125524954133119854098295237009196035026166673233119770563450591892579320506321057613654498533587220650488
vkb = 65688978401277131473823458327986456671102371680113356406304400658392310250365927310489958482763796192142867733518062042165471200051231000803669302278594531742806625723640933967704113303831708
c_hex = 'fe29e5ff72f28160027959474fc462e2a9e0b2d84b1508f7bd0e270bc98fac942e1402aa12db6e6a36fb380e7b53323'
c = bytes.fromhex(c_hex)

# Calculate modulus n
n = p * q

# --- Divide by p to work modulo q (as v = p * x) ---
# Check if the division is exact (i.e., vka, vkab, vkb are multiples of p)
if vka % p != 0 or vkab % p != 0 or vkb % p != 0:
    print("Error: Intermediate values are not multiples of p.")
    exit()

# aka = (vka / p) = (x * k_A) mod q
xka = (vka // p)
# xkab = (vkab / p) = (x * k_A * k_B) mod q
xkab = (vkab // p)
# xkb = (vkb / p) = (x * k_B) mod q
xkb = (vkb // p)

# --- Recover private key k_A modulo q ---
# k_A = xkab * inverse(xkb, q) mod q
# xkab / xkb = (x * k_A * k_B) / (x * k_B) = k_A mod q
k_A = (xkab * inverse(xkb, q)) % q

# --- Recover secret value x modulo q ---
# x = xka * inverse(k_A, q) mod q
# xka / k_A = (x * k_A) / k_A = x mod q
x = (xka * inverse(k_A, q)) % q

# --- Calculate original secret v mod n ---
# v = x * p % mod n
v = (p * x) % n

# --- Derive the AES key and decrypt ---
# The key is sha256(v)
key = sha256(long_to_bytes(v)).digest()

# The expected key from out.txt for verification
# expected_key_hex = '6bd39a9a6846f1acf573e58304cd9eac29722311a0ef06392c8f3c4779bc664d'
# print(f"Recovered Key: {key.hex()}")
# print(f"Expected Key: {expected_key_hex}")

# Decrypt the ciphertext c with AES-ECB

```

```

cipher = AES.new(key, AES.MODE_ECB)
decrypted_padded = cipher.decrypt(c)
flag = unpad(decrypted_padded, 16)

print(f"\nRecovered FLAG: {flag.decode()}")

```

— **Flag:** `crypto{1nv3rt1bl3_k3y_3xch4ng3_pr0t0c0l}`

— **Explanation:**

I. Exploiting the Structure of v

Since v is a multiple of p , we can divide all intermediate values by p and move the calculations to the modular field \mathbb{Z}_q , simplifying the relations:

$$\begin{cases} xka &= vka/p \equiv (x \cdot k_A) \pmod{q} \\ xkabb &= vkabb/p \equiv (x \cdot k_A \cdot k_B) \pmod{q} \\ xkb &= vkb/p \equiv (x \cdot k_B) \pmod{q} \end{cases}$$

II. Recovering the Secret Key k_A

Alice's secret key k_A , coprime to n , can be recovered by dividing $xkabb$ by xkb in the modular sense:

$$k_A \equiv xkabb \cdot xkb^{-1} \pmod{q}$$

Where xkb^{-1} is the modular inverse of xkb modulo q .

III. Recovering the Secret Factor x

After recovering k_A , the value x (a component of v) is calculated from the relation xka :

$$x \equiv xka \cdot k_A^{-1} \pmod{q}$$

IV. Final Calculation of v and Decryption

1. **Recovering v :** The full value of v is calculated:

$$v = (p \cdot x) \pmod{n}$$

2. **Deriving the AES Key:** The symmetric key key is the SHA-256 hash of v converted to bytes:

$$\text{key} = \text{SHA-256}(\text{long_to_bytes}(v))$$

3. **Decryption:** The ciphertext c is decrypted using AES-ECB with the key key and the padding is removed.

As a result of the calculations, the decrypted flag is: `crypto{1nv3rt1bl3_k3y_3xch4ng3_pr0t0c0l}`

3. Brainteasers Part 2

3.1. Ellipse Curve Cryptography

— **Code:**

— **Flag:**

— **Explanation:**

3.2. Roll your Own

— **Code:**

```

from pwn import *
import json

def solve():
    # Connect to the challenge server
    conn = remote('socket.cryptohack.org', 13403)

    # Receive the prime q
    conn.recvuntil(b'Prime generated: ')
    q_hex = conn.recvline().strip().decode().strip(' ')
    q = int(q_hex, 16)
    log.info(f'Received q: {q}')

    # Choose n and g to make the DLP easy
    # We choose n = q^2 and g = q + 1.
    # This satisfies the server's condition pow(g, q, n) == 1 because:
    # (q+1)^q mod q^2 = 1 + q*q + ... = 1 (mod q^2) by binomial expansion.
    n = q * q

```

```

g = q + 1

log.info(f"Using n = q^2: {n}")
log.info(f"Using g = q + 1: {g}")

# Send g and n to the server
conn.recvuntil(b'Send integers (g,n) such that pow(g,q,n) = 1: ')
payload = json.dumps({'g': hex(g), "n": hex(n)})
conn.sendline(payload.encode())
log.info(f"Sent g and n")

# Receive the public key h
try:
    conn.recvuntil(b'Generated my public key: ')
    h_hex = conn.recvline().strip().decode().strip(' ')
    h = int(h_hex, 16)
    log.info(f"Received h: {h}")
except EOFError:
    log.error("Server closed connection. Parameters were likely rejected.")
    conn.close()
    return

# Solve for x
# The server computed h = pow(g, x, n) = pow(q+1, x, q^2).
# By binomial expansion, (q+1)^x = 1 + x*q (mod q^2).
# So, h = 1 + x*q (mod q^2).
# This means h - 1 = x*q.
# We can find x by x = (h - 1) / q.
x = (h - 1) // q
log.info(f"Found x: {x}")

# Send x to the server
conn.recvuntil(b'What is my private key: ')
payload = json.dumps({'x': hex(x)})
conn.sendline(payload.encode())

# Receive the flag
response = conn.recvall()
log.success(f"Received response: {response.decode()}")
conn.close()

if __name__ == "__main__":
    solve()

```

— **Flag:** crypto{Grabbing_Flags_with_Pascal_Paillier}

— **Explanation:** (Explanation is already included in the document. This is an attack on the discrete logarithm problem through a **malicious choice of parameters**.

1. **Parameter Choice:** We choose $n = q^2$ and $g = q + 1$.
2. **Binomial Expansion (Newton's):** This technique is used twice.
 - To prove to the server that $g^q \equiv 1 \pmod{n}$:

$$(q+1)^q \equiv \binom{q}{0}q^0 + \binom{q}{1}q^1 + \dots \equiv 1 + q \cdot q + \dots \equiv 1 \pmod{q^2}$$

— To recover x from $h \equiv g^x \pmod{n}$:

$$h \equiv (q+1)^x \pmod{q^2} \equiv \binom{x}{0}q^0 + \binom{x}{1}q^1 + \dots \equiv 1 + x \cdot q \pmod{q^2}$$

3. **Linear Algebra:** Instead of a difficult discrete logarithm problem, we reduce the problem to a simple linear equation $h \equiv 1 + xq \pmod{q^2}$.
4. **Recovering x :** This equation is trivial to solve. It means $h - 1 = xq + k \cdot q^2$ for some k . Dividing by q , we get $\frac{h-1}{q} = x + kq$. Assuming $x < q$ (which is standard for private keys), k must be 0. Thus, x can be calculated by simple integer division: $x = (h - 1) // q$.

)

3.3. Unencryptable

— **Code:**

```

from Crypto.Util.number import inverse, long_to_bytes
import math

# Values from output.txt
N = 0x7fe8cafec59886e9318830f33747cafd2005884067c42741859e15994ab62410438991ab5d9fc94f386219e3c27d6ffc73754f791e7b2c565611f8fe5054dd132b8c4f3eadcf1180cd8f2a3cc756b06996f2d5b67c390adcb9d444697b13d1
e = 0x10001
c = 0x5233da71cc1dc1c5f21039f51eb51c80657e1af217d563aa25a8104a4e84a2379040ecdffd5afa191156ccb40b6f188f4ad96c58922428c4c0bc17fd5384456853e139afde40c3f95988879629297f48d0efa6b335716a4c24bfec36f714d34

# DATA from source.py
DATA_hex = "372f0e88f6f7189da7c06ed49e87e0664b988ecbee583586dfd1c6af99bf20345ae7442012c6807b3493d8936f5b48e553f614754deb3da6230fa1e16a8d5953a94c886699fc2bf409556264d5ced76a1780a90fd22f3701fdbc183d"
m_data = int(DATA_hex, 16)

# The fixed point property m^e = m (mod N) implies that m^(e-1) = 1 (mod p) and m^(e-1) = 1 (mod q).
# Since e-1 = 65536 = 2^16, this is a perfect setup for a Pollard's p-1 like attack.
# We can try to find a factor by computing gcd(m^(2^k) - 1, N) for k from 1 to 16.
# We are looking for a k where m^(2^k) is not 1 (mod N), but m^(2^k) - 1 shares a factor with N.

a = m_data
for k in range(1, 17): # e-1 = 2^16, so we check up to k=16
    a = pow(a, 2, N)
    p = math.gcd(a - 1, N)
    if 1 < p < N:

```

```

        print(f"Factor found at k={k}")
        break
    else: # This else belongs to the for loop, it runs if the loop completes without break
        p = 1 # Reset p if no factor was found

if p == 1 or p == N:
    print("Failed to factor N with this method.")
else:
    # Once we have p, we can find q
    q = N // p

    # Now we can calculate the private key d
    phi = (p - 1) * (q - 1)
    d = inverse(e, phi)

    # Decrypt the flag ciphertext
    m_flag = pow(c, d, N)
    flag = long_to_bytes(m_flag)

    print(f"p = {hex(p)}")
    print(f"q = {hex(q)}")
    print(f"flag: {flag.decode()}")

```

— **Flag:** crypto{R3m3mb3r!_F1x3d_P0iNts_aR3_s3crE7s_t00}

— **Explanation:** I. The Key Vulnerability We are given m_{data} , for which:

$$m_{\text{data}}^e \equiv m_{\text{data}} \pmod{N}$$

Rearranging (and assuming $\gcd(m_{\text{data}}, N) = 1$), we get:

$$m_{\text{data}}^{e-1} \equiv 1 \pmod{N}$$

We know that $e = 0x10001 = 65537$, so $e - 1 = 65536 = 2^{16}$. Therefore:

$$m_{\text{data}}^{2^{16}} \equiv 1 \pmod{N}$$

This means that $m_{\text{data}}^{2^{16}} \equiv 1 \pmod{p}$ and $m_{\text{data}}^{2^{16}} \equiv 1 \pmod{q}$.

II. Attack Method (Variant of Pollard's p-1) The attack consists of iteratively checking powers of m_{data} . We define $a_k = m_{\text{data}}^{2^k} \pmod{N}$.

The **for** loop in the code successively calculates a_1, a_2, \dots, a_{16} . In each iteration k :

1. It calculates $a_k = (a_{k-1})^2 \pmod{N}$. (In code: **a = pow(a, 2, N)**)
2. It calculates $p_{\text{test}} = \gcd(a_k - 1, N)$.

The attack succeeds if, for some k , we find a p_{test} such that $1 < p_{\text{test}} < N$. This happens when $a_k \equiv 1 \pmod{p}$, but $a_k \not\equiv 1 \pmod{q}$ (or vice versa). In that case, $a_k - 1$ is a multiple of p , but not of q , so $\gcd(a_k - 1, p \cdot q) = p$.

III. Decrypting the Flag After finding the factor p :

1. The second factor is calculated: $q = N/p$.
2. Euler's totient function is calculated: $\phi(N) = (p - 1)(q - 1)$.
3. The private key d is calculated as the modular inverse of e :

$$d \equiv e^{-1} \pmod{\phi(N)}$$

(In code: **d = inverse(e, phi)**)

4. The flag is decrypted by calculating:

$$m_{\text{flag}} = c^d \pmod{N}$$

(In code: **m_flag = pow(c, d, N)**)

5. Finally, the numerical representation of the flag m_{flag} is converted back to a byte string (**long_to_bytes**).

3.4. Cofactor Cofantasy

— **Code:**

— **Flag:**

— **Explanation:**

3.5. Real Eisenstein

— **Code:**

— **Flag:**

— **Explanation:**

4. Primes

4.1. Prime and Prejudice

— Code:

```
from Crypto.Util.number import *
import itertools
from tqdm import tqdm
import json
from pwn import remote

HOST = "socket.cryptohack.org"
PORT = 13385

def generate_prime_basis(n):
    """Generate all primes up to n using Sieve of Eratosthenes."""
    sieve = [True] * n
    for i in range(3, int(n**0.5) + 1, 2):
        if sieve[i]:
            sieve[i::2*i] = [False] * ((n - i*i - 1) // (2*i) + 1)
    return [2] + [i for i in range(3, n, 2) if sieve[i]]

def miller_rabin_test(n, max_base):
    """
    Miller-Rabin primality test using all prime bases < max_base.
    Returns True if n is probably prime, False if definitely composite.
    """
    prime_bases = generate_prime_basis(max_base)

    if n == 2 or n == 3:
        return True
    if n % 2 == 0:
        return False

    # Write n-1 as 2^r * s
    r, s = 0, n - 1
    while s % 2 == 0:
        r += 1
        s //= 2

    # Test with each prime base
    for base in prime_bases:
        if base >= n:
            continue
        x = pow(base, s, n)
        if x == 1 or x == n - 1:
            continue

        for _ in range(r - 1):
            x = pow(x, 2, n)
            if x == n - 1:
                break
        else:
            return False
    return True

def extended_gcd(a, b):
    """Extended Euclidean algorithm. Returns (gcd, s, t) where gcd = a*s + b*t."""
    s, s1 = 0, 1
    t, t1 = 1, 0
    r, r1 = b, a

    while r != 0:
        q = r1 // r
        r1, r = r, r1 - q * r
        s1, s = s, s1 - q * s
        t1, t = t, t1 - q * t

    return (r1, s1, t1)

def chinese_remainder_theorem(residues, modulus):
    """
    Solve system of congruences: x ≡ residues[i] (mod modulus[i]).
    Returns (solution, combined_modulo) or (-1, -1) if no solution exists.
    """
    result_mod = modulus[0]
    result_res = residues[0]

    for residue, modulo in zip(residues[1:], modulus[1:]):
        g = GCD(result_mod, modulo)

        # Check if solution exists
        if residue % g != result_res % g:
            return -1, -1

        _, s, t = extended_gcd(modulo // g, result_mod // g)
        result_res = result_res * (modulo // g) * s + residue * (result_mod // g) * t
        result_mod *= modulo // g
        result_res %= result_mod

    return result_res, result_mod

def legendre_symbol(a, p):
    """Compute Legendre symbol (a/p) = a^((p-1)/2) mod p."""
    if p < 2:
        return 0
    return pow(a, (p - 1) // 2, p)

def find_valid_residues(primes, num_factors):
    """
    Find residues that satisfy the Legendre symbol condition for fooling Miller-Rabin.
    """
    valid_residues = []
    ks = [1, 998244353, 233] # Multipliers for constructing the pseudoprime

    for prime in primes:
        residue_set = set()
        larger_primes = generate_prime_basis(200 * prime)[1:]
```

```

    for q in larger_primes:
        if legendre_symbol(prime, q) == q - 1:
            residue_set.add(q % (4 * prime))

    valid_residues.append(list(residue_set))

# Filter residues to work with all factors
filtered_residues = []
for idx, residue_list in enumerate(valid_residues):
    prime = primes[idx]
    modulus = prime * 4
    current_set = set(residue_list)

    for i in range(1, num_factors):
        new_set = set()
        for res in residue_list:
            try:
                transformed = ((res + ks[i] - 1) * inverse(ks[i], modulus)) % modulus
                if transformed % 4 == 3:
                    new_set.add(transformed)
            except ValueError:
                pass # No inverse
        current_set = current_set.intersection(new_set)

    filtered_residues.append(current_set)

return filtered_residues, ks

def generate_strong_pseudoprime(primes, filtered_residues, ks, num_factors,
                               min_bits=600, max_bits=900):
    """
    Generate a strong pseudoprime that passes Miller-Rabin test.
    Returns (pseudoprime, factors) or (None, None) if not found.
    """
    total_combinations = 1
    for res_set in filtered_residues:
        total_combinations *= len(res_set)
    print(f"Total combinations to try: {total_combinations}")

    for residue_tuple in itertools.product(*filtered_residues):
        residues = []
        modulus = []

        # Build CRT system from residue tuple
        for i, res in enumerate(residue_tuple):
            residues.append(res)
            modulus.append(primes[i] * 4)

        # Add constraints from ks multipliers
        try:
            residues.append(ks[1] - inverse(ks[2], ks[1]))
            modulus.append(ks[1])
            residues.append(ks[2] - inverse(ks[1], ks[2]))
            modulus.append(ks[2])
        except ValueError:
            continue # No inverse

        solution, combined_mod = chinese_remainder_theorem(residues, modulus)

        if solution == -1:
            continue

        # Start search from a large value
        candidate = 2**73 * combined_mod + solution

        for _ in tqdm(range(100000)):
            if isPrime(candidate):
                # Build the pseudoprime from candidate and its multiples
                pseudoprime = candidate
                factors = [candidate]

                for i in range(1, num_factors):
                    factor = ks[i] * (candidate - 1) + 1
                    factors.append(factor)
                    pseudoprime *= factor

                # Check if it passes Miller-Rabin and has correct bit length
                if miller_rabin_test(pseudoprime, 64):
                    bit_len = pseudoprime.bit_length()
                    if min_bits <= bit_len <= max_bits:
                        print(f"Found pseudoprime! isPrime check: {isPrime(pseudoprime)}")
                        print(f"Pseudoprime: {pseudoprime}")
                        print(f"Factors: {factors}")
                        return pseudoprime, factors

                candidate += combined_mod

    return None, None

# Main execution: Generate strong pseudoprime
NUM_FACTORS = 3
prime_bases = generate_prime_basis(64)
print(f"Number of prime bases: {len(prime_bases)}")
print(f"Prime bases: {prime_bases}")

filtered_residues, ks_multipliers = find_valid_residues(prime_bases, NUM_FACTORS)
print(f"Filtered residue sets: {filtered_residues}")

pseudoprime, factors = generate_strong_pseudoprime(
    prime_bases, filtered_residues, ks_multipliers, NUM_FACTORS
)
found = (pseudoprime is not None)

def solve(p, facts):
    """
    This function will connect to the server and send the payload.
    Uses the generated strong pseudoprime and its factors.
    p = product of facts, where p is composite but passes Miller-Rabin

    The key: since p is composite, we can choose 'a' such that gcd(a, p) > 1
    or such that a^(p-1) is NOT 1 mod p.
    """
    # Strategy: Make 'a' share a factor with p

```

```

# If a = k * facs[0] for some k, then gcd(a, p) = facs[0] > 1
# The server checks a < p, so we need a to be smaller than p but share a factor

# Try using one of the factors directly or a small multiple
for i, fac in enumerate(facs):
    print(f"\nTrying with factor {i}: {fac}")

    # Try small multiples of this factor
    for k in range(2, 10):
        a = k * fac
        if a >= p:
            break

    print(f"Trying a = {k} * factor = {a}")

    # Check what we get locally
    result = pow(a, p-1, p)
    print(f"Local test: pow(a, p-1, p) = {result}")

    r = remote(HOST, PORT)
    r.recvuntil(b"primes!\n")

    payload = json.dumps({"base": a, "prime": p})
    r.sendline(payload.encode())

    response = r.recvline().decode()
    try:
        data = json.loads(response)
        if "Response" in data:
            print(data["Response"])
            if "crypto" in data["Response"]:
                print(f"\n*** FOUND FLAG! ***")
                r.close()
                return
        else:
            print(data)
    except json.JSONDecodeError:
        print(response)

    r.close()

if __name__ == "__main__":
    if found:
        print(f"Generated pseudoprime with bit length: {pseudoprime.bit_length()}")
        print(f"Factors: {factors}")
        solve(pseudoprime, factors)
    else:
        # Fallback to precomputed value if generation fails
        print("Failed to generate suitable pseudoprime. Using precomputed value.")
        pre_p = 4697986095346038938634731346766468081691850626338691515269502540600143161323848037380120300137197089849204913217201880336284687541604702008398403214578051778940881775762923583133957
        pre_facs = [190805096574824360341517400306381535441501, 1079323138806282361628108420455314051012301, 2280263150530483863414002621370221375351301]
        solve(pre_p, pre_facs)

```

— **Flag:** `crypto{Forging_Primes_with_Francois_Arnault}`

— **Explanation:** This problem exploits a weakness in the **Fermat primality test**, which is a simplified version of the **Miller-Rabin test**.

1. **Fermat vs Miller-Rabin:** The server we connect to (`solve`) only uses the Fermat test: it checks if $a^{p-1} \equiv 1 \pmod{p}$. The full Miller-Rabin test (implemented in `miller_rabin_test`) is stronger and checks additional conditions.
2. **Objective:** The goal is to find a number p that is **composite**, but passes the Miller-Rabin test for all small bases a (here: all primes up to 64). Such a number is called a **strong pseudoprime**. At the same time, p must be constructed so that the Fermat test $a^{p-1} \equiv 1 \pmod{p}$ fails for some base a that the server does not check.
3. **Construction (Mathematics):** The code in `generate_strong_pseudoprime` constructs such a "fake" prime p as a product of several prime factors ($p = f_1 \cdot f_2 \cdot f_3$). Using advanced techniques (including the **Chinese Remainder Theorem** to combine conditions and the **Legendre Symbol** to set them), the code imposes conditions on the factors f_i such that p "fools" the Miller-Rabin test for all bases $a < 64$. This is a known construction (e.g., Arnault's).
4. **The Attack (Function solve):** Once we have our composite number p and we know its factors (`facs`), we can easily fail the Fermat test.
 - Fermat's Little Theorem ($a^{p-1} \equiv 1 \pmod{p}$) only applies when p is prime, or (for composite numbers) when $\text{GCD}(a, p) = 1$.
 - The code sends the server a base a that is *not* coprime to p . It chooses a as a multiple of one of the known factors of p , e.g., $a = 2 \cdot f_1$ (in the code `a = k * fac`).
 - For such an a , $\text{GCD}(a, p) = \text{GCD}(2f_1, f_1 f_2 f_3) \geq f_1 > 1$.
 - Because $\text{GCD}(a, p) > 1$, the server, when calculating `pow(a, p-1, p)`, will almost certainly *not* get 1. This reveals that p is composite, which the server rewards with a flag.