

paxmeet_icons

Custom icon-font package — Documentation

Install & usage · Adding / renaming / removing icons

Using paxmeet_icons (Flutter app + Web)

One icon set, defined once, used the same way everywhere. The names are **identical** across platforms, so designers and developers refer to the same list (open [index.html](#) to browse & search every icon).

Platform	How you use an icon
Flutter	<code>Icon(PaxmeetIcons.home)</code>
Web (React/Next.js)	<code><PaxmeetIcon name="home" /></code> or <code><i className="pmi pmi-home" /></code>

Both render from the **same font file** (`fonts/PaxmeetIcons.ttf`), so an icon can never look different between the app and the website.

A) Flutter app

1. Add the dependency

In your app's `pubspec.yaml` under `dependencies:` — pick one:

```
# Git (recommended — works in any project)
paxmeet_icons:
  git:
    url: https://github.com/letssuhail/paxmeet_icons.git
    ref: main          # or a tag like v0.0.1 to pin a version

# ...or local path (same repo / monorepo)
# paxmeet_icons:
#   path: ../paxmeet_icons
```

2. Install

```
flutter pub get      # this repo uses fvm:  fvm flutter pub get
```

3. Use

```
import 'package:paxmeet_icons/paxmeet_icons.dart';

Icon(PaxmeetIcons.home);
```

```
Icon(PaxmeetIcons.heart, size: 28, color: Theme.of(context).primaryColor);

IconButton(
  icon: const Icon(PaxmeetIcons.search),
  onPressed: () {},
);
```

That's it — no font setup in your app's `pubspec.yaml`; the font ships inside the package. The color comes from Flutter (`color:`), the font is monochrome.

App size: all icons are ~12 KB and Flutter **tree-shakes** the ones you don't use out of release builds automatically. Just always use the constants directly (`PaxmeetIcons.home`) — never build `IconData` from a variable codepoint, or tree-shaking turns off.

B) Web (Next.js / React)

The package ships ready-to-use web assets in its `web/` folder: `paxmeet-icons.css`, `PaxmeetIcon.jsx`, `icon-names.js`.

1. Copy the assets into the site

```
git clone https://github.com/letssuhail/paxmeet_icons.git
mkdir -p <your-site>/src/components/paxmeet-icons
cp paxmeet_icons/web/* <your-site>/src/components/paxmeet-icons/
```

2. Load the CSS once (App Router → `src/app/layout.js`)

```
import "../globals.css";
import "@components/paxmeet-icons/paxmeet-icons.css";
```

⚠ Use a **JS import** like above. Do **not** add `@import "...paxmeet-icons.css"` inside `globals.css` if it already has other `@import` s (e.g. Google Fonts) — CSS requires all `@import` s first, and Next.js will error.

3. Use it

```
import { PaxmeetIcon } from "@components/paxmeet-icons/PaxmeetIcon";

<PaxmeetIcon name="search" size={20} color="#7332D6" />
```

Or with plain CSS classes (no component):

```
<i className="pmi pmi-search" style={{ fontSize: 20, color: "#7332D6" }} />
```

`icon-names.js` exports `paxmeetIconNames` — the full list, handy for dropdowns.

TypeScript site? Rename `PaxmeetIcon.jsx` → `.tsx` and type the props: `{ name: string; size?: number; color?: string; className?: string }`.

Finding icon names

- Open `index.html` (repo root) in a browser — search any icon, click to copy its name / Flutter code. Host it on GitHub Pages to share a public reference.
- Names are camelCase and the same on both platforms: `addCircle`, `wallet`, `volume`, `profileCircle`, `chevronLeft`, ...

See `ADDING_ICONS.md` to add or change icons.

Adding / updating / removing icons (updates app + web together)

You edit **one** folder of SVGs and run **one** command. That regenerates the font, the Flutter class, **and** the web assets — so the app and website always get the same icons. The single source of truth is `alliconsvg/` — a flat folder where **the filename is the icon name**.

```
alliconsvg/home.svg      ┌─> lib/paxmeet_icons.dart    (Flutter: PaxmeetIcons)
alliconsvg/heart.svg     ┌─ tool/build.sh → ┌─> web/paxmeet-icons.css    (Web: <PaxmeetIcon name=
alliconsvg/search.svg    └─ (one font)      └─> index.html, preview.png (reference)
```

One-time setup (first time on a machine)

```
cd paxmeet_icons

# Python tools: picosvg (stroke→fill normalization) + markdown (for the PDF)
python3 -m venv tool/.venv
tool/.venv/bin/pip install picosvg markdown

# Dart tool: the font generator
dart pub global activate icon_font_generator
```

Add a new icon

1. **Prepare the SVG**
2. **Single color** (monochrome) — the color is applied later (`Icon(color:)` in Flutter, `color` in CSS). Multi-color/brand icons can't be a font glyph.
3. Fill-based **or** stroke-based both work — strokes are auto-converted to filled outlines by picosvg.
4. Recommended: `24×24` viewBox, no embedded raster images.
5. **Name it well** and drop it into `alliconsvg/`
6. Use **snake_case**; it becomes a **camelCase** name on both platforms:
 - `event_ticket.svg` → Flutter `PaxmeetIcons.eventTicket` / Web `name="eventTicket"`
7. Name by **what the icon depicts** or its UI meaning — `wallet` not `empty_wallet`, `message` not `message_text`, `microphone` not `microphone_2`.
8. **Build everything (one command)** `bash bash tool/build.sh` This updates the font, Flutter class, web CSS/component, and the reference page.
9. **Commit & push** so apps and sites can pull it `bash git add -A && git commit -m "icons: add eventTicket" && git push`
10. **Pick it up in each project**
11. **Flutter app:** `flutter pub get` (or `fvm flutter pub get`) + full restart.
12. **Website:** re-copy `web/*` into the site (`cp paxmeet_icons/web/* <site>/src/components/paxmeet-icons/`).

Rename an icon

1. Rename the file in `alliconsvg/` (e.g. `empty_wallet.svg` → `wallet.svg`).
2. `bash tool/build.sh` (the build clears stale names automatically).
3. Update usages: Flutter `PaxmeetIcons.emptyWallet` → `PaxmeetIcons.wallet` ; Web `name="emptyWallet"` → `name="wallet"` .
4. Commit, push, update each project.

Remove an icon

1. Delete the file from `alliconsvg/` .
2. `bash tool/build.sh` , commit, push.

What each file/script is

File / folder	Role
<code>alliconsvg/</code>	Source of truth — flat, clean-named SVGs you edit.
<code>tool/build.sh</code>	The one command — runs the whole pipeline below.
<code>tool/import.sh</code>	Normalizes SVGs with picosvg → <code>tool/svgsg/</code> (clears old files).
<code>tool/generate.sh</code>	<code>icon_font_generator</code> : <code>tool/svgsg/</code> → <code>.ttf</code> + <code>lib/paxmeet_icons.dart</code> .
<code>tool/build_web_assets.py</code>	Generates <code>web/</code> CSS + React component from the font.
<code>tool/build_web.py</code>	Generates the <code>index.html</code> reference page.
<code>tool/preview.py</code>	Generates <code>preview.png</code> .
<code>fonts/PaxmeetIcons.ttf</code>	The generated font — used by both app and web (committed).
<code>lib/paxmeet_icons.dart</code> , <code>web/*</code>	Generated outputs (committed).

Gotchas

- **Empty / wrong glyph** → the SVG was multi-color or had an embedded image. Flatten it to a single-color vector and rebuild.
- `import.sh` prints **"PICOSVG FAILED"** for a file → picosvg can't resolve it (multi-color/raster). Simplify and re-export.
- Always commit the regenerated `fonts/` , `lib/paxmeet_icons.dart` , and `web/` together with the SVG change, so app and web stay in sync.
- After updating, **restart** the Flutter app fully (not just hot reload) and re-copy `web/*` into the website.