

paxmeet_icons

Custom icon-font package — Documentation

Install & usage · Adding / renaming / removing icons

Adding `paxmeet_icons` to a Flutter project

This guide shows how to use the Paxmeet icon set in any Flutter app. You add the package once, then use icons anywhere with `Icon(PaxmeetIcons.xxx)` — no asset files, no font declaration in your app.

Browse all icons and copy their code from the reference page: open `index.html` in a browser (or its hosted GitHub Pages URL).

1. Add the dependency

Pick **one** of the following based on where the package lives, and add it under `dependencies:` in your app's `pubspec.yaml`.

Option A — Same repo / monorepo (local path)

```
dependencies:
  paxmeet_icons:
    path: ../paxmeet_icons      # relative path to the package folder
```

Option B — Private Git repo (recommended for sharing across apps)

```
dependencies:
  paxmeet_icons:
    git:
      url: https://github.com/<your-org>/paxmeet_icons.git
      ref: main                # or a tag like v0.0.1 to pin a version
```

Option C — Published on pub.dev (public package)

```
dependencies:
  paxmeet_icons: ^0.0.1
```

2. Install

```
flutter pub get
# (this project uses fvm, so: fvm flutter pub get)
```

3. Use an icon

```
import 'package:paxmeet_icons/paxmeet_icons.dart';

// anywhere a widget is allowed:
Icon(PaxmeetIcons.home);

// with size + color (color comes from Flutter, the font is monochrome):
Icon(PaxmeetIcons.heart, size: 28, color: Theme.of(context).primaryColor);

// in a button:
IconButton(
  icon: const Icon(PaxmeetIcons.search),
  onPressed: () {},
);
```

That's it — the font ships **inside** the package (each `IconData` already carries `fontPackage: 'paxmeet_icons'`), so you do **not** add anything to the `fonts:` section of your app's `pubspec.yaml`.

App size — nothing to worry about

The font holds all icons in ~12 KB, and Flutter **tree-shakes** the glyphs you don't use out of release builds automatically. You'll see this during a release build:

```
Font asset "PaxmeetIcons.ttf" was tree-shaken, reducing it from 33 to 6 glyphs (82% reduction).
```

⚠ One rule to keep tree-shaking working: always use the constants directly (`PaxmeetIcons.home`). Don't build `IconData` from a runtime/variable codepoint — that disables tree-shaking for the whole font.

Troubleshooting

Symptom	Fix
Icons show as empty boxes (□)	Run <code>flutter pub get</code> ; do a full restart (not just hot reload) so the new font loads.
Undefined name 'PaxmeetIcons'	Add the import: <code>import 'package:paxmeet_icons/paxmeet_icons.dart';</code>
Git dependency won't resolve	Check the <code>url</code> / <code>ref</code> ; ensure you have access to the repo.
Wrong icon shows	Names map to glyphs by codepoint; if you regenerated the font, re-run <code>flutter pub get</code> and restart.

Adding / updating / removing icons

The package turns a folder of SVGs into one icon font. The **single source of truth** is the `alliconsvg/` folder — a flat folder where the **filename is the icon name**. You edit that folder, run the build, and the font, the Dart class, and the reference webpage all regenerate.

```
alliconsvg/home.svg  ┌
alliconsvg/heart.svg ┤ build → fonts/PaxmeetIcons.ttf
alliconsvg/search.svg└      lib/paxmeet_icons.dart → PaxmeetIcons.home ...
                                index.html (reference page)
```

One-time setup (first time on a machine)

The build uses **picosvg** (converts strokes→fills) and **icon_font_generator**.

```
cd paxmeet_icons

# 1. picosvg (Python) – for stroke/shape normalization
python3 -m venv tool/.venv
tool/.venv/bin/pip install picosvg

# 2. icon_font_generator (Dart) – builds the font
dart pub global activate icon_font_generator
```

Add a new icon

1. **Prepare the SVG.** It must be:
2. **Single color** (monochrome). The color is applied later in Flutter via `Icon(color:)`. Multi-color/brand icons cannot be a font glyph.
3. Either fill-based **or** stroke-based — both are fine, picosvg converts strokes to filled outlines automatically.
4. Recommended canvas: `24×24` viewBox, no embedded raster images.
5. **Name it well** and drop it in `alliconsvg/`:
6. Use **snake_case**; the filename becomes a **camelCase** Dart identifier.
 - `add_circle.svg` → `PaxmeetIcons.addCircle`
 - `event_ticket.svg` → `PaxmeetIcons.eventTicket`
7. Name by **what the icon depicts** or its **UI meaning**, not the design-tool export name: `wallet` not `empty_wallet`, `message` not `message_text`, `microphone` not `microphone_2`.
8. **Build:** `bash bash tool/import.sh # normalize alliconsvg/ -> tool/svg/ (picosvg) bash tool/generate.sh # build the .ttf + lib/paxmeet_icons.dart tool/.venv/bin/python tool/build_web.py # refresh index.html reference page`
9. **Use it:** `Icon(PaxmeetIcons.eventTicket)`. In an app already depending on the package, run `flutter pub get` + full restart to pick up the new font.

Tip: there's no need to remember the three commands separately — they always run together. See **One-command build** below.

Rename an icon

1. Rename the file in `alliconsvg/` (e.g. `empty_wallet.svg` → `wallet.svg`).
2. Re-run the build (`import.sh` clears stale files, so the old name disappears).
3. Update any usages in apps from `PaxmeetIcons.emptyWallet` → `PaxmeetIcons.wallet` .

Remove an icon

1. Delete the file from `alliconsvg/` .
2. Re-run the build. The glyph and its constant are gone.

One-command build (optional convenience)

Run all three steps at once:

```
bash tool/import.sh && bash tool/generate.sh && tool/.venv/bin/python tool/build_web.py
```

How it works (reference)

Folder / file	Role
<code>alliconsvg/</code>	Source of truth — flat, clean-named SVGs you edit.
<code>tool/import.sh</code>	Normalizes each SVG with picosvg into <code>tool/svgsg/</code> (clears old files first).
<code>tool/svgsg/</code>	Generated, normalized SVGs — the actual font input. Don't hand-edit.
<code>tool/generate.sh</code>	Runs <code>icon_font_generator</code> : <code>tool/svgsg/</code> → <code>.ttf</code> + Dart class.
<code>tool/build_web.py</code>	Builds the self-contained <code>index.html</code> reference page.
<code>fonts/PaxmeetIcons.ttf</code>	The generated font (committed).
<code>lib/paxmeet_icons.dart</code>	The generated <code>PaxmeetIcons</code> class (committed).

Gotchas

- **Empty or wrong-looking glyph?** The SVG was probably multi-color or had an embedded image. Make it a single-color vector and rebuild.
- `import.sh` says **"PICOSVG FAILED"** for a file → that SVG has something picosvg can't resolve (e.g. multi-color, raster). Simplify/flatten it in the design tool and re-export.
- **Name collisions:** two files can't share a name. Filenames are unique by definition, so just pick distinct, descriptive names.

- Always commit the regenerated `fonts/PaxmeetIcons.ttf` and `lib/paxmeet_icons.dart` together with the SVG change.