EyeReport → Eye TV hand-off (for the EyeReport team)

When an EyeReport moderator **approves a report that contains a video**, EyeReport sends it to Eye TV automatically. Eye TV puts it in its **review queue** (status *pending*, shown as "From EyeReport"). An Eye TV editor then reviews and publishes it. Nothing is published on Eye TV automatically, and **no personal details of the citizen are ever sent**.

1. One-time setup

1. Create a **shared secret**: **64 characters of random letters and numbers** (32 random bytes written as hex). Minimum 40 characters, no spaces, never reused from another system. How to make one:
   - Terminal: `openssl rand -hex 32`
   - or a password generator set to 64 characters, letters and numbers only. Use a **different secret for staging and for production**. Share it with the EyeReport team through a password manager, never by chat or email, and never put it in source code.
2. **Eye TV (cPanel → Setup Node.js App → Add Variable):**

Name	Value
`EYE_REPORT_WEBHOOK_SECRET`	the shared secret
`EYE_REPORT_CALLBACK_URL`	the https address on EyeReport that receives Eye TV's decisions (section 5)
Then **Save** and **Restart**. Without the secret the hand-off answers 503; without the callback address, decisions are kept and sent once the address is added.	

3. **EyeReport:** store the same secret in its own secret store / environment.
4. Endpoint: `POST https://webtv.eyemedia.ng/api/integrations/eye-report` (use the staging address while testing).
5. Eye TV must also have Mux connected (see the Mux setup guide), because Eye TV hands the video link to Mux.

2. The request

`Content-Type: application/json`, plus a signature header so Eye TV knows the call really comes from EyeReport:

`X-EyeReport-Signature: t=<unix seconds>,v1=<hex HMAC-SHA256>`

- `t` is the current time in seconds. Requests older or newer than **5 minutes** are refused.
- `v1` is the HMAC-SHA256, keyed with the shared secret, of the text `<t>.<raw request body>` (the exact bytes you send), written as lowercase hex.

Body

Field	Required	Notes
`externalId`	yes	EyeReport's own id for the report (letters, numbers, `. _ : -`, up to 100). Sending the same id again never creates a second video.
`title`	yes	3–200 characters
`videoUrl`	yes	An **https** link to the video file that stays valid for at least a few hours (a time-limited signed storage link is ideal). Mux downloads it; Eye TV does not keep it.
`description`	no	up to 4000 characters
`category`	no	Eye TV category slug, e.g. `public-safety`, `traffic-transport`. Unknown or missing: the editor chooses.
`location`	no	up to 160 characters

No other field is accepted. A request that includes a name, email, phone number or anything else is rejected with `400`. This is on purpose: the citizen's contact details stay in EyeReport.

Example (Node.js)

```
import { createHmac } from 'node:crypto'
const body = JSON.stringify({ externalId: 'ER-1042', title: 'Pothole on Ojota flyover',
  description: 'Large pothole during rush hour.', category: 'traffic-transport',
location: 'Ojota, Lagos',
  videoUrl: 'https://files.example.com/er/1042.mp4?signature=…' })
const t = Math.floor(Date.now() / 1000)
const v1 = createHmac('sha256',
process.env.EYE_REPORT_WEBHOOK_SECRET).update(`${t}.${body}`).digest('hex')
const res = await fetch('https://webtv.eyemedia.ng/api/integrations/eye-report', {
  method: 'POST', headers: { 'Content-Type': 'application/json', 'X-EyeReport-
Signature': `t=${t},v1=${v1}` }, body })
```

Example (PHP, for the PCF backend)

```
$body = json_encode(['externalId' => 'ER-1042', 'title' => 'Pothole on Ojota flyover',
'videoUrl' => $signedUrl]);
$t = time();
$v1 = hash_hmac('sha256', $t . '.' . $body, getenv('EYE_REPORT_WEBHOOK_SECRET'));
// POST $body with header:  X-EyeReport-Signature: t=$t,v1=$v1
```

3. Responses

Status	Meaning	What EyeReport should do
`201`	Created. Body: `{ "id", "status": "pending", "duplicate": false }`	Mark the report as handed over
`200`	Already received (`duplicate: true`)	Same as 201
`400`	Invalid payload, or an extra field. Body lists the problems	Fix the data; do not retry unchanged
`401`	Bad or expired signature	Check the secret and the clock
`422`	Mux could not use the video link	Check the link/file, then resend
`429`	Too many requests	Retry later
`502` / `503`	Eye TV or Mux is temporarily unavailable	**Retry** with the same body (safe: it is idempotent), e.g. after 1, 5, 15 minutes

4. What happens on Eye TV

1. The video appears in the **Moderation Queue** as “From EyeReport”, and is **private** on Mux.
2. It is ready to review after Mux finishes processing (usually a few minutes). The editor completes the checklist and approves or rejects.
3. Only when an editor approves does the video get a public link and appear on Eye TV.
4. The audit log records the hand-over (“Received video from EyeReport”).
5. Eye TV tells EyeReport about the decision (section 5).

5. Eye TV → EyeReport: decision callback

When an Eye TV editor **publishes**, **rejects** or later **unpublishes** a video that came from EyeReport, Eye TV calls EyeReport. EyeReport provides a URL for this (`EYE_REPORT_CALLBACK_URL`) and verifies the signature, exactly like the other direction but with the header `X-EyeTV-Signature` (same secret, same `t=…,v1=…` format, HMAC of `<t>.<raw body>`).

```
{ "event": "video.published", "externalId": "ER-1042", "videoId": "…",
  "eyeTvUrl": "https://webtv.eyemedia.ng/tv/pothole-on-ojota-flyover-ab12c",
  "occurredAt": "2026-10-19T17:02:11.000Z" }
```

- `event` is `video.published` , `video.rejected` or `video.unpublished` . `eyeTvUrl` is only set for `video.published` .
- `externalId` is the id EyeReport used in the hand-over. Use `occurredAt` to order events if several arrive for one report.
- **Rejection reasons are internal and are never sent.** EyeReport should show the citizen a neutral status.
- Answer with any `2xx` status to confirm. Anything else (or no answer within 10 seconds) is retried automatically: after 1, 2, 4, 8 … minutes up to 6 hours, 12 attempts in all. Make your

receiver safe to call twice with the same event.

- Rejected or unpublished videos are not deleted on EyeReport's side by Eye TV; EyeReport decides what to show.