

Project Report

Submitted in partial fulfilment of the requirements for the completion of the Course

EDS Lab Codetantra**Practical No.2****(2304102L)***Submitted by,****Payal Ankush Ghule -202501090088****Under the Guidance of,***Ms. Savita Mane(SM)**

(An Autonomous Institute Affiliated to Savitribai Phule Pune University)

Department of Mechanical Engineering,**MIT Academy of Engineering,****Alandi road, Pune - 412 105,****Maharashtra (India)**

2.1.1. List operations

08:32

Write a Python program that implements a menu-driven interface for managing a list of integers. The program should have the following menu options:

1. Add
2. Remove
3. Display
4. Quit

The program should repeatedly prompt the user to enter a choice from the menu.

Depending on the choice selected, the program should perform the following actions:

Add: Prompts the user to enter an integer and add it to the integer list. If the input is not a valid integer, display "Invalid input".

Remove: Prompts the user to enter an integer to remove from the list. If the integer is found in the list, remove it; otherwise, display "Element not found". If the list is empty, display "List is empty".

Display : Displays the current list of integers. If the list is empty, display "List is empty".

Quit: Exits the program.

The program should handle invalid menu choices by displaying "Invalid choice". Ensure that the program continues to prompt the user until they choose to quit (option 4).

#listOps.py

```
int_list = []
```

```
while True:
```

```
    print("1.
```

```
    Add")
```

```
    print("2. Remove")
```

```
    print("3. Display")
```

```
    print("4. Quit")
```

```
choice = input("Enter choice: ")
```

```
if choice == '1': # Add
```

```
    value = input("Integer: ")
```

```
    try:
```

```
        num = int(value)
```

```
        int_list.append(num)
```

```
        print("List after adding:", int_list)
```

```
    except ValueError:
```

```
        print("Invalid input")
```

```
elif choice == '2': #
```

```
    Remove if not int_list:
```

```
        print("List is empty")
```

```
    else:
```

```
        value = input("Integer: ")
```

```
        try:
```

```
num = int(value)
```

```
    if num in int_list:

        int_list.remove(num)

        print("List after removing:", int_list)

    else:

        print("Element not found")

except ValueError:

    print("Invalid input")


elif choice == '3': #

    Display if not int_list:

        print("List is empty")

    else:

        print(int_list)


elif choice == '4': # Quit

    break


else:

    print("Invalid choice")
```

Expected output

```
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 1
Integer: 11
List after adding: [11]
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 1
Integer: 25
List after adding: [11, 25]
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 2
Integer: 26
Element not found
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 2
Integer: 11
List after removing: [25]
1. Add
2. Remove
```

Actual output

```
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 1
Integer: 11
List after adding: [11]
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 1
Integer: 25
List after adding: [11, 25]
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 2
Integer: 26
Element not found
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 2
Integer: 11
List after removing: [25]
1. Add
2. Remove
```

Terminal

Test cases

< Prev

Reset

Submit

Next >

Integer: 11

List after removing: [25]

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 2

Integer: 25

List after removing: []

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 3

List is empty

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 2

List is empty

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 8

Invalid choice

1. Add

2. Remove

Integer: 11

List after removing: [25]

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 2

Integer: 25

List after removing: []

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 3

List is empty

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 2

List is empty

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 8

Invalid choice

1. Add

2. Remove

< Prev

Reset

Submit

Next >

List is empty

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 8

Invalid choice

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 4

List is empty

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 8

Invalid choice

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 4

< Prev

Reset

Submit

Next >

2.1.2. Dictionary Operations

07:23

Write a Python program to perform insertion, update, deletion, and traversal operations on a dictionary. An initial dictionary containing 10 predefined records is already given in the program.

Operations to be Performed:

1. Insertion – Insert a new key-value pair into the dictionary using user input.
2. Update – Update the value of an existing key using user input.
3. Deletion – Delete a specified key from the dictionary using user input.
4. Traversal – Traverse the final dictionary and display all key-value pairs.

Input and Output Format:

1. Read an integer representing the key to be inserted and a string representing its value. Insert this new key-value pair into the dictionary and display the dictionary after insertion.
2. Read an integer representing the key to be updated and a string representing the new value. Update the value of the specified key (only if it exists) and display the dictionary after the update.
3. Read an integer representing the key to be deleted. Delete the specified key from the dictionary (only if it exists) and display the dictionary after deletion.
4. Finally, traverse the dictionary and display all key-value pairs.

The program should also display the original dictionary before performing any operations. Each output should be printed with appropriate messages.

Note:

All operations must be performed using dictionary methods.

Perform deletion only if possible; leave the dictionary unchanged.

Refer to the visible test cases for better understanding and strictly match with the input/outputs.

#Initial dictionary with 10 predefined records

```
student = {
```

```
1: "Amit",
2: "Riya",
3: "Kiran",
4: "Neha",
5: "Arjun",
6: "Pooja",
7: "Rahul",
8: "Sneha",
9: "Vikram",
10: "Anjali"
}

#Display original dictionary
print("Original Dictionary:", student)

#Insertion
key = int(input())
value = input()
student[key] =
value
print("After Insertion:", student)

#Update
upd_key = int(input())
upd_value = input()
if upd_key in student:
    student[upd_key] =
```

```
upd_value print("After Update:",  
student)
```

Deletion

```
del_key = int(input())
```

```
if del_key in student:
```

```
    student.pop(del_key)
```

```
print("After Deletion:",
```

```
student)
```

#Traversal

```
print("Traversing Dictionary:")
```

```
for k, v in student.items():
```

```
    print(k, ":", v)
```

The screenshot displays a code execution environment with the following components:

- Performance Metrics:**
 - Average time: 0.027 s (27.00 ms)
 - Maximum time: 0.044 s (44.00 ms)
- Test Results:**
 - 2 out of 2 shown test case(s) passed
 - 2 out of 2 hidden test case(s) passed
- Expected output:**
 - Original Dictionary: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali'}
 - 11: Suresh
 - After Insertion: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}
 - 3: Karthik
 - After Update: {1: 'Amit', 2: 'Riya', 3: 'Karthik', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}
 - 5
 - After Deletion: {1: 'Amit', 2: 'Riya', 3: 'Karthik', 4: 'Neha', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}
 - Traversing Dictionary:
 - 1: Amit
 - 2: Riya
 - 3: Karthik
 - 4: Neha
 - 6: Pooja
 - 7: Rahul
 - 8: Sneha
 - 9: Vikram
 - 10: Anjali
 - 11: Suresh
- Actual output:**
 - Original Dictionary: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali'}
 - 11: Suresh
 - After Insertion: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}
 - 3: Karthik
 - After Update: {1: 'Amit', 2: 'Riya', 3: 'Karthik', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}
 - 5
 - After Deletion: {1: 'Amit', 2: 'Riya', 3: 'Karthik', 4: 'Neha', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}
 - Traversing Dictionary:
 - 1: Amit
 - 2: Riya
 - 3: Karthik
 - 4: Neha
 - 6: Pooja
 - 7: Rahul
 - 8: Sneha
 - 9: Vikram
 - 10: Anjali
 - 11: Suresh
- Terminal:** Test cases
- Navigation:** < Prev, Reset, Submit, Next >

2.2.1. Linear search

Technique 04:45

Write a program to check whether the given element is present or not in the array of elements using linear search.

Input format:

The first line of input contains the array of integers which are separated by space The last line of input contains the key element to be searched

Output format:

If the element is found, print the index.

If the element is not found, print **Notfound** .

Sample Test

Case: Input:

1 2 3 4 3 5 6

3

Output:

2

```
#Read input array
```

```
arr=list(map(int, input().split()))
```

```
#Read key element
```

```
key=int(input())
```

```
#Linear search
```

```
found = False
```

```
for i in range(len(arr)):
```

```
if arr[i] == key:
```

```
    print(i)
```

```
    found = True
```

```
    break
```

```
#If not found
```

```
ifnot found:
```

```
    print("Not found")
```

The screenshot displays a code execution environment with the following details:

- Performance Metrics:**
 - Average time: 0.010 s (9.75 ms)
 - Maximum time: 0.012 s (12.00 ms)
- Test Results:**
 - 2 out of 2 shown test case(s) passed
 - 2 out of 2 hidden test case(s) passed
- Test Case 1 (10 ms):**
 - Expected output:** 1 2 3 4 3 5 6, 3, 2
 - Actual output:** 1 2 3 4 3 5 6, 3, 2
- Test Case 2 (12 ms):** Passed

2.2.2. Captain of the

Team 01:32

You are provided with the heights of 11 cricket players (in centimeters). Your task is to identify the tallest player, who will be selected as the captain of the team.

Input Format:

The first line of input will contain 11 integers, each representing the height of a player (in centimeters), each separated by a space.

Output Format

The output should be the height (in centimeters) of the tallest player.

```
# Read heights of 11 players
```

```
heights = list(map(int, input().split()))
```

```
#Find the tallest player
```

```
tallest = max(heights)
```

```
#Output the tallest height
```

```
print(tallest)
```

The screenshot displays a code execution environment with the following components:

- Performance Metrics:**
 - Average time: 0.005 s (5.33 ms)
 - Maximum time: 0.006 s (6.00 ms)
- Test Results:**
 - 1 out of 1 shown test case(s) passed
 - 2 out of 2 hidden test case(s) passed
- Test Case 1 Details:**
 - Status: Passed (6 ms)
 - Buttons: Debug, Test cases
 - Expected output: 171 169 185 156 174 191 186 190 187 172 160
 - Actual output: 171 169 185 156 174 191 186 190 187 172 160
- Terminal/Output Area:** Shows the expected and actual output lines.
- Navigation:** Includes buttons for Terminal, Test cases, < Prev, Reset, Submit, and Next >.