Chapter 14. Object-Oriented Programming in Python

Object-Oriented Programming, or **OOP**, is a programming style where code is organized using **classes** and **objects**.

14.1.1 OOPS Fundamentals

Basic idea

Class -> blueprint
Object -> real item created from class

Example idea:

Class: Student;
Objects:
student1
student2
student3

Why OOP is Used

1. To organize large programs.
2. To reuse code.
3. To group data and behavior together.
4. To model real-world entities.
5. To make code easier to maintain.

14.1.1 Classes

A **class** is a blueprint for creating objects.

Syntax

```python
class ClassName:
    statement
```

1. A class defines the structure of an object.
2. A class can contain attributes and methods.
3. Class names usually use PascalCase.
4. A class does not represent one real object by itself.
5. Objects are created from classes.

CodeWithNishchal

Example 1

```
PYTHON CODE
class Student:
    pass

student1 = Student()
print(type(student1))
```

Output: <class '__main__.Student'>

Class Naming Style

Good Class Name	Reason
Student	Clear class name
BankAccount	Uses PascalCase
EmployeeRecord	Meaningful name

14.1.2 Objects

An **object** is an instance created from a class.

Syntax

object_name = ClassName()

1. An object is created from a class.
2. One class can create many objects.
3. Each object can have its own data.
4. Objects are also called instances.

Example 1

```
PYTHON CODE
class Student:
    pass
student1 = Student()
student2 = Student()
print(student1)
print(student2)
```

CodeWithNishchal

Output:
<__main__.Student object at ...>
<__main__.Student object at ...>
The memory address may be different in every run.

Class vs Object

Point	Class	Object
Meaning	Blueprint	Real instance
Created using	class keyword	Class name with ()
Example	Student	student1 = Student()
Memory	No object data yet	Stores actual object data

14.1.3 Attributes

Attributes are variables that belong to an object or class.

Syntax

object_name.attribute_name = value

Explanation

1. Attributes store data about an object.
2. Each object can have different attribute values.
3. Attributes are accessed using dot . notation.

Example 1

PYTHON CODE

```
class Student:
    pass


student1 = Student()
student1.name = "Aman"
student1.age = 21
print(student1.name)
print(student1.age)
```

Output: Aman
21

devWithNishchal

Attribute Table

Code	Meaning
student1.name	Accesses name attribute
student1.age	Accesses age attribute
student1.name = "Aman"	Creates/updates attribute

14.1.4 Methods

A **method** is a function defined inside a class.

Syntax

```python
class ClassName:
    def method_name(self):
        statement
```

1. Methods define object behavior.
2. Methods are functions inside a class.
3. Instance methods usually take self as the first parameter.
4. Methods are called using an object.

Example 1

```
PYTHON CODE
class Student:
    def greet(self):
        print("Hello")

student1 = Student()
student1.greet()
```

Output: Hello

14.1.5 self

deWithNishchal

self refers to the current object.

Syntax

```
def method_name(self):
    statement
```

1. self represents the object that is calling the method.
2. It is used to access object attributes and methods.
3. Python automatically passes the object as self.
4. self is not a keyword, but it is the standard convention.
5. Always use self for instance methods.

Example 1

PYTHON CODE

```
class Student:
    def show_name(self):
        print(self.name)

student1 = Student()
student1.name = "Aman"
student1.show_name()
```

Output: Aman

14.1.6 __init__

__init__ is a special method used to initialize object data.

Syntax

```
Python

class ClassName:
    def __init__(self):
        statement
```

1. __init__ runs automatically when an object is created.
2. It is used to set initial attribute values.
3. It is commonly called a constructor.
4. Technically, __init__ initializes the object after it is created.
5. The actual object creation is handled by __new__, which is advanced and usually not needed in core notes.

Example 1

CodeWithNishchal

```
PYTHON CODE
class Student:
    def __init__(self, name, age):
        self.name = name
        self.age = age

student1 = Student("Aman", 21)
print(student1.name)
print(student1.age)
```

Output: Aman
21

14.1.7 Instance Variables

Instance variables are variables that belong to a specific object.

Syntax

self.variable_name = value

1. Instance variables are usually created inside __init__.
2. Each object gets its own copy.
3. Changing one object's instance variable does not affect another object.
4. They are accessed using object.variable_name.

Example 1

```
PYTHON CODE
class Student:
    def __init__(self, name):
        self.name = name


student1 = Student("Aman")
student2 = Student("Riya")
print(student1.name)
print(student2.name)
```

Output: Aman
Riya

NOTE: student1.name and student2.name are separate instance variables.

14.1.8 Class Variables

WithNishchal

Class variables are variables shared by all objects of a class.

Syntax

```python
class ClassName:
    class_variable = value
```

Explanation

1. Class variables are defined directly inside the class.
2. They are shared by all objects.
3. They are useful for common data.
4. They can be accessed using the class name or object name.
5. Prefer accessing class variables using the class name.

Example 1

```
PYTHON CODE
class Student:
    school_name = "ABC School"

    def __init__(self, name):
        self.name = name

student1 = Student("Aman")
student2 = Student("Riya")
print(student1.school_name)
print(student2.school_name)
print(Student.school_name)
```

Output:
ABC School
ABC School
ABC School

Instance Variable vs Class Variable

hNishchal

Point	Instance Variable	Class Variable
Belongs to	Object	Class
Created where	Usually inside __init__	Inside class, outside methods
Shared?	No	Yes
Access	self.name	ClassName.variable
Example	self.name	school_name

Important Warning

Avoid mutable class variables unless shared data is intentional.

```python
class Student:
    subjects = []
```

This list is shared by all objects, which can cause unexpected behavior.

14.1.9 Methods vs Functions

A function is independent.
A method belongs to a class or object.

Comparison Table

Point	Function	Method
Defined where?	Outside class	Inside class
Called using	Function name	Object or class
First parameter	No automatic self	Instance method gets self
Example	greet()	student.greet()

14.2 OOPS Principles

14.2.1 Encapsulation

Code With Nishchal

Encapsulation means **binding data and methods together inside a class** and controlling how data is accessed or modified.

Basic Idea

Data + Methods = Encapsulation

1. Encapsulation keeps related data and behavior inside one class.
2. It helps protect data from direct unwanted changes.
3. Python does not have strict private variables like Java or C++.
4. Python uses naming conventions to show access level.
5. Encapsulation is commonly handled using:
    1. Public attributes
    2. Protected attributes
    3. Private/name-mangled attributes
    4. Getter and setter methods
    5. @property

PYTHON CODE

```
class BankAccount:
    def __init__(self, balance):
        self.__balance = balance

    def deposit(self, amount):
        if amount > 0:
            self.__balance += amount

    def get_balance(self):
        return self.__balance

account = BankAccount(1000)
account.deposit(500)
print(account.get_balance())
```

Output: 1500

Here, __balance is not directly accessed from outside. It is accessed using methods.

Public, Protected, and Private Members

Python uses naming conventions for access control.

Access Level Table

Nishchal

Type	Syntax	Meaning	Example
Public	name	Can be accessed normally	self.name
Protected	_name	Meant for internal use	self._salary
Private / Name mangling	__name	Avoid accidental outside access	self.__pin

Example 1

```
PYTHON CODE
class Student:
    def __init__(self):
        self.name = "Aman"
        self._marks = 85
        self.__grade = "A"

student = Student()
print(student.name)
print(student._marks)
```

Output: Aman
85
Direct access to __grade will fail:
print(student.__grade)
Output: AttributeError: 'Student' object has no attribute '__grade'

Important Point

Double underscore does not make data fully private.
It performs name mangling to avoid accidental access.
Internally, Python changes:
__grade -> _Student__grade
So technically it can still be accessed, but it should not be used directly.

Getter and Setter Methods

Getter and setter methods are used to read and update private data safely.

CodeWithNishchal

```python
def get_value(self):
    return self.__value

def set_value(self, value):
    self.__value = value
```

1. Getter method reads private data.
2. Setter method updates private data.
3. Setter can validate data before updating.
4. This protects the object from invalid values.

Example 1

PYTHON CODE

```python
class Student:
    def __init__(self, marks):
        self.__marks = marks

    def get_marks(self):
        return self.__marks

    def set_marks(self, marks):
        if marks >= 0:
            self.__marks = marks
        else:
            print("Marks cannot be negative")
student = Student(80)
student.set_marks(90)
print(student.get_marks())
```

Output: 90

Encapsulation Using @property

Nishchal

@property allows a method to behave like an attribute.

Syntax

```python
@property
def attribute_name(self):
    return value
```

1. @property is a clean way to control access to data.
2. It allows validation before changing data.
3. It supports getter and setter behavior.
4. It makes code look simple while still protecting data.

Example 1

PYTHON CODE

```
class Student:
    def __init__(self, marks):
        self.marks = marks

    @property
    def marks(self):
        return self._marks

    @marks.setter
    def marks(self, value):
        if value < 0:
            raise ValueError("Marks cannot be
negative")
        self._marks = value

student = Student(85)
student.marks = 95
print(student.marks)
```

Output: 95

14.2.2 Inheritance

Nishchal

Inheritance allows one class to reuse the properties and methods of another class.

Syntax

```python
class ChildClass(ParentClass):
    statement
```

Explanation

1. Inheritance supports code reuse.
2. The parent class is also called base class or superclass.
3. The child class is also called derived class or subclass.
4. The child class can use parent class attributes and methods.
5. The child class can also define its own attributes and methods.
6. The child class can override parent methods.
7. Inheritance represents an **is-a** relationship.

Basic Example

PYTHON CODE

```python
class Animal:
    def eat(self):
        print("Eating")

class Dog(Animal):
    def bark(self):
        print("Barking")
dog = Dog()
dog.eat()
dog.bark()
```

Output: Eating
Barking

Inheritance Flow

Parent class

hNishchal

|
v
Child class
|
v
Child class can reuse parent features

Why Inheritance is Used

Use	Meaning
Code reuse	Child class reuses parent code
Extensibility	Child class can add new features
Maintainability	Common logic stays in parent class
Polymorphism	Same method can behave differently
Real-world modeling	Represents is-a relationship

Example:
Dog is an Animal
Car is a Vehicle
Student is a Person

Types of Inheritance in Python

Python supports these major types of inheritance:

Type	Meaning
Single inheritance	One child inherits from one parent
Multilevel inheritance	Child inherits from parent, and another child inherits from that child
Hierarchical inheritance	Multiple child classes inherit from one parent
Multiple inheritance	One child inherits from multiple parents
Hybrid inheritance	Combination of two or more inheritance types

CodeWithNishchal

Single Inheritance

Single inheritance means one child class inherits from one parent class.

Syntax

```python
class Parent:
    pass

class Child(Parent):
    pass
```

Example 1

```
PYTHON CODE
class Animal:
    def eat(self):
        print("Eating")

class Dog(Animal):
    def bark(self):
        print("Barking")

dog = Dog()
dog.eat()
dog.bark()
```

Output: Eating
Barking

CodeWithNishchal

Multilevel Inheritance

Multilevel inheritance means a class inherits from a child class, forming a chain.

Syntax

```python
class A:
    pass

class B(A):
    pass

class C(B):
    pass
```

Example 1

```python
class Animal:
    def eat(self):
        print("Eating")

class Dog(Animal):
    def bark(self):
        print("Barking")

class Puppy(Dog):
    def weep(self):
        print("Weeping")

puppy = Puppy()
puppy.eat()
puppy.bark()
puppy.weep()
```

Output:
Eating
Barking
Weeping

Hierarchical Inheritance

Hierarchical inheritance means multiple child classes inherit from one parent class.

Nishchal

Syntax

```python
class Parent:
    pass

class Child1(Parent):
    pass

class Child2(Parent):
    pass
```

Example 1

```
PYTHON CODE
class Animal:
    def eat(self):
        print("Eating")


class Dog(Animal):
    def bark(self):
        print("Barking")

class Cat(Animal):
    def meow(self):
        print("Meowing")

dog = Dog()
cat = Cat()
dog.eat()
dog.bark()
cat.eat()
cat.meow()
```

Output: Eating
Barking
Eating
Meowing

Diagram



Multiple Inheritance

Multiple inheritance means one child class inherits from more than one parent class.

Code Nishchal

Syntax

```
PYTHON CODE
class Parent1:
    pass

class Parent2:
    pass

class Child(Parent1, Parent2):
    pass
```

1. Python supports multiple inheritance.
2. A child class can use methods from multiple parent classes.
3. If parents have methods with the same name, Python uses MRO.
4. MRO means Method Resolution Order.

Example 1

```
PYTHON CODE
class Father:
    def father_skill(self):
        print("Gardening")

class Mother:
    def mother_skill(self):
        print("Painting")

class Child(Father, Mother):
    def child_skill(self):
        print("Coding")

child = Child()

child.father_skill()
child.mother_skill()
child.child_skill()
```

Output:

Gardening
Painting
Coding

Diagram

Father Mother
  \ /

Nishchal

v v

Child

Hybrid Inheritance

Hybrid inheritance is a combination of two or more types of inheritance.

1. Hybrid inheritance mixes different inheritance types.
2. It can include multiple, multilevel, or hierarchical inheritance together.
3. It is powerful but can become complex.
4. MRO is important in hybrid inheritance.

Example 1

PYTHON CODE

```
class Person:
    def show_person(self):
        print("Person")

class Student(Person):
    def show_student(self):
        print("Student")

class Employee(Person):
    def show_employee(self):
        print("Employee")

class TeachingAssistant(Student, Employee):
    def show_ta(self):
        print("Teaching Assistant")

ta = TeachingAssistant()
ta.show_person()
ta.show_student()
ta.show_employee()
ta.show_ta()
```

Output:

Person

Student

Employee

Teaching Assistant

Diagram

Person

Nishchal