

#	Reference Qty	Value	DNP	Exclude frc	Exclude frc	Footprint	Datasheet	Description
1	C1,C5,C17	3 10uf				Capacitor_~		Polarized capacitor
2	C2,C3,C4,C	9 0.1uf				Capacitor_~		Unpolarized capacitor
3	C10	1 1uf				Capacitor_~		Polarized capacitor
4	C11	1 2.2uf				Capacitor_~		Unpolarized capacitor
5	C13,C14	2 22pf				Capacitor_~		Unpolarized capacitor
6	D1	1 LED_user				LED_SMD: ~		Light emitting diode
7	D2	1 LED_PWR				LED_SMD: ~		Light emitting diode
8	FB1,FB2	2 FerriteBead_Small				Inductor_S~		Ferrite bead, small symbol
9	J1	1 USB_C_Receptacle_USB2.0_14P				Connector_~	https://www.usb.org/developers/connected/14pin_type_c_receptacle_connectors.html	USB 2.0-only 14P Type-C Receptacle connector
10	J2	1 SWD				Connector_~		Generic connector, single row, 01x05, script
11	J3	1 UART				Connector_~		Generic connector, single row, 01x03, script
12	J4	1 I2C				Connector_~		Generic connector, single row, 01x03, script
13	J5	1 SPI				Connector_~		Generic connector, single row, 01x05, script
14	J6	1 GPIO_A				Connector_~		Generic connector, single row, 01x12, script
15	J7	1 GPIO_B				Connector_~		Generic connector, single row, 01x11, script
16	J8	1 GPIO_C				Connector_~		Generic connector, single row, 01x11, script
17	J9	1 POWER				Connector_~		Generic connector, single row, 01x06, script
18	J10	1 GPIO_D				Connector_~		Generic connector, single row, 01x08, script
19	JP1	1 DFU				TestPoint: ~		Jumper, 2-pole, open
20	R1,R2	2 5.1K				Resistor_S ~		Resistor
21	R3,R4	2 10K				Resistor_S ~		Resistor
22	R5,R6	2 470R				Resistor_S ~		Resistor
23	R7,R8	2 4.7K				Resistor_S ~		Resistor
24	SW1	1 SW_RST				Button_Sw~		Push button switch, generic, two pins
25	SW2	1 SW_user				Button_Sw~		Push button switch, generic, two pins
26	U1	1 NCP1117-3.3_SOT223				Package_T	http://www.onsemi.com/pdf/datasheet/ncp1117-d.pdf	1A Low drop-out regulator, Fixed Output 3.3V
27	U2	1 USBLC6-2SC6				Package_T	https://www.onsemi.com/pdf/datasheet/usb6lc6-d.pdf	Very low capacitance ESD protection diode, 100V
28	U3	1 STM32F401RETx				Package_C	https://www.st.com/en/microcontrollers/stm32f401.html	STMicroelectronics Arm Cortex-M4 MCU, 512KB
29	Y1	1 8MHz				Crystal:Cry~		Two pin crystal, small symbol

2KB flash, 96KB RAM, 84 MHz, 1.7-3.6V, 50 GPIO, LQFP64