



JOINT INSTITUTE
交大密西根学院



Review class

Liang Yuxuan

Outline



- Determinant
- Diagonalization
- Phase Diagram
- Matrix Exponential
- Linear homogeneous systems
- Nonhomogeneous systems

Determinant



The determinant of an $n \times n$ matrix is defined recursively as

$$\blacksquare \det(A) = \begin{cases} a_{11} & n = 1 \\ a_{11}C_{11} + a_{12}C_{12} + \cdots + a_{1n}C_{1n} & n > 1 \end{cases}$$

where C_{ij} is cofactor, and is given by

$$C_{ij} = (-1)^{i+j}M_{ij}$$

where M_{ij} is minor, and is given by


***deleting the i th row and j th column from the original matrix**

Determinant



■ Determinant of
$$\begin{vmatrix} a_{11} & a_{12} & a_{13} \\ a_{21} & a_{22} & a_{23} \\ a_{31} & a_{32} & a_{33} \end{vmatrix}$$

is $a_{11}a_{22}a_{33} + a_{12}a_{23}a_{31} + a_{13}a_{21}a_{32} - a_{13}a_{22}a_{31} - a_{12}a_{21}a_{33} - a_{11}a_{23}a_{32}$



Diagonalization Eigenvalues and Eigenvectors



- satisfy $A\mathbf{x} = \lambda\mathbf{x}$ (nontrivial solution for λ and \mathbf{x})
 λ is the Eigenvalues and \mathbf{x} is the corresponding Eigenvectors

- Way to solve

$$\det(A - \lambda I) = 0$$

Expand this determinant and find a polynomial with λ

*It is called Characteristic polynomial

*The highest degree of λ is equal to the size of square matrix

- So there will n solution for the Characteristic polynomial to $n \times n$ matrix

Diagonalization

Eigenvalues and Eigenvectors



E.g. Find the eigenvalues and eigenvectors of the following.

$$\blacksquare A = \begin{bmatrix} 1 & 1 & 1 \\ 0 & 1 & 1 \\ 0 & 0 & 1 \end{bmatrix}$$

■ The characteristic equation is given by

$$\det(\mathbf{A} - \lambda \mathbf{I}) = (1 - \lambda)^3 = 0$$

$$\text{So } \lambda_1 = \lambda_2 = \lambda_3 = 1$$

$$(\mathbf{A} - \mathbf{I})\mathbf{x} = \begin{bmatrix} 0 & 1 & 1 \\ 0 & 0 & 1 \\ 0 & 0 & 0 \end{bmatrix} \mathbf{x} = \mathbf{0}$$

$$\mathbf{x} = [0 \ 0 \ 1]^T$$

Diagonalization

Eigenvalues and Eigenvectors



- The degree of a root λ_i of the characteristic polynomial of a matrix is called the **algebraic multiplicity** of the eigenvalue.
- The dimension of the eigenspace corresponding to an eigenvalue λ_i is called the **geometric multiplicity** of the eigenvalue.
- **Geometric multiplicity** is smaller or equal to **algebraic multiplicity**
- **Geometric multiplicity** is bigger or equal to one

Diagonalization Eigenvalues and Eigenvectors



properties:

When facing complex Eigenvalues the matrix and Eigenvectors are also complex

- complex Eigenvalues is in pair

λ is a Eigenvalues, then $\text{conj}(\lambda)$ is also an Eigenvalue

- Transposed property

λ is a Eigenvalues to A , λ is a Eigenvalues to A^T

Diagonalization

Eigenvalues and Eigenvectors



- A square matrix ($n \times n$) is said to be diagonalizable if there is an invertible matrix P and a diagonal matrix D such that:

$$A = PDP^{-1}$$

- The necessary and sufficient condition for the diagonalizable is all Eigenvalues have same **algebraic multiplicity** and **geometric multiplicity**.

Just it have n linear independent Eigenvectors

- The columns of P are n LI eigenvectors
- The diagonal elements of D are corresponding eigenvalues.

Diagonalization Eigenvalues and Eigenvectors



Diagonalize the following

$$\mathbf{A} = \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix}$$

The eigenvalues and corresponding eigenvectors of \mathbf{A} are

$$\lambda_1 = \lambda_2 = 0 : \begin{bmatrix} -1 \\ 1 \\ 0 \end{bmatrix}, \begin{bmatrix} -1 \\ 0 \\ 1 \end{bmatrix} \quad \lambda_3 = 3 : \begin{bmatrix} 1 \\ 1 \\ 1 \end{bmatrix}$$

Thus,

$$\begin{aligned} \mathbf{A} &= \begin{bmatrix} -1 & -1 & 1 \\ 1 & 0 & 1 \\ 0 & 1 & 1 \end{bmatrix} \begin{bmatrix} 0 & & \\ & 0 & \\ & & 3 \end{bmatrix} \begin{bmatrix} -1 & -1 & 1 \\ 1 & 0 & 1 \\ 0 & 1 & 1 \end{bmatrix}^{-1} \\ &= \begin{bmatrix} -1 & -1 & 1 \\ 1 & 0 & 1 \\ 0 & 1 & 1 \end{bmatrix} \begin{bmatrix} 0 & & \\ & 0 & \\ & & 3 \end{bmatrix} \begin{bmatrix} -1/3 & 2/3 & -1/3 \\ -1/3 & -1/3 & 2/3 \\ 1/3 & 1/3 & 1/3 \end{bmatrix} \end{aligned}$$

Diagonalization Eigenvalues and Eigenvectors



Diagonalize the following

$$\mathbf{A} = \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix}$$

The eigenvalues and corresponding eigenvectors of \mathbf{A} are

$$\lambda_1 = \lambda_2 = 0 : \begin{bmatrix} -1 \\ 1 \\ 0 \end{bmatrix}, \begin{bmatrix} -1 \\ 0 \\ 1 \end{bmatrix} \quad \lambda_3 = 3 : \begin{bmatrix} 1 \\ 1 \\ 1 \end{bmatrix}$$

Thus,

$$\begin{aligned} \mathbf{A} &= \begin{bmatrix} -1 & -1 & 1 \\ 1 & 0 & 1 \\ 0 & 1 & 1 \end{bmatrix} \begin{bmatrix} 0 & & \\ & 0 & \\ & & 3 \end{bmatrix} \begin{bmatrix} -1 & -1 & 1 \\ 1 & 0 & 1 \\ 0 & 1 & 1 \end{bmatrix}^{-1} \\ &= \begin{bmatrix} -1 & -1 & 1 \\ 1 & 0 & 1 \\ 0 & 1 & 1 \end{bmatrix} \begin{bmatrix} 0 & & \\ & 0 & \\ & & 3 \end{bmatrix} \begin{bmatrix} -1/3 & 2/3 & -1/3 \\ -1/3 & -1/3 & 2/3 \\ 1/3 & 1/3 & 1/3 \end{bmatrix} \end{aligned}$$

Phase Diagram



- solving system of differential equations


$$\begin{cases} \frac{dR}{dt} = a_{11}R + a_{12}J \\ \frac{dJ}{dt} = a_{21}R + a_{22}J \end{cases}$$

$$\dot{\mathbf{x}} = \mathbf{A}\mathbf{x} \quad \mathbf{x} = \begin{bmatrix} R \\ J \end{bmatrix} \quad \mathbf{A} = \begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{bmatrix}$$

$$\mathbf{F} = \frac{dR}{dt}\mathbf{e}_R + \frac{dJ}{dt}\mathbf{e}_J.$$

Phase Diagram

e.g.




$$\mathbf{A} = \begin{bmatrix} 1 & 2 \\ 0 & -2 \end{bmatrix}$$

Eigenvalues: 1, -2

Eigenvector: $[1 \ 0]^T, [2 \ -3]^T$

Phase Diagram

e.g.



$$\mathbf{A} = \begin{bmatrix} 0 & 1 \\ -1 & 0 \end{bmatrix}$$


Eigenvalues: $i, -i$

Real part is 0

find $d[R J]/dt$ for $[1 \ 0]$ is $\mathbf{A}[1 \ 0]^T$ is $[0 \ -1]^T$ so the arrow shall at the direction of $[0 \ -1]^T$ just down side so it is clockwise

Phase Diagram

e.g.



Eigenvalues: 0, 1

Phase Diagram



Eigenvalues		Stability	Origin case
Real	$\lambda_1 \geq \lambda_2 > 0$	Unstable	source
	$\lambda_1 \leq \lambda_2 < 0$	stable	sink
	$\lambda_1 < 0 < \lambda_2$	Unstable	Saddle point
	$\lambda_1 = 0$	e.g.	
Complex	$\text{Re}(\lambda_1) = 0$	Stable	Center of circle
	$\text{Re}(\lambda_1) > 0$	Unstable	Spiral source
	$\text{Re}(\lambda_1) < 0$	stable	Spiral sink

*caution: do not find dJ/dR to define whether clockwise or conter-clockwise

Matrix Exponential



- We define the exponential of a matrix same as exponential of function:

$$e^x = 1 + x + \frac{x^2}{2} + \frac{x^3}{6} + \dots + \frac{x^n}{n!} + \dots$$

$$e^A = 1 + A + \frac{A^2}{2} + \frac{A^3}{6} + \dots + \frac{A^n}{n!} + \dots$$

- If D is diagonal, then

$$D^k = \begin{bmatrix} \lambda_1 & & & \\ & \lambda_2 & & \\ & & \ddots & \\ & & & \lambda_n \end{bmatrix}^k = \begin{bmatrix} \lambda_1^k & & & \\ & \lambda_2^k & & \\ & & \ddots & \\ & & & \lambda_n^k \end{bmatrix}$$

- Thus $e^D = \text{diag}(e^{D_{11}}, e^{D_{22}}, e^{D_{33}}, \dots)$

Matrix Exponential



- For the reason that we have the formula $A^k = PD^kP^{-1}$

Prove: e.g for $k=3$

$$A^3 = AAA = PD(P^{-1}P)D(P^{-1}P)DP^{-1} = PDIDIDP^{-1} = PD^3P^{-1}$$

- $e^A = 1 + A + A^2/2 + A^3/6 + \dots + A^n/n! + \dots$

- For all $A^k = PD^kP^{-1}$

we can extract P and P^{-1} and get $e^A = Pe^DP^{-1}$

Linear homogeneous systems



■ Elimination Method

For a homogeneous system of first-order diff equ.

$$\begin{cases} \dot{R} = a_{11}R + a_{12}J \\ \dot{J} = a_{21}R + a_{22}J \end{cases}$$

$$\begin{aligned} \ddot{R} &= a_{11}\dot{R} + a_{12}\dot{J} \\ &= a_{11}\dot{R} + a_{12}a_{21}R + a_{12}a_{22}J \\ &= a_{11}\dot{R} + a_{12}a_{21}R + a_{22}\dot{R} - a_{22}a_{11}R \end{aligned}$$

$$\ddot{R} - (a_{11} + a_{22})\dot{R} + (a_{11}a_{22} - a_{12}a_{21})R = 0$$

Linear homogeneous systems



- For higher order it is too difficult to eliminate!

For a linear homogeneous system $\dot{\mathbf{x}} = \mathbf{A}\mathbf{x}$

$$d\mathbf{x}/dt = \mathbf{P}\mathbf{D}\mathbf{P}^{-1}\mathbf{x}$$

Thus: $\mathbf{P}^{-1}d\mathbf{x}/dt = \mathbf{D}\mathbf{P}^{-1}\mathbf{x}$

we assume $\mathbf{P}^{-1}\mathbf{x} = \mathbf{y}$ then $d\mathbf{y}/dt = \mathbf{P}^{-1}d\mathbf{x}/dt$

Thus $d\mathbf{y}/dt = \mathbf{D}\mathbf{y}$

we get $\mathbf{y}_i = \mathbf{C}_i e^{\lambda_i t}$

Thus $\mathbf{y} = e^{\mathbf{D}t}\mathbf{C}$ where \mathbf{C} is Arbitrary vector

Linear homogeneous systems



- e.g. $\dot{\mathbf{x}} = \mathbf{A}\mathbf{x}$ where $\mathbf{A} = \begin{bmatrix} 1 & 2 \\ 2 & 4 \end{bmatrix}$

$$\mathbf{A} = \mathbf{P}\mathbf{D}\mathbf{P}^{-1} = \begin{bmatrix} -2 & 1 \\ 1 & 2 \end{bmatrix} \begin{bmatrix} 0 & 0 \\ 0 & 5 \end{bmatrix} \begin{bmatrix} -2 & 1 \\ 1 & 2 \end{bmatrix}^{-1}$$

- The solution is $e^{\mathbf{A}t}\mathbf{C}$ where $\mathbf{C}=\mathbf{x}(0)$

$$\begin{aligned} e^{\mathbf{A}t} &= \mathbf{P}e^{\mathbf{D}t}\mathbf{P}^{-1} = \begin{bmatrix} -2 & 1 \\ 1 & 2 \end{bmatrix} \begin{bmatrix} 1 & 0 \\ 0 & e^{5t} \end{bmatrix} \begin{bmatrix} -2/5 & 1/5 \\ 1/5 & 2/5 \end{bmatrix} \\ &= \begin{bmatrix} \frac{e^{5t}}{5} + \frac{4}{5} & \frac{2e^{5t}}{5} - \frac{2}{5} \\ \frac{2e^{5t}}{5} - \frac{2}{5} & \frac{4e^{5t}}{5} + \frac{1}{5} \end{bmatrix} \end{aligned}$$

Thus solution is $\begin{bmatrix} \frac{e^{5t}}{5} + \frac{4}{5} & \frac{2e^{5t}}{5} - \frac{2}{5} \\ \frac{2e^{5t}}{5} - \frac{2}{5} & \frac{4e^{5t}}{5} + \frac{1}{5} \end{bmatrix} \mathbf{x}(0)$

Nonhomogeneous systems



- Formula:

$$dx/dt = Ax + \beta$$

- Solution is $x = e^{At}x(t_0) + e^{At} \int_{t_0}^t e^{-A\tau} \beta(\tau) d\tau$

- The formula is very difficult to calculate!
- The method is same as previous one

$$dx/dt = PDP^{-1}x + \beta$$

$$P^{-1}dx/dt = DP^{-1}x + P^{-1}\beta$$

$$y = P^{-1}x$$

$$dy/dt = Dy + P^{-1}\beta$$

$$y = e^{Dt}C - D^{-1}P^{-1}\beta \quad (\text{maybe not right you can check it})$$

This is more simple than formula

спасибо
danke 謝謝
ngiyabonga
teşekkür ederim
tapadh leat
gracias
mochchakkeram
go raibh maith agat
arigatō
takk
dakujem
merci
ευχαριστώ
grazie
kop khun krap
sukriya
sagolun
dziękuję
hvala
mauriuru
obrigado
bedankt
thank you
dank je
terima kasih
감사합니다